



Ultra-slim backup battery
with built-in Lightning and
Micro USB cables



Made for  iPod  iPhone  iPad

Please read the following carefully before using the Extreme Trio 10,000. Incorrect use or incompatibility with device may result in reduced battery performance or damage to your device.

01. Please check the voltage compatibility of this product (4.75V~5.25V DC) and your device.
02. Do not insert any metallic object into the Extreme Trio 10,000. This may cause the unit to short out.
03. Please use the Extreme Trio 10,000 within the following temperature ranges: -10 ~ 40 °C (14 ~ 104°F)
04. Do not disassemble or mishandle product.
05. Do not place product near fire or high-temperature environments, to avoid risk of fire or explosions.
06. Avoid leaving product in a humid environment.
07. Keep product out of reach of children and pets.
08. Product will heat up slightly when charging and discharging.
09. Product will charge more quickly with a 2.1A AC charger. It will take a longer to charge the product through your computer.
10. Marked capacity is based on internal 3.7 V standard battery.
11. In case of abnormalities during usage, stop using the product immediately and contact our service department.

※ Thank you for purchasing this iWALK product. In order for your product to operate properly, please read all instructions and usage information contained in this manual prior to use.

Product Name : Trio10000

Model No : UBO10000

Capacity : 3.7V 10,000mAh (37W)

Battery Type : Lithium polymer battery

Input : 5V / 1.0–2.4A (Only 6.5 hours for charging Trio if using 2.4A charger, not included)

Output : 5V, 3.4A

- Built-in USB charging cable, Mono Output Universal USB Port: 0.5–2.4A (Max)
- Built-in lightning charging cable, Mono Output Built-in Micro USB Cable: 0.5–2.4A (Max)
- USB output connector, Mono Output Built-in Micro USB Cable: 0.5–2.4A (Max)

(total voltage of 3 ports: 5V / 3.4A)

Dimensions :145 x 78 x 13mm (5.7 x 3.1 x 0.5 in)

Weight : 224g (7.91 oz)

TRIO

Built-in Lightning cable
0.5–2.4 A (MAX)*

Built-in Micro USB cable
0.5–2.4 A (MAX)*

Pass-through Technology

Charge 3 devices simultaneously
HIGH SPEED

Anti-skid pad
Keeps Trio firmly against phone when placed back to back.

Rapid charging
2.4 A USB port
0.5–2.4 A (MAX)*

Power ON/OFF button
Short press to start up. Press and hold for 3 seconds to shut down.
Short press to turn on LCD.

Micro USB charging input
(Only 6.5 hours for charging Trio if using 2.1 A charger, not included)

When Trio is charging,
__H shows the unit's required charging time.

When Trio is discharging,
percentage will decrease until auto shutoff.

IN	V	A	%
5V IN	1A	100%	
OUT	5V	3A	80%
5V	100%		

*Total voltage of 3 ports: 5 V / 3.4 A

Q: Why won't the Extreme Trio 10,000 power on if not used for an extended duration?
A: When the Extreme Trio 10,000 is left unused for an extended duration, it will discharge gradually until no power remains. The Extreme Trio 10,000 will function normally after 2-3 minutes of charging. We suggest charging the product every 3 months to maintain its best functionality.

Q : Why does the product heat up when it is charging / discharging?
A : This is a common occurrence, due to power consumption, and will not affect product's functionality.
The product will not overheat due to its built-in overcharge protection circuitry.

We know our products better than anyone

Head Office : U20 Building, Huanzhu Road 385, Jimei, Xiamen, Fujian, China, 361021
Korea Office : 407, Woolim Lions Valley, 144-4, Seongnam-Si, Korea
U.S. Office : 90 Gordon Drive, Syosset NY, 11791
U.K. Office : 1 Consort Road, Birmingham, B30 3HD, UK

Head Office HP : +86-592-5030-771
Visit : www.iwalk.net / E-mail : Service@iwalk.net

Backlit LCD display

Press power button to check the following:

Battery meter

OUT 5V 80%

80%

Device charging current

OUT 5V 3.4A 80%

3.4A

Charging time for Trio

IN 1H 80%

1H

When your device is almost fully charged, the charging current will lower slightly. This is a feature of the Trio's lithium battery.

Although maximum output current for a single output source could reach 2.4A, actual output current shown on the screen depends on the type of device connected.

The LCD screen will remain on while the Trio is charging or discharging. It will automatically turn off 30 minutes after charging is complete.

PLUG USB INTO COMPUTER

Please disconnect the product from the cable once the product is fully charged. Please use qualified adapter (5V / 1.0–2.4A) to charge the Trio.

PLUG USB INTO AC ADAPTER

Charging by 2.4A current; fully charged in about 6.5 hours.

▲ All three output sources (USB port, Micro USB arm, and Lightning connector arm) all have pass-through technology, which allows for simultaneous charging of the Trio 10,000 and 1 device.

Charging Information

Charges iPhone 5S	Charges Galaxy S5	Charges iPad Air
4.5 Times	2.5 Times	0.8 Times

※ Operation times may differ depending on device type and usage. The Trio starts charging after your device is almost fully charged.

Charge 3 devices simultaneously

Charge Apple device with built-in Lightning cable

Charge Android device with built-in Micro USB cable

Charge any USB-based device with a USB cable

While charging Trio and your device simultaneously, Trio will begin charging when your device is almost fully charged. H will blink when Trio begins charging, and remain on LCD screen while Trio is charging.

Thank you for purchasing this iWALK product.

Our product's warranty period is 12 months starting from the date of purchase. Within the warranty period, free service will be provided if the product has any quality problems (requiring warranty card with distributor's official stamp and valid S/N).

Paid service: customer will incur a repair charge in the following cases:

- No valid warranty card or warranty card incompatible.
- No S/N or S/N incompatible with warranty card.
- Malfunction caused by artificial damages (like external impact or submerging product into water, etc).
- Misuse of the product. User has not followed the instructions in the owner's manual.
- Product disassembled or repaired by individual or unauthorized service center.
- Damages caused by storing the product in a hot or humid environment.

Model no.		Address	
Product name			
Serial no.			
Date of purchase		Customer service date	
Manufacturer		Customer name	
Maintenance record			

(Please complete warranty card and use for any future warranty service)

PA664