User Manual

TS JQuery Form Plugin version 0.1



TECHNOSOFT

Table of Contents

1. Getting Started with "TS JQuery Form Plugin"	3
2. External Dependencies:	3
3. How to Use "TS JQuery Form Plugin":	3
3.1 Include CSS file:	3
3.2 Write an HTML for Plugin:	3
3.3 Include JavaScript file:	7
3.4 JavaScript to Invoke Plugin:	7
4. Plugin Options:	8
4.1 Theme for Plugin	8
4.2 Form Layout	9
4.3 Change Header Style	10
4.4 Quick Navigation among Pages	11
4.5 Use Icons Instead of Save and Cancel Buttons	11
4.6 Show Cancel Button	12
4.6 Show Save Button	12
4.7 Form Data Submission	12
4.8 Set Plugin Height	13
4.9 Set Plugin Width	13
4.10 Set Field Highlight Style	14
4.10.1 Field Highlighter Options	14



1. Getting Started with "TS JQuery Form Plugin"

TS JQuery Form Plugin allows user to develop a decent looking web-form where the plugin will cater the alignment and basic design. There are various options such as control and their respective label positioning, control grouping and also have the ability change the form interface to wizard.

2. External Dependencies:

Following are the files which need to be added to use the plugin:

- jquery-1.8.3.js : The file is added to the package. Latest version can also be used. Visit <u>http://www.jquery.com</u> to get the latest version
- json2.js : The file is added to the package. Latest version can also be used.
 Visit <u>https://github.com/douglascrockford/JSON-js/blob/master/json2.js</u> to get the latest version

3. How to Use "TS JQuery Form Plugin":

Follow the procedure described below to use the plugin functionality

3.1 Include CSS file:

Include the Plugin's CSS file as shown in code example below:



There is another CSS file "**jquery.ts-jform-ie-fix.css**" in a package, there is no need to include this file as Plugin will detect the IE Browser version, it will be loaded by dynamically against IE 6, 7 or 8

3.2 Write an HTML for Plugin:

Plugin takes an html as an input, which needs to be according to the format which is described below:

Step 1 – Place Container for Plugin

Place the container <div> inside <form> tag; Plugin will use the container div and place the generated form html inside it





o data-heading: this data attribute use for form heading

Step 2 - Write an HTML Inside Container

For section or pages fieldset should be placed inside container div. Code example given below is for single page and single column structure

Code sample:
<pre><div data-heading="Registration" id="jFormContainer"></div></pre>

JForm (one column form)

Registration - Login Information	 Save	Cancel
User Name		
Password		
Confirm Password		

NOTE:

- <fieldset> inside container represents the page/section of a form
- <div> inside <fieldset> represent the a column
- Plugin will apply styling on control as well such as width, height etc,
- Incase inline styling or CSS class is applied on controls then plugin will not apply its styling and adjust the form accordingly



Similarly, for more than one page or section another field set can be added, code example below will generate two page or section and both having single column structure

```
Code sample:
   <div id="jFormContainer" data-heading="Registration">
       <fieldset data-heading="Login Information">
              <div>
               <input data-label="User Name" type="text" />
                <input data-label="Password" type="password" />
                <input data-label="Confirm Password" type="password" />
              </div>
       </fieldset>
       <fieldset data-heading="Personal Details">
            <div>
                <input data-label="First Name" type="text" />
                <input data-label="Last Name" type="text" />
            </div>
        </fieldset>
   </div>
```

Furthermore, if multiple column structure is required, add div inside fieldset and plugin will generate new column inside page or section and adjust the form accordingly, see the code and figure below

```
Code sample:
   <div id="jFormContainer" data-heading="Registration">
        <fieldset data-heading="Login Information">
             <div>
               <input data-label="User Name" type="text" />
                <input data-label="Password" type="password" />
                <input data-label="Confirm Password" type="password" />
              </div>
       </fieldset>
       <fieldset data-heading="Personal Details">
             <div>
               <input data-label="First Name" type="text" />
                <input data-label="Last Name" type="text" />
              </div>
             <div>
               <input data-label="Phone" type="text" />
                <select data-label="country">
                    <option value="USA">USA</option>
               </select>
              </div>
        </fieldset>
   </div>
```

JForm (two columns form)



	Registration - Pers	sonal Details [••••]	Save	Cancel	
«	First Name	Phone +92 300 1111111		>	>
	Last Name	Country USA			

• *data-heading:* Use data-heading attribute for setting page heading which will be shown in the header area of the page, see the code below



 data-label: data-label attribute is very important attribute, as this is the attribute using which label can be assigned to the controls. Add data-label attribute to control tag, plugin will dynamically use it as label, all the formatting and alignment will be handled by the Plugin itself



Step 3 – Place Save/Cancel Button

Plugin allows users to place save and cancel button and gives leverage to submit data, add save and cancel button inside plugin container div as shown in code below:

Code sample:
<pre><div data-heading="Registration" id="jFormContainer"> <!--Place your save/cancel button HTML here--></div></pre>
<pre><input id="btnCancelForm" type="button" value="Cancel"/> </pre>



	Registration - Login Information	I Save Cancel	
«	User Name		»
	Password		
	Confirm Password		

Note:

- Plugin will handle the save and cancel button layout.
- if no functionality is applied, plugin will apply default functionality to "Cancel" button i.e. it will clear all the form fields,
- By default "" plugin for further details please see "useCancelButton" Plugin option
- Plugin submit data using JSON format, see "submitUrl" option
- For successful data submission add *id* or *name* attribute to control tag, see the code below



3.3 Include JavaScript file:

Include the Plugin's JS file in head tag of the form as shown in code example below:



3.4 JavaScript to Invoke Plugin:

Now, we are ready to use "TS JQuery Form Plugin", Place the code sample below in form to invoke the plugin



Note:

• In code example above JQuery \$(document).ready function is used, JQuery anonymous function or any other method as per requirement can be used to invoke the plugin

4. Plugin Options:

5.1 Theme for Plugin

Built-in themes can be applied on plugin generated form. *themeLayout* is the property for applying theme on plugin generated form.

There are three built-in options i.e. blue, green and brown.

Default: blue

```
Code sample:
$("#jFormContainer").tsJForm({
    themeLayout: "green" // blue, green or brown
});
```



If it is required to create custom theme, go to file *css/jquery.ts-jform.0.1.css* and see group of theme classes for green, blue and brown etc. create own set of classes with specifying name in the end of their



name. Specify the newly created theme name against *themeLayout* property; plugin will load the newly custom theme

4.2 Form Layout

Plugin gives the option to change the web form layout to wizard or full page. *jFormType* is the property for that.

Default: wizard

• fullpage:

Will convert the whole HTML to just one page, no forward/backward/jump to slide options are available

• wizard:

Will convert the HTML to slides, forward/backward/jump to slide options are available

```
Code sample:
$("#jFormContainer").tsJForm({
    jFormType: "fullpage" // fullpage or wizard
});
```

	Web page layout	(fullpage):
Registration		Save Cancel
Login Information		
User Name		
Password		
Confirm Password		
Personal Details		
First Name	Phone +92 300 1111111	Email
Last Name	Country USA 💌	 Male Female
Payment		
Name on Card		
Credit Card Visa		
Card Number		
Pin Code		



Page layout (wizard):

Registration - Login Information [• • • •]	Save Cancel	
UserName		>
Password		
Confirm Password		
Confirm Password		

4.3 Change Header Style

By using "**useHeaderLayout**" property, plugin can change the header background (i.e. make a main application header) according to the selected theme. There are two options i.e. yes or no

Default: no

Code sample:
<pre>\$("#jFormContainer").tsJForm({ useHeaderLayout: "yes" // yes or no</pre>
});

Plugin header (blue header layout):

	Registration - Login Information [•]	Save	Cancel	
«	User Name				>>
	Password				
	Confirm Password				



4.4 Quick Navigation among Pages

In Wizard layout, Plugin gives the option to navigate directly to any specific for that plugin creates navigation symbols against each page/section

"navigationSymbol" is the property for the symbols. Options for this property are mentioned below:

Default: circle

circle: this will convert navigation symbol to circles **square**: this will convert navigation symbol to squares **none**: this will hide the navigation symbols

Code sample:	
<pre>\$("#jFormContainer").tsJForm({</pre>	
<pre>navigationSymbol: "square" // square, circle or none</pre>	
});	

Navigation	Symbols	(square):
------------	---------	-----------

	Registration - Login Information] Save Cancel
«	User Name	*
	Password	
	Confirm Password	

4.5 Use Icons Instead of Save and Cancel Buttons

Based on requirement icons can also be placed against save and cancel button, all it need is url/path of an icon to replace the button. "cancellconUrl" and "savelconUrl" are the property for that. Code sample is given below

Default: empty (no icons)

```
Code sample:
$("#jFormContainer").tsJForm({
    cancelIconUrl: "css/images/cancel.png",
    saveIconUrl: "css/images/save.png"
});
```



4.6 Show Cancel Button

By default plugin does not show cancel button. If the cancel button is required on form place it html as explained in start of the manual and set "**useCancelButton**" property to true.

Default: false (hide the button)

```
Code sample:
$("#jFormContainer").tsJForm({
    useCancelButton: true // true or false
});
```

4.6 Show Save Button

By default plugin show the save button if the html is properly placed as explained in start of the manual. If the save button is not required on form, set "**useSaveButton**" property to false.

Default: true

```
Code sample:
$("#jFormContainer").tsJForm({
    useSaveButton: true // true or false
});
```

4.7 Form Data Submission

Plugin supports submission of data as well, it requires target URL on which it can submit the data. "submitURL" is the property exposed for mentioning the target URL.

Code example below is written in php. "submitURL" property is set to "**registration.php**" and in target form data is being saved in "**output.txt**".

Note: plugin submits the data in JSON format





Sample Code (PHP - registration.php):

Example below gets the json and save it in a file name output.txt.

```
Code sample:
<?php
if(isset($_POST["json"])){
    $jsonData = $_POST['json'];
    $file = fopen("output.txt", "w");
    fwrite($file, $jsonData);
    fclose($file);
    }
}</pre>
```

4.8 Set Plugin Height

Plugin gives the option to set its height as well as it can also dynamically set the height based on the content. "**jFormHeight**" is the property for this purpose. There are multiple options which are mentioned below:

Default: auto

Options:

- *auto:* plugin will calculate height and fix all page/slide height
- *autofit:* Height of all pages/slide will be calculated dynamically, based on how many controls each column contains
- **Custom height value:** This will fix the height of the plugin. Note that numeric value will be applied in pixels

```
Code sample:
$("#jFormContainer").tsJForm({
    jFormHeight: "autofit" // auto, autofit or numeric value
});
```

OR,

```
Code sample:
$("#jFormContainer").tsJForm({
   jFormHeight: 400 // auto, autofit or numeric value
});
```

4.9 Set Plugin Width

Plugin gives the option to set its width as well as it can also dynamically set the width based on the content or number of columns. "**jFormWidth**" is the property for this purpose. There are multiple options which are mentioned below:



Default: auto

Options:

- *auto:* plugin will calculate the width of plugin dynamically.
- Custom width value: This will fix the width of plugin, value will be applied in pixels

Code sample:	
<pre>\$("#jFormContainer").tsJForm({</pre>	

4.10 Set Field Highlight Style

Plugin has option to highlight fields. Colors are automatically applied based on the plugin theme. Clicking on field label or control plugin highlights the field and brings the keyboard focus on field control. Figure below is showing the highlighted field

Plugin which controls the field rendering labeling and its layout theming it also perform some other functionality i.e. apply effect on field when hover or click functions are called.

el	Can	Save	ation [••••]	tration - Login Informa	F
				Name	«
				word	1
				m Password	
				m Password	

Field Highlighter (By Clicking on a field (input, textarea, select etc) will highlight it):

Plugin also give some options to the user to customize field highlight style which are explained further in "4.10.1 Field Highlighter Options" section below:

4.10.1 Field Highlighter Options

It uses the color scheme of the current theme set for the plugin, "blue" is the default theme of plugin. Properties are divided into two parts one is related to the field i.e. highlight style on field focus, field border color etc. and the other one is related to label i.e. label positioning and its text alignment. "**fieldHighlighterOptions**" is the main property containing two sub property which are explained below:



fieldHighlighterOptions -> Field Property:

• Style:

Using this property highlight style can be set. Plugin supports three styles which are explained below:

Default: strip

Options:

- *shadow:* label position will be at top of control
- o gradient: label position will be at left side of control
- o strip: label will be written inside field/control like placeholder
- Border Color:

Plugin gives the leverage to the user to set border color of the highlighted portion **Default:** white

Options: any standard color name can be used

Field property is further explained below using the code samples and figures below:



Field Highlighter (strip):

Cancel	Save	••]	Information	egistration - Log	F
				Jser Name	*
				Password	1
				Confirm Password	4
				Confirm Password	

```
Code sample:
$("#jFormContainer").tsJForm({
    fieldHighlighterOptions: {
        field: { borderColor: "white", style: "gradient"}
        // borderColor: any legal color name or value can be used
        // style: shadow, gradient and strip
     }
});
```



Field Highlighter (gradient):

F	Registration - Login Information	Save Cancel
«	User Name	×
	Password	
	Confirm Password	

Code sample:
<pre>\$("#jFormContainer").tsJForm({</pre>
<pre>fieldHighlighterOptions: {</pre>
field: { borderColor: "white", style: "shadow"}
<pre>// borderColor: any legal color name or value can be used</pre>
<pre>// style: shadow, gradient and strip</pre>
}
});

Field Highlighter (shadow) and theme (brown):

	Registration - Personal Details			Cancel
«	First Name	Phone +92 300 1111111	Email	>>
	Last Name	Country USA 🔹	 Male Female 	

Code sample:
<pre>\$("#jFormContainer").tsJForm({</pre>
themeLayout: "green",
<pre>fieldHighlighterOptions: {</pre>
<pre>field: { borderColor: "white", style: "strip"}</pre>
<pre>// style color will be applied according to the themelayout</pre>
<pre>// borderColor: any legal color name or value can be used</pre>
// style: shadow, gradient and strip
}
});



Field Highlighter (strip) and theme (green):

Save Cancel

fieldHighlighterOptions -> Label Property:

• position:

Using this property label position can be set. Plugin supports three options which are explained below:

Default: top

- top: label position will be at top of control
- *left:* label position will be at left side of control
- inline: label will be written inside field/control like placeholder

• align:

Plugin gives the leverage to the user to set label text alignment **Default:** left

- *left:* label will be aligned to left
- *right:* label will be aligned to right
- center: label will be aligned to center

Label property is further explained below using the code samples and figures below:

```
Code sample:
$("#jFormContainer").tsJForm({
    fieldHighlighterOptions: {
        label: { align:"left", position:"left" }
        // align: left or right
        // position: top, left or inline
    }
});
```



Label positioning (left):

	Registration - Login Information	Save Cancel
«	User Name	»
	Password	
	Confirm Password	

Code sample:
<pre>\$("#jFormContainer").tsJForm({</pre>
fieldHighlighterOptions: {
label: {
<pre>// align: left or right</pre>
<pre>// position: top, left or inline</pre>
}
});

Label positioning (inline):

	Registration - Perso	nal Details	1	Save	el
«	First Name	Phone	Email		»
		Country	Male		
	Last Name	USA) 💿 Female		

Code sample:
<pre>\$("#jFormContainer").tsJForm({</pre>
fieldHighlighterOptions: {
label: {
// align: left or right
<pre>// position: top, left or inline</pre>
}
});



Label alignment (right):

	Registration - Login Information	Save Cancel	
«	User Name	>>	>
	Password		
	Confirm Password		

Code sample:
<pre>\$("#jFormContainer").tsJForm({ fieldHighlighterOptions: { label: {</pre>
// align: left or right
// position: top, left or inline
});

Label alignment (right) and position (top):

Reg	gistration - Login Information [• • • • •]	Save Cancel
«	User Name	»
	Password	
	Confirm Password	