





## LIGHTING CONSOLES

### 3000 SERIES

- (4) or (8) dimming control channels
- (4) or (8) recordable scene memory
- Master output fader

### MC 7000 SERIES

- Individual control channels
- 2-scene or 1-scene (wide mode)
- User programmable memory scenes and chase functions

### MC 7500 SERIES

- 2-scene, 1-scene or wide mode presets
- Dual split dipless manual crossfaders
- Audio sync to chase effects mode
- Cue stacking
- 120V or 230V

### 1000 SERIES

- (6) sub-masters and (1) master fader
- Backup Console Mode – scene fade and activation upon sudden loss of incoming DMX signal

### PICCOLO

- Operating modes – two scene, single scene and sub-master “theater” mode
- Full access to all channels via faders
- (32) attributes for automated device support

### PICCOLO SCAN

- Powerful Piccolo features with expanded capabilities
- 256 automated device attributes
- Effects based moving lights control
- Trackball plus attribute encoder

### INNOVATOR

- Dual independent auto crossfaders address discrete cue lists
- Up to (128) simultaneous crossfades may be executed
- Supports up to (256) automated devices (512 channels of intelligent light attributes)
- 120V or 230V

### ENLIGHTEN

- Multiple views to arrange fixtures graphically in different rooms or areas
- Direct fader control with virtual wheel controls
- Color coded button groups, allowing for multiple fixture types on a single page
- Move any button to any position on-screen

## SYSTEMS MANAGEMENT

### DMX OPTICALLY ISOLATED SPLITTER/ REPEATER

- (1) Input (8) Outputs
- Optically isolated outputs
- Connectors on front terminals on rear

### DMX INPUT MERGER

- (8) Inputs (1) Output
- Merge in highest level takes precedence (HTP) mode
- Connectors on front terminals on rear

### NPC SERIES

- Interface between devices on differing networks
- Models include: NPC XP, NPC DLR

### NPC2D (2-PORT NPC)

- Cost effective DMX-over-Ethernet connectivity
- Programmable from Piccolo, Piccolo Scan or Ethernet
- Models available with both male or female XLR's or one of each

### IF501

- DMX / AMX / CMX / MPX conversion
- Interface between a computer and the Luma-Net® network for programming Luma-Net® stations
- A precision (20) cue sequence of (16) channels with fade and wait times from 0.1 seconds to 50 minutes may be programmed via the RS-232 port and triggered remotely

### WIRELESS DMX

- CRMX wireless transmissions never disturb or are disturbed by other wireless equipment
- Indoor and outdoor transmitter/receiver models available
- Synchronization and error correction

## SATELLITE DIMMER PACKS

### D4DMX

- Micro-plex and DMX512 protocols
- Resettable circuit breakers (no fuses to change)
- (16) pre-programmed chase patterns with chase speed and chase output level controls
- Channel level output control
- 120V

### DDS 5600

- Micro-plex and DMX512 protocols
- (4) individual dimmer channels
- User select for dimmer/relay operation
- User select for soft start operation to increase lamp life
- 120V or 240V

### DDS 6000

- Micro-plex and DMX512 protocols
- (4) individual dimmer channels
- (512) channel address capable (DMX or micro-plex)
- External fusing for each individual channel
- User select for dimmer/relay operation
- Up to (2) 20A inputs
- 120V or 230V

## RACK MOUNT DIMMERS

### NRD 8000

- (8) circuit programmable
- 120/240V single phase power operation
- Dual SCR circuit design
- Micro-plex control
- 120V or 240V

### DS MODULAR DIMMER

- Micro-plex and DMX512 protocols
- Fully modular design
- Dimmer and control modules are easily serviced using removable front panel while chassis remains in rack
- (8) and (12) channel versions
- 1200kW and 2400kW per channel
- 120V or 230V

## HIGH DENSITY DIMMING

### iSERIES DUAL/iSERIES QUAD

- All rack configuration data is stored in rack electronics
- Optional handheld terminal provides feedback and control at each rack or remotely
- Full feed back option
- Models include: (24), (48) and (96) circuit racks
- i48 Quad Dimmer model also available
- 120V or 230V, 1 Phase or 3 Phase

## DIMMING PANELS

### 2408 CD

- (8) individual dimmer circuits
- 2,400W per channel, 19,200W maximum
- Convection cooling
- 120V or 230V

## DISTRIBUTION EQUIPMENT

### SKYHOOK

- Revolutionary hide-away retractable lighting support
- 1,000 pound load capable
- Many power and control configurations available

### DISTRIBUTION EQUIPMENT

- Connector strips
- Floor pockets
- Plug boxes
- Gridiron junction boxes

## FIXTURES

### LEO LED ELLIPSOIDAL ZOOM

- Comes in three zoom models covering an 8-55° field angle
- Two color temps:
  - 3,200K
  - 5,600K
- 4 shutters
- High quality light output

### LEO LED FRESNEL ZOOM

- 100, 200 & 300W models, 3,200K only
- 6", 8" or 10" Fresnel lens
- Optical zoom models with 8-22° field angle cone of light
- High quality light output

### LEO

- 15°, 19°, 26°, 36° and 50° field angles
- Up to 750W lamp
- Cosine (flat) and peak focus with all recommended lamps and beam angles

### FRESNEL

- Lightweight rugged aluminum construction
- High intensity spot with a smooth even field
- Models include: 6" 1kW or 8" 2kW

### MULTI-LENS PAR

- (4) field angles with (1) fixture
- Black or white finishes available
- Same lamps as LEO – 575W and 750W

### PAR CANS

- Models include: Par 38, 56 and 64
- Includes color frame at no extra cost
- Black, white and chrome finishes available

### SET LIGHT

- Compact light producing asymmetric pattern
- Barn doors provide sharp cutoff

### FAR CYC

- Uniformly illuminates 40 vertical feet on 10-12 ft centers
- 1K - 2K lamps available
- Models include: (1), (2), (3) or (4) circuits

## ENTERTAINMENT PACKAGED SYSTEMS

- Turn key systems include 3000 Series controller, D4DMX, Par Cans, lamps, color frames, color gels, and stand
- Easily expandable by adding more dimmers and lights
- Models include: mini, standard and expansion

Visit our Website at: [www.leviton.com/les](http://www.leviton.com/les)  
 © 2015 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.  
 Leviton S. de R.L. de C.V.  
 Lago Tana 43, Mexico DF, Mexico CP 11290  
 Tel: (+52) 55-5082-1040 • FAX: (+52) 5386-1797  
 www.leviton.com.mx  
 Leviton Manufacturing of Canada, Ltd.  
 165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9  
 Telephone: 1-800-469-7890 • FAX: 1-800-563-1853  
 Tech Line (6AM-4PM P.S.T. Monday-Friday): 1-800-959-6004  
 20497 SW Tilton Avenue, Tualatin, OR 97062  
 Telephone: 1-800-736-6682 • FAX: 503-404-5594  
**Lighting & Energy Solutions**  
**Leviton Manufacturing Co., Inc.**

**CONSOLE SELECTION CONSIDERATIONS**

- Channel Capacity
- Memory Support
- Channels of Control
- Effects
- Point & Shoot Moving Lights or Effects Moving Lights
- Interface Type (Sliders, Trackball, Touch Screen, Monitor, etc.)

**Entertainment Consoles Selection Guide**

THE FUTURE IS ON™

