SIEMENS Version 2.2 4.2.2010

Saturn VOIP+ISDN/PSTN AM (with DECT) Gigaset DX800A all in one

"High-End Desktop Phone Family with 3,5 "-TFT- colour display and modern high-quality design" USP:

• High-End Desktop Phone

Key Benefits:

Outstanding High-Quality Design

• Large (3,5") TFT-Colour Display

Full Dial Keypad and Sound in HSP-Quality

Interface: Ethernet for VoIP a/b (analogue) or Point-to-multipoint S0 (DSS1) plus

,,,

link to GSM via Bluetooth

Standards: DECT, GAP, F-SMS, Bluetooth, Euro-ISDN/PSTN, Ethernet

Configuration: Connection of up to 2 external ISDN(2 B-channels)/1 PSTN lines and up to 4 external IP lines simultaneously

System: Up to 6 handsets can be registered

Sound quality

- o Wideband capable based on Cat-IQ 1.0
- o Certification for Cat-IQ 1.0 (vb)
- o Internal calls always in full wideband quality
- o External calls via VoIP support Wideband
- Nearly Full-Duplex handsfree in brilliant quality (80 ccm sound reflex box in desktop base)
 - activated by illuminated handsfree key, volume adjustable (5 volume steps)
- o Adjustable volume of corded handset sound (3 levels)
- o Headset connection via Bluetooth or 2,5mm jack connector
- o Ringertones and music-on hold in full wideband quality
- Polyphonic ringer-melodies and download of real-sounds in best quality possible
- Ringer melodies with 4-steps adjustable volume settings plus crescendo
- o Ringer melody output via handsfree speaker
- o Mute (via separate hardkey)
- o Earpiece: Wideband capable
- o Earpiece: HAC (hearing aide compatible)

Convenience – phoning essentials

Phonebook and dialing

- Address book with 1000 vCard entries, each containing 7 fields - name, surname, 3 numbers, e-mail and anniversary
- Anniversary day and time can be stored for each directory entry (vCard). Assign individual ring tone melody and picture for picture clip
- VIP-entries (a specific melody and predefined picture can be assigned to each directory entry)
- Auto-accelerating navigation through local phonebook with full text search
- o Extra large digits displayed for dial preparation
- Dial preparation (input of phone numbers before connecting) with correction possibility
- o Redialing of the 20 last different numbers
- User-programmable speed-dial shortcuts using keys 2-9
- o Dialing: tone, pulse
- o Automatic redial functionality
- 6 Configurable function keys: can be set as call by call key, pre-programmable with service numbers, line-selection. Rkey)
- o Full Intercom functionality (internal calls)

Receiving Calls

o Caller indication displayed via CLIP and CNIP displayed

 Picture clip for individual callers or VIP groups (xx pictures pre-stored)

- o Display and handsfree key lighted
- o Ringer melody output
- o Polyphonic ringer melodies (16 chords): xx predefined
- o Standard ringer melodies: 10 predefined
- o Selectable ringer melody for internal calls
- o Number (MSN)-specific ringer tone selectable

Missed Calls

- Display signaling missed calls
- Comfortable access to missed calls list by dedicated, illuminated message key
- List showing up to 30 missed calls saving calls with caller indication (CLIP) and time

General additional features

- Dynamic and elegant high-quality design with modern base design
- Plug & Play (unpack, connect the phone and conduct a call)
- Optimized Configuration via improved Installations assistants for ISDN and VoIP settings
- o Automatic SMS registration
- Comfortable time and date setting (initial installation; buffered in case of power loss); date and time automatically synchronized via D-Channel after first call
- Comfortable dial and text editors
- Free programmable Soft key
 - (e.g. Quick dial, Call-by-call, Alarm, Calendar)
- o Red illuminated MWI and Handsfree key
- o 5 configurable keys (Flash-key (R), Pause predefined)
- 5 -way Navikey
- o In call status you get automatically recall softkey
- In connect status you get automatically
 - alternation between 2 lines or
 - conference
- In conference status you get separate function
- o Mute-functionality with extra Mute-key
- Calendar with month view, visualization, administration of events and anniversaries
- o Event-Scheduler / anniversary:

in total up to 30 events can be stored with text

- user can select type from list or edit title
- melody for signaling settable
- signaling with type related icon



SIEMENS

- Alarm clock functionality with snooze function set occurrence Monday-Friday or. daily
- Editable internal basestation name

Display and menu features

Display

- Illuminated full graphical display (7 lines), 320 x 240 pixel, 3,5 "TFT display, brilliant Color (>=65k color)
- Night Mode: Display of Desktop can be switched off timecontrolled (Power saving and non-disturbing at night)

Standby

- Display of digital clock or color picture as screensaver 0 (settable by user)
- Slide show on display (time-controlled)

In idle

- Date and time, state of charging, signal strength, ECO-mode 0 and Bluetooth, basestation name displayed
- Softkeys for prompt executing of functions

While conducting a call

Display of call duration or units/costs (AOC-D, AOC-E, AOC-S is generally supported)

Next Generation Graphical Interface

- Comfortable menu with colored icons and text for easy use in 20 display languages (tbd)
- Icon based menu
- Direct access to call-lists (all/missed/accepted/outgoing)
- Optimized picture clip for desktop display 0
- Improved reaction speed on menu due to high-performing 0 processor
- Night mode: time-controlled ringer off

Messaging functions (SMS)

- Sending/receiving of SMS with up to 640 characters²⁾
- Storage of up to 63 SMS with 160 digits ??
- Transmission of e-mails via SMS (separate directory for E-Mail-Addresses)
- Copy of telephone numbers from SMS to directory 0
- SMS protocol 1
- MSN-specific SMS-Inbox

ECO DECT

- DECT is switched off, if no handset is registered Ω
- Non-Disturb Mode: Time-controlled Switch Off of DECT
- ECO Mode manual reduction of transmitting power by
- ECO Mode Plus for 100% reduction of transmitting power 0 of base station and all registered handsets
- Variable reduction of transmitting power according to distance between handset and base station
- Up to 60% less energy consumption³⁾ thanks to an energy-saving power supply
- FXS Port can be switched off (power save if not needed) 0
- Night Mode: Display of Desktop can be switched off timecontrolled (Power saving and non-disturbing at night)

ISDN features

- Administration of up to 10 MSNs (auto MSN recognition)
- Date/time with synchronizing via ISDN
- Call number display (CLIP, COLP)

- Restriction of call number display (CLIR, COLR)
- Call hold/consultation/toggle (HOLD)
- Three-party conference (3PTY)
- Call waiting, accept/reject (CW)
 Call forwarding (CF) 0
- 0
- External callback on busy/no answer)
- (CCBS,CCNR) 0
- Malicious call identification (MCID) O
- 0 Advice of charge (AOC-D, -E, -S) (display of messages)
- Connection in the exchange (ECT)
- Busy-on-Busy switchable system-wide
- Automatic switch from Keypad to DTMF-signaling

Connectivity (via Bluetooth and Ethernet)

PC connection via Ethernet and "Gigaset QuickSync for

- Direct Connection to PC via Ethernet possible
- Addressbook Synchronization with desktop phone book (1000 Entries!)
 - Synchronization of directory entries with Microsoft Outlook 2003/2007/Express and Vista Contacts
- Download of indivual ringer-tones (e.g. in MP3, WMV (Microsoft), AAC (Apple iPod TM)-format) in wideband quality (automatically converted to G.722-format)
- Download of pictures for screensaver / slideshow and picture
- CTI-Interface with Outlook (and Vista Contacts, XP-Addressbook)
 - dialing direct from outlook contacts on PC via 1-click
 - displaying the contact on PC while phone rings (if entry is in contact list)

Bluetooth

- 2 Bluetooth connections supported in parallel (bluetooth headset and OBEX transfer/or PC connection)
- Supported Bluetooth Profiles
 - serial
 - headset
 - handsfree (for headset)
 - OBEX with vCard exchange of addresses
- GSM connection (Link-to-Mobile)
 - Several Mobile phones supported
 - (1-5 mobile phones, automatic switching to best or default mobile phone)
- Outgoing-Call via GSM-connection from any handset or desktop base
- Incoming call from mobile phone is signalled and transfered (configurable to any handset or desktop base ring: yes or no on mobile call)
- vCard transfer to mobile phones via Bluetooth

WEB-Interface for easy configuration and setup

- Easy configuration of lines and numbers via Web-Interface
- Save / load of phonebooks (of desktop phone and all connected handsets)
- Save / load of Configuration settings from/to PC
- Dialling-Plan configurable via Web-Interface (rules to use different linetypes for different numbers)
- Call-Lists shown on WebUI O
- Language download for WebServer
- Configuration of provider profiles via WEB Server

connection for all Saturn Variants **Ethernet**

- 2 Ethernet connectors with integrated 100 Mbit switch (PC can be connected via Base, only one Ethernet port nec.) 1 Ethernet port for analogue and ISDN version
- Simple: automatic setting of date and time via NTP (parallel to via D-channel in ISDN or CLIP-info in analogue)



SIEMENS

- Online-Phonebook access
 - Search in Public Directory & Yellow Pages
 - Reverse search functionality (i.e. search by number)
 - Auto-Lookup functionality (i.e. display of caller's ID) display name, address, mobile number of caller when
 - Country specific providers selectable via web-interface
- Network based private phonebook
- Email notification subject / header / time & date / begin of
 - Direct access to POP3/IMAP accounts without PC (phone is always on)
 - Email content reading on PC (up to first 560 chars)
 - New Emails signaled by illuminated MWI-key with comfortable access to message list:
- Automatic search for available firmware updates 0
- Firmware Update directly from base without file handling
- Support of further WEB-based services (RAP1.0 and 1.1)) e.g. weather, RSS feeds, Ebay
- DHCP client (or static IP address)

Accessories

- o Headset via Bluetooth connection or 2,5mm jack connector (headset not included)
- Gigaset Home Control (GHC) protocol for the operation of HC 450 door interface
- 1 Separate analogue FSX-port for connecting analogue **FAXes**
- Easy to use User-Interface (no setting of ISDN-line type required)
- Support of analog Fax T.30 up to 14.4 kHz

Features with additional handset

- Support of SoHo Requirements:
 - Up to 4 lines available in parallel for 4 calls at the same time
 - (1 analogue + 3 VoIP, 2 ISDN lines + 2 VoIP, up to 4 VoIPlines)
- Future Proof Flexible System for analogue or ISDN interface (setable during installation) and VoIP-Calls in parallel
- Hybrid Calls possible (menu base easy selection of line type used)
- Phonebook transfer between handsets
- Internal transfer of external calls to another handset with prior consultation call
- 3 party conference (1 external / 2 internal participants) 0 via internal recall or call-waiting
- Collective ringing on incoming external calls

Answering machine features

- Up to 3 answering machines, not simultaneously
- Digital recording of voice messages with up to 55 minutes (combined) recording time (saved against power loss)
- Listening in to incoming calls possible on all handsets and on desktop base
- Answering machine comfortable controlled via Navi-key / 3 separate AM keys and large colour display
- Predefined announcement (plug & play)
 - 3 Individual announcement and
 - 3 advisory announcement (170 Sec.) recordable by user
- Time-controlled change between announcement and advisory message
- Recording date and time are announced
- Recording time adjustable: 1 / 2 / 3 minutes, unlimited
- Call acceptance adjustable: O
 - immediately, automatic, after 10, 20, 30 Sec.
- 0 Display of new messages at the desktop phone and handset
- New message notification via SMS to external number containing CLIP, date, time

- Remote listening of messages via
 - PIN-protected remote playback
 - SMS initiated call-back from AM
- o Live recording of a telephone call

IP Net Features

- Up to 4 VoIP-Calls in parallel at the same time
- Block-Dialing and (simulated) "step-by-step dialing" for all calls
- Multiline with up to 6 SIP accounts:
 - Configure up to 6 SIP accounts from different providers
 - Assign accounts individually to handsets (send & receive direction specifically)
- VoIP support (embedded SIP VoIP, G711, G722, G726, G729AB)
- Quality of service*: ToS, Diffserv (dependent on country, network and provider)
- Operation behind router providing LAN connection
- VoIP supplementary services (device controlled):
 - conference, hold/toggle, call forwarding
- Autoprovisioning via MAC address (TR069) or code for auto configuration including SIP username and password (on
- request) Easy selection of provider profiles from HS
- Configuration of system via WEB Server
- Configuration of provider profiles via WEB Server
- Gigaset.net VoIP service:
 - free of charge calls between Gigaset VoIP phones
 - zero configuration
- Gigaset.net directory

Email notification /subject/header/ time & date / begin of message

- Direct access to POP3 accounts without PC
- Email content reading on PC
- New Emails signaled by illuminated MWI-key with comfortable access to message list: Information about sender, time & date,
 - Direct access to POP3/IMAP accounts without PC (phone is always on)
 - Email content reading on PC (up to first 560 chars)
 - New Emails signaled by illuminated MWI-key with comfortable access to message list

Future proof SW architecture

- Linux based operating system
- Large (automatically updateable) Flash with 32 Mbyte
- Allows future improvement due to huge available free/open
- Multi-Linetype system (analog/ISDN + VoIP *1a) *1b)) allows: Line Selection for each call via function key on desktop phone or on any handset via Menu-Selection (alternatively : default line-type)

Fixed net operator features

- Support of supplementary services (provider features)
 - via soft key and menu
 - (e.g. automatic call back, call forwarding) by the use of R-button, *-button and #-button
- Configurable Key can be set as Call by call button with specific provider numbers in the production



SIEMENS

Technical data

Base Station

- o Connection of 1 external ISDN line (2 B-channels)
- o Connection port for fax
- o 2 xEthernet ports for PC connection and firmware update
- o Connection of up to 6 handsets
- o Dimensions: H x W x L / weight
 - Desktop Phone: ???mm x ???mm x ???mm / ???g

Package contents

- o 1 Comfort Base station
- o 1 Power supply unit
- o 1 Telephone cord, 1 Ethernet cable
- o 1 User manual (short)
- o 1 CD-ROM with PC SW Gigaset QuickSync and full user

Author

Name: Horst, Lindmeier

Org.: Gigaset Communcations GmbH, PM V

Tel.: +49-89-722-32733

E-Mail: horst.lindmeier@gigaset.com

Copyright Gigaset 2010

Reproduction of the content of this document in whole or part and/or its disclosure to a third party is strictly forbidden without the permission of its owner. Offenders are liable to pay for the damages. All rights reserved in the event of the grant of a patent or the registration of a utility model or design.

Color

o silver black

Market Introduction

(M3 in June 2010)

Market launch in July 2010 (Germany)

History of Changes

Version	Date	Author(s)	Remake
1.0	29.08.2008	Horst Lindmeier	M0: Version1.0
2.0	7.4.2009	Horst Lindmeier	M1: Version 2.0
	12.5.2009	Horst Lindmeier	Adaption Number of Phonebook-Entries, number of Function keys
2.1	9.12.2009	Horst Lindmeier	Name and picture added
2.2.	4.2.2010	Horst Lindmeier	Answering Machine: Recording Time 55 Minutes

COMPUTER & TELEPHONE SERVICES LTD NZ 0800 366363 / info@cts.co.nz

