

STAY CONNECTED IN HD - ANYWHERE YOU GO



- HD Dual-Lens camera
- Real-Time (30fps) HD 1280x800 Mega-pixel resolution
- View & Record anytime, anywhere
- Control with Smartphone/Tablet App
- Dual-Lens for enhanced day & night video
- 2-Way audio with internal speaker and microphone
- Built-in Infrared temperature sensor with alarm feature
- Event Push notifications
- Easy 3-Step Set-up



RECORD, PLAYBACK & SHARE.

Record directly to the camera, your smartphone, tablet, PC or Mac. Multiple recording options, no recurring fees.*

DUAL MOTION DETECTION.


Advanced audio & motion sensors with smart video motion detection for improved alert accuracy.

EXPAND YOUR VIEW.

Watch over multiple locations simultaneously. Your home, your office or your vacation property, all in one screen.⁵

QUICK SETUP.

Activate your camera by simply scanning a QR code with your smartphone or tablet.

**LIVE** PING**LNC204 Series**

► FEATURES

- iOS, Android, PC and Mac compatible*
- Real-Time (30fps) HD 1280x800 Mega-pixel resolution
- Wi-Fi & wired internet connectivity
- 5 Second pre-recording on SD card
- Easy connection to Wi-Fi networks with WPS ¹
- Night vision up to 30ft with single high-power IR LED ²
- microSD recording & playback supported ³
- Infrared thermometer and temperature alarm control
- Built-in Speaker and Mic for 2-way audio
- Dual motion detection: PIR & video
- Sound activated alerts
- Push notification of events & email alerts with snap shot attachment
- H.264 video compression
- Supports up to 20 simultaneous users
- Triple streaming for simultaneous SD card, PC and Mobile Recording ⁴
- Flexible indoor mounting (counter, wall, ceiling)
- Expandable up to 4 cameras
- Watchdog function to prevent system failure

► EASY THREE STEP SETUP

STEP 1



INSTALL FREE APP

STEP 2



SCAN QR CODE

STEP 3

VIEW YOUR WORLD



Mobile Application - iPad, iPhone & Android App shown.
 (tablet and mobile phones not included)



PC Viewing Application. (PC not included)

www.lorextechnology.com


• SPECIFICATIONS

Mode:	Day & Night	Video management software:	L-View software for viewing and recording up to 4 cameras (PC/Mac)
Power:	5V (USB) - 12V, 1A		Lorex Ping app for viewing cameras on mobile (iOS/Android™)
Processors:	RISC CPU, hardware video processing and compression.	Security:	Web management username/password protection
Network interface:	Ethernet 10BaseT/100BaseTX, Auto-MDIX, RJ-45		Video display ID/password protection
Wireless interface:	IEEE 802.11b / g / n	Installation, management and maintenance:	WiFi WEP and WPA/WPA2 security mode
Image sensor:	HD up to 1280x800 resolution 1/4" Megapixel Color CMOS Separate sensors for day and night with automatic gain, white balance, exposure and brightness control Effective distance – 7 meters		Plug & play by ID/password. Firmware upgrades via FTP L-View SW upgrade Push Notification
PIR sensor:	Automatically turn on the IR LED on low light environment.	Users	Up to 20 simultaneous users (depends on video settings and internet bandwidth)
Light sensitivity:	0.2 Lux (IR LED off) 0 Lux (with 9 meters IR LED on)	Alarm and event management:	Events triggered by PIR and sound detection Email/ftp alarm message Temperature alarm for low/high room temperature Push notification on supported mobile devices.
Infrared thermometer:	Infrared Range: -40 ~ 115 °C, accuracy: ±0.5°C		68 x 25 x 95mm/2.8 x 1.0 x 3.7" (W x D x H)
Lens:	4.2 mm, F2.4, viewing angle: 66°, fixed iris. Day and night separate lens	Dimensions:	0.28kg/0.62lbs (including camera bracket)
Buttons:	One reset button, to factory default settings One WPS button for automatic WiFi setup One LED for Internet connection status indication	Weight:	EMC - CE, FCC Part 15 Subpart B Class B, IC Class B
Indicators:	One LED for Ethernet connection indication One LED for SD card recording indication	Approvals:	Wireless RF - CE, FCC Part 15 Subpart C, RSS210
Video compression:	H.264, baseline profile level 3.1		Power supply: CE, FCC, UL, EN 60950
Video streaming:	Separate frame rate/resolution/bandwidth settings for PC and mobile.	Operating conditions	0-50 °C Humidity 20 – 80% RH (non-condensing)
Resolution:	1280x800, 1024x768, VGA(640x480), QVGA(320x240)		
Bandwidth:	64Kbps ~ 3Mbps		
Frame rate:	1~30 fps		
Audio:	Built-in 0.5W speaker for alarm and half-duplex two-way audio. Speaker jack for external speaker		

• PRODUCT INFORMATION

MODEL	CONFIGURATION	PACKAGE	W x D x H	WEIGHT	CUBE	UPC Code
LNC204	Wireless HD Network Camera	Retail Giftbox	162 x 89 x 162mm/ 6.4 x 3.5 x 6.4"	0.53 kg/1.2 lbs	0.0024 CBM x 0.085 CBF	7-78597-00204-1
Includes:	1 IP Camera, 1 Camera Bracket, 1 Ethernet cable, 1 Power adapter, Quick Start Guide, CD (user manual included on CD)					

Dimensions:



• DISCLAIMERS

1. Compatible with WPS enabled routers (not included).
2. Infrared illumination range under ideal conditions. Actual range and clarity may vary depending on scene/object reflection and camera application.
3. microSD Card not included (supports up to 32GB).
4. Connection speed may vary depending on internet bandwidth.
5. Up to 4 simultaneous camera views available on PC, Mac and tablets. Selectable single camera viewing on smartphones.

Lorex Technology Inc.

250 Royal Crest Court
Markham, Ontario L3R 3S1
Canada

901 Elkridge Landing Road, Suite 100
Linthicum, Maryland 21090
USA

www.lorextechnology.com

©2013 Lorex Technology Inc.
As our product is subject to continuous improvement, Lorex Technology & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE