I²C and SMBus Control DLL User's Manual

Version 4

Date: February 16, 2004



Information provided in this document is solely for use with Win-I2CNTDLL. SB Solutions reserves the right to make changes or improvements to this document at any time without notice. We assume no liability whatsoever in the sale or use of this product, including infringement of any patent or copyright. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of SB Solutions.

Microsoft Visual Basic, Windows and Windows NT are registered trademarks of Microsoft Corporation. Other brand names are trademarks or registered trademarks of their respective owners.

Delphi is a trademark of Borland International, Inc.

Questions or comments regarding this document should be emailed to: support@demoboard.com.

Suggestions for enhancements should be emailed to: support@demoboard.com.

© 1999-2004 SB Solutions. All rights reserved.

Revision 4 Feb-04

Table of Contents

I ² C PROTOCOL	<u>5</u>
GENERAL CHARACTERISTICS	5
BIT TRANSFER	
START AND STOP CONDITIONS	5
I2C ADDRESS	5
SUBADDRESS	
DATA TRANSFER	6
ACKNOWI EDGE	
I ² C Bus Documentation	6
MINIMUM SYSTEM CONFIGURATION	7
	-
WIN-I2CNIDLL CONTENIS	<u>7</u>
FILES INSTALLED SPECIFICALLY FOR WIN-I2CNTDLL	7
FILES INSTALLED SPECIFICALLY FOR WIN-I2CNT	7
COMMON FILES INSTALLED FOR WIN-I2CNTDLL AND WIN-I2CNT:	7
LOCATION OF DI L	7
	····· /
TESTING THE INSTALLATION	7
TESTING THE INSTALLATION	7
TESTING THE INSTALLATION	
TESTING THE INSTALLATION	7
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADE?	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS Why upgrade? Upgrading from Win-I2CNTDLL V3.2 and earlier to Win-I2CNTDLL V4.x	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS Why upgrade? Upgrading from Win-I2CNTDLL V3.2 and earlier to Win-I2CNTDLL V4.x EXPORTED FUNCTIONS USING THE STDCALL CONVENTION	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-I2CNTDLL V3.2 AND EARLIER TO WIN-I2CNTDLL V4.x EXPORTED FUNCTIONS USING THE STDCALL CONVENTION	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-I2CNTDLL V3.2 AND EARLIER TO WIN-I2CNTDLL V4.X EXPORTED FUNCTIONS USING THE STDCALL CONVENTION CHECKDRIVERSTATUS CHECKDRIVERSTATUS	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-I2CNTDLL V3.2 AND EARLIER TO WIN-I2CNTDLL V4.X EXPORTED FUNCTIONS USING THE STDCALL CONVENTION CHECKDRIVERSTATUS CLOSEI2CDRIVER	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-I2CNTDLL V3.2 AND EARLIER TO WIN-I2CNTDLL V4.x EXPORTED FUNCTIONS USING THE STDCALL CONVENTION CHECKDRIVERSTATUS CLOSEI2CDRIVER	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-I2CNTDLL V3.2 AND EARLIER TO WIN-I2CNTDLL V4.x EXPORTED FUNCTIONS USING THE STDCALL CONVENTION CHECKDRIVERSTATUS CLOSEI2CDRIVER GETACCESSMODE GETL PT A DREES	
TESTING THE INSTALLATION	
TESTING THE INSTALLATION	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-I2CNTDLL V3.2 AND EARLIER TO WIN-I2CNTDLL V4.X EXPORTED FUNCTIONS USING THE STDCALL CONVENTION CHECKDRIVERSTATUS CLOSEI2CDRIVER GETACCESSMODE GETLPTADDRESS GETLPTADDRESS GETMAXI2CFREQUENCY HARDWARE	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-I2CNTDLL V3.2 AND EARLIER TO WIN-I2CNTDLL V4.x EXPORTED FUNCTIONS USING THE STDCALL CONVENTION CHECKDRIVERSTATUS CLOSEI2CDRIVER GETACCESSMODE GETLPTADDRESS GETLPTNUMBER GETMAXI2CFREQUENCY HARDWAREDETECT	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-I2CNTDLL V3.2 AND EARLIER TO WIN-I2CNTDLL V4.X EXPORTED FUNCTIONS USING THE STDCALL CONVENTION CLOSEI2CDRIVER GETACCESSMODE GETI2CFREQUENCY GETLPTADRESS. GETLPTNUMBER GETMAXI2CFREQUENCY HARDWAREDETECT I2C_READ	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-I2CNTDLL V3.2 AND EARLIER TO WIN-I2CNTDLL V4.x EXPORTED FUNCTIONS USING THE STDCALL CONVENTION CHECKDRIVERSTATUS CLOSEI2CDRIVER GETACCESSMODE GETL2CFREQUENCY GETLPTADDRESS. GETLPTADDRESS. GETLPTNUMBER GETMAXI2CFREQUENCY	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-I2CNTDLL V3.2 AND EARLIER TO WIN-I2CNTDLL V4.x EXPORTED FUNCTIONS USING THE STDCALL CONVENTION CheckDriverStatus CLOSEI2CDRIVER GETACCESSMODE GETLPTADRESS GETLPTADRESS GETMAXI2CFREQUENCY HARDWAREDETECT I2C_READ I2C_READARRAY I2C READARRAY	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-12CNTDLL V3.2 AND EARLIER TO WIN-12CNTDLL V4.x EXPORTED FUNCTIONS USING THE STDCALL CONVENTION CHECKDRIVERSTATUS CLOSE12CDRIVER GETACCESSMODE GETL2CFREQUENCY GETMAX12CFREQUENCY HARDWAREDETECT 12C_READARRAY 12C_READARRAYNS 12C_READRATE	
TESTING THE INSTALLATION UPGRADING FROM EARLIER VERSIONS WHY UPGRADE? UPGRADING FROM WIN-I2CNTDLL V3.2 AND EARLIER TO WIN-I2CNTDLL V4.x EXPORTED FUNCTIONS USING THE STDCALL CONVENTION CheckDriverStatus CloseI2CDRIVER GETACCESSMODE GETLPTADDRESS GETLPTADDRESS GETMAXI2CFREQUENCY HARDWAREDETECT. I2C_READ I2C_READARRAY I2C_READARRAYNS I2C_READBYTE	
TESTING THE INSTALLATION	
TESTING THE INSTALLATION	

I2C_WRITEARRAY	
I2C10_WRITEARRAY	
I2C_WRITEBYTE	
MILLISECONDS	
OPENI2CDRIVER	
SETNORMALACCESSMODE	
SETI2CFREQUENCY	
SETLPTNUMBER	
SETSLOWACCESSMODE	15
SETWAITTIME	

CHECKDRIVER	16
GET_ACCESSMODE	16
GETADDRESS	16
GetFrequency	16
GetLPT	16
GetMaxFrequency	16
HWDETECT	16
I2CREAD	17
I2CSTART	17
I2CSTOP	17
I2CWRITE	17
MSDELAY	17
READARRAY	17
READARRAYNS	18
READBYTE	18
SetFrequency	18
SETLPT	19
SetNormalMode	19
SETSLOWMODE	19
SetWait	19
STARTI2CDRIVER	19
STOPI2CDRIVER	20
WRITEARRAY	20
WRITEBYTE	20
	• •
ERROR CODES	<u> 21</u>
EXAMPLES	<u> 22</u>

VISUAL BASIC EXAMPLE	. 22
DELPHI EXAMPLE	. 23

I²C Protocol

General Characteristics

The I²C protocol allows data to be transferred between devices using two open-drain (or open-collector) bidirectional lines. One line is the serial clock (SCL) and the other is the serial data (SDA). The bus master generates the Start conditions, the clock signals on SCL, as well as the Stop condition. An acknowledge is transmitted by the receiving device on the bus after each byte is sent.

Bit Transfer

Data on SDA must be stable while SCL is high. The state of SDA when SCL is high determines the logic level of the transmitted data bit.

Start and Stop Conditions

Within the procedure of the I²C bus, unique situations arise which are defined as START and STOP conditions. A HIGH to LOW transition on the SDA line while SCL is HIGH is one such unique case. This situation indicates a START condition. A LOW to HIGH transition on the SDA line while SCL is HIGH defines a STOP condition. The master always generates START and STOP conditions. The bus is considered to be busy after the START condition. The bus is considered to be free again a certain time after the STOP condition.



I²C Address

The first seven bits of an I²C transmission, after a Start condition, make up the slave address. The eighth bit (or the least significant bit) is the R/W bit that determines the direction of the message.



A '0' in the least significant position of the first byte means that the master will WRITE information to the selected slave. A '1' in this position means that the master will READ information from the slave. When an I²C address is sent, each device in a system compares the first seven bits after the START condition with its own address. If they match, the device considers itself addressed by the master as a slave-receiver or slave-transmitter, depending on the R/W bit.

When transmitting an address using Win-I2CNTDLL, the user should use the I2CWrite or I2C_Write functions and then ensure that the correct least significant bit has been appended ('1' for read, '0' for write). See the Examples section for further information.

Subaddress

When an I²C device contains more than one register, the various registers are generally accessed using a subaddress that is sent following the device address (see the WriteArray and ReadArray sections below). The subaddress acts like a pointer to the register that needs to be accessed.

Data Transfer

Every byte on the SDA line must be 8-bits long. The number of bytes that can be transmitted per transfer is unrestricted. Each byte must also be followed by an acknowledge bit. Data is transferred with the most significant bit first. If a receiver can't receive another complete byte of data until it has performed some other function, it can hold the clock line SCL low to force the transmitter into a wait state. Although the I²C specification does not specify a maximum wait state, Win-I2CNTDLL has set an arbitrary maximum wait state length of approximately 50ms.

Acknowledge

The acknowledge related clock pulse is generated by the master (Win-I2CNT and Win-I2CNTDLL are always the bus masters). The transmitter releases the SDA line during the acknowledge clock pulse. The receiver must pull down the SDA line during the acknowledge clock pulse so that it remains stable low during the high period of the clock pulse.

The master-receiver signals the end of a read by not acknowledging the last byte it requires.

I²C Bus Documentation

The complete I²C Bus specification can be found at <u>http://www.philipslogic.com/products/collateral/i2c/</u>.

Minimum System Configuration

- ✓ PC with a Pentium 60 and 8MB RAM or better
- ✓ Windows 95, 98, ME, NT3.5, NT4, 2000, or XP
- ✓ 6 MB of free HDD space
- ✓ CD ROM drive (used for installation only)
- ✓ Bi-directional Parallel Port (DB-25, LPT port)

Win-I2CNTDLL Contents

- Win-I2CNTDLL installation CD ROM
- Parallel Port adapter (I2CPORT2.0) with 256-byte EEPROM

Files installed specifically for Win-I2CNTDLL

- sbsi2c4.dll this is the actual dll file you will link to your application. The installation process places this file in the appropriate Windows\System folder
- Win-I2CNTDLL User's manual (Win-I2CNTDLL v4 User's Manual.PDF; this document)
- Visual C++, Delphi, C++ Builder, LabView, and Visual Basic example files

Files installed specifically for Win-I2CNT

- Win-I2CNT.exe application
- Win-I2CNT Installation and User's Guide (Win-I2CNT UG.pdf; Acrobat version)
- Win-I2CNT Software User's Manual (Win-I2CNT Software User's Manual v4.pdf)
- Help file (I2C.hlp)

Common files installed for Win-I2CNTDLL and Win-I2CNT:

TVICHW32.SYS - installed in the WinNT\system32 directory (Windows NT, 2000, XP only) TVICHW32.VXD - installed in the Windows\System directory (Windows 95, 98, ME only) TVicHW32.DLL - installed for all operating systems Parallel Port Adapter schematic (I2cprt20.pdf) Software license agreement (license.txt) Win-I2CNT user Registration Form (Regfrm4x.txt)

Location of DLL

The sbsi2c4.dll is placed in the Windows\System directory during installation. The sbsi2c4.dll may be moved to the same directory as the application using the dll.

Testing the Installation

After Win-I2CNTDLL has been installed on your hard disk, the installation of the driver can be tested with the included Win-I2CNT application. The I2CPort2.0 hardware should be inserted into an available parallel port, and then the application can be started. If the installation was successful, you should be able to read and write from the on-board EEPROM using the 256x8 EEPROM from the Win-I2CNT Device pull-down menu. Note that when installing the software to a Windows NT, 2000, or XP system, you must have Administrator privileges or the parallel port drivers will not be loaded correctly. After the software has successfully been installed, normal user privileges can be restored.

Users who do not install with Administrator privileges commonly encounter a 'Privileged Instruction' error. If you see this error message, please log back on as the Administrator and reinstall the software.

Upgrading from earlier versions

Why upgrade?

- Win-I2CNTDLL v4.x adds support for Windows XP
- Win-I2CNTDLL V3.2 and earlier versions did not support Windows XP.
- Three new functions were added to Win-I2CNTDLL v4.x:
- SetWaitTime allows the user to increase the wait/hold times for slow I²C peripherals
- I2C10_WriteArray (10-bit addressing)
- I2C10_ReadArray (10-bit addressing)

Upgrading from Win-I2CNTDLL V3.2 and earlier to Win-I2CNTDLL V4.x

- 1. Uninstall the previous version of Win-I2CNTDLL, if desired
- 2. Install Win-I2CNTDLL V4.x
- 3. Your existing projects will need minor modifications to work with v4.x depending on your development software:

Visual C++

- replace the sbsi2c.h file with sbsi2c4.h
- replace the sbsi2c.lib file with sbsi2c4.lib if using stdcall calling convention or cdecl4.lib if using
- cdecl convention
- these files can be found in the Examples folder

Delphi

- add the file I2Cdeclarations.pas in your project
- the I2Cdeclarations.pas file can be found in the Delphi example directory

Visual Basic

- add the module sbsi2c4.bas in your project
- the sbsi2c4.bas file can be found in the VB example directory

Exported Functions using the stdcall convention

Most programming languages, such as Visual C++, Delphi, C++ Builder, and Visual Basic, can use the **stdcall** calling convention. The stdcall convention passes the parameters to the functions in the dll from right to left and it is up to the called functions (in this case, the functions in sbsi2c4.dll) to clean up the stack.

CheckDriverStatus

This function takes no argument and returns the current state of the hardware driver. If the return value is '1' (true) when the driver is functioning and a '0' (false) is returned if the driver is not started. Use this function to ensure that the driver is active before attempting any I²C communications.

```
C++: short int CheckDriverStatus(void)
Delphi: CheckDriverStatus: WordBool;
VB: CheckDriverStatus() As Boolean
```

Closel2CDriver

Closes the kernel-mode driver and releases memory allocated to it. It is highly recommended that this function be called before an application is terminated.

```
C++: void CloseI2CDriver(void)
Delphi: CloseI2CDriver
VB: CloseI2CDriver()
```

GetAccessMode

The GetAccessMode function determines whether the kernel-mode driver is using 'Normal' or 'Slow' access to the I/O ports. If true, 'Normal' access is in use while a false indicates that 'Slow' access is in use. 'Normal' access provides higher performance access to ports, but may fail if the port(s) addressed is already in use by another kernel-mode driver. While slower, 'Slow' access provides more reliable access to ports that have already been opened by another kernel-mode driver.

```
C/C++: short int GetAccessMode(void)
Delphi: GetAccessMode: WordBool;
VB: GetAccessMode() As Boolean
```

Getl2CFrequency

This function takes no arguments and returns the current I²C clock frequency.

C/C++: int GetI2CFrequency(void) Delphi: GetI2CFrequency: integer; VB: GetI2CFrequency() As Long

GetLPTAddress

The computer's parallel ports have a physical address that can be found using the GetLPTAddress function. This function takes no arguments and returns a two byte unsigned integer containing the LPT address. Using this function is not required but is available for the user's information.

C/C++: **short int** GetLPTAddress(**void**) Delphi: GetLPTAddress: **word**; VB: GetLPTAddress() As Integer

GetLPTNumber

The GetLPTNumber functions takes no arguments and returns the value of the currently selected parallel port. The function returns 1, 2, or 3, corresponding to LPT1, LPT2, and LPT3, respectively.

```
C/C++: unsigned char GetLPTNumbr(void)
Delphi: GetLPTNumber: byte;
VB: GetLPTNumber() As byte
```

GetMaxI2CFrequency

The GetMaxI2CFrequency function returns the maximum I²C clock frequency possible with the user's computer hardware. The value is hardware dependent.

C/C++: int GetMaxI2CFrequency(void) Delphi: GetMaxI2CFrequency: integer; VB: GetMaxI2Cfrequency() As Long

HardwareDetect

This function checks to see if the I2CPort2.0 hardware is attached to the currently selected parallel port. The two byte boolean value returned by HardwareDetect contains true (non-zero) if hardware was detected while the return value is false ('0') if the hardware was not detected. It is important to ensure that hardware is detected since no I²C communications will begin until hardware has been detected. Therefore, after calling the SetLPTNumber function, it is a good idea to call HardwareDetect to see if the Win-I2CNT hardware was detected.

```
C/C++: short int HardwareDetect(void)
Delphi: HardwareDetect: wordbool;
VB: HardwareDetect() As Boolean
```

I2C_Read

This function takes a two byte boolean value and a pointer to data byte and then reads one byte from the I²C bus. The boolean value indicates whether the byte will be the last byte read from the I²C bus. A true ('1') indicates that it is the last byte to read while a false ('0') indicates that additional bytes will be read. The returned value contains the error condition. See Error Codes section for return values. The data byte is written to the memory location specified by Data.

```
C/C++: unsigned char I2C_Read(short int LastByte, unsigned char *Data)
Delphi: I2C_Read(LastByte: wordbool; var Data: byte): byte;
VB: I2C_Read(ByVal LastByte As Boolean, ByRef Data As Byte) As Byte
```

I2C_ReadArray

The I2C_ReadArray function takes four arguments: the device address, the device subaddress, the number of bytes to read, and a pointer to an element within an array of bytes. I2C_ReadArray sends the I²C message shown below and returns any error condition it encounters. It is the calling program's responsibility to allocate the correct memory space for the array. The function ensures that the lsb of the address is appropriate ('1' or '0' depending on Write or Read) before it is sent to the target device.

```
C/C++: unsigned char I2C_ReadArray(unsigned char address,
    unsigned char subaddress, int nBytes, unsigned char *ReadData)
Delphi: I2C_ReadArray(address, subaddress: byte; nBytes: integer;
    var ReadData): byte;
VB: I2C_ReadArray(ByVal address, ByVal subaddress As Byte, nBytes As
    Long, ByRef ReadData As Byte) As Byte
```



I2C10_ReadArray

The I2C10_ReadArray function (read an array with 10-bit device addressing) is similar to the I2C_ReadArray function, however, it uses 10-bit I²C addressing. The I²C specification states that the 10-bit address has the following format:

First byte: 1111 0xx + R/W bit

Second byte: xxxx xxxx; where x = the 10 bits of address

The function takes the received 16-bit address data and uses the lower 10 bits to generate the proper 10-bit I²C compliant format. A subaddress is also sent after the second byte of the address (not shown in diagram below).



C/C++: unsigned char I2C10_ReadArray(short int address,

unsigned char subaddress, int nBytes, unsigned char *ReadData)
Delphi: I2C10_ReadArray(address: word ,subaddress: byte; nBytes: integer;

var ReadData): **byte**;

VB: I2C10_ReadArray(ByVal address As Integer, ByVal subaddress As Byte, nBytes As Long, ByRef ReadData As Byte) As Byte

I2C_ReadArrayNS

The I2C_ReadArrayNS function (read an array with no subaddress) is similar to the I2C_ReadArray function, however, it does not perform the write to a subaddress before the read is transmitted. This function takes three arguments: the device address, the number of bytes to read, and a pointer to an element within an array of bytes. It is the calling program's responsibility to allocate the correct memory space for the array. The function ensures that the lsb of the address is set to a '1' before it is sent to the target device.

C/C++: unsigned char I2C_ReadArrayNS(unsigned char address, int nBytes, unsigned char *ReadArray)

I2C_ReadByte

The I2C_ReadByte function reads one byte from an I²C bus/SMBus device. The function takes the device address and a pointer to a locatioon in memory to store the data byte. I2C_ReadByte returns any error condition it encounters. The function ensures that the lsb of the address is a '1' before it is sent to the target device.

```
C/C++: unsigned char ReadByte(unsigned char address, unsigned char *ReadData)
```

Delphi: ReadByte(address: **byte**; var ReadData: **byte**): **byte**;

VB: ReadByte(**ByVal** address **As Byte**, **ByRef** ReadData **As Byte**) **As Byte**



I2C_Start

This function takes no arguments and generates an I²C Start Condition via the parallel port. The function returns any error condition it encounters. If the hardware has not been detected, the Start condition will not be performed. See Error Code section for return values.

```
C/C++: unsigned char I2C_Start(void)
Delphi: I2C_Start: byte;
VB: I2C_Start() As Byte
```

I2C_Stop

This function generates an I²C Stop Condition via the parallel port. The function returns any error condition it encounters during the transmission. See Error Code section for return values.

```
C/C++: unsigned char I2C_Stop(void)
Delphi: I2C_Stop: byte;
VB: I2C_Stop() As Byte
```

I2C_Write

This function writes one byte, passed by the calling program, to the I²C bus via the parallel port. The function returns any error condition it encounters during the transmission. See Error Code section for return values.

```
C/C++: unsigned char I2C_Write(unsigned char DataByte)
Delphi: I2C_Write(DataByte: byte): byte;
VB: I2C_Write(ByVal DataByte As Byte) As Byte
```

I2C_WriteArray

The I2C_WriteArray takes four parameters: device address, device subaddress, number of bytes to be sent, and a pointer to an element within an array of bytes. It is up to the calling program to correctly define the array of

memory to store the data. The function ensures that the lsb of the address is a '0' before it is sent to the target device. The function returns any error conditions it encounters. See Error Code section for return values.

unsigned char I2C WriteArray(unsigned char address, unsigned char C/C++: subaddress; int nBytes; unsigned char *WriteData)

```
Delphi: I2C WriteArray(address, subaddress: byte; nBytes: integer;
        var WriteData: byte): byte;
```

VB:

I2C_WriteArray (ByVal address As Byte, ByVal subaddress As Byte, ByVal nBytes As Long, ByRef WriteData As Byte) As Byte



I2C10_WriteArray

The I2C10_WriteArray function (write an array with 10-bit device addressing) is similar to the I2C_WriteArray function, however, it uses 10-bit I²C addressing. The I²C specification states that the 10-bit address has the following format:

First byte: 1111 0xx + R/W bit

Second byte: xxxx xxxx; where x = the 10 bits of address

The function takes the received 16-bit address data and uses the lower 10 bits to generate the proper 10-bit I²C compliant format. A subaddress is also sent after the second byte of the address (not shown in diagram below), followed by the data.



subaddress; int nBytes; unsigned char *WriteData)

Delphi: I2C10_WriteArray(address, subaddress: byte; nBytes: integer; var WriteData: byte): byte;

VB: I2C10_WriteArray(ByVal address As Integer, ByVal subaddress As Byte, ByVal nBytes As Long, ByRef WriteData As Byte) As Byte

I2C_WriteByte

The I2C_WriteByte function writes one data byte to an I²C bus device. The function takes two parameters: the device address and a single data byte and returns any error condition it encounters (see Error Codes section). The function ensures that the lsb of the address is a '0' before it is sent to the target device.

C/C++: unsigned char I2C_WriteByte(unsigned char address, unsigned char Data)

Delphi: I2C_WriteByte(address,Data: **byte**): **byte**; VB: I2C_WriteByte(**ByVal** address **As Byte**, **ByVal** Data **As Byte**) **As Byte**



milliseconds

The milliseconds delay function allows the user to program a delay, measured in milliseconds, into their I²C messages. This is particularly useful when programming EEPROM devices that require a minimum erase/write time between write transactions.

```
C/C++: void milliseconds(int Data)
Delphi: milliseconds(Data: integer);
VB: milliseconds(ByVal Data As Long)
```

OpenI2CDriver

Loads the virtual device driver under Windows 95/98/ME or the kernel mode device driver under Windows NT/2000/XP, providing direct access to the LPT ports. If the driver was successfully opened, the function returns True; if the function fails it returns False.

The only valid device numbers that may be passed to OpenI2CDriver is either '0' or '1'. Only one instance of device '0' and one instance of device '1' may be started at one time, therefore, only two applications may access the kernel mode driver. Note that Win-I2CNT uses '1' so if you have Win-I2CNT running, you will be limited to using '0'.

```
C/C++: short int OpenI2CDriver(int device)
Delphi: OpenI2CDriver(device: integer): wordbool;
VB: OpenI2CDriver(ByVal device As Long) As Boolean
```

SetNormalAccessMode

The SetNormalAccessMode function puts the kernel-mode driver in 'Normal' access mode to the I/O ports. 'Normal' access provides higher performance access to ports, but may fail if the port(s) addressed is already in use by another kernel-mode driver. While slower, 'Slow' access provides more reliable access to ports that have already been opened by another kernel-mode driver.

If a false is returned by the function, the kernel-mode driver failed and it will need to reopened in Slow access mode.

C/C++: **short int** SetNormalAccessMode(**void**) Delphi: SetNormalAccessMode: **wordbool**; VB: SetNormalAccessMode() **As Boolean**

SetI2CFrequency

This function sets the I²C clock frequency to the value passed by the user's program. The frequency must be a positive integer. If a frequency is selected which is above the maximum frequency (use GetMaxI2CFrequency

to determine the value), the dll will set the frequency to the maximum I²C frequency. The function returns the measured frequency.

It is important to note that although we expect better than 5% tolerance on the frequency, the actual frequency generated by Win-I2CNTDLL cannot be guaranteed. If an accurate frequency is needed, it is recommended that the frequency be verified using test equipment.

```
C/C++: int SetI2CFrequency(int frequency)
Delphi: SetI2CFrequency(frequency: integer): integer;
VB: SetI2Cfrequency(ByVal frequency As Long) As Long
```

SetLPTNumber

If you have more than one parallel port in your computer, you can choose which parallel port to communicate with, by using the SetLPTNumber function. The function allows you to choose values 1, 2, or 3 corresponding to LPT1, LPT2, and LPT3 respectively. The 16-bit boolean return value is 'true' ('1') if the parallel port was detected and set to the value passed to the function, while it returns 'false' ('0') if the chosen parallel port was not available. The dll initialization routine attempts to set the active parallel port to LPT1.

```
C/C++: short int SetLPTNumber(unsigned char LPT)
Delphi: SetLPTNumber(LPT: byte): wordbool;
VB: SetLPT (ByVal LPT As Byte) As Boolean
```

SetSlowAccessMode

The SetSlowAccessMode function puts the kernel-mode driver in 'Slow' access mode to the I/O ports. 'Slow' access provides lower performance access to ports, but is more reliable when another kernel-mode driver has already opened the port.

There may also be situations where you want to use 'Slow' access mode as it adds additional set-up and hold times to the I^2C signal.

When the driver is initially started, the default state is 'Slow' access mode.

```
C/C++: short int SetSlowAccessMode(void)
Delphi: SetSlowAccessMode: wordbool;
VB: SetSlowAccessMode() As Boolean
```

SetWaitTime

The I²C bus specification does not specify the amount of time that a device can hold the clock line low to inject a wait/hold state in a transmission. In order to ensure that the software responds in a predictable manner, this dll has arbitrarily set the maximum wait time between the time it releases the clock and the time that any device holding the clock line low must release the bus as 50ms. If this time is exceeded, the dll will exit the function. The SetWaitTime function allows the user to change the maximum wait/hold times for the situation where a slow device needs more than the 50ms initialized by the dll. The function returns the value set by the function. The minimum time allowed by the function is 5ms.

```
C/C++: int SetWaitTime(int NewWaitTime)
Delphi: SetWaitTime(NewWaitTime: integer): integer;
VB: SetWaitTime(ByVal NewWaitTime As Long) As Long
```

Exported Functions using a C type calling convention (cdecl)

For programming languages that require a C calling convention (cdecl) use the functions listed below. In the cdecl calling convention, parameters are passed on the stack from right to left, and it is up to the application using the dll to clean up the stack.

CheckDriver

This function takes no argument and returns the current state of the hardware driver. If the return value is '1' (true) when the driver is functioning and a '0' (false) is returned if the driver is not started. Use this function to ensure that the driver is active before attempting any I²C communications.

short int CheckDriver(void)

Get_AccessMode

The Get_AccessMode function determines whether the kernel-mode driver is using 'Normal' or 'Slow' access to the I/O ports. If true, 'Normal' access is in use while a false indicates that 'Slow' access is in use. 'Normal' access provides higher performance access to ports, but may fail if the port(s) addressed is already in use by another kernel-mode driver. While slower, 'Slow' access provides more reliable access to ports that have already been opened by another kernel-mode driver.

short int Get_AccessMode(void)

GetAddress

The computer's parallel ports have a physical address that can be found using the GetLPTAddress function. This function takes no arguments and returns a two byte unsigned integer containing the LPT address. Using this function is not required but is available for the user's information.

```
short int GetAddress(void)
```

GetFrequency

This function takes no arguments and returns the current I²C clock frequency.

```
int GetFrequency(void)
```

GetLPT

The GetLPT function takes no arguments and returns the value of the currently selected parallel port. The function returns 1, 2, or 3, corresponding to LPT1, LPT2, and LPT3, respectively.

unsigned char GetLPT(void)

GetMaxFrequency

The GetMaxFrequency function returns the maximum I²C clock frequency possible with the user's computer hardware. The value is hardware dependent.

int GetMaxFrequency(void)

HWDetect

This function checks to see if the I2CPort2.0 hardware is attached to the currently selected parallel port. The two byte value returned by HWDetect contains true ('1') if hardware was detected while the return value is

false ('0') if the hardware was not detected. It is important to ensure that hardware is detected since no I²C communications will begin until hardware has been detected. Therefore, after calling the SetLPT function, it is a good idea to call HWDetect to see if the I2CPort2.0 hardware was detected. The dll initialization routine attempts to detect the hardware at LPT1 if the driver was successfully started.

short int HWDetect(void)

I2CRead

This function passes a two byte boolean value and a pointer to data byte and returns any error condition it encounters during the I²C bus transmission. See Error Code section for return values. The boolean value indicates whether the byte will be the last byte read from the I²C bus. A true ('1') indicates that it is the last byte to read while a false ('0') indicates that additional bytes will be read. The data byte, which is read from the I²C bus, is stored in the memory location specified by ReadData.

unsigned char I2CRead(short int LastByte, unsigned char *ReadData)

I2CStart

This function takes no arguments and generates an I²C Start Condition via the parallel port. The function returns a byte containing the error condition it encounters. See Error Code section for return values.

unsigned char I2CStart(void)

I2CStop

This function generates an I²C Stop Condition via the parallel port. The function returns a byte containing any error condition it finds. See Error Code section for return values.

unsigned char I2CStop(void)

I2CWrite

This function writes one byte, passed by the calling program, to the I²C bus via the parallel port. The function returns one byte containing error information. See Error Code section for return values.

unsigned char I2CWrite(unsigned char DataByte)

msDelay

The msDelay delay function allows the user to program a delay, measured in milliseconds, into their I²C messages. This is particularly useful when programming EEPROM devices that require a minimum erase/write time between write transactions.

void msDelay(int milliseconds)

ReadArray

The ReadArray function takes four arguments: the device address, the device subaddress, the number of bytes to read, and a pointer to an element within an array of bytes. ReadArray sends the I²C message shown below and returns any error condition it encounters. It is the calling program's responsibility to allocate the correct memory space for the array. The function ensures that the lsb of the address is appropriate ('1' or '0' depending on Write or Read) before it is sent to the target device.



ReadArrayNS

The ReadArrayNS (read an array with no subaddress) is similar to the I2C_ReadArray function, however, it does not perform the write to a subaddress before the read is transmitted.

This function takes three arguments: the device address, the number of bytes to read, and a pointer to an element within an array of bytes. I2C_ReadArray sends the I²C message shown below and returns any error condition it encounters. It is the calling program's responsibility to allocate the correct memory space for the array. The function ensures that the lsb of the address is set to a '1' before it is sent to the target device.

ReadByte

The ReadByte function reads one data byte from an I²C bus device. The function takes the device address and a pointer to the memory location to store the data byte. ReadByte returns any error condition it encounters. See the Error Codes section for the list of error conditions. The function ensures that the lsb of the address is a '1' before it is sent to the target device.

unsigned char ReadByte(unsigned char: address, unsigned char *ReadData)



SetFrequency

This function sets the I²C clock frequency to the value passed by the user's program. The frequency must be a positive integer. If a frequency is selected which is above the maximum frequency (use GetMaxFrequency to determine the value), the dll will set the frequency to the maximum I²C frequency. The function returns the measured frequency.

It is important to note that although we expect better than 5% tolerance on the frequency, the actual frequency generated by Win-I2CNTDLL cannot be guaranteed. If an accurate frequency is required, it is recommended that the frequency be verified using appropriate test equipment.

```
int SetFrequency(int frequency)
```

SetLPT

If you have more than one parallel port in your computer, you can choose which parallel port to communicate with, by using the SetLPT function. The function allows you to choose values 1, 2, or 3 corresponding to LPT1, LPT2, and LPT3 respectively. The 16-bit boolean return value is 'true' ('1') if the parallel port was detected, while it returns 'false' ('0') if the chosen parallel port was not available. LPT is set back to LPT1 if the requested LPT was not available.

short int SetLPT(unsigned char LPT)

SetNormalMode

The SetNormalMode function puts the kernel-mode driver in 'Normal' access mode to the I/O ports. 'Normal' access provides higher performance access to ports, but may fail if the port(s) addressed are already in use by another kernel-mode driver. While slower, 'Slow' access provides more reliable access to ports which have already been opened by another kernel-mode driver. If a false is returned by the function, the kernel-mode driver failed and it will need to reopened in Slow access mode.

```
short int SetNormalMode(void)
```

SetSlowMode

The SetSlowMode function puts the kernel-mode driver in 'Slow' access mode to the I/O ports. 'Slow' access provides lower performance access to ports, but is more reliable when another kernel-mode driver has already opened the port. There may also be situations where you want to use 'Slow' access mode as it adds additional set-up and hold times to the I^2C signal.

When the driver is initially started, the default state is 'Slow' access mode.

```
short int SetSlowMode(void)
```

SetWait

The I²C bus specification does not specify the amount of time that a device can hold the clock line low to inject a wait state in a transmission. In order to ensure that the software responds in a predictable manner, this dll has arbitrarily set the maximum wait time between the time it releases the clock and the time that any device holding the clock line low must release the bus to 50ms. If this time is exceeded, the dll will exit the function. The SetWait function allows the user to change the maximum wait/hold times for the situation where a slow device needs more than the 50ms initialized by the dll. The function returns the value set by the function. The minimum time allowed by the function is 5ms.

```
C/C++: int SetWait(int NewWaitTime)
Delphi: SetWait(NewWaitTime: integer): integer;
VB: SetWait(ByVal NewWaitTime As Long) As Long
```

Startl2CDriver

Loads the virtual device driver under Windows 95/98/ME or the kernel-mode device driver under Windows NT/2000/XP, providing direct access to the LPT ports. If the driver was successfully opened, the function returns True; if the function fails it returns False.

The only valid device numbers that may be passed to OpenI2CDriver is either '0' or '1' (Other values have no effect). Only one instance of device '0' and one instance of device '1' may be started at one time, therefore, only two applications may access the kernel-mode driver. Note that Win-I2CNT uses '1' so if you have Win-I2CNT running, you will be limited to using device '0'.

```
short int StartI2CDriver(device: integer)
```

Stopl2CDriver

Closes the kernel-mode driver and releases memory allocated to it. It is highly recommended that this function be called before an application is terminated.

void StopI2CDriver(void)

WriteArray

The WriteArray takes four parameters: device address, device subaddress, number of bytes to be sent, and a pointer to an element within an array of bytes. It is up to the calling program to correctly define the array of data. The function ensures that the lsb of the address is a '0' before it is sent to the target device.



WriteByte

The WriteByte function writes one data byte to an I²C bus device. The function takes two parameters: the device address and a single data byte and returns any error condition it encounters (see Error Codes section). The function ensures that the lsb of the address is a '0' before it is sent to the target device.

unsigned char WriteByte(unsigned char address, unsigned char Data)



Error Codes

The following error codes are returned by the various functions in sbsi2c4.dll:

```
0x00: No error
0x01: Address not acknowledged (only valid for a WriteByte, ReadByte, WriteArray, ReadArray function)
0x02: Acknowledge not received
0x03: Read acknowledge corrupted - should be a '1' but a '0' was found
0x04: SCL/SDA stuck low - both lines found low while they should be high
0x08: SDA stuck low - SDA line could not be set to a logic '1'
0x09: SDA stuck high - SDA line could not be set to a logic '0'
0x08: SDA and SCL stuck high - both SDA and SCL could not be set low
0x80: SCL stuck low - SCL line could not be set to a logic '1'
0x08: SDA and SCL stuck high - both SDA and SCL could not be set low
0x80: SCL stuck low - SCL line could not be set to a logic '1'
```

Examples

Visual Basic Example

This example writes two bytes to the EEPROM, located on the I2CPort2.0 hardware, and then reads them back.

In order to use the dll functions, they must be imported into the calling program. Add the Modulel.bas file (included with Win-I2CNTDLL) into your project. See the Visual Basic example included with Win-I2CNTDLL.

The following code example writes two bytes to an EEPROM, and then reads them back. The user should ensure that the error codes returned from the functions are handled appropriately.

Private Sub Command1_Click() Dim ErrorCode As Byte Dim ReadData As Byte Dim Init As Boolean Frequency As Integer 'Check to ensure that the hardware driver has been Init=CheckDriverStatus 'loaded successfully and the hardware is detected. Init=HardwareDetect Init=SetLPTNumber(1) //Set the LPT Number. Frequency=SetI2CFrequency(50) //Set the I²C clock frequency to 50 KHz. ErrorCode=I2C Start 'Generate I²C Start Condition. ErrorCode=I2C_Write(174) 'Send the EEPROM address ... in this case 0xAE. 'Send the subaddress. ErrorCode=I2C_Write(0) ErrorCode=I2C Write(0) 'Send first data byte. ErrorCode=I2C Write(1) 'Send second data byte. ErrorCode=I2C_Stop 'Generate I²C Stop Condition. milliseconds(50) 'wait 50ms for the erase/write cycle to complete. ErrorCode=I2C_Start 'Generate I²C Start Condition. ErrorCode=I2C_Write(174) 'Send the EEPROM write address in this case 0xAE. ErrorCode=I2C_Write(0) 'Send the subaddress. ErrorCode=I2C_Start 'Generate I²C Start Condition. ErrorCode=I2C_Write(175) 'Send the EEPROM read address... in this case 0xAF. ErrorCode=I2C_Read(false,ReadData) 'Read one byte (not last byte). Label1.Caption=Int(ReadData) ErrorCode=I2C_Read(true,ReadData) 'Read one byte (last byte). Label2.Caption=Int(ReadData) ErrorCode=I2C_Stop 'Generate I²C Stop Condition. End Sub

Delphi Example

This example writes two bytes to an EEPROM, located on the I2CPort2.0 hardware, and then reads them back. Before writing or reading, it is best to go through an initialization process to ensure everything is functioning correctly. This example code shows the minimum functionality and it is up to the user to ensure the returned error codes are handled appropriately.

In order to use the dll functions, they must be imported into the calling program. The easiest way to do this is to add the I2Cdeclarations.pas file (included with Win-I2CNTDLL) to your project by placing this file in the same folder as your project and then using the 'Add to Project' menu item from the 'Project' menu in Delphi. You must also add 'I2Cdeclarations' statement in the **uses** clause of your application (see example in the Delphi folder which was installed with Win-I2CNTDLL).

```
procedure TDLLForm.btnWriteandRead(Sender: TObject);
var
ErrorCode, ReadData: byte;
InitOK: WordBool;
Freq: integer;
begin
                             //Check to ensure that the hardware driver has been
if CheckDriver then
                             //loaded successfully.
begin
                             //Check to ensure that the hardware is detected.
InitOK:=HardwareDetect;
InitOK:=SetLPTNumber(1);
                             //Set the LPT Number.
Freq:=SetI2CFrequency(50); //Set the I<sup>2</sup>C clock frequency to 50KHz.
                             //It is not necessary to set the frequency
                             //since it defaults to 10KHz at start-up
ErrorCode:=I2C_Start;
                             //Generate I<sup>2</sup>C Start Condition.
ErrorCode:=I2C Write(174); //Send the EEPROM address ... in this case 0xAE.
ErrorCode:=I2C_Write(0);
                            //Send the subaddress.
ErrorCode:=I2C Write(0);
                            //Send first data byte.
ErrorCode:=I2C_Write(1);
                             //Send second data byte.
ErrorCode:=I2C_Stop;
                             //Generate I<sup>2</sup>C Stop Condition.
milliseconds(50);
                             //wait 50ms for the erase/write cycle to complete.
ErrorCode:=I2C_Start;
                             //Generate I<sup>2</sup>C Start Condition.
ErrorCode:=I2C_Write(174); //Send the EEPROM write address...in this case 0xAE.
ErrorCode:=I2C_Write(0);
                            //Send the subaddress.
ErrorCode:=I2C Start;
                             //Generate I<sup>2</sup>C Start Condition.
ErrorCode:=I2C_Write(175); //Send the EEPROM read address... in this case 0xAF.
ErrorCode:=I2C_Read(false,ReadData);//Read one byte from the EEPROM, not last byte.
Label1.Caption := IntToStr(ReadData);
ErrorCode:=I2C_Read(true); //Read one byte from the EEPROM, last byte.
Label2.Caption := IntToStr(ReadData);
ErrorCode:=I2C Stop;
                             //Generate I<sup>2</sup>C Stop Condition.
end
else ShowMessage('Driver not started');
end;
```