RHEEM RESIDENTIAL TANKLESS

74 TANKLESS SERIES

Endless hot water for 3 bathroom homes

RTG-74PV indoor, RTG-74X outdoor and RTG-74DV indoor direct vent natural and LP models – 19,000 - 199,900 BTU max.

8.5 gal./min at 35° F rise max., 7.4 gal./min. at 45° F rise

Limited Warranty:

12-Year on heat exchanger, 5-Year on parts, 1-Year on laborSee Residential Warranty Information Brochure for complete warranty information.

- UMC-117 remote control is included and can be set from the out-of-the-box 120 degrees – up to a 140 degree maximum (additional remote control thermostats are available – sold separately)
- EZ-Link™ cable available for high demand applications to connect two tankless units to operate as one
- Exclusive! Guardian SBT™ sensing burner technology
- Exclusive! Guardian OFW™ overheat film wrap
- **Exclusive!** Two high-altitude options up to 6,560 or 9,840 ft. elevations above sea level (altitude chip required sold separately)
- Exclusive! All Rheem models can be linked in up to 20 unit manifold installations by using the optional MIC-180 and MICS-180 manifold control assembly
- All Rheem tankless models are third-party efficiency certified by GAMA
- Continuous hot water, energy saving and compact, space saving design
- Intelligent electronic controls designed to increase energy efficiency and safety
- Self diagnostic program
- · Digital display shows temperature setting and maintenance codes
- · Built-in electric blower
- Indoor units use Category III stainless steel vents and vent horizontally or vertically
- · Indoor models supplied with a 120 volt power cord
- Environmentally friendly Low NOx burner meets SCAQMD rule 1146 requirements
- Installation vent kits available sold separately
- Indoor and outdoor models feature freeze protection to -30°F





Tankless water heaters
Endless hot water





Specifications

| DESCRIPTION | | | FEATURES | | | | ROUGHING IN DIMENSIONS (SHOWN IN INCHES) | | | | | | | ENERGY INFO. | |
|---|-------------------------|-----------------------|-------------------|-----------|--------------------------------------|-----------|--|-----|--------|--------|--------|------------------------------|---------------------------|------------------|-----------------------------------|
| MODEL Number | GAS INPUT BTU/HR. | ТҮРЕ | TEMP. Range | GPM @ 77° | TER FLOW R GPM @ 45° Rise Max. | GPM @ 35° | CONNE WATER | | HEIGHT | WIDTH | DEPTH | VENT DIAMETER (INCHES) | SHIP. WEIGHT (LBS.) | ENERGY FACTOR | D.O.E. ANN. OP. COST NAT/LP |
| RHEEM TANKLESS WATER HEATERS FOR 3 BATHROOM HOMES | | | | | | | | | | | | | | | |
| RTG-74PVN-1 | 19,000 - 199,900 | Indoor | 100° to 140° F | 4.3 | 7.4 | 8.5 | 3/4 | 3/4 | 25-3/8 | 14-7/8 | 11-1/8 | 4 | 55 | .82 | \$223/\$374 |
| RTG-74XN-1 | 19,000 - 199,900 | Outdoor | 100° to 140° F | 4.3 | 7.4 | 8.5 | 3/4 | 3/4 | 25-3/8 | 14-7/8 | 11-1/8 | N/A | 55 | .82 | \$223/\$374 |
| RTG-74DVN-1 | 19,000 - 199,900 | Indoor Direct Vent | 100° to 140° F | 4.3 | 7.4 | 8.5 | 3/4 | 3/4 | 25-3/8 | 14-7/8 | 11-1/8 | 4 by 4 2-PIPE | 55 | .82 | \$223/\$374 |

All models are available in Natural Gas and Propane (LP). For Propane replace the N with P when ordering.

- Factory set maximum temperature is 120° F. See Use and Care Manual for setting.
- For installations above 3,280 feet, a high altitude chip is required. Refer to Rheem price list or consult factory for details.
- Consult factory for information on sizing the application.

Installation Vent Kits available separately: 4" diameter for RTG-74PV models.


Vent Termination Kits are required for Direct Vent models. Contact your distributor for details.

Proper gas pressure must be ensured to supply tankless gas water heaters – up to 199,900 BTU for RTG-74 models. (Consult your gas supplier)

| | Temperature Rise (°F) | | | | | | | | |
|-------------------------|-----------------------|-----|-----|-----|-----|-----|-----|-----|------|
| Model Number | 35° | 45° | 50° | 60° | 70° | 77° | 80° | 90° | 100° |
| RTG-74 Water Flow (GPM) | 8.5 | 7.4 | 6.6 | 5.5 | 4.7 | 4.3 | 4.1 | 3.7 | 3.3 |

Above estimates are for sizing purposes only.





These units are designed to meet or exceed ANSI (American National Standards Institute) requirements and have been tested according to D.O.E. test procedures and meet or -exceed the energy efficiency requirements of NAECA, ASHRAE standard 90, ICC Code and all state energy efficiency performance criteria for energy consuming appliances.

Before purchasing this appliance, read important energy cost and efficiency information available from your supplier.

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

Rheem Heating, Cooling & Water Heating 101 Bell Road • Montgomery, AL 36117-4305 1-866-720-2076 • www.rheemtankless.com

Rheem Canada Ltd./Ltée • Water Heater Division 128 Barton Street West, Hamilton, Ontario L8N 3P3

Rheem manufactures residential & commercial heating, cooling & water heating products.

Printed in U.S.A. 07/08 WP Form No. 101-50-74

Energy Factor and Average Annual Operating Costs based on D.O.E. (Department of Energy) test procedures. D.O.E. national average fuel rate natural gas \$1.218/therm; LP \$1.87/gallon.













