



*PRZEDSIĘBIORSTWO HANDLOWE
EXPORT -IMPORT - HURT*

BIURO HANDLOWE WARSZAWA

*01-797 Warszawa
ul. Powązkowska 15
tel. 0-22 / 669 10 11
fax 0-22 / 669 11 60*

ATEL ELECTRONICS

*45-323 Opole
ul. Zielonogórska 3
tel. 0-77 / 455 60 76
fax 0-77 / 455 80 56
e-mail: cust@atel.com.pl
www.atel.com.pl*

**#05215 RP-WR1910
USER'S MANUAL**

Multimedia Security Center

User's Manual

Table of Contents

Chapter 1: Introduction	1
Overview	1
Key Features	1
Package Content	2
System Requirement	2
Chapter 2: Get to know your Multimedia Router	3
Front Panel LEDs (LAN Indicators)	3
Front Panel LEDs (WAN Indicators)	4
Rear Panel Interfaces	5
Chapter 3: Connecting the Router to the Internet	6
Hardware Installation	6
Login to Web-Based Management Tool	7
Quick Setup - WAN Interface	8
Chapter 4: Interface Configurations	17
LAN Interface	17
WAN Interface	18
Wireless Interface	20
WEP Setting	23
Access Control	24
Chapter 5: Content Filtering	25
Keyword filtering	25
URL Blocking	26
Trusted IP	26
Port Checking	27
Chapter 6: Advanced Configurations	28

DHCP	28
DDNS	30
Firewall	31
Remote Management	33
Block WAN Echo Request	33
WAN Protection	33
Virtual Server	36
IP Sharing	36
NAT LoopBack	36
DMZ Host	36
UPnP	36
QoS Bandwidth Management	37
VPN	40
IPSec	40
PPTP Server	44
Static Route	45
Chapter 7: Mail Monitoring	47
Chapter 8: Maintenance	49
System Management	49
Clock	51
System Information	52
USB Device	53
Online Users	53
Firmware Upgrade	54
Restore Configuration	54
Ping	55

Trace Route	56
Log	56
Restart Router	57
Save Changes	57
Logout	58
Chapter 8: USB 2.0 Utilities	59
Printer Server	60
Web Camera Server	70
FTP Server	75
Appendix A: Web Camera Compatible List	89

Chapter 1: Introduction

Overview

A true heart of your home/office network, Multimedia Security Gateway simplifies your network complexity by combining a multitude of functions into a single device.

Utilizing 56-bit DES and 168-bit 3DES encryption, header authentication, and IKE key exchange access control, Multimedia Security Gateway's full IPSec Virtual Private Network (VPN) capability provides complete data privacy.

Functions supported are IP sharing, PPPoE, DHCP, DDNS, Firewall, VPN, content filtering, four USB 2.0 ports, a four-port switch hub, printer server, web cam server, motion detection, a 802.11a/g access point, USB Storage devices, UPnP and many more.

Equipped with the most advanced technology available today, this router is the only TOTAL SOLUTION for your networking needs.

Key Features

- High Performance CPU MIPS 170MHz
- Enterprise-Class Firewall
 - * SPI Firewall
 - * DoS
 - * True Content Filtering
- Full IPSec VPN capability
 - * Support (168-Bit) 3 DES Encryption Algorithms
 - * Support MD5 and SHA Authentication Algorithms
 - * Support IKE Key Management
 - * Support 100 VPN tunnels for S/W VPN and 200 Tunnels for H/W VPN
- Compatible with other IPSec VPN products
- Support QoS Bandwidth management
- 4 * USB 2.0 Port for Plug and Share Utilities
- Print Server, Web Cam Server and FTP Server built-in

Package content

- One Multimedia VPN/Firewall Router with 4*USB 2.0 Interfaces
- One Power Supply
- One User's manual in CD


System Requirements

- One RJ-45 Broadband Internet connection
- One PC with 10/100Mbps Network card installed
- TCP/IP network protocol for each PC which connect to the router
- Internet Browser installed in PC
- RJ-45 Cat.5 network cables

Chapter 2: Get to know your Multimedia Router

Hardware Features

Front Panel LEDs



LAN indicators

Power

On Green The Power LED illuminates when the router is powered on.
Off The router is not power on.

E-mail Green & Orange

The two LED are used for E-mail notification indicators and will describe at later chapter

Link/Act

Green The Link/Act LED serves two purposes. If the LED continuously illuminated, the router is then successfully connected to a device through the corresponding port (1-4). If the LED is flashing, it means the router is actively sending or receiving date through that specific port.

10/100M

Orange The LED illuminates when a successful 100Mbps connection is made through the corresponding port.

WAN Indicators

PPPoE

Red The LED illuminates when successful broadband Internet connection is made via PPPoE connection type

Status

Red The LED illuminates when router is boot-up after connected to power or the router has connection failure. It is necessary to reset the router by pressing the reset button at rear panel of router

WAN


Green The LED illuminates when successful connection is made between router and your broadband device or network

Orange The LED illuminates when a successful 100Mbps connection is made through the corresponding port

Air (Wireless LAN)

Green The LED flashes when successful wireless connection is made between your PC and router.

Rear Panel Interfaces



WAN The WAN port is where you will connect your Cable or DSL modem.

LAN 1-4 These four LAN ports are where you will connect PC/Notebook

USB These four USB 2.0 ports are where you connect to other USB devices such as Printers, Web Cameras, USB HDD, Flash drive, MP3 player, Digital Camera and USB Media Reader

Reset

1. Press Reset button with pencil tip to re-boot the router when the router is having problem connecting to Internet
2. Press on the Reset button for 3 seconds until Status LED is flashing to clear all configurations.

HDD Power

Attach PS/2 cable from USB HDD to HDD Power Connector for additional power support when the router is connected to USB HDD. When USB HDD is equipped with PS/2 cable, it means the power needed for HDD is greater than the power provided by USB port. It is necessary to connect its PS/2 cable for stable power management.

Power Power Port is where you connect power supply

Chapter 3: Connecting the router to the Internet

Hardware Installation

1. Power down your PC, Cable/DSL modem and the Router
2. Connect a cable from one of your PC's Ethernet port to one of the LAN ports on the rear panel of the router. Do the same with all the PC you wish to connect to the router.
3. Connect the network cable from your Cable/DSL modem to the WAN port on the router's rear panel.
4. Connect the power supply to the power port on the rear panel of the router, and then plug the power supply to the power outlet. The **power** LED on the front panel will light up green as soon as the power supply is connected properly. The **Status** LED will light up red for few seconds when the router goes through its self-diagnostic test. The LED will turn after the self-test is completed.
5. Power on your Cable/DSL modem
6. Press the **Reset Button** on the router's rear panel with paper clip. Hold the button until the **Status** LED flashing. This will restore the router's factory default settings.

Login to Web-Based Management Tool

Once the hardware installation is completed and the router is properly wired into your network, the software configuration of the router can begin.

The default IP address of the router is **192.168.1.254**

The default password is **admin**

1. Open a web browser and type 192.168.1.254 in the browser's address box. Press Enter. The following **Web-Based Management** Screen will appear.



2. Enter **admin** in the password field and click on **Login** to enter Web-Based Management page. After successfully login to the system, the following screen will appear.
3. Click on **Quick Setup** from the main menu on the left side of the screen to begin connecting your network to Internet.

Quick Setup

There are four connection types in Quick Setup menu. Please select the most suitable connection type provided by your ISP. You can choose the connection type by pressing the check box on **Connection type** field.

There are four major sections associated with each of connection type when configuring Quick Setup. There are WAN Interface, LAN Interface, Web-Based Management Password and Network Time Protocol (NTP).

Quick Setup

WAN Interface

*Connection Type: Static (selected)
*IP Address: DHCP (selected) <A.B.C.D>
*Subnet Mask: Static (selected)
*Default Gateway: PPPoE (selected) <A.B.C.D>
*DNS[1]: Static-PPTP (selected) <A.B.C.D>
DNS[2]: DHCP-PPTP (selected) <A.B.C.D>
Static-L2TP (selected) <A.B.C.D>
DHCP-L2TP (selected) <A.B.C.D>

LAN Interface

*IP Address: 192.168.1.254 <A.B.C.D>
*Subnet Mask: 255.255.255.0

Web-Based Management Password

*New Password: [text field]
*Verify: [text field]

Network Time Protocol


Time Zone: (GMT) England
NTP Server: None

Set Reset

WAN Interface

PPPoE

If your ISP provided PPPoE service for Internet connection, please take the following Setup steps:




1. Select **PPPoE** from **Connection Type**
2. Enter the **User Name** you use to log onto your Internet connection. Some ISP may require the format of **User Name** to be id@isp.net. Please check double check with your ISP for this information.
3. Enter your corresponding **password**.
4. Click on **Set** to activate the connection.
5. When the **PPPoE** LED on front panel of the router illuminates, it means the router is successfully connected to Internet. To check the connection status or IP address information, please go to **Interface > WAN > Show WAN Information**.

NOTE:

Please **DO NOT** change the value of PPPoE MRU, PPPoE MTU, LCP Echo Failure and LCP Echo Interval unless it is request by your ISP. Please remain the values as factory default.

Static

If your ISP provides fixed IP for Internet connection, please take the following Setup steps:



The screenshot shows the 'Quick Setup' page for a 'Wireless VPN Firewall Router'. The left sidebar contains a navigation menu with options: Quick Setup, Interface, Content Filtering, Advanced, Mail Monitoring, Webcam, FTP Server, Maintenance, Restart Router, Save Changes, and Logout. The main content area is titled 'Quick Setup' and contains several configuration sections:

- WAN Interface:**
 - *Connection Type: Static (selected)
 - *IP Address: 192.168.2.1 (<A.B.C.D>)
 - *Subnet Mask: 255.255.255.0
 - *Default Gateway: 192.168.2.254 (<A.B.C.D>)
 - *DNS[1]: (<A.B.C.D>)
 - DNS[2]: (<A.B.C.D>)
- LAN Interface:**
 - *IP Address: 192.168.1.254 (<A.B.C.D>)
 - *Subnet Mask: 255.255.255.0
- Web-Based Management Password:**
 - *New Password: (password field)
 - *Verify: (password field)
- Network Time Protocol:**
 - Time Zone: (GMT) England
 - NTP Server: None

At the bottom of the configuration area, there are two buttons: 'Set' and 'Reset'.

1. Choose **Static** from **Connection type** pull-down box.
2. Enter **IP address**, **Subnet mask** and **Default gateway** as provided by your ISP.
3. Enter at least one **DNS Server** IP address as provided by your ISP.
4. Click on **Set** to activate the connection.

DHCP

The screenshot displays the 'Quick Setup' page of a Wireless VPN Firewall Router. The left sidebar contains a navigation menu with the following items: Quick Setup, Interface, Content Filtering, Advanced, Mail Monitoring, Webcam, FTP Server, Maintenance, Restart Router, Show Changes, and Logout. The main content area is titled 'Quick Setup' and contains the following sections:

- WAN Interface**: Connection Type is set to DHCP.
- LAN Interface**: IP Address is 192.168.1.254 (with a '<A.B.C.D>' hint) and Subnet Mask is 255.255.255.0.
- Web-Based Management Password**: New Password and Verify fields are present, both showing masked characters (****).
- Network Time Protocol**: Time Zone is set to (GMT) England and NTP Server is set to None.

At the bottom of the form, there are two buttons: 'Set' and 'Reset'.

If your ISP provides DHCP service for Internet connection then all you need to do is to select **DHCP** and click on **Set**. In order to make sure the WAN connection is made, you can go **Interface > WAN > Show WAN Information** to check the connection status.

PPTP-DHCP

If your ISP provides PPTP-Static service for Internet connection, please take the following Setup steps:

The screenshot shows the 'Quick Setup' page for a 'Wireless VPN Firewall Router'. The left sidebar contains navigation options: Quick Setup, Interface, Content Filtering, Advanced, Mail Monitoring, Webcam, FTP Server, Maintenance, Restart Router, Save Changes, and Logout. The main content area is titled 'Quick Setup' and contains the following configuration sections:

- WAN Interface**
 - *Connection Type: DHCP-PPTP (dropdown)
 - *Gateway: isp.mytelecom.net (text input) <Host Name | A.B.C.D>
 - *User Name: id@your.isp (text input)
 - *Password: (password input)
 - *PPTP MRU: 1492 (text input) <1-1500>
 - *PPTP MTU: 1492 (text input) <1-1500>
 - *LCP Echo Failure: 3 (text input) <1-10>times
 - *LCP Echo Interval: 20 (text input) <1-60>seconds
- LAN Interface**
 - *IP Address: 192.168.1.254 (text input) <A.B.C.D>
 - *Subnet Mask: 255.255.255.0 (dropdown)
- Web-Based Management Password**
 - *New Password: (password input)
 - *Verify: (password input)
- Network Time Protocol**
 - Time Zone: (GMT) England (dropdown)
 - NTP Server: None (dropdown)

At the bottom of the form are 'Set' and 'Reset' buttons.

1. Select DHCP-PPTP from Connection type pull-down box
2. Enter **Gateway host name** as provided by your ISP.
3. Enter the **User Name** you use to log onto your Internet connection.
Some ISP may require the format of **User Name** to be id@isp.net.
Please check double check with your ISP for this information.
4. Enter your corresponding Password
5. Click on **Set** to confirm the settings.

NOTE:

Please **DO NOT** change the value of PPPoE MRU, PPPoE MTU, LCP Echo Failure and LCP Echo Interval unless it is request by your ISP. Please remain the values as factory default.

PPTP-Static

If your ISP provides PPTP-Static service for Internet connection, please take the following Setup steps:

The screenshot shows the 'Quick Setup' window for a 'Wireless VPN Firewall Router'. The 'WAN Interface' section is expanded, showing the following configuration:

- Connection Type:** Static PPTP
- IP Address:** 192.168.2.1
- Subnet Mask:** 255.255.255.0
- Gateway:** 192.168.2.254
- User Name:** id@your.isp
- Password:** [Redacted]
- PPTP MRU:** 1492
- PPTP MTU:** 1492
- LCP Echo Failure:** 3
- LCP Echo Interval:** 20

The 'LAN Interface' section shows:

- IP Address:** 192.168.1.254
- Subnet Mask:** 255.255.255.0

The 'Web-Based Management Password' section has two fields for 'New Password' and 'Verify'.

The 'Network Time Protocol' section shows:

- Time Zone:** (GMT) England
- NTP Server:** None

Buttons for 'Exit' and 'Reset' are located at the bottom right of the configuration area.

1. Select PPTP from Connection type box
2. Enter **IP address**, **Subnet mask** and **Default gateway** as provided by your ISP.
3. Enter the **User Name** you use to log onto your Internet connection. Some ISP may require the format of **User Name** to be id@isp.net. Please check double check with your ISP for this information.
4. Enter your corresponding Password

NOTE:

Please **DO NOT** change the value of PPTP MRU, PPTP MTU, LCP Echo Failure and LCP Echo Interval unless it is request by your ISP. Please remain the values as factory default.

L2TP-DHCP

If your ISP provides DHCP-L2TP service for Internet connection, please take the following Setup steps:

The screenshot shows the 'Quick Setup' page for a 'Wireless VPN Firewall Router'. The left sidebar contains a navigation menu with options: Quick Setup, Interface, Content Filtering, Advanced, Mail Monitoring, Webcam, FTP Server, Maintenance, Restart Router, Save Changes, and Logout. The main content area is titled 'Quick Setup' and is divided into several sections:

- WAN Interface:**
 - *Connection Type: DHCP-L2TP (selected in a dropdown)
 - *Gateway: isp.mytelecom.net (with a hint '<Host Name | A.B.C.D>')
 - *User Name: id@your.isp
 - *Password: [masked]
 - *PPPoE MRU: 1492 (range <1-1500>)
 - *PPPoE MTU: 1492 (range <1-1500>)
 - *LCP Echo Failure: 3 (range <1-10>times)
 - *LCP Echo Interval: 20 (range <1-60>seconds)
- LAN Interface:**
 - *IP Address: 192.168.1.254 (range <A.B.C.D>)
 - *Subnet Mask: 255.255.255.0 (dropdown)
- Web-Based Management Password:**
 - *New Password: [masked]
 - *Verify: [masked]
- Network Time Protocol:**
 - Time Zone: (GMT) England (dropdown)
 - NTP Server: None (dropdown)

At the bottom of the form are two buttons: 'Set' and 'Reset'.

1. Select **DHCP-L2TP** from Connection type pull-down window.
2. Enter **Gateway**, **User name** and **Password** into their columns.
3. Click on **Set** to confirm the settings.

NOTE:

Please **DO NOT** change the value of PPPoE MRU, PPPoE MTU, LCP Echo Failure and LCP Echo Interval unless it is request by your ISP. Please remain the values as factory default.

L2TP-Static

If your ISP provides Static-L2TP service for Internet connection, please take the following Setup steps:

The screenshot shows the 'Quick Setup' interface with the following configuration details:

WAN Interface	
*Connection Type	Static-L2TP
*IP Address	192.168.2.1 <A,B,C,D>
*Subnet Mask	255.255.255.0
*Gateway	192.168.2.254 <A,B,C,D>
*User Name	id@your.isp
*Password	*****
*PPPoE MRU	1492 <1-1500>
*PPPoE MTU	1492 <1-1500>
*LCP Echo Failure	3 <1-10>times
*LCP Echo Interval	20 <1-60>seconds

LAN Interface	
*IP Address	192.168.1.254 <A,B,C,D>
*Subnet Mask	255.255.255.0

Web-Based Management Password	
*New Password	*****
*Verify	*****

Network Time Protocol	
Time Zone	(GMT) England
NTP Server	None

Buttons: Set, Reset

1. Select **Static-L2TP** from Connection type pull-down window.
2. Enter **IP address, Subnet Mask, Gateway, User name** and **Password** into their columns.
3. Click on **Set** to confirm the settings.

NOTE:

Please **DO NOT** change the value of PPPoE MRU, PPPoE MTU, LCP Echo Failure and LCP Echo Interval unless it is request by your ISP. Please remain the values as factory default.

BIGPOND Cable (Australia only)

This broadband connection service is only available for Australian users. If you're located in Australia, please take the following steps:

The screenshot shows the 'Quick Setup' configuration page for a 'Wireless VPN Firewall Router'. The left sidebar contains navigation options: Quick Setup, Interface, Content Filtering, Advanced, Mail Monitoring, Webcam, FTP Server, Maintenance, Restart Router, Save Changes, and Logout. The main content area is titled 'Quick Setup' and contains the following sections:

- WAN Interface:**
 - *Connection Type: BIGPOND Cable (dropdown)
 - *User Name: yourname (text input)
 - *Password: masked (password input)
 - *Authentication Server: sm-server (text input)
 - *Authentication Domain: jrc.bigpond.net.au (text input)
- LAN Interface:**
 - *IP Address: 192.168.1.254 (text input) <A.B.C.D>
 - *Subnet Mask: 255.255.255.0 (dropdown)
- Web-Based Management Password:**
 - *New Password: masked (password input)
 - *Verify: masked (password input)
- Network Time Protocol:**
 - Time Zone: GMT England (dropdown)
 - NTP Server: None (dropdown)

At the bottom of the form are 'Set' and 'Reset' buttons.

1. Select **BIGPOND Cable** from Connection type pull-down window.
2. Enter **User name** and **Password** into the related column.
3. Enter the **Authentication Server** and **Authentication Domain**.
4. Click on Set to confirm the settings.

LAN Interface

This Section allows users to modify Router's LAN IP address and subnet mask. When these values are modified, it is necessary to modify your IP and DHCP setting otherwise Web-Based Management could not be accessed.

Web-Based Management Password

This section allows you to change Web-Based Management Login password. Enter the new password and verify it again. The new password will activate the next time you login.

Network Time Protocol

Time Zone – This field indicates time zone where you are locating in.
 NTP Server - This field allows you to set IP address of NTP Server to synchronize your system time.

Chapter 4: Interface Configuration

Interface

This is to where LAN, WAN and Wireless interface relevant parameters can be configured. If you've already gone through the Quick Setup first, the fields should have values in it. If that is the case, you can skip the Interface configuration of LAN and WAN.

LAN Interface




IP address Enter the IP address. This field should be filled-in automatically already. The value is 192.168.1.254 unless you've changed it.

Subnet Mask Enter the subnet mask. This field should be filled-in already.

Show LAN Information

Click on **Show LAN Information** in order to access to LAN interface in details.

WAN Interface



Mac

Your router's MAC address is a 12-digit code assigned to a unique piece of hardware for identification. Some ISPs require that you register the MAC address of your network card/adaptor, which was connected to your cable or DSL modem during installation. If your ISPs require MAC address registration, find your adapter's MAC address by doing the following:

1. Click the Start button, and select Run. Run `winipcfg`, and then click more info. Or at the command prompt, run `ipconfig/all`, and look at your adapter's physical address.
2. Enter 12-digits into the fields and click on Set button. This "clones" your network adapter's MAC address onto your router, and prevents you from having call your ISP to change the registered MAC address to the router's MAC address.

MTU

It stands for maximum transmission unit. Usually it is set as 576 or 1500.

Connection Type

This shows the connection type where the router was connected to Internet. Please refer to the previous section for connection details.

IP address

this field indicates WAN IP address.

Multimedia Security Center

Subnet Mask this field indicates subnet mask address

Default Gateway this field indicates Default Gateway address.

Show WAN Information

Click on this button to get access to WAN interface detailed information.

Wireless Interface (Only available to Wireless Router)

In this Wireless section, it lets you make changes to the wireless network settings. You can make changes to the wireless name (SSID), operating channel, encryption security settings, and configure router to be used as an access point.

The screenshot shows the 'Wireless Interface' configuration page. On the left is a navigation tree with options like 'Quick Setup', 'Interface', 'LAN', 'WAN', 'Wireless', 'Content Filtering', 'Advanced', 'Mail Monitoring', 'Webcam', 'FTP Server', 'Maintenance', 'Reset Router', 'Save Changes', and 'Logout'. The main content area is titled 'Wireless Interface' and contains two sections:

- Radio:**
 - Radio: ON
 - SSID: Router
 - SSID Broadcast: Enable
 - Mode: 11g & 11b
 - Channel: 4
 - Beacon Interval: 100 milliseconds (Default: 100)
 - RTS Threshold: 2347 (Default: 2347)
 - Fragmentation Threshold: 2346 (Default: 2346)
 - Turbo Mode: Enable
- WEP Setting:**
 - WEP Encryption: 64/128/152/168/192/256 bits ASCII
 - Key 1: aaaaa
 - Key 2: bbbbb
 - Key 3: ccccc
 - Key 4: ddddd
 - Current Key: 1
 - WEP Status: Disable

Buttons for 'Set' and 'Reset' are provided for both sections. An 'Access Control' button is located at the bottom of the page.

Radio

The default setting is **on**. When Radio setting is off, the wireless function will be disabled and wireless radio signal will be transmit and distribute from the router.

SSID (Service Set Identifier)

The SSID is an identification string of up to 32 ASCII characters that differentiate one wireless Access Point router or Access Point from other manufacturers. You can use default SSID or create your own and radio channel unless more than one Wireless Router or Access Point is deployed in the same area. In that case, you should use a different SSID and radio channel for each Wireless Router and Access Point. All Wireless Router and

802.11g/802.11b WLAN client adapters must have the same SSID to allow a wireless mobile client to roam between the wireless routers. By default, the SSID is set to "**Router**".

SSID Broadcast

When wireless clients searching the local area of wireless networks to associate with, they will detect the SSID broadcast by the router. To broadcast the router's SSID, please keep the default setting "enable". If you do not wish to broadcast router's SSID, please select "Disable".

Mode

Your Wireless Router is compatible with both WLAN 11g/11b Client Adapters. In this field, you are able to choose connection mode with both 11g/11b clients or 11g only or 11b only. The default setting is **11g/11b**.

Channel

IEEE 802.11g and 802.11b devices are direct sequence spread spectrum devices that spread a radio signal over a range of frequencies. The range of frequencies used by a direct sequence device is called Channels.

Make sure that all nodes on the same wireless LAN network use the same channel, or the channel usage is automatic when a connection between WLAN clients and your wireless multimedia router are made

Authentication Type

Using "**Shared Key Only**" is recommended for greater security. If "**Both**" is selected, the wireless multimedia router may accept connection requests from unauthorized wireless clients.

Beacon Interval

The default value is 100. Enter a value between 1 and 65,535 milliseconds. The beacon interval value indicates the frequency interval of the beacon. A beacon is a packet broadcast by the router to synchronize the wireless network.

RTS Threshold

This value should remain at its default setting of 2347. The range is 0-2347 bytes. Should you encounter inconsistent data flow, only minor modifications are recommended. If a network packet is smaller than the

present RTS threshold size, the RTS/CTS mechanism will not be enabled. The router sends Request to Send (RTS) frames to a particular receiving station and negotiates the sending of a data frame. After receiving an RTS, the wireless station responds with a Clear to Send (CTS) frame to acknowledge the right to begin transmission.

Fragmentation Threshold

If the length of data frame needing transmission exceeds the fragmentation threshold you set in the column, the data frame will be fragmented. If there is significant interference or high utilization in your wireless network, the smaller fragmentation value can increase the reliability of transmission. However, it is more efficient to set the large fragment size.

Turbo Mode

When Turbo mode is enabled, it allows the router or access point to use frame bursting to deliver the maximum throughput of 2 times faster than any standard 802.11g equipment to 802.11g clients. This measurement is based on aggregate throughput in a mixed 802.11g and 802.11b environment. 802.11g clients also need to support turbo mode in order to make this utility work. Clients that do not support turbo mode will operate normally when it enabled.

WEP Setting

WEP (Wired Equivalent Privacy) is a method of encrypting data transmitted on a wireless network for greater security. If WEP security is enabled, data is encrypted before being transmitted, making communication more secure.

WEP Encryption

Current encryption technology offers 64-bit and 128-bit WEP encryption. Where encryption is concerned, 128-bit has greater security than 64-bit. A WEP key is a string of hexadecimal characters that your wireless network uses in two ways. First, all nodes in your wireless network are identified with a common key. Second, these WEP keys encrypted and decrypted data sent over your wireless network. So, a higher security ensures that hacker have a harder time breaking into your network.

In this field, you are able to select what type of data encryption you wish to use for WEP security. Select the encryption type from drop-down menu by clicking on the options. It is recommended to use 128-bit encryption for higher security. From this drop-down menu, you have option to decide the character format for WEP key entries.

Hex Set WEP key entries with the range of 0-9 and A-F.

ASCII Set WEP key entries with any character or symbol button on your keyboard.

After selected WEP encryption type, you will require to put WEP key entries. Select which WEP key (1-4) will be used when the router send data, then select that number from the **Current Key** field. Type in the values in the field by following to Hex and ASCII entry rules indicated above. Keep typing the values until the letters or digits stop appearing on KEY field.

Select **Enable** from **WEP** field after you had completed the WEP key value entries. Click on **SET** to confirm your WEB settings.

Access Control

As the figure, the wireless network access control is divided into two parts. The upper part is the access policy; the lower part is the MAC table.

The screenshot shows the 'Wireless Access Control' interface. At the top, there is a 'Policy' dropdown menu currently set to 'Any'. Below the dropdown are the options 'Any', 'Allow', and 'Deny'. To the right of the dropdown is a 'Set' button. Below the policy section is a 'MAC Table' section. It contains a table with two columns: 'MAC Address' and 'Operation'. The 'MAC Address' column has a text input field with the placeholder '<XX:XX:XX:XX:XX:XX>'. The 'Operation' column has an 'Add' button.

There are three value options of access policy:

- Any** the MAC table does not work, and all the wireless equipments will be accepted
- Allow** only accept the wireless equipments set in MAC table
- Deny** deny the the wireless equipments set in MAC table

After the access policy is selected, you have to click Set button to make the new setting work.

If you want to add wireless equipment to MAC table, enter the hardware address of the lower left field, and then press Add button to add it. If you want to delete equipment from MAC table, please check the corresponding Delete block on the right, and then press Delete button to delete the selected equipment. Reset button can be used to cancel the selection.

Chapter 4: Content Filtering

There are four selections under Content Filter: **Keyword Filtering, URL Blocking, Trusted IP** and **Port Checking**.

Trusted IP has the highest priority. In other words, if certain URL or keyword is being blocked, but the IP address is in the Trusted IP range, it is considered safe.

Keyword Filtering

Content Keyword Filtering Setting

Decompress
 Drop
 Log
 No Case

Set

Regular Expression / Keyword	Operation
	Add

If you input "sex" as keyword, it will search content for "sex", like sex, sexy, sexangle... So if you want to find exactly the word "sex", try to input "sex " as keyword. You can also input BIG-5, UTF-8, GB ... encoded words, just change the browser character encoding to what you like.

If you set above "No Case" check box, it will search content for "sex", "Sex", "sEx", "seX", "SEx", "SeX", "sEX", "SEX".

If you set above "Decompress" check box, it will extract content from gzip encoding pages.

If you set above "Drop" check box, it will drop matched packets.

If you set above "Log" check box, it will log. Log format likes 1999-11-30 10:53:27 1.1.1.1 80 -> 1.1.1.2 65535 string matches with sex.

Regular expression document

1. Determine first what action would be applied to the keyword. Check off the appropriate box and click Set.
2. Enter the expression that wishes to be blocked. For example, you can enter the word "violence" in the field. Click Add to add it to the expression list. The action chosen in Step 1 will be applied to the

situation when the keyword appears. For example, if **DROP** is chosen; then web pages contain the word, violence, will be dropped and will not be available.

URL Blocking

Enter the URLs that are considered inappropriate and wish to be blocked. Click **Add** for it to be effective.

URL Blocking Setting

URL	Operation
http://	Add

URL ex: www.google.com, www.google.com:80, www.google.com:80/d/e/f, 216.239.51.99, 216.239.51.99:80, 216.239.51.99:80/d/e/f

Trusted IP

Content Filter Trusted IP Setting

IP Address / Port Range	Operation
IP Address <input type="text"/> ~ <input type="text"/> Port Range <input type="text"/>	Add

IP ex 1.1.1.1,

- 1.1.1.1:80
- 1.1.1.1:1-65535,
- 1.1.1.1~1.1.1.2,
- 1.1.1.1~1.1.1.2:80,
- 1.1.1.1~1.1.1.2:1-65535

Trusted IP means that the IP addresses are considered safe and will not pose

any damage to you. Enter the range of **IP addresses** and the **Port Number** in the fields. Click **Add**.

Trusted IP has the highest priority. That means if there is a conflict between the rules in Trusted IP and URL Blocking (or Keyword Filtering or Port Checking), the rules under Trusted IP takes precedence of others.

Port Checking

Content Filter Port Checking

Port	Operation
80	☐ Delete
<input type="text"/> Delete Clear All	
<input type="text"/>	<input type="button" value="Add"/>

Port ex: 80, 1:65535

NOTE

If you don't set this, all port will be checked!

Enter the **port number** in the field and click **Add**. Ports entered will be scanned and checked for security measures. If nothing is entered here, all ports will be checked.

Chapter 5: Advanced Configurations

DHCP

DHCP Server

DHCP Setting

DHCP Server Status	ON
Network Range	192.168.1.10 - 192.168.1.200 <1-253>
Lease	86400 <0-604800>seconds
Max-Lease	604800 <0-604800>seconds

A DHCP (Dynamic Host Configuration Protocol) Server automatically assigns IP addresses to each computer on your network. Unless you already have one, it is highly recommended that the router set up as a DHCP Server.

- **DHCP Server Status**

Click ON to activate DHCP server; OFF to disable and Restart to restart the DHCP server. If the DHCP server status is OFF, click the Set button for it to be effective after changes. IF the DHCP server status is ON, click the Restart button and the new changes will be effective.

- **Network Range**

Define IP range for DHCP server when issuing IP.

- **Lease Time**

This is the default time duration that a DHCP client is able to keep the IP if the time duration is not specified.

- **Maximum Lease Time**

DHCP clients can only request lease time smaller than this value. If the requested lease time is greater than Maximum Lease Time, this

is the default value taken by the system.

- **Show DHCP Clients**

Click on this button to show the current DHCP client information

- **Set DHCP Clients**

This function allows user to instruct DHCP server to assign IP address to a particular Mac ID in your network. Apart from assigning IP automatically, you can assign IP to specific device manually. Please enter the name of the device, its IP address, and the MAC address accordingly. The first three columns are mandatory. You can leave the last two empty. For servers that requires booting files from some other servers, make sure you enter its booting file and the TFTP IP address accordingly. After all the parameters are completed, click Add. To delete the rule, select Delete and then click the Delete box. Click Reset to undo the delete action

DDNS

Dynamic DNS Client Setting

DynDNS.org

Status	<input type="text" value="Disable"/>
*User	<input type="text"/>
*Password	<input type="text"/>
*Host	<input type="text"/>
Wildcard	<input type="text" value="Disable"/>
MX	<input type="text"/>

ODS.org


Status	<input type="text" value="Disable"/>
*User	<input type="text"/>
*Password	<input type="text"/>
*Host	<input type="text"/>

DDNS allows user to export host name to Internet through DDNS service provider. Each time the router is connect to Internet and get an IP address from ISP, this function will update your IP address to DDNS service provider automatically, so that any user on Internet can get access to Server behind it through a predefined name registered in DDNS service provider.

Multimedia VPN/Firewall router support the URL links to DynDNS.org and ODS.org. Move your mouse pointer on **DynDNS.org** or **ODS.org** and click. You can get access to free trail link to start with a free trail account.

After complete registration, please fill in all information in the fields such as **user**, **password** and **host name**. Select **Enable** from **Status** field and click on Set to confirm your settings. If you have an Email Server, please enter its IP address into **MX** field. Enable **Wildcard** to determines of domain name with wildcard is also redirected to your IP address.

Firewall



A Firewall is a set of related programs, located at a network gateway server that protects the resources of a network from users from other networks. (The term also implies the security policy that is used with programs.) An enterprise with an intranet that allows its workers access to the wider Internet installs a firewall to prevent outsiders from accessing its own private data resources and for controlling what outside resources to which its own users have access.

In this Firewall section, it divides into three parts. There are **Add Firewall Rule**, **Remote Management**, **Block WAN Echo-Request** and **WAN Protection**.

Add Firewall Rule



1. To configure Firewall, please select Firewall from main menu
2. To set a new firewall rule, please click on **Add Firewall Rule** button.

Remote Management

The screenshot shows the 'Firewall Setting' page. At the top, there is a blue header with the text 'Firewall Setting'. Below the header is a button labeled 'Add Firewall Rule'. Underneath the button is a table with three rows of settings. The first row is 'Remote Management' with a dropdown menu set to 'Disable' and a 'Set' button to its right. The second row is 'Block WAN Echo-Request' with a dropdown menu set to 'Enable'. The third row is 'WAN Protection' with a dropdown menu set to 'Enable'.

Remote Management	Disable	Set
Block WAN Echo-Request	Enable	
WAN Protection	Enable	

This Router is able to managed by WAN IP. When Remote Management is set on enable, user can enter Web-Based Management page by typing the router's WAN IP on web browser to manage the router.

Please take caution that once the Remote Management is enabled, the router may face the possibility of being attack by Internet hackers. You can reduce the risk of being attack by change connection PORT or use SSL for your connection. Also, make sure you frequently check the LOG records from LOG function in Web-Based Management.

To activate Remote Management, please select **Enable** and click on **Set** to confirm the setting.

Block WAN Echo-Request

This Function allows user to set its WAN IP to stop giving response to outside request. When this function is enable, outsider will not get any response when they trying to PING the WAN IP. By doing this, you can avoid your router to be detected by hacker and prevent intrusion. The Default setting is **Enable**.

WAN Protection

When this option is enabled, the router will discard WAN packets that do not match the IP address specified. When IP Sharing is enabled, it is recommended to enable this option as well.

Virtual Server

Virtual Server Setting

Add Virtual Server

IP Sharing	Enable	Set
NAT Loopback	Enable	Set
DMZ Host Status	Disable	Set
IP Address	<A.B.C.D>	
UPnP Function	Disable	Set
UPnP Firewall	Disable	Set

Virtual Server

To make services, like WWW, FTP, provided by a server in your local network accessible for outside users, you should specify a local IP address to the server.

Please take the following steps to set up a Virtual Server for your router.

Add Virtual Server Setting

Name	<input type="text"/>
Status	Enable
IP Address	<input type="text"/> <A.B.C.D>
Service	DNS <input type="button" value="Edit Service"/>
<input type="button" value="Add"/>	

1. Select **Virtual Server** from the main menu and then click on **Add Virtual Server** button
2. Type in **Server** name. It can be anything as long as it is recognized by user
3. To activate Virtual Server function, click on **Enable** from Status box
4. **IP Address** – enter destination IP address that you like to redirect the matched packet to.
5. From **Service** window, select desired service of your demand. If you could not find the desired service, please click on **Edit Service** button to customize your own settings. The screen will appear as below.

Edit Service

Service Setting

Service Name	Protocol	Port Range/Type	Operation
Ping	icmp	echo-request	<input type="checkbox"/> Delete
DNS	udp	53	<input type="checkbox"/> Delete
SNMP	udp	161	<input type="checkbox"/> Delete
IKE	udp	500	<input type="checkbox"/> Delete
FTP	tcp	20-21	<input type="checkbox"/> Delete
Telnet	tcp	23	<input type="checkbox"/> Delete
SMTP	tcp	25	<input type="checkbox"/> Delete
HTTP	tcp	80	<input type="checkbox"/> Delete
POP3	tcp	110	<input type="checkbox"/> Delete
NNTP	tcp	119	<input type="checkbox"/> Delete
IMAP	tcp	143	<input type="checkbox"/> Delete
HTTPS	tcp	443	<input type="checkbox"/> Delete
eMule	tcp	4662	<input type="checkbox"/> Delete
BitTorrent	tcp	6881-6889	<input type="checkbox"/> Delete

Delete Reset

TCP
[To] <0-65535>
any
Add

1. Enter your desired **Service Name**.
2. Select **Protocol** of your choice from pull-down window
3. Select port number or range of ports. Once the destination port of incoming packets matches the port within the port range, the incoming packets will be redirect to IP address specified in previous setting.
4. Click **Add** to confirm your Virtual Server Settings

Virtual Server Setting

Add Virtual Server

IP Sharing	Enable	Set
NAT Loopback	Enable	Set
DMZ Host Status	Disable	Set
IP Address	<input type="text" value="A.B.C.D"/>	Set
UPnP Function	Disable	Set
UPnP Firewall	Disable	Set

IP Sharing

The host has to have a public IP in order to communicate with others on the Internet. Because of the fact of insufficient IP addresses, ISP provides dynamic IP address instead of static IP address. Dynamic IP address means that the IP address is different every time you log in. For those who need a static IP, higher price has to be paid. Most home users or SOHOs use either one of them.

Since a public IP address is required to communicate with others on the Internet, IP sharing capability is required if there are more than one servers that wish to connect to the Internet. NAT (Network Address Translation) will do the address translation between LAN and WAN. Please enable IP sharing capability for situation described above.

NAT Loopback

This function allows the redirection of packets back to the virtual server when the request is initiated from the LAN side. To enable this function, please select **Enable** and click on **Set** to confirm your setting.

DMZ Host

The DMZ Host feature allows one local user to be exposed to the Internet to use a special-purpose service such as Internet gaming or video conferencing

1. Select **Enable** from **Status** window
2. Enter the **IP address** of PC which you would like to expose to Internet
3. Click on **Set** to confirm the setting

UPnP

UPnP allows users to connect their UPnP-enabled broadband router, print server and other devices right to the network with zero-configuration, meaning easier setup for installing the device on the network. The automatic discovery feature enables the device to obtain an IP address, present and describe itself to other devices and PCs on the network without having to install drivers, and then configure and use those devices.

UPnP Function	Select Enable and click Set to activate this service
UPnP Pass Through Firewall	Select Enable and click Set to allow UPnP pass through firewall


Bandwidth Management

QoS Bandwidth Management

Today, millions of people around the world share their MP3 music, Movies or other image files through freeware Peer-to-Peer platform such as E-Donkey, eMule, Kazza and so on. P2P application provides public platform of linking people around the world and share MP3, or movie files from each other's hard disk. When you're online and downloading music from other people's computer, at the same time, you are also sharing your music archive to other users on P2P network. When other online user downloading the MP3 from your hard disk, your Internet's upstream bandwidth will be eat up and that cause other user on your LAN network to have extreme difficult time to access Internet at very low speed due to lack of upstream bandwidth. With QoS Bandwidth management, this problem can be solved by pre-define the maximum upstream bandwidth allowed to each Internet application and set upstream packets in priority upon its importance.

Moreover, you are allowed to customize your own upstream QoS bandwidth management control depends on your bandwidth requirements. You are free to set what bandwidth priority you wish to give for each Internet application in respect of high, medium and low priority. With this outstanding bandwidth management feature, all users from LAN network will never have to worry about limited upstream bandwidth in broadband Internet environment.

There are two different solutions of efficiently managing the bandwidth. You can either managing the bandwidth by IP or IP group of your LAN network. Also, you can manage the bandwidth by giving priority queue according to its importance on each particular application of your choice.



Managing bandwidth by IP/IP group

In order to manage your network bandwidth more efficiently and to avoid some particular users on the LAN network is taking too much bandwidth by running heavy loaded applications, you're allowed to assign bandwidth priority to one or more users on your LAN network according to its importance.

To configure the settings, please take the following steps:

1. Go to **QoS Status** pull-down window and select **Enable**.
2. Enter IP address or IP group of LAN user you wish to manage and assign their priority of importance.
3. In each section of IP group QoS setting, you are required to enter bandwidth value in each section. **Please note the sum of total bandwidth in each section should not exceed the total upstream bandwidth provided by your broadband service provider.**
4. Click on **Set** to confirm the settings.

Manage bandwidth by applications

To manage your network bandwidth by particular application, please take the following steps


1. Select **enable** from **QoS status** pull-down window.
2. You need to know the maximum upstream bandwidth is allowed for your Internet connection provided by your ISP.
3. For each priority queue, you need to assign the upstream bandwidth value into each priority queue according to its importance from high to low. Please make sure all values sum up from each priority queue is equal to the total upstream bandwidth provided by your ISP.
4. From each priority queue, you need to select what applications you wish to include into QoS bandwidth management. You can do it by select enable or disable from the pull-down box beside each application.
5. After the selection, you need to decide what priority should be given to the application you selected. All P2P applications has been given the lowest priority and fixed as default.
6. Click on **Set** to confirm your settings.

VPN

Virtual Private Networking (VPN) is a security measure that basically creates a secure connection between two remote locations.

IPSec


In order to create a secure VPN tunnel or channel between two endpoints by IPSEC, please take the following steps.



1. Go to **Advanced Configuration** in main menu and select **VPN**.
2. Click on **Add VPN Tunnel**.
3. Enter the name of the tunnel in the **Tunnel name** field. It allows you to identify multiple tunnels from your tunnel group. It does not have to match the name used at the other end of the tunnel.
4. Select **Enable** from Tunnel Status field to activate the tunnel.
5. The **Local Secure Group** is the computer (s) on your LAN that can access the tunnel. Enter the IP address and subnet mask of your local VPN router in the field.
6. The **Remote Secure group** is the computer (s) on the remote end of the tunnel that can access the tunnel. Enter the IP address and subnet mask of the computer at the other end of the tunnel in this field.


7. The Remote Security Gateway is the VPN device, such as a second VPN router on the remote end of the VPN tunnel. Enter the IP address of the VPN device at the other end of the tunnel. The remote VPN device can be another VPN router, a VPN server, or a computer with VPN client software that supports IPSec. The IP address may either be static or dynamic, depending on the settings of the remote VPN device. Make sure that you have entered the IP address correctly, or the connection cannot be made.
8. Currently you have only one option to select one type of **Encryption** as **3DES**. This is the most secure type of encryption and it is set as the default value.
9. From **Authentication**, you have option to select either **MD5** or **SHA1**. It is recommended to select SHA1 as it is more secure than MD5.
10. From **Key Management** section, select Auto (IKE) as default value and select PFS (Perfect Forward Secrecy) and enter a series of numbers or letters in the **Pre-Shared Key** field. Based on this word, which must be entered at both ends of the tunnel. You may use any combination of up to 24 numbers or letters in this field. No special characters or spaces are allowed. In the **Key Lifetime** field, you may optionally select to have the key expire at the end of a time period of your choosing. Enter the number of seconds you like the key to be useful. The default value if Key Lifetime is 3600 seconds.
11. Click on **add** to confirm your VPN tunnel settings..

After the VPN tunnel has been established, you should see the name of VPN tunnel and status from the first page as following:




Show VPN Tunnel Summary

To view IPsec VPN tunnel setting values, please click on **Show VPN Tunnel Summary** button to access these information.




Show Pre-Shared Key Summary

To view all Pre-shared Key configuration information, please click on Show Pre-Shared Key Summary button.



Show IPsec SPI Information

After a VPN tunnel has been established between two end points, you can access to VPN connection status by click on **Show IPsec SPI Information** button.



VPN PPTP Server

This router also supports PPTP tunneling protocol. Users can remotely login to the office via PPTP with supports up to 10 PPTP connections. To configure PPTP server, please click **VPN** from the main menu (on the left column) and click **PPTP Server Setting** button on the bottom of the page.

PPTP Server

PPTP Server Status: **Enable**

Local IP Address:

Remote IP Address:

Account Management

User Name	Password
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>

1. Firstly, please check the **PPTP Server Status** pull-down window and select **Enable**.
2. Please enter Local IP Address and Remote IP Address into their related column.
3. After complete your entries, please click on **Set** to confirm your setting.
4. In **Account Management** section, please enter **Account name** and **password** of both local user and remote user for VPN connection.
5. Please click on Set button to confirm after complete the entries.

Static Route

Specify Static Routes

Destination	Gateway	Distance Value	Operation
<input type="text" value="<A.B.C.D/M>"/>	<input type="text"/>	<input type="text" value="<1-255>"/>	<input type="button" value="Add"/>

If the router is connected to more than one network, it may be necessary to set up a static route between them. A static route is a pre-determined pathway that network information must travel to reach a specific host or network. Click on Static Route from main menu to view the current static routing information.

Enter **Destination IP address** of the remote network or host which you wish to assign a static route. Enter the **Gateway IP** address of the gateway device that allows for contact between the router and the remote network or host. Enter **Distance Value** from 1 ~ 255 and click on **Add** to confirm your setting.

Show Routing Table

Click on **Show Routing Table** to check your new static route information.

Routing Table Information

Destination	Gateway	Mask	Interface
192.168.2.0	*	255.255.255.0	WAN
192.168.1.0	*	255.255.255.0	LAN
239.0.0.0	*	255.0.0.0	LAN
Default	192.168.2.254	0.0.0.0	WAN

Show ARP Table

Before all packets are transmitted, the MAC address of the receiving host should be identified. Therefore, Matrix can auto learn the MAC address and the mapping IP. See below for the translation table.

ARP Table

IP Address	Hardware Address	Flags	Interface	Delete
192.168.1.150	00:04:75:FE:65:95	C	lan	<input type="checkbox"/>

Specify Static ARP Table

IP address	Hardware address	Operation
<input type="text" value="<A.B.C.D>"/>	<input type="text" value="<XXXXXXXXXXXXXX>"/>	<input type="button" value="Add"/>

Host Name Table

It is the mapping of host name and its IP address respectively. The default is blank.

Host Name Table


IP Hostname Table

Host Name	IP Address	Operation
<input type="text"/>	<input type="text" value="<A.B.C.D>"/>	<input type="button" value="Add"/>

Chapter 6: Mail Monitoring

In this section, Mail Monitor is used to monitor the incoming mails. Users can pre-define Mail Group and Mail Server for some specific people in advance. When these senders sent mail to you, the E-mail LED at the front panel will flash in accordance of your setting. You DO NOT need to open Outlook or your email system in order to know who has sent you E-mails.


To set up E-mail of your friends or customers who you wish to monitor, please take the following steps:



1. Select **Mail Monitor** utility from main menu and click on **Mail Group**.
2. In Mail Group setting, you have option to configure up to six different Email Server groups with six people in one group.

NOTE: Two email addresses from different Email Server must not exist in the same Mail Group.

3. After enter sender's email address, please select LED display for this sender. Click on **Set** to confirm the setting.
4. Go to **Mail Server** to configure Email Server Settings.




5. Define the value for **Monitor Interval**. The router will check the specific Email server based on this pre-defined time interval.
6. You have option to monitor any incoming mails and use Group 1's LED settings. If you wish to do that, please check the box and click **Set**.
7. Enter Email server IP address or domain name, user name and password.
8. Select Mail Server type and tick on **Active**.
9. Click on **Set** to confirm the setting.

Chapter 7: Maintenance

System Management

System management Utility provide user to configure router's system settings.



System Settings

Network Name

You can set up a name for your router in this field.

Domain Name

You can set domain name of where your router is located here. If you did not apply the domain name from your ISP, please leave it blank.

Domain Lookup This utility provides the function of searching domain from DNS Server you configured. Default is **ON**.

Management Timeout

This section allows you to set the time interval of when Web-Based Management should logout automatically when it is not in use. The default value is 5 minutes.

DNS Server

When the domain name is defined, this is where the router should search for DNS Server. Please input the DNS Server IP address provided by your ISP.

Password Setting

Here is where you set your password when login into Web-Based Management. Default password is **admin**

Server Configuration


Here is where you can set the connection port for Web-Based Management. Based on security concern, it is recommended to set the port number between 5000 ~ 65535 in order to prevent intrusion attack. You can also select HTTPS from Status field in order to increase the security.

Management Access Control

You can define Accept or Deny for specific IP or domain where the Web-Based Management is login. Default is **Accept**.

Clock

In this section, you can set Local Time and System Clock for your router. Select time values in every time fields by scrolling down the time menu. Click on **Set System Clock** or **Local -> System** to confirm your time settings.



NTP Server allows you to set IP address of NTP server to synchronize your system time. Select **Time Zone** at your region and appropriate NTP Server. Click on **Set** to confirm the settings.

System Information

In this section, you are able to view the current status of **Firmware version**, **CPU information** and **System information** of the router.

The screenshot displays the web-based management interface for a Ruijie Dual Management System. The browser address bar shows the URL `http://192.168.1.254/ysw/ysw_index`. The left sidebar contains a navigation tree with the following items: Quick Setup, Interface, Content Filtering, Advanced Configuration, Mail Monitoring, Webcore, FTP Server, Maintenance, System Management, System Information (selected), Clock, USB Devices, On-Line Users, Upgrade Firmware, Ping, Traceroute, Log, Restart Router, Save Changes, and Logout.

The main content area is titled "System Information" and contains three sections:

- Copyright**: 1999-2003
- Web-Based Management Software Version 1.5** Dec 17 2003 19:17:16
- SysCTRL v1.0.2**, 2003
- MSP MultiND v1.0.1**, 2003.
- Firmware Version 1.01.023** Wed Dec 17 19:19:12 CST 2003
- O.S. Build** Wed Dec 17 16:49:03 CST 2003

The **CPU Information** section shows the following data:


User	3.4%
System	7.7%
Nice	0.0%
Idle	83.7%

The **System Information** section shows the following data:

System Time	Fri Dec 19 09:48:36 2003		
System Uptime	0 day 0 hour 56 minutes		
Load Average	1.05	1.28	1.28
Memory Information	Total 30276 K	Used 13260 K	Free 17016 K


USB Devices

In the section, you are able to view and check the status of any USB device connected to the router. If an USB device is connected to the router and it does not show on this section, it means the USB device is not recognize by the router or it has compatibility problem.




On-Line Users

In this section, you are able to view and check all online users within your network group. You can force disconnection for some particular users by ticking on **Kick** box and click on **Kick** to confirm your setting.



Firmware Upgrade

Updated firmware can be upgraded anytime through this utility. Before upgrading firmware, please make sure you had obtained new firmware from your supplier and save in your hard disk.




1. Select **Maintenance** from main menu and click on **Upgrade Firmware**.
2. Before upgrading new firmware, if you would like to back up the configuration, please do so by click on **Back-up configuration**.
3. Click on **Browse** to obtain the new firmware from your hard disk.
4. Click on **Upgrade** to start firmware upgrade.
5. Firmware upgrading may take few minute, wait until the pop-up window appear for the next instruction.
6. After the firmware has successfully upgraded, please use paper clip to press **Reset Button** for 5 seconds in order to clear old configurations.
7. Re-login Web-Based Management to reconfigure your network.

Restore Configuration

1. From Restore configuration section, Click on **browse** to search your back-up file from your hard disk.
2. Click on **Restore** to restore your previous configurations.

Ping

You can use this utility to determine whether a particular IP address or domain is online. It is used to test or debug a network by sending out a packet and waiting for a response.



IP Address or Domain Name

In this field, enter the IP you wish to Ping

Set Source Address

Enter the source address


Times

Enter the value of how many times you wish to Ping

Click on Start to Ping

Trace route


You can use this utility to trace the routing path for a particular IP address or domain.



Enter IP address or domain name you wish to trace.

After enter Source Address, please enter maximum number of Hops should be carry out. Click on **Start** to begin.


Log



The log feature provides you with a log of all information regards to firewall, system, incoming/outgoing IP address and content filtering of the router. Please select what type of log file you want to view and click on **Show** to view all log files. Click on **clear** if you wish to delete the log.


Restart Router

If you had entered the wrong configuration while setting up your router or other utilities, you can always reboot your router by clicking Restart Router icon.



Save Changes

It is strongly recommended to click on **Save Changes** when every time the Web-Based Management is logged out after configuration. By performing this action, the router will ensure all configurations and settings will not lost even when the router is not powered.



Logout

Clicking on **Logout** to exit Web-Based Management page.

Chapter 8: USB 2.0 Utilities

Multimedia VPN/Firewall Router has built-in 4 USB 2.0 ports for easy plug and share with wide range of USB devices. There is no need to install driver for these USB devices. Simply plug and Share to enjoy the fun and benefits from the following utilities.

1. **Printer** Up to four printers can be shared to your network at the same time
2. **USB Web Cam** The router has built-in Web Cam Server. By connecting web camera to the router, it allows user to monitor their home or office from remote locations. Motion Detection function also been built-in and allows user to use web cam to detect any motion at their home or office and send email alert with captured images.
3. **FTP Server** By connecting USB HDD, USB Flash, MP3 Player, USB Media Reader or Digital camera to the router, user can easily set up a FTP Server to share or download files for local or remote users.

The following table shows the MAXIMUM number of each USB device you can connect to the router in any combination of up to 4 ports:

Printer	WebCam	USB HDD	Flash Drive	MP3 Player	Card Reader	Digital Camera
4	1	1	2	2	2	2

Printer Server

Follow the following steps to how to setup your PC to connect to a print server.

When installing print server, you need to know its IP Address and Port Number. IP Address is the LAN IP address (IP Address of the printer). Port Number is 9100. If you are installing more than one print server, the second Port Number will be 9101, and so on.

Please have the appropriate "printer driver" ready, either on a floppy, or a network shared drive. If your printer is not included in the default list, use the "have disk" method after you've gone through the steps below. In some situations, you may have to install the printer driver first as if it were hooked up directly to LPT1.

For Windows 98/ME, AXIS monitor (or any other similar products) has to be installed. The reason is that Windows 98/ME does not support TCP/IP printing. You can download AXIS monitor from the following site:

ftp://ftp.axis.com/pub_soft/prt_srv/utility/printmon/latest/setup.exe

The general setup steps are summarized below and the details are at the later pages.

If you are running Windows XP

Start -> Control Panel -> Printers and Faxes -> Add Printer -> Local Printer (check off Auto Detect PnP) -> Next -> Create New Port -> Standard TCP/IP Port

IP Address = IP Address of the Printer

Port Name = PrintSrv (or any name you wish)

Custom Settings -> Raw Port

Raw Port = 9100

If you are running Windows 2000

Method A

Start -> Settings -> Printers -> Add Printers -> Local Printer -> Create New Port -> Choose Standard TCP/IP Port

IP Address = IP Address of the Printer

Port Name = PrintSrv (or any name you wish)

Port Number = 9100

Custom Settings -> Raw Port

Raw Port = 9100

Method B

Start -> Settings -> Printers -> Add Printers -> Local Printer -> Create New Port -> Choose AXIS Port -> Choose RAW TCP/IP Port

IP Address = IP Address of the Printer

Port Number = 9100


If you are running:

Windows 2000 and XP


Please note that the installation screen (Method A and Method B) looks a little bit different under different operating system, differing from step 4.

Method A


1. Click Start, Settings, Control Panel, and then Printers and Faxes. Click Add Printer.
2. Click Next. Choose Local Printer. Next.




3. Choose New Port.
4. Select Standard TCP/IP Port. Click Next.





5. IP Address: Please enter the LAN IP Address that the server is connected.
6. Port Name: PrintSrv or any name you wish. Click Next.
7. Click Custom Settings.
8. Click the Raw button. Enter 9100 as Raw Port Number. Click OK.





9. You can see your settings here. Click Back if you want to change anything. Click Finish if everything is right.
10. Choose your printer from the list of printers. Click Next.
11. Congratulations! Now you've successfully installed the print server.





Method B

1~3

The installing screen looks different starting from step four, where you have to specify using TCP/IP protocol. But the underlying principle is the same.

Start -> Control Panel -> Printer and Faxes -> Add Printer -> Local Printer -> Next -> Create New Port -> Choose AXIS Port

4. Click NEXT after AXIS Port.
5. Click RAW TCP/IP. Click OK.




Method B

6. Enter LAN IP address.
7. Enter Port Number, which is 9100. Click OK.
8. Select your printer from the list.




Multimedia Security Center



If you are running Linux

1. Enable CUPS.
2. Enter the default of URL:
<http://localhost:631/printers>.
3. Click ADD PRINTER.
4. Give your printer a name.




5. Select your printer from the list of device. Click CONTINUE.
6. Device URI is the LAN IP Address and the port number.
7. Click CONTINUE.





8. Choose the printer model, click CONTINUE.
9. Choose the Driver for the Model selected. Click



10. The screen shows that you've successfully added a new printer. In this case, it's called "test".
11. Click "test" and



Web Camera Server

By directly connecting USB Web Camera to any port of USB 2.0, the router can act as Web CAM server and perform the following functions

1. Digital Home/Office Surveillance Security system

Simply connecting a Web Camera to the router, users can surveillance their home or office through the web page from any remote or local location wherever Internet connection is available. This is the cheapest way to help users to keep close eyes on their office and home or other properties.

2. Motion Detection Security Alert System

This function allows movement from any unauthorized intruders to be detected at home or office. Once the router detected the movement, it will automatically send alert emails to pre-defined email address with captured images.

Caution: Web Cam server is compatible with limited web cameras. Please find the Compatible list from the Appendix 1 in this manual.

The surveillance image resolution may be affected by the quality of the web cam you purchased. Only use the high-resolution web cam from the compatible list. It is recommended to use "Logitech QuickCam 4000 Pro" or "Logitech QuickCam Zoom" for high quality resolution.

Home/Office Surveillance function

To activate Home/Office Surveillance function, please take the following steps:

Motion Detection Configuration

Webcam Server: ON OFF

Motion Detection: ON OFF

Record: ON OFF

Threshold: 20 % <1-100>

Delay Time: 0 seconds

Mail With Captured Image: YES NO

Mail Counts Within 1 Minute: 0 for unlimited

Schedule Setting

	Mon	Tue	Wed	Thu	Fri	Sat	Sun
Start time(hour)							
Start time(minute)							
Stop time(hour)							
Stop time(minute)							
0-2							
3-5							
6-8							
9-11							
12-14							
15-17							
18-20							
21-23							

Mail Setting


Mail Server	Mail Address	User Name	Password

1. Before activate surveillance function, please make sure Web Cam is properly plug into any USB port on the router and make sure web cam is detected by the router. You can check it at **"USB Devices"** function in maintenance menu.
2. Go to **"Web Cam"** in main menu and click on **Setting**.
3. **Web Cam Server** – To activate web cam server, please select **"ON"**.
4. Click on **"Set"** to activate the service.
5. Click on **"Web Cam Live"** from main menu to get access to live motion.
6. Only ONE Web Camera can be connected and viewed.

To view web cam live images from remote locations

You can access to live images from any remote location where Internet access is allowed. Please take the following instructions:

1. Make sure the web camera is properly connected to the any USB port of the router.
2. Make sure **Remote Management** from **Firewall** Section is set to **enable**.
3. Open a web browser and type in your router's WAN IP address. (WAN IP can be obtained from main menu on **Interface -> WAN**). Or, apply for a DDNS account from **DDNS** utility described in previous section.
4. After type in WAN IP in your web browser, it will then lead you to Web-Based Management utility page. Type in your password to login into Web-Based Management page. Select **Web cam live** to view the live images.



Motion Detection System

To activate Motion Detection System, please take the following steps:

1. Go to **Mail Address Setting** and enter all mail server information of where alert e-mail should be sent. Click on **Set** after your Email information has been entered.
2. Go to **Motion Detection Configuration** and make sure both **Web Cam Server** and **Motion Detection** are set as **enable**.
3. **Threshold** - Enter a threshold value. This value works in conjunction with the noise level. Ignore this field if motion detection is OFF.
4. **Delay Time** – This feature allows the router to automatically enabling the Motion Detection function after a period of time set in this field. This function allows you to have enough time to leave your home/office without been detected after configured the motion detection function to your router.
5. **Mail With Captured Image** - Choose **No** to mail the motion detection alert message with just words. Choose **YES** to mail the motion detection alert message with pictures taken.
6. **Mail Counts within 1 minute** - Enter the maximum alert emails mailed out within one minute. 0 is for unlimited emails mailed out if detected. The default value is 5.
7. Click on **Set** to activate Motion Detection function.

Digital Recording

The recording function allows you to digitally record movement when motion is detected. The recording function must work in conjunction with Motion Detection function.

To activate recording function, please take the following steps:

1. Connect a USB storage device to any USB port of your router.
2. Make sure both **Web Cam Server** and **Motion Detection** is set as **On**
3. Go to **Recording** and select **On** from pull-down window.
4. Select a directory on USB storage device of where the recorded files need to be stored.
5. Click on **Set** to confirm your settings.

Schedule Setting

Motion Detection System can be activated through pre-set time schedule on dairy or weekly basis. To set time schedule, please go to **Schedule Setting** and enter the desired time schedule in related time box. Click on **Set** after completion.

Schedule Setting

Start Hour	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Start Minutes	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Stop Hour	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Stop Minutes	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	Mon	Tue	Wed	Thu	Fri	Sat	Sun
0~2							
3~5							
6~8							
9~11							
12~14							
15~17							
18~20							
21~23							

FTP Server

By directly connecting USB storage devices to any USB 2.0 port, FTP server can be created with simple configuration. FTP Server utility allows both local and remote users to upload or download files, pictures or MP3 music from the same storage device in most easy and timely fashion. It is also cost effective where users do not need to purchase a dedicated PC to set up a 24 hours FTP service.

Before configure FTP Server, please make sure one of the following storage devices is properly plug into any USB port on the router and make sure this USB storage device is detected by the router. You can check it at "USB Devices" function in main menu.

1. USB Hard Disk Drive

(It is much recommended use USB HDD that equipped with its own Power supply)

2. USB Flash Drive

3. MP3 Player


4. USB Media Reader

Caution:

FTP server is compatible with FAT32 or EXT2 format USB storage device. In case you need to format your USB storage device. Please always make sure the device is formatted with FAT32 or EXT2 standard.

Account Creation

In order to configure FTP Server, please click on “**FTP Server**” icon in the main menu and click on “**setting**”. To configure basic simple FTP server, please take the following steps:



To create a new FTP account. Please go to “**Account Creation**” and enter information into following columns.


1. **Account name** – You can input any name you like and it will be used to identify the FTP server.
2. **Password** – Up to 8 characters of password can be applied in any combination of digits or letters. Verify the password in the next column.
3. **Partition** – Your storage device could have more than two separate partitions. This column allows you to select which partition to be used for FTP server.
4. **Directory** – The section provides option of which folder should be used for FTP Server.
5. **Access Right** – Set “**Read**” for download only and set “**Read/Write**” for both upload and download.
6. Click “**Add**” after above information is given.

Account Creation – Advanced Setting

- **Download throttling (kb/s)** – Download speed can be limited by a given value.
- **Upload throttling (kb/s)** – Upload speed can be limited by a given value.
- **Download/Upload ratio** – When the value is set, you are able to download and upload according to desired ratio.
- **Allowed client from which domain name/IP address < A.B.C.D> or < A.B.C.D./M>**
- This function allows you to give FTP access authority to limited users by entering IP address of authorized users.

FTP Server Setting

To activate FTP server, please go to “**FTP Server Setting**” and take the following steps:



- **FTP Server** – Select “**On**” to activate FTP server function.
- **Connection Allow** – Both WAN and LAN IP of router can be used to identify FTP Server. Select “**Accept Connections only from LAN**” will activate FTP server within local LAN group. Select “**Accept Connections from LAN and WAN**” will activate FTP Server for remote users.
- Click “**Apply**” after above information is given.

FTP Server Setting – Advance setting

- **Port number** – Port number - Define the FTP command transfer service port. Default value is 21. If you have changed this, remember to change the service port setting of your FTP client.
- **SSL/TLS** –Enable/Disable the SSL transfer of the FTP command. There are three choices of this option, you can use only normal connections, only SSL/TLS connections, or accept both of them at the same time. Enable the SSL/TLS connections only when you have the security concern. The default value of this option is <Accept only normal connections>.
- **Connection mode** – Passive mode served as default value. The data can be transmitted through Port 5000 ~ 65535. When select Active mode, the data transmitted through standard Port 20.
- **Maximum clients** – You can restrict limited number of clients access FTP at the same time. Leave it blank for unlimited access.
- **Maximum clients per IP** – You can restrict limited number of clients access FTP at the same time with same IP. Leave it blank for unlimited access.
- **Disallow rename** – Default value is “No”. Select “Yes” if do not allow rename the files.
- **Maximum idle time (minutes)** – When a specific time value is added, FTP Server will be de-activated if it has no activity within the time limit.
- **Disallow upload if partition is more than (%)** – This function allow users to limit their storage capacity in their storage device.
- **USB Disk Mount Language** – The function allows the file name to be viewed in different languages from FTP web page.

How to create a FTP Server IP address??

After completed the configuration steps listed above, FTP server can be accessed through web page by keying its unique FTP IP address. The formula of creating FTP IP address is listed below:

ftp://Account-name@WAN IP Address
(Need to type in password when log in)

ftp://Account-name:Password@WAN IP Address
(Do not need to type password when log in)

For example: If the account name of the FTP server you configured is "Fiber" and your WAN IP address is 192.168.1.254, Password is 1234.

Then, Your FTP IP address should be

ftp://fiber@192.168.1.254


Or

ftp://fiber:1234@192.168.1.254


How to access your FTP server??

After the FTP server is set up, it is open for access from both local and remote network via web page.

1. Open a web page and type in FTP IP address




2. Once the FTP IP address is entered, the screen will pop up and required to enter Account name and Password. Please enter the information and click ok.




To create “Network Neighborhood” by using FTP Server (WIN 98)

After successfully set up a FTP server, you can also use this FTP server to act as one of your “Network Neighborhood” within your LAN network.

1. After log onto FTP Server web page, please go to “Favorites” and click on “Add to favorites”.




2. Please change the name if necessary and click on OK.




3. Please select “Organize Favorites” from “Favorites” menu.



4. Please find the name of your FTP server which you added to “favorites” and hit single click on the name. Click on the right button of your mouse in order to find “properties” function.




5. After click on “properties”, the following screen will appear.




7. Click on OK to finish the setting. Now you can find the FTP folder appear in your Network Neighborhood from File Manager.

To create “Network Neighborhood” by using FTP Server (Win 2000/XP)


1. Open “Window Explorer” and click on “Network Neighborhood” or “My Network Places”.




2. You will then find a utility called “Add a Network Place”.



3. After click on "Add a Network Place", a welcome page of setup wizard will appear. Click next to begin the setup.





4. Click on next again to continue the set up of creating Network Neighborhood from FTP location.




5. Type in FTP address where you need to set up for Network Neighborhood.

Tip: If you do not wish to enter password every time when you access the FTP server from "My Network Places", it is recommended to add password into FTP IP address so other users do not need to enter the password again if they need to access it within your LAN network. The FTP address should be in the following format.


ftp://Account-name:Password@WAN IP Address




6. In this section, you need to type the name of FTP server in “Network Neighborhood”. Click next to continue.



6. Now you had completed the setup. Click finish to exit Setup Wizard.




7. Now go back to "File management" and then go to Network Neighborhood, you should find the folder of FTP Server appear in this section.



FTP Server Status

In this section, all FTP server activity can be monitored or forced disconnection when the file is uploading or downloading.

- **Account** – this section indicate the account name of FTP Server which currently transmitting the data.
- **State** – this section indicate the connection status.
- **Remote IP** – this section indicate Remote IP when it connect to FTP Server.
- **Time** – this section indicate the connection time
- **Filename** – this section indicate the file name when downloading or uploading are in processing.
- **Operation** – Downloading or uploading transmission can be discounted at any time if “Kick” box is checked and “Set” button is pressed.



Appendix A**Web Camera Compatible List**

Manufacturer	Model
Aiptek	HyperVcam Home
Amitech	AWK-300
Askey	Askey VC010
Alpha Vision Tech.	AlphaCam SE (model AC-520)
Avaks	AvCam USB-600
AverMedia	Intercam Elite
BestBuy	EasyCam U
Creative Labs	WebCam (model PD1001, alternate version)
Creative Labs	WebCam 3
Creative Labs	WebCam 5 (PID=400c)
Creative Labs	WebCam Plus (Model CT6840)
Creative Labs	WebCam Plus ("WebCam Mini"; model PD0040)
Creative Labs	WebCam Pro (model PD1030)
Creative Labs	Webcam Pro Ex
D-Link	DSB-C100
D-Link	DSB-C310
D-Link	DU-C300
Elecom	UCAM-C1C30
Elta	WEBCam 8211 PCC
Ezonics	EZPhone Cam
Hawking Tech.	UC-110
Hawking Tech.	UC-300
Hawking Tech.	UC-310
I-View	NetView NV300M
Intel	Me2Cam
LG Electronics	LPC-UM10

Multimedia Security Center

LG Electronics	LPC-UM15
Liferview	USB CapView
Liferview	RoboCam
Lifetec	LT 9388
Logitech	QuickCam 3000 Pro
Logitech	QuickCam 4000 Pro
Logitech	QuickCam Notebook Pro
Logitech	QuickCam Zoom
Logitech	QuickCam Orbit/Sphere
Maxxtro	CAM22U
Maxell	Maxcam (MPCC-1)
Medion	MD9388
MediaForte	MV300
MediaForte	PC Vision 300
Mustek	WCam 3X
Mtekvision	Zeca MV402
OmniVision	OV7110 Eval Board
OmniVision	OV511 +/OV7120 Eval Board
OmniVision	OV511 +/OV7620 Eval Board
Pretec	PCC-600
Prochips	PCA-3100
Puretek	PT-6007
Philips	PCA645VC
Philips	PCA646VC
Philips	PCVC675K "Vesta"
Philips	PCVC680K "Vesta Pro"
Philips	PCVC690K "Vesta Scan"
Philips	PCVC720K/40 "ToUCam XS"
Philips	PCVC730K "ToUCam Fun"
Philips	PCVC740K "ToUCam Pro"

Multimedia Security Center

Philips	PCVC750K "ToUCam Scan"
Sotec	Sotec Afina Eye
Suma	EON
Samsung	MPC-C10
Samsung	MPC-C30
Samsung	Anycam MPC-M10
TRENDNet	TV-PC100
TRENDNet	TV-PC300
TRENDNet	TV-PC301
Trust	Sp@ceC@m USB
Trust	Sp@ceC@m 200
Trust	Sp@ceC@m 300
Typhoon	WebShot 350
TEVion	MD 9308
TCE	NetCam 310u
Terratec	TerraCam PRO
Visionite	Visionite VCS UM100
Visionite	Visionite VCS UC300
Waytech	I-Pac VIC-30
Webeye	2000B