







HANDLING EQUIPMENT DIVISION



L SERVION DIVISION



Specials>2008





Index



PARTS DIVISION

+32 56 43 42 11 > FAX +32 56 43 44 88 > E-MAIL parts@tvh.com





Parts Division 5-45 / 60-63

| General | 5-15 | > Smart.ON | 28 |
|---|-------|---|-------|
| > References and brands | 5 | > Float valves | 29 |
| > TVH Quick Source | 6-7 | > Tyres | 30 |
| > Product groups | 8-11 | - Solid cushion tyres & tyre press | 30 |
| > New product groups | 12-13 | > Seats / Seat heating | 31 |
| > New, reconditioned or second-hand parts | 14 | > Bearings & hardware | 32 |
| > Service exchange parts | 14 | > Special chains with plastic inner or outer leaves | 33 |
| > Quality | 15 | > Valves | 34-35 |
| | | > Side shifts / Attachments | 36-37 |
| | | > Forks | 38 |
| Products | 16-45 | > Panoramic mirror | 39 |
| > Electronics | 16-18 | > Oil seal tool kit | 39 |
| - Electronic department | 16 | > Absorbing materials / Sealing products | 40 |
| - A selection of our testers | 17 | > BETA tools | 41 |
| - Electronic component cleaner | 18 | > BETA clothes | 42 |
| > Horizontal pre-cleaner / Safe-T-Lock™ | 19 | > BETA safety shoes | 43 |
| > Back-up alarms & horns | 20-21 | > Accessories for aerial platforms | 44 |
| - Safe-T-Alert back-up alarm | 20 | > Scale models | 45 |
| - bbs-tek™ back-up alarm & horns | 21 | | |
| > Lights | 22-23 | | |
| > DC/AC convertors | 24 | Why work with TVH? | 60-63 |
| > Battery chargers | 25 | > What can you expect from TVH Parts Division? | 60 |
| > SmartBlinky - Cyclops | 26 | > Catalogues | 61 |
| > Water filling pistols | 26 | > Trade fairs | 62 |
| > HydroFill | 27 | > Contacts Parts Division | 63 |
| > HydroPure | 27 | | |

© February 2008 TVH Forklift Parts N.V., Brabantstraat 15, B-8790 Waregem, all rights reserved.

All the information contained in this catalogue remains the property of TVH Forklift Parts and may not be copied, reproduced, transmitted or communicated in any other way to third parties without prior written permission.

- All photographs, illustrations, brand names and part numbers are included for identification purposes only.
- > TVH and TotalSource are registered trademarks of TVH Forklift Parts N.V.
- > Printing errors reserved
- In the catalogue of TVH, company and/or personal details are collected from forms. When you provide us with such information, it is stored in the files of TVH. You have the right to access and, if necessary, correct your company and/or personal data, according to the applicable law.

The databases containing your information are protected against unauthorized access. The information collected is not transmitted to third parties.

All offers and pricing contained in this catalogue were correct at the time of publication (February 2008), however, TVH Forklift Parts N.V. reserves the right to review pricing and availability at the time of ordering.

Index



FORKLIFT DIVISION

- +32 56 43 43 11 +32 56 43 43 45
- > E-MAIL forklift@tvh.com



Forklift Division 46-51

| > Our export salesteam | 46 |
|--------------------------|-------|
| > Purchase | 46 |
| > Used forklifts | 47-49 |
| > Used clamps | 49 |
| > Used aerial platforms | 50 |
| > Loading ramp LR TN 100 | 51 |
| > Our used stock on-line | 51 |



HANDLING EQUIPMENT DIVISION

+32 56 43 48 20

+32 56 43 49 20

> E-MAIL handling@tvh.com



Handling Equipment Division

| 52-59 |
|-------|
|-------|

| > | Handling your business! | 53 |
|---|---|-------------------------------|
| | - Hand pallet truck | 53 |
| | - Stainless steel hand pallet truck | 53 |
| | - Scissor hand pallet truck | 53 |
| | - Weighing hand pallet truck | 53 |
| > | Stacking your business! | |
| | - Manual stacker | 54 |
| | - Electric stacker | 54 |
| | | |
| | - Ergonomic stacker | 54 |
| > | - Ergonomic stacker Loading & lifting your business! | |
| > | Loading & lifting your business! | 55-56 |
| > | _ | 55-56 55 |
| > | Loading & lifting your business! - Safety trestle | 55-56 55 55 |
| > | Loading & lifting your business! - Safety trestle - Ramps for forklift trucks | 55-56 55 55 |
| > | Loading & lifting your business! - Safety trestle - Ramps for forklift trucks - Safety jack | 55-56 55 55 55 |
| > | Loading & lifting your business! - Safety trestle - Ramps for forklift trucks - Safety jack - Hydraulic jacks | 55-56 55 55 55 56 |

| > | New products! | 57 |
|---|--------------------------------------|------|
| | - Mechanic lifter | 57 |
| | - Lifting tables | 57 |
| | - Special hand pallet truck | 57 |
| > | Climax Handling Equipment 5 | 8-59 |
| | - Galvanised hand pallet truck | 58 |
| | - Stainless steel hand pallet truck | 58 |
| | - Weighing hand pallet truck | 58 |
| | - Manual scissor hand pallet truck | 58 |
| | - Electric scissor hand pallet truck | 58 |
| | - Manual stacker | 58 |
| | - Semi-electric stacker | 59 |
| | - Electric stackers | 59 |
| | - Electric pallet trucks | 59 |
| | | |

Foreword



Dear customer,

TVH has released a brand-new brochure 'Specials 2008' for you!

As recent studies have shown us, our clients are enthusiastic to learn more about our novelties. We are eager to meet your wishes and are pleased to introduce our **new products** and services to you in a yearly magazine, of which you are now holding the first version.

This brochure highlights several new products such as the DC/AC converter (Parts Division), the safety trestle (Handling Equipment Division), the loadramp (Forklift Division), and more...

TVH's mission is to offer you a maximum satisfaction by offering the right product at the most competive price with a guaranteed quick delivery. There is no doubt that this brochure will bring us closer to achieving that goal.

The Parts Division of TVH is committed to be a **leading supplier**, **globally spread** and therefore **easy to reach**. TVH is your true one-stop shop for material handling equipment, aerial platforms and other in-plant industrial vehicles.

Take a look at our new brochure and discover the new products and services that will help you lifting your business.

Kind regards,

Filip Goethals, Sales Manager

Parts Division - General References and brands

TVH offers you 450 000 spare parts in stock and over 11 000 000 known references.

A computer-controlled stock management, professionally trained people and a wide range of products lead to a fast and complete solution. Wherever you are, we supply your parts within 24/48 hrs.

With our extensive range we try to meet your needs as much as possible. We can offer you parts for the following groups:





- > Aichi
- > Allis Chalmers Kalmar AC
- Artison
- Atlet
- > Balkancar
- **>** Baumann
- > Bobcat
- > Bolzoni
- Bonser

- > Boss
- > BT
- > Bulli
- > BV Vestergaard
- Caterpillar

- > Clark
- Cesab
- Kalmar
- Conveyancer

- > Crown
 - Datsun
 - Desta

 - Dieci
 - > Fenwick
 - > Fiat
 - > Genie
- > Climax Coventry > Grove
 - Halla
 - > Hangcha

TOTAL SOL

- > 450 000 stock items
- > **11 000 000** known references
- > Hangzhou
- Haulotte
- > HC
- > Heli
- Henley
-) Hyster
-) Hyundai
- > Icem
- > JCB
- > JLG
- Jungheinrich
- > Kalmar LMV
- > Kalmar-Climax
- > Kalmar-Irion
- > Kentruck
- > Komatsu
- > Kooi Aap > Lafis
- > Lancer Boss

- Lansing
- > Lifter > Linde
- > Lugli
- Manitou
- Matral
- > MIC
- > Niftylift
- Nissan
- > Nyk-Nichiyu
- **>** OM
- > OMG
- > Patria
- > Peg Fenwick
- > Pimespo
- > Prat
- > Rocla
- > Salev
- Saxby

- > Sichelsmidt
- Skyjack
- > SMV
- > Stam
- > Steinbock
- > Still
- > Stocklin
- > SVE Truck
- > Tailift
- > TCM
- Tecnocar
- Toyota
- Upright
- Wagner
- Yale
- > Yang Yam -Puma

TVH Quick Source



Go on-line with Europe's biggest one-stop-shop for forklift parts!

VERSION

5.2

Order your free CD-ROM

REF 115TA7014 (In 17 languages)

On-line inquiry & order

- > Inquiries/orders with or without part number.
- > Available 7d/week, 24 hours/day.
- On-line search for part numbers of all truck models (more than 4800 truck types).
- > Available in 17 languages and used in more than 100 countries.
- > Includes all interactive catalogues.

To find out how to install the new version of TVH Quick Source and learn more about the new features, visit our web page www.tvh.com/quicksource or contact the e-commerce department on +32 56 43 48 66 or ecommerce@tvh.com

Did you know that with the version TVH Quick Source 5.2 you can...


- now also select these **NEW LANGUAGES**: Polish, Czech, Romanian, Hungarian, Turkish, Swedish, Norwegian, Finnish, Danish and Lithuanian?
- ... call up our **SPECIALS** and **PROMOTIONS**?
- ... look up **RUBBER TRACKS**?

In our TVH Quick Reference database you can search for 206 brands and 2381 types of rubber tracks.

- ... look up parts of **AERIAL PLATFORMS**?

 In our TVH Quick Reference database you can search for 8 different brands and 341 types of aerial platforms.
- ... **FILE** your **COMPLAINTS** and **RETURNS** on-line? Clicking on a few buttons will enable you to register your complaint in swift and easy manner.
- find an **OVERVIEW** of your **COMPLAINTS** and **RETURNS**?
 You can check history and details of every complaint as well as your contact person handling the complaint.
- ... **PRINT** and **OVERVIEW** your outstanding **INVOICES** as well as invoices that have been paid already?
- ... trace all your **BACK ORDERS**?

 Clicking on a single button will show you a list of your back orders with the relevant delivery term.







- > Batteries and chargers
- > Battery accessories
- > Safety products
- > Electric cables
- > Battery connectors
- > DC-DC convertors



- > Switches and accelerators
- > Emergency switches
- > Relays
- > Fuses
- Contactors
- > Lift truck electronics



- > Hour meters and battery indicators
- Horns and back-up alarms
- > Signals, lighting and bulbs
- > Electronic accessories
- > Ex-proof accessories



- Motors and armatures
- > Brushes, springs and holders
- > Electric motor parts
- > Electric brakes
- > Electric fans
- > Universal pump motors



- > Hoses and accessories
- **>** Pumps
- Distributor valves, slices and handle kits
- > Fittings and seals
- > Pump units
- > Steering units



- > Starters and alternators
- > Key switches and keys
- > Ignition and carburation
- > LPG parts
- > Fuel systems diesel / gasoline



- > Engine parts
- > Filters
- > Exhaust systems
- Cooling system parts



- > Steering parts
- > Transmission & drive axles







- > Hydraulic brake parts
- > Air brake parts
- > Brake pads and shoes
- > Cables



- > Tyres
- > Rims
- > Wheels
- Castors



- > Upright parts
- > Forks
- Mast rollers
- **>** Chains
- Attachments



- > Cabs and parts
- > Cab heaters
- > Wipers
- Gas springs
- > Mudguards
- > Pedal pads
- > Seats
- > Hood and chassis parts



-) Hardware
- Maintenance
- > Oil and greases
- > Paint and accessories
- > Warehouse & workshop tools



- > Pallet truck parts
- > Seal kits



- > Sweepers
- > Brushes
- > Vacuum motors
- Accessories



- > Scale models
- Order forms
- Catalogues
- > Various marketing items



New product groups






Parts for Aerial Platforms

Suitable for:

- Aichi
- Dinolift
-) Genie
- > Grove
- > Haulotte
- > JLG
- > Skyjack
- > Upright
- Snorkel
- > Manitou-
 - Maniacces



Parts for Telescopic Forklifts

Suitable for:

- Manitou-Maniscopic
 - > Komatsu > Terex
- Dieci
 - Matbro
- Caterpillar
- > JLG > Genie

> Sambron

- > JCB Sanderson
 - **>**
- > Bobcat



Parts for Truck-Mounted Forklifts

Suitable for:

- Moffett-Kooi
- Manitou-Manitransit
- > Palfinger-Terberg
- > Kinglifter
- **>** ...

Parts for Attachments

Suitable for:

- Cascade
- > Cam
- > Bolzoni
- > Roncari
- Auramo
- > Atib
- > Kaup
- > Seith
- > Stabau
- Meyer Wifo
- **>** ...





Parts for Tow Tractors

Suitable for:

> Charlatte

> Rofan

> Clark

Spijkstaal

> Cushman

> Still

) Harlan

Toyota

> Linde

> Tracma

Mafi

Tiger

Mol

Terberg

Mulag

> Taylor Dunn

Nissan

> ...

> OM Pimespo

Parts for **Sweepers and Scrubbers**

Suitable for:

- **>** Tennant
-) Hako
- > Power Boss
- > Nilfisk Advance
- > Dulevo
- Xärcher
- > RCM
- Comac
- **>** ...

Parts for Tail Lifts

Suitable for:

- > Dhollandia
- Zepro
- > Erhel Hydris

Rubber tracks

TVH is now also your specialist in the field of rubber tracks and rubber pads!

Send the make and type of mini-excavator, skid steer loader or dumper and we send vou a custom-made offer.





Also available! Rubber pads for steel tracks

New, reconditioned or second-hand parts

New parts

- > Parts and accessories that are new
- > 6-month guarantee

All possible spare parts and accessories.

Reconditioned parts

- High-value parts that are restored to a "good-as-new" state
- > 6-month guarantee
- Sold with or without return of old part

Examples: see below

Second-hand parts

- Parts that are sold without restoration in the state as they are at that moment
- > Without guarantee period

Masts, attachments (clamp, side shift, rotator,...)



1. Supplier rating & sourcing

To be able to offer continuously the best quality to our customers, we use an extensive system to rate our existing suppliers and to source new products with new suppliers. We rate all our suppliers on:

- > Product quality (equal to OEM in use, life cycle and dimensions, with warranty on all parts)
- > Packaging of the goods we order (packaging fitted for transportation, with minimal risk of damage)
- > Overall supplier reliability (on-time deliveries, response time to our questions, pricing and availability of the products,...)

2. Sample testing

All samples we receive from our suppliers are subjected to profound testing in our Quality Control Department. Therefore we have invested in top-quality testing and measuring devices, such as a hardness tester, spectrometer, 3D-measurement, PCB testing installations, and several others.

All samples are measured, compared and tested. Some of them are built in machines to test in a real work environment.

Thanks to a new universal transmission testing bank, TVH can guarantee a high quality for all delivered transmissions.

The customer receives, together with his repaired transmission, a testing report on which all the measured pressures by several rpm are mentioned. Furthermore, the testing bank also tests with both cold and heated oil.

Spectrometer



3. Entry control & storage

A random check determines which parts per shipment will be tested. Parts are measured and tested, based on the information we have stored in our system in technical sheets, technical drawings, sample test reports, and spec sheets of that specific part.

This way, we can check the conformity of the shipment with the received samples and compliance with agreements made with supplier. Those results reflect back to the supplier rating system we have set up. If the quality of the pieces is approved, they get an internal code and label, are all individually packed and are put in stock under excellent warehouse conditions (humidity, temperature,...)

3D-measurement



Transmission testing bank




Hardness tester



Parts Division - Products

Electronics - Electronic department



We can offer you:

- > New (all makes)
- > Service Exchange
- > Repair

The Electronics Department is one of the fastest growing departments of TVH and has over 30 qualified electronic engineers to give you support and to repair all your electronic cards and controllers. Our repair programme is growing day by day and we keep on searching for the right people to give you the best service possible.

Did you know that:

- > TVH repairs over 10 000 cards a year.
- > All controllers are thoroughly load tested.
- You get a 6-month warranty on all new, repaired and service exchange parts.
- You can send us your own card/controller for repair if TVH has no new or service exchange available.
- > TVH also repairs:
 - joy sticks, displays, accelerators,...
 - electronic parts for aerial lifts.





Electronics - A selection of our testers

Tester used for Linde transistors and SKiiP modules

Tester: REF 122TA8869
Transistor: REF 116TA5184
SKiiP Module: REF 128TA4027







REF 122TA8869

REF 116TA5184

REF 128TA4027

Breakout box used for Linde trucks

- > Breakout box 25-pole: REF 122TA8863
- > Breakout box 29-pole with Saab (AMP) connector: REF 122TA8864
- > Breakout box 42-pole with Saab (AMP) connector: REF 122TA8865
- > Breakout box 55-pole: REF 122TA8866
- > Breakout box 121-pole AMP + Bosch connector: REF 123TA6821

A lot of "sealed" connectors prevent the engineer from carrying out measurements in a working lift truck. This breakout box offers you the possibility to carry out all measurements in a comfortable way.



REF 122TA8865

Zapi handset / Software + interface cable

- > Standard programmer: **REF 105TA4796**
- > Standard software + interface cable: REF 127TA3794
- > Zapi programmer used for:
 - BT: REF 127TA3783
 - Cesab: REF 127TA3784
 - Clark: **REF 127TA3785**
 - Crown: REF 127TA3786
 - Fiat: REF 127TA3787
 - Komatsu: **REF 127TA3788**
 - Linde: REF 127TA3789
 - Mitsubishi: REF 127TA3790
 - Montini: **REF 127TA3791**
 - Pimespo: **REF 127TA3792**
 - Rocla: REF 127TA3793



REF 105TA4796

REF 127TA3794

Clamp meter

REF 127TA3795

RMS readings in AC-mode 1000A AC/DC, 700VAC, 1000VDC, resistance, diode + continuity, backlight, analog bargraph, min/max, hold function, jaws lighting,...

- > IEC1010 & IEC1010-1-032 double insulation
- > CAT III 600V & pollution 2
- Included: user manual, batteries and test lead



REF 127TA3795

Electronics -

Electronic component cleaner



- Offers the service engineer the possibility to perform an efficient and time-saving cleaning of all electronic controllers, electric motors, batteries... (e.g.: cleaning the controller as shown on the picture only takes 5 min, consumption = ± 1 litre)
- > Prevents moisture problems
- Does not affect electronic components and does not cause corrosion or leakage currents
- > Excellent water-/dust-/oil-repellent
- > Product evaporates and does not leave a residue
- Motors can be cleaned without being removed
- Can be used to clean the electronic parts when buying a second-hand truck



Grafite gun

> With compressed air connection (6-10 bar)



REF 127TA3797

Electronics cleaner

REF 127TA3798: 1L
 REF 127TA3799: 5L
 REF 127TA3800: 10L
 REF 127TA3801: 30L
 REF 127TA3802: 100L



REF 127TA3798

Procedure

- > Spray the part and let the product operate on the part for about three minutes.
- > Clean the part completely.
- > Remove residue by blowing out the part with compressed air.

Horizontal pre-cleaner / Safe-T-Lock™



Prevents unauthorized use of your vehicle!



Horizontal pre-cleaner

This new air cleaner family offers two-stage filtration in a single, compact unit that delivers superior filtration performance. This non-metal air cleaner (except for cover clamps) is ideal for medium- and heavy-duty equipment operating in severe dust environments.

Applications:

- Off-road equipment operating in medium to heavy dust conditions with engine airflow ranges up to 20 m³/min (700 CFM).
- Oval housing shape allows for a narrow or wide mounting orientation. Models include end filter service access and side filter service access.

Features:

- Improved engine protection: no media movement, expansion, contraction or bunching.
- Improved filtration efficiency: three times more than the average conventional pleated filter.


The built-in mounting brackets eliminate the need to purchase separate mounting bands.



Safe-T-Lock™

Programmable code switch

- > 12-120 VDC.
- > Up to 99 different users/drivers.
- Maintenance cycle 250 "ON" hours. Unit will beep intermittently until reset.
- Last user ID function supervisor can easily identify the last operator.
- > Waterproof, IP65.



The SAFE-T-LOCK™, a new programmable code switch is now available. This switch prevents unauthorized use of your vehicle.

The STL 1000 switch accepts the input from 99 different users. If an accident occurs the supervisor can easily identify the last operator.

The SAFE-T-LOCK™ also has an internal clock that records the operating hours and warns the user when the vehicle reaches the 250-hour mark.

It can also be connected through the seat switch to deactivate the vehicle after 3 minutes of inactivity.

Back-up alarms & horns

Safe-T-Alert back-up alarm



Safe-T-Alert 2000 series

| Voltage | Volume | Reference | |
|--|-------------|-----------------|--|
| 12 - 24 V | 87 dB | REF 115TA6948* | |
| 12 - 80 V | 87 dB | REF 115TA6949* | |
| 12 - 24 V | 97 dB | REF 115TA6951* | |
| 12 - 48 V | 97 dB | REF 115TA6952* | |
| 12 - 80 V | 97 dB | REF 115TA6953* | |
| 12 - 24 V | 102 dB | REF 115TA6955* | |
| 12 - 24 V | 77 - 102 dB | REF 115TA6945** | |
| 12 - 48 V | 77 - 97 dB | REF 115TA6944** | |
| * conforms to SAE J994 type C or D ** self-adjusting | | | |

Safe-T-Alert 2500 series



| Voltage | Volume | Reference | |
|------------------------------------|------------------------------|----------------|--|
| 12 - 80 V | 87 dB | REF 123TA2002* | |
| 12 - 48 V | 97 dB | REF 123TA2003* | |
| 12 - 24 V | 102 dB REF 123TA2004* | | |
| * conforms to SAE J994 type C or D | | | |

Safe-T-Alert 3200 series



| Voltage | Volume Reference | | |
|------------------------------------|---------------------------|----------------|--|
| 12 - 24 V | 97 dB | REF 115TA6958* | |
| 12 - 24 V | 107 dB REF 115TA69 | | |
| * conforms to SAE J994 type B or C | | | |

Back-up alarms & horns

bbs-tek™ back-up alarm & horns

bbs-tek™ back-up alarm

The bbs-tek™ BACKALARM® uses multi-frequency broadband sound instead of the traditional single-frequency sound of a conventional alarm. The sound dissipates much quicker, is directional, and is localized in the danger zone, resulting in an enormous reduction in noise nuisance and complaints.

Operators involved in all types of vehicle movement from conventional road transport, including trucks, RCV's, buses and low loaders to off-road applications, including quarry vehicles, are already experiencing the unique benefits of the bbs-tek™ BACKALARM®.

Not only are noise nuisance and complaints considerably reduced, but the unique localization feature of the bbs-tek™ BACKALARM® means that in busy environments you can instantly tell where the sound is coming from and, therefore, which vehicle is reversing.

| Voltage | Volume | Reference |
|-----------|--------|---------------|
| 12 - 24 V | 82 dB | REF 111TA3741 |
| 12 - 24 V | 87 dB | REF 111TA3742 |
| 36 - 80 V | 82 dB | REF 111TA3743 |
| 36 - 80 V | 87 dB | REF 111TA3744 |

Lifetime warranty

Limited noise, big sound safety all round




bbs-tek™, it goes shh! Not bleep!

Electronic horn

> 36/48V

Extra long life spanVolume: 112 dB

> Diameter: 90 mm





REF 127TA3155

Low tone horn

Volume: 112 dBDiameter: 90 mm

REF 107TA1178: 12V - 5A - 345 Hz
 REF 106TA1408: 24V - 4A - 345 Hz
 REF 111TA3927: 36/48V - 1A - 345 Hz
 REF 111TA3929: 72/80V - <0.5A - 345 Hz



Lights



LED-technology provides extremely long life span, low power consumption and high resistance to shock and vibration.



LED oval horizontal work light

- Durable nylon housing, impact-resistant polycarbonate lens sealed against water, dust and corrosion
- > Eliminates costly bulb replacement, maintenance calls and downtime
- > Mounting 5/16" bolt
- > LED-light 12V-48V



LED rear combination light

- > Incorporates stop, tail, turn & back-up functions
- > Designed for extremely long life span
- > Completely sealed lamp, protection from water, dust,...

Kit = 2 lamps + 1 flasher

- **LED-light kit 12V REF 122TA7699**
- > LED-light kit 24/36V REF 122TA7700
- > LED-light kit 48V REF 122TA7701

Lamps

- > 12V REF 122TA7702
- > 24/36V **REF 122TA7703**
- > 48V REF 122TA7704

Flasher

> Flasher REF 122TA7705



REF 123TA1992

Meteorlite - ML5 - LED

- > Microprocessor controlled
- > Current draw 0.1 Amp
- > Epoxy filled base
- > Amber
- > Strobe light 12/80V





Meteorlite - ML2 - LED

- > Microprocessor controlled
- \rightarrow 60 \pm 6 quad FPM
- > Current draw 0.1 Amp
- > Epoxy filled base
- **>** Amber
- > Strobe light 12/80V



Lights

Mini MagLite® LED and MagLite® LED

The new Mini MagLite® LED and MagLite® LED flashlight are crafted after the legendary (Mini) MagLite® flashlight. Its durability and patented features are now available with the new MagLED® Technology. For the mini MagLite® LED you can choose between the super bright 2-Cell AA for its smaller size or the longer 3-Cell AA with its even higher performance. The MagLite® LED is available in 2, 3 & 4 Cell D size.

The benefits include:

- > A powerful projecting beam
- > Balanced optics™
- > Intelligent energy source management (patent pending)
- > Candle Mode (only available for the Mini MagLite® LED)
- > Interchangeable Light Sourcing (only available for the MagLite® LED)
- > PLUS: All of the quality features professionals and consumers expect from a MagLite® flashlight:
 - Rugged, machined aluminium construction with knurled design.
 - Anodized inside and out for improved corrosion resistance.
 - Water and shock resistant.



-) 1. REF 127TA3813: Mini MagLite® LED
- 2. REF 127TA3814: Mini MagLite® LED
- > 3. REF 127TA3815: MagLite® LED
- > 4. REF 127TA3816: MagLite® LED
- **>** 5. **REF 127TA3817**: MagLite® LED

Work Light 24V

- > Extreme shock and vibration resistance
- > Light source: 35W D2S Xenon-gas discharge lamp
- > Nominal voltage: 24V
- > Start: 24V 2.9A
- > Operation: 24V 1.7A
- > Operating temp: -40°C...+85°C
- > IP-rating: IP 68
- > Lens: hardened glass
- > Housing: aluminium
- > Ballast unit: integrated
- > Integrated Deutsch 2 pin



REF 127TA3818

Strobe light heavy duty 10/110 VDC

- > Strobe light 10/110VDC
- > Flash rate 75: ± 10 flashes/minute
- **>** Nominal power \pm 5 Watts
- > Economic version: REF 127TA3819



REF 105TA4896

DC/AC convertors

Technical Specifications

- > Output voltage: 230VAC 50Hz
- > Modified sine wave
- > With ON/OFF-switch and LED-indicator
- Input Protection: Over and under voltage
 - Low battery alarm and
 - shut down
- > Output Protection: Short circuit
 - Over load
 - Over temperature

| | 12VDC | 24VDC |
|---------------------------|---------------|---------------|
| Input voltage range | 10.5 – 15.0 V | 20.5 - 29.8 V |
| Low voltage shut down at | < 9.8 V | < 19.8 V |
| High voltage shut down at | > 15.6 V | > 30.1 V |



REF 127TA3822

| Max. continuous power (W) | Surge capacity (W) | Dimensions (mm) L x W x H | Input voltage (VDC) | Reference |
|---------------------------------|--------------------------|---------------------------------|------------------------|-----------|
| 150 | 300 | 165 x 100 x 55 | 12 | 127TA3820 |
| 150 | 300 | 165 X 100 X 55 | 24 | 127TA3821 |
| 300 | 600 | 105 v 100 v 55 | 12 | 127TA3822 |
| 300 | 000 | 195 x 100 x 55 | 24 | 127TA3823 |
| 500 | 1 000 | 235 x 100 x 55 | 12 | 127TA3824 |
| 300 | 1 000 | 235 X 100 X 55 | 24 | 127TA3825 |
| 700 | 1 400 235 x 1 | 0 1400 235 x 147 x 60 | 12 | 127TA3826 |
| 700 | 1 400 | 230 X 147 X 00 | 24 | 127TA3827 |



REF 127TA3830

| Max. continuous power (W) | Surge capacity (W) | Dimensions (mm) L x W x H | Input voltage (VDC) | Reference |
|---------------------------------|--------------------------|---------------------------------|------------------------|-----------|
| 1000 | 2000 | 265 v 100 v 75 | 12 | 127TA3828 |
| 1000 | 2000 | 265 x 180 x 75 | 24 | 127TA3829 |
| 1500 | 3000 | 215 v 100 v 75 | 12 | 127TA3830 |
| 1 300 | 3000 | 315 x 180 x 75 | 24 | 127TA3831 |
| 2000 | 4000 | 395 x 180 x 75 | 12 | 127TA3832 |
| 2000 | 4000 | 383 X 100 X 73 | 24 | 127TA3833 |



| Max. continuous power (W) | Surge capacity (W) | Dimensions (mm) L x W x H | Input voltage (VDC) | Reference |
|---------------------------------|--------------------------|---------------------------------|------------------------|-----------|
| 3000 | 6000 | 205 v 100 v 140 | 12 | 127TA3834 |
| 3000 | 6000 | 395 x 180 x 140 | 24 | 127TA3835 |



Accessory

Universal adaptor for use in UK, USA, Denmark, Switzerland, Middle East, South America, Russia, Germany, Egypt, Italy, Australia and Taiwan.



REF 115TA6975

Battery chargers

The new 3-phase range of Energic Plus high frequency chargers
NG5 / NG7 / NG9 / NG9 PLUS





Energic Plus high frequency chargers

New features

- > New technical solution for the board
- > New selection mode
- > New display
- > New bigger powers available:
 - 24V 200A
 - 36V 200A
 - 48V 135A



Why do high frequency chargers have success? We are talking about "controlled" battery chargers: the battery charger is able to make the optimal recharge by succeeding in controlling and adjusting the current, the voltage and all the charging parameters as stated by the batteries manufacturers.

Advantages:

- > Exceptional charging quality
- Longer life span of the battery
- > 15% of saving on the charging costs
- > Water consumption almost halved
- > Battery maintenance reduced of about 50%
- > Lower gas emissions
- Weight and size about 10 times reduced: Every battery charger can be embarked

Technical specifications

The Three-phase Chargers NG5/7/9 are innovative devices with extraordinary versatility, reliability and efficiency. The high power and efficiency of these chargers assures the user of **considerable energy savings** with subsequent **economic benefit**. Thanks to this **advantage**, the investment in high frequency products is quickly amortized. Energic Plus (hf) chargers are classified amongst the products with the best quality/price ratio on the market.

| | IUIa charging curves Selector adjustment | | | | | | | | | | | |
|--------|--|-----------|------------|------------|-----------|----------|-------|------|------------|----------|-----------|-----------|
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | | | | DEE 8 11 | |
| | What tin | ne do you | have avail | able to ch | arge your | battery? | | V | l1-lmax | Model | REF. Acid | REF. Gel |
| | | С | harging ti | mes (hour | s) | | | | | | | |
| 11/12 | 10.5 | 9.5 | 9 | 8 | 7.5 | 7 | 6.5 | | | | | |
| 960Ah | 880Ah | 800Ah | 720Ah | 640Ah | 560Ah | 480Ah | 400Ah | | 100A | NG5 | 127TA3886 | 127TA3901 |
| 1150Ah | 1055Ah | 960Ah | 865Ah | 770Ah | 670Ah | 575Ah | 480Ah | 24 V | 120A | NG9 | 127TA3887 | 127TA3902 |
| 1920Ah | 1760Ah | 1600Ah | 1440Ah | 1280Ah | 1 120Ah | 960Ah | 800Ah | | 200A | NG9 PLUS | 127TA3888 | 127TA3903 |
| 960Ah | 880Ah | 800Ah | 720Ah | 640Ah | 560Ah | 480Ah | 400Ah | 36 V | 100A | NG5 | 127TA3889 | 127TA3904 |
| 1630Ah | 1495Ah | 1360Ah | 1225Ah | 1090Ah | 950Ah | 815Ah | 680Ah | 30 V | 170A | NG9 PLUS | 127TA3890 | 127TA3905 |
| 770Ah | 705Ah | 640Ah | 575Ah | 510Ah | 450Ah | 385Ah | 320Ah | | 80 - 95A | NG5 | 127TA3891 | 127TA3906 |
| 960Ah | 880Ah | 800Ah | 720Ah | 640Ah | 560Ah | 480Ah | 400Ah | 48 V | 100A | NG7 | 127TA3892 | 127TA3907 |
| 1150Ah | 1055Ah | 960Ah | 865Ah | 770Ah | 670Ah | 575Ah | 480Ah | 40 V | 120A | NG9 | 127TA3893 | 127TA3908 |
| 1295Ah | 1 190Ah | 1080Ah | 970Ah | 865Ah | 755Ah | 650Ah | 540Ah | | 135 - 160A | NG9 PLUS | 127TA3894 | 127TA3909 |
| 670Ah | 615Ah | 560Ah | 505Ah | 450Ah | 390Ah | 335Ah | 280Ah | 72 V | 70 - 85A | NG7 | 127TA3895 | 127TA3910 |
| 865Ah | 790Ah | 720Ah | 650Ah | 575Ah | 505Ah | 430Ah | 360Ah | /2 V | 90 - 110A | NG9 | 127TA3896 | 127TA3911 |
| 480Ah | 440Ah | 400Ah | 360Ah | 320Ah | 280Ah | 240Ah | 200Ah | 80 V | 50 - 60A | NG5 | 127TA3897 | 127TA3912 |
| 770Ah | 705Ah | 640Ah | 575Ah | 510Ah | 450Ah | 385Ah | 320Ah | 00 V | 80 - 100A | NG9 | 127TA3898 | 127TA3913 |
| 385Ah | 350Ah | 320Ah | 290Ah | 255Ah | 225Ah | 190Ah | 160Ah | 96 V | 40 - 50A | NG5 | 127TA3899 | 127TA3914 |
| 530Ah | 485Ah | 440Ah | 395Ah | 350Ah | 310Ah | 265Ah | 220Ah | 90 V | 55 - 65A | NG7 | 127TA3900 | 127TA3915 |

SmartBlinky -Cyclops



Water filling pistols

Most industrial batteries need to be topped up with water regularly. Topping up batteries with hoses, watering cans, jugs, or other containers can be dangerous and inaccurate. Water and acid may be spilled or splashed onto the operator and batteries may be over or under filled.

WateringGuns fill battery cells with water and automatically shut off when the electrolyte reaches the correct level. The guns can connect to our HydroPure deionisers, HydroFill watering cart, or suitable mains water supply. The WateringGun is compact, lightweight and easy to operate. Set the level control, open the flip top vent and insert the nozzle. Squeeze the trigger until the shutoff occurs and then release the trigger.

- > Quick and efficient filling of batteries
- > Reduced labour costs
- > Automatic shutoff
- > Improve filling accuracy
- Improve operator safety

'The clever way to manage battery watering'

The biggest problem in battery maintenance is knowing when to fill the batteries with water.

Time is often wasted when inspecting and topping up batteries that do not require filling, while batteries left under-filled can suffer costly permanent damage.

The SmartBlinky – Cyclops is the new revolution in advanced technology battery watering!



"The SmartBlinky – Cyclops has a LED mounted in a housing that is located behind the battery plug. This will allow the operator to visually check the electrolyte-level, every time the battery is disconnected from the charger."

- Safest electrolyte level monitor on the market: Low voltage (4V nominal) - fuse protected - low current draw - internationally certified
- **Easy to see and to use:** A green light means the electrolyte level is OK; a red light means it is time to water the cells.
- Protects your battery investment: The SmartBlinky Cyclops helps protect against battery dry-out.
- > Gives bright, unambiguous signals
- Engineered to be durable: The SmartBlinky Cyclops is built to withstand the harsh environment of industrial battery applications.
- Inexpensive and cost effective: Over a battery lifetime, the SmartBlinky – Cyclops saves a surprising amount of time – or labor cost – and delivers a rapid return on investment.

WateringGun B

- Automatic shutoff and regulator
- 22 mm nozzle, fits most batteries
- > High flow rate 7.6l per minute
- Attaches to any standard hose (quick connect fittings included)



WateringGun G

- Automatic shutoff
- > 16 mm nozzle, for small vent openings



REF 124TA1726

WateringGun R

- > Automatic shutoff
- > Extra narrow 12 mm nozzle
- > With 228 mm extension



REF 124TA1728

WateringGun C

- Automatic shutoff
- 16 mm nozzle, for small vent openings
- Steep bend for limited access applications



WateringGun N

- > Automatic shutoff
- > Extra narrow 12 mm nozzle



REF 124TA1727

WateringGun S

- For watering transparent jar type stationary batteries
- > Gun operates outside the cell
- Does not have automatic shutoff



REF 124TA1729

HydroFill

HydroPure





'No matter where your battery is, you can fill it!'

Most industrial batteries need regular watering but it is often difficult to bring the battery to an adequate water supply for refilling. Batteries and trucks can often be located in separate areas on site and this often leads to wasted time and improper watering.

With the HydroFill water can be transported to the battery wherever required. The HydroFill is a battery powered cart that is used with our WateringGuns or float filling system to top up batteries. The operation is simple, you just top up the cart with a deioniser unit, bottled water, from the tap (if suitable for topping up batteries), attach to topping system, turn on the cart and you're ready to go.

- > Easy transportation of water to the battery
- Inbuilt pump and battery
- > No long wires or hoses
- > Perfect for small fleets
- 1. Easy to manoeuvre: handles like a hand truck
- 2. Easy to use: instructions on unit
- 3. Easy to fill: large opening
- 4. Sturdy 30 litre tank
- 5. ON/OFF switch located on the rear of the unit
- 6. 3 metre hose attaches to all our WateringGuns
- 7. Sealed rechargeable battery is included. Charge the unit from any 230VAC outlet with the provided charger.

'Make buying distilled water a thing of the past'

The HydroPure is a low cost deioniser system that allows you to make pure water straight from the tap!

Make your own pure water directly from your tap water. This deioniser reduces the high price of buying bottled water and it's more convenient as well. Each disposable cartridge purifies about 2400 litres of water and the purity light will tell you exactly when the cartridge is used up.

- HydroPure 300: deioniser system complete supplied with DC battery powered purity light and 1 replaceable cartridge: REF 127TA3874
- Replacement deioniser cartridge for 300/400: REF 127TA3875

Specifications

| Flow rates | | | |
|---|--------------------|--|--|
| Maximum intermittent flow | 8 litres/min | | |
| Maximum continuous flow | 2 litres/min | | |
| Output | | | |
| Maximum output (input purity 50ppm) | 5760 litres | | |
| Typical output (input purity 120ppm) | 2400 litres | | |
| Poor water output (input purity 250ppm) | 1 150 litres | | |
| Maximum input pressure | 80 psi | | |
| Cartridge resin volume | 4.5 litres | | |
| Indication | | | |
| Purity light indication water OK | Steady green flash | | |
| Purity light indication water BAD | Double red flash | | |
| Purity light OK max threshold | 50 ppm | | |

- Professional quality deionisers: Not just a filter, which only removes particles, but a real ion-exchange medium which electrostatically removes dissolved impurities. Purity is comparable with distilled water and ideal for batteries
- **Large capacity:** The cartridge is rated for 2400 litres of pure water.
- Purity light: This "magic eye" monitors the conductivity of the output water continuously and signals when it is time to change the cartridge.
- Pressurised system, easy installation, easy cartridge replacement

Smart.ON




Monitoring device for traction and stationary batteries.

History files of work cycles, voltage and current graphs.

For the entire life span of battery Smart.ON monitors the following data:


- > Voltage
- Current
- Capacity
- **>** Temperature





Software SmartView II

- 1. System status
- 2. Battery level indicator
- 3. Smart.ON inside temperature
- 4. Smart.ON panel
- 5. Battery voltage



- > Measured instantaneous data: V, I, T, and A
- > Storage and analysis of history data
- > Statistics analyses
- > Data download onto a PC
- > Graphic display of voltage and current
- > Programming of charging and discharging parameters


| Description | Ah Battery | Reference | Optional accessories | | | | |
|------------------|------------|-----------|----------------------|--|-----------|--|--|
| | ≤ 170 | 127TA3855 | | AP160 UIR - | | | |
| Version 24/36/48 | 170 ÷ 345 | 127TA3856 | | USB connection cable (necessary for data | 107742062 | | |
| Volt | 345 ÷ 740 | 128TA4029 | | | 127TA3863 | | |
| | > 740 | 127TA3858 | | download) | | | |
| | ≤ 170 | 127TA3859 | | | | | |
| Version 72/80/96 | 170 ÷ 345 | 127TA3860 | | Management Software SmartView II | 107742004 | | |
| Volt | 345 ÷ 740 | 127TA3861 | | | 127TA3864 | | |
| | > 740 | 127TA3862 | | | | | |

New and unique float valves suitable for all batteries

- > One size fits all: Adjustable float heights
- > Instant tubing installation: Unique push-fit tubing ports make tubing installation fast, easy and secure
- > Lowest profile on the market: 15 mm high
- > Wide range of operating pressure: From 3 to 45psi
- > Abuse-resistant tubing: With a small bend radius it fits even the smallest cells easily
- > Highly visible fill level indicator: Visible from the top and side
- > No barbed fittings to break

Low profile

Specific gravity port and fill level indicator



Adjustable float







Quick fit tubing



Complete kit references

| Part Numbers | Description | Technical Information | Reference |
|--------------|---------------|---|-----------|
| FLT-KD6 | Float Kit 12V | Float valve kit for 6 cell Din battery | 127TA3865 |
| FLT-KD12 | Float Kit 24V | Float valve kit for 12 cell Din battery | 127TA3866 |
| FLT-KD18 | Float Kit 36V | Float valve kit for 18 cell Din battery | 127TA3867 |
| FLT-KD20 | Float Kit 40V | Float valve kit for 20 cell Din battery | 127TA3868 |
| FLT-KD24 | Float Kit 48V | Float valve kit for 24 cell Din battery | 127TA3869 |
| FLT-KD36 | 2 x FLT-KD18 | For 72V use | 127TA3870 |
| FLT-KD40 | Float Kit 80V | Float valve kit for 40 cell Din battery | 127TA3871 |
| FLT-KD48 | 2 x FLT-KD24 | For 96V use | 127TA3872 |

The above float kits include floats, tubing, input coupling and filter assembly, cable ties and instructions for installation and operating.

Tyres - Solid cushion tyres & tyre press





Solid cushion tyres

Structure

- > Three compounds
- > Steel ring reinforced base
- > Thicker wear-resistant tread
- > Deeper and across tread groove
- > Concave sidewall design
- > Square shoulder
- > Wider section

Features

- > Long life span
- > High load capacity
- > High wear-resistance
- > Low vibration
- Low rolling resistance
- Low energy consumption
- > Good cushion effect
- More stability
- > Comfortable for long distances
- > Increased adhesion to the road

Application

- > Forklift trucks & other industrial vehicles
- > Especially for high frame forklift trucks

Tyre press

Specifications

- > Capacity: 120 ton
- Max. tyre dimension: 20 inch
- > Cylinder: double-acting
- > Total height: 2222 mm
- > Total width: 2160 mm
- > Total depth: 850 mm
- > Operating pressure: 230 bar
- > Cylinder stroke: 400 mm
- > Stroke complete out: 35 sec
- > Stroke complete in: 95 sec
- > Oil tank: 30 L
- > Electromotor: 5.5 HP
- > Shipping weight: 1800 kg
- Supplied with a basic tool kit for tyres from 8" up to 15" comprising cages, cones and support rings

Seats / Seat heating



- > Automatic locking retractor.
- > Twin release buckle with rigid bracket. EEC-type approved (directive 77/541). With bolt set.



REF 106TA5147

VS12*

- > Semi-suspension seat with slide rails
- > VS12 has been tested and approved to ISO3776, ISO5353, prEN1726, EN474-1, EN-474-3 and stVZ0 (sections 30 and
- > With back rest and weight adjustment
- > Weight: 15 kg



standard version

with retractable seat belt

REF 106TA8622

REF 111TA4092

Grammer MSG20*

- > Comfortable suspension seat with weight, seat back angle and fore/aft adjustments
- > Seat belt brackets included
- > Weight: 18.5 kg



standard version

with retractable seat belt **REF 106TA8602**

REF 110TA8673

ES12: (GS12 Equivalent)*

- > Semi-suspension seat
- > Slide rails included
- > With weight and back rest adjustment
- > Weight: 15 kg



standard version

with retractable seat belt

REF 119TA8975

REF 122TA7477

KAB 211*

- > Suspension seat with weight, cushion and back adjustment (complete with runners)
- > Weight: 20 kg



standard version

REF 106TA8610

with retractable seat belt **REF 110TA8879**

Seat heating

To fit on top of seat cushions with thermostat. The heat cushion contains two connected elements, back and seat element. A temperature regulator in the current circuit of the seat element is energized at 20 \pm 3.3° C (68 \pm 6° F) and opens at $28.3 \pm 2.8^{\circ}$ C ($83 \pm 5^{\circ}$ F).

> REF 106TA8620: 12V

> REF 106TA8621: 24V





OPTIONAL

- Adaptor cigarette lighter
- > 2 exits
- > REF 115TA1802

Seat heating

- > For KAB and BEGE seats
- > To fit in seat and back cushion
- > With thermostat
- > REF 106TA8617: 12V
- > REF 106TA8618: 24V
- > REF 106TA8619: 48V




Bearings & hardware

TVH now has access to a stock of more than 70000 different bearings.



Hexagon socket set screws

- > 245 pieces
- > Black zinc
- > Metric DIN 916



Hexagon socket head cap screws

- > 95 pieces
- > Metric Black



Retaining rings

- > 326 pieces
- > Internal and external circlips
- **>** DIN 472 and DIN 471
- > Phosphated

8; 9; 10; 11; 12;



REF 107TA5452

13; 14; 15; 16

Tappered screws

- > 500 pieces
- > DIN 7981C
- > Zinc plated



REF 107TA5456

REF 107TA5445

Nuts with plastic insert

- > 214 pieces
- > DIN 985

M5 M6 M7 M8 M10 M12 M14 M₁₆



REF 107TA5444

REF 107TA5455

Split pins

- > 600 pieces
- > Size Imperial & Metric
- **>** DIN 94

1 x 25 1.6 x 32 2 x 40 2.5 x 40 3.2 x 40 - x50 4 x 32 - x50 5×50



REF 107TA5462

Starlock without cap, speednuts

> 580 pieces

3; 4; 5; 6 mm

SNP: 5020 (M3); 5021 (M4) SMG: M6 - M8

CV: 4824 (M4); 4825 (M5); 4826 (M) SFP: 1743 (1.6); 5011 (2.0); 1722 (2.4); 0211 (3.2); 0212 (4.0);

0213 (4.8); 0215 (6.35)

REF 123TA8019

Assortment hexagon bolts, screws & nuts UNF

> 148 pieces

Zinc plated

7/16 x 1" - x 1 1/4" -7/16 x 1 1/2" - x 1 3/4" - x 2" 1/2 x 1" - x 1 1/4" - x 1 1/2" - x 2" 9/16 x 1 3/4" - x 2" 5/8 x 1 1/2" - x 2" -5/8 x2 1/2"

REF 128TA4028

Assortment hexagon bolts, screws & nuts UNC


> 126 pieces

1/4 x 5/8 1/4 x 3/4 1/4 x 1 1/4 x 1.1/4 5/16 x 1 5/16 x 1.1/2 $3/8 \times 1$ 3/8 x 1.1/2 1/2 x 1.1/4



REF 123TA8023

Special chains with plastic inner or outer leaves



Valves

Valves for direct in-line mounting with threaded connections suitable for general use.

Due to the variety of operating conditions and applications for these products, it is important that you analyze all aspects of your application before selecting or using one.

Through his own analysis and testing, the user is solely responsible for making the final selection of his products and systems. He has to make sure that the environmental requirements of the application are met.

Check valves

| Reference | Flow | Ports | | |
|-----------|----------|-----------------------------------|----------|----------|
| 127TA3836 | 16l/min | G1/4 | > Symbol | |
| 127TA3837 | 35I/min | G3/4 | | |
| 127TA3838 | 60l/min | G1/2 | | - W (II) |
| 127TA3839 | 150l/min | G3/4 | | |
| 127TA3840 | | Threaded connections = G1/4 | > Symbol | |
| 127TA3841 | | Port A, B = G3/8 Port Z = G1/4 | > Symbol | |
| 127TA3842 | | Threaded connections = G3/8 | > Symbol | Sec. |

Directional valves

| Reference | Voltage | Ports | | |
|---------------|------------------|-----------------------------|---------------------------------|--|
| 2/2-way | | | | |
| REF 127TA3843 | 12VDC | Threaded connections = G3/8 | > Symbol | |
| REF 127TA3844 | 24VDC | | (M) = - | |
| 6/2-way | | | | |
| REF 127TA3845 | Manual operation | Ports = G3/8 | > Symbol Color Part Part | |

Directional valves

| Reference | Voltage | Ports | | |
|---------------|---------|--------------|---|----|
| 3/2-way | | | | |
| REF 127TA3846 | 12VDC | Ports = G3/8 | > Symbol (spool type) = Without YZ S A B B B B B | |
| REF 127TA3847 | 24VDC | | A B A B B A A B A A A A A A A A A A A A | |
| 8/3-way | | | | |
| REF 127TA3848 | 12VDC | Ports = G3/8 | > Symbol Symbol | |
| REF 127TA3849 | 24VDC | | | 00 |

Flow control valves


| Flow divider | | | | | | | | |
|---------------|-----------|-------------------|-------------------|-------|---------------------------|----------|----------|---|
| Reference | | Min. flow rate | Max. flow rate | Ports | Max. pressure range | Dividing | | |
| REF 127TA3850 | DTP-6-20 | 8 l/min | 20 l/min | G3/8 | 350 | 50:50 | > Symbol | _ |
| REF 127TA3851 | DTP-6-35 | 12 l/min | 35 l/min | G3/8 | | | | |
| REF 127TA3852 | DTP-6-50 | 16 l/min | 50 l/min | G3/8 | | | | |
| REF 127TA3853 | DTP-10-70 | 35 I/min | 70 l/min | G1/2 | | | | |
| Flow control | valve | | | | | | | |
| REF 127TA3854 | | To 50 I/min | To 350 Bar | | | | > Symbol | |

Side shifts / Attachments

Sideshifting fork positioner with bar-mounted FEM fork carriers

Fork adjustment is obtained with 2 hydraulic cylinders, which offer a smooth uniform movement. Delivered without forks, the orginal forks of the truck will suit without modification. Stroke of side shift, 100 mm left and 100 mm right. Sideshifting is still possible when the fork positioner is at its maximum opening position. Please keep in mind that the width of the fork is not as big as dimension W.

- > Working pressure 180 DaN/cm².
- > 2 hydraulic functions required.
- > Forks not included.





| REF | Capacity | Mounting class | Frame width | Min. width of fork carriage | Opening forks min-max | Width forks min-max | Height | Visibility | Lost load | Centre of gravity | Weight |
|-----------|----------|----------------|----------------|-----------------------------------|-----------------------------|---------------------------|-----------|------------|--------------|-------------------------|--------|
| | kg/mm | ISO-2328 | B (mm) | (mm) | A-0 (mm) | W (mm) | H (mm) | V (mm) | ET (mm) | CGH (mm) | kg |
| 123TA1956 | 2500/500 | 2 | 1040 | 860 | 340-930 | 80-130 | 720 | 230 | 60 | 32 | 107 |
| 123TA1958 | 2500/500 | 2 | 1 160 | 920 | 340-1050 | 80-130 | 720 | 230 | 60 | 32 | 118 |
| 123TA1965 | 5000/500 | 3 | 1 110 | 780 | 380-980 | 100-150 | 820 | 268 | 73 | 44 | 175 |

Work platforms

Work platforms perform a variety of applications, they are particularly suitable for routine maintenance, inspection and for stock taking purposes. Whatever the application, work platforms ensure confidence and safety to all users when working at high levels. Be aware that national restrictions on use may exist. Check with local authorities first.

| REF | REF with 4 castors | Mounting | Tool box | Weight (kg) | Capacity (kg) | | | | |
|---------------------------------|-----------------------|----------|----------|----------------|------------------|--|--|--|--|
| 107TA6395 | 107TA6397 | fork | yes | 120 | 300 | | | | |
| 107TA6396* | 107TA6398* | fork | yes | 130 | 300 | | | | |
| * authorised in The Netherlands | | | | | | | | | |

- **)** Platform size: 1115 x 1200 x 1890 mm.
- > Capacity: 2 persons.
- > Safely secured to truck using lock pins behind the fork heels.
- All models suitable for maximum 200 x 80 mm fork sizes, min. fork spread between forks 600 mm.
- > Fully tested.
- > Painted orange.





Fork extensions (closed version)

Many other lengths on demand!

| | Lenght of the fork extension | | | | | | | | | | |
|---------------|------------------------------|---------------|---------------|---------------|----------------|-----------|-----------|-----------|-----------|--|--|
| Fork section | 1200 mm | 1 400 mm | 1500 mm | 1 600 mm | 1800 mm | 2000 mm | 2200 mm | 2400 mm | 2500 mm | | |
| 80 x 40 | 128TA4036 | 128TA4049 | 128TA4062 | 128TA4075 | 128TA4088 | 128TA4101 | 128TA4114 | 128TA4127 | 128TA4140 | | |
| 100 x 40 | 128TA4037 | 128TA4050 | 128TA4063 | 128TA4076 | 128TA4089 | 128TA4102 | 128TA4115 | 128TA4128 | 128TA4141 | | |
| 100 x 50 | 128TA4038 | 128TA4051 | 128TA4064 | 128TA4077 | 128TA4090 | 128TA4103 | 128TA4116 | 128TA4129 | 128TA4142 | | |
| 100 x 45 | 128TA4039 | 128TA4052 | 128TA4065 | 128TA4078 | 128TA4091 | 128TA4104 | 128TA4117 | 128TA4130 | 128TA4143 | | |
| 120 x 50 | 128TA4040 | 128TA4053 | 128TA4066 | 128TA4079 | 128TA4092 | 128TA4105 | 128TA4118 | 128TA4131 | 128TA4144 | | |
| 125 x 40 | 128TA4041 | 128TA4054 | 128TA4067 | 128TA4080 | 128TA4093 | 128TA4106 | 128TA4119 | 128TA4132 | 128TA4145 | | |
| 125 x 45 | 128TA4042 | 128TA4055 | 128TA4068 | 128TA4081 | 128TA4094 | 128TA4107 | 128TA4120 | 128TA4133 | 128TA4146 | | |
| 130 x 45 | 128TA4043 | 128TA4056 | 128TA4069 | 128TA4082 | 128TA4095 | 128TA4108 | 128TA4121 | 128TA4134 | 128TA4147 | | |
| 130 x 50 | 128TA4044 | 128TA4057 | 128TA4070 | 128TA4083 | 128TA4096 | 128TA4109 | 128TA4122 | 128TA4135 | 128TA4148 | | |
| 130 x 60 | 128TA4045 | 128TA4058 | 128TA4071 | 128TA4084 | 128TA4097 | 128TA4110 | 128TA4123 | 128TA4136 | 128TA4149 | | |
| 140 x 50 | 128TA4046 | 128TA4059 | 128TA4072 | 128TA4085 | 128TA4098 | 128TA4111 | 128TA4124 | 128TA4137 | 128TA4150 | | |
| 150 x 50 | 128TA4047 | 128TA4060 | 128TA4073 | 128TA4086 | 128TA4099 | 128TA4112 | 128TA4125 | 128TA4138 | 128TA4151 | | |
| 150 x 60 | 128TA4048 | 128TA4061 | 128TA4074 | 128TA4087 | 128TA4100 | 128TA4113 | 128TA4126 | 128TA4139 | 128TA4152 | | |
| Attention: le | ngth of the ex | xtension shou | ld never exce | ed 60% of the | e fork length! | | | | | | |


Manual telescopic crane jib adjustable in length and height

- > The carriage-mounted crane jib has two adjustable turning safety hooks.
- > The hook can be manually adjusted in 14 positions in length and in height.
- > The crane jib is safely secured with a chain to the fork carriage.
- > Standard length of the arm is 2000 mm, maximum length of the arm is 3690 mm.
- > The crane jib has to be mounted to the forks and with the back of the jib to the back of the forks.

| REF | Capacity at 695 mm load centre | Minimum fork length | Min. fork spread between forks | Max. fork section | Centre of gravity | Weight |
|-----------|--------------------------------------|------------------------|--------------------------------------|----------------------|----------------------|--------|
| 107TA6423 | 2500 kg | 800 mm | 150 mm | 160 x 70 mm | 580 mm | 218 kg |
| 107TA6424 | 5000 kg | 800 mm | 150 mm | 160 x 70 mm | 600 mm | 250 kg |

| DEE | Capacity / Load centre | | | | | | | | | | | | | |
|-----------|------------------------|------|-------|------|-------|------|-------|------|------|------|-------|-------|------|------|
| REF | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
| | 695 | 990 | 1 285 | 1580 | 1825 | 2090 | 2290 | 2490 | 2690 | 2890 | 3090 | 3290 | 3490 | 3690 |
| | kg | kg | kg | kg | kg | kg | kg | kg | kg | kg | kg | kg | kg | kg |
| 107TA6423 | 2500 | 2500 | 2500 | 1800 | 1 400 | 1200 | 1 050 | 950 | 850 | 770 | 700 | 650 | 600 | 560 |
| 107TA6424 | 5000 | 3550 | 2750 | 2250 | 1950 | 1700 | 1550 | 1400 | 1300 | 1200 | 1 150 | 1 050 | 1000 | 950 |

- > Please keep the capacity of the lift truck in mind.
- > Fully tested and supplied with EC Declaration of Conformity.
- > Painted orange.
- > Options: longer arms.



Adjustable fork-mounted hooks

| REF | Capacity | Min. fork spread | Max. fork section between forks | Weight |
|-----------|----------|---------------------|---------------------------------------|--------|
| 107TA6425 | 2500 kg | 300 mm | 160 x 60 mm | 20 kg |
| 107TA6427 | 4000 kg | 300 mm | 160 x 60 mm | 27 kg |
| 107TA6428 | 5000 kg | 300 mm | 160 x 60 mm | 30 kg |

- > Fully tested and supplied with EC Declaration of Conformity.
- > Secured to the forks with thumb screws.
- > Safety swivel hook turns 360°.
- > Painted orange.



Forks




- All types: fem hook, din hook, pin, blank forks
- > All carriages: 2A, 2B, 3A, 3B, 4A, 4B
- Knife forks, carpet booms, fork extensions, blank forks
- > All capacities all lengths
- Most competitive prices, most complete programme

Special forks on request

Certification on request

| Class Fem - I.T.A. | Lift truck capacity kg | Norm | A | Carriage height B | Н2 | Choose fork section = w x t |
|--------------------------|---------------------------|----------|------------|----------------------|-----|-----------------------------------|
| 1 | 0 - 999 | 1A 1B | 76 114 | 331 | 306 | 80 x 35 |
| 2 | 1000 - 1500 | 2A 2B | 76 152 | 407 | 382 | 100 x 35 100 x 40 |
| 3 | 2800 - 3500 | 3A 3B | 76 203 | 508 | 477 | 100 x 50 100 x 45 |
| 4 | 5000 - 8000 | 4A 4B | 127 254 | 635 | 598 | 150 x 60 150 x 75 |



Hydraulic telescopic forks

Quality assurance:


- > Can be supplied with certificate.
- > Lightweight and durable product.
- > Sleeves run on hardened roller bearings which are permanently smooth, so there are no wear pads to change.

Supplied complete with:

- > 2 x Telescopic fork arms.
- > 1 x Flow divider block.
- > 2 x 540 mm hoses / 2 x 700 mm hoses / 2 x 1000 mm hoses.
- **)** 1 x T-bar.
- > All connectors supplied are 7/16" JIC Standard configuration.

Available with or without pallet stop

Save time & money!



Available range:

- > 1070 / 1770 mm
- > 1220 / 2020 mm
- > 1350 / 2350 mm
- > 1600 / 2600 mm

Panoramic mirror

Oil seal tool kit





Panoramic mirror heavy duty version

- Dimensions: 280 x 146 mm.
- > Panoramic mirror.
- Unbreakable mirror.
- > High European quality.
- Mirror body is made of impactresistant material.
- > Extra wide angle view.
- Very easy to mount on all kinds of applications. Can easily be mounted on existing brackets (10-20 mm diameter) or can easily be installed to the roof by accompanied bracket kit.

Oil seal tool kit

Oil seals are durable and versatile components, whose functionality depends to a great extent upon their being properly installed. Thus, for example, up to 30 % of early failures of rotary shaft seals are traceable to faulty installation. TVH offers now an assembly set that minimizes installation errors and simplifies deinstallation.

Panoramic mirror economic version



REF 116TA4481

Absorbing materials / Sealing products



Absorbing socs

> Absorbs oil & liquids



Thread locker low strength 50 ml

- > Low strength anaerobic adhesive for thread locking of nuts, bolts and screws of all types that require to be easily dismantled.
- > Highly resistant to temperatures $(-50^{\circ} \text{ to } +150^{\circ}\text{C}),$ corrosion, vibrations, water, gas, oils, hydrocarbons and many chemicals.



Thread locker medium strength 50 ml

- > Medium strength anaerobic adhesive for thread locking of nuts and bolts of all types that require to be dismantled.
- Suitable to be used on oily surfaces.
- > Highly resistant to temperatures (-50° to +150°C), corrosion, vibrations, water, gas, oils, hydrocarbons and many chemicals.



REF 126TA5184

Thread locker high strength 50 ml

- > High strength anaerobic adhesive for locking and sealing of studs, nuts, bolts and threaded fasteners not requiring dismantling.
- > Highly resistant to temperatures $(-50^{\circ} \text{ to } +150^{\circ}\text{C}),$ corrosion, vibrations, water, gas, oils, hydrocarbons, and many chemicals specially formulated for oily surfaces.



REF 107TA8521

REF 107TA8525

Pipe sealant for small

> Seals against gas, water, LPG, hydrocarbons, oils and other chemicals.

threaded joints 50 ml

- > Thixotropic property prevents migration from thread of the sealant before or during curing.
- Shock and vibration resistant, properties of sealing in the range of temperature from -50° to $+150^{\circ}$ C.



Hydraulic sealant 50 ml

- > To replace P.T.F.E. tapes in the sealing of gases, water, LPG, hydrocarbons, oils and other chemicals.
- > Easy to dismantle with standard tools.
- > Highly resistant to temperatures $(-50^{\circ} \text{ to } +150^{\circ}\text{C}),$ corrosion, shocks and vibrations.



REF 127TA3878

Instant gasket 50 ml

- > Seals against gases, water, LPG, hydrocarbons, oils and other chemicals.
- > Thixotropic property prevents migration of the sealant before or durina curina.
- > Shock and vibration resistant. properties of sealing in the range of temperature from -50° to 150°C.



REF 107TA8524

BETA tools



TVH is the Authorised Factory Distributor for BETA quality tools and workwear. Opting for BETA means opting for top quality and interesting prices. Design, ergonomics and userfriendliness have been combined with safety and efficiency.

For more info and a view on our catalogue, go to www.tvh.com/beta を

























Storage systems and assortments



Spanners



Allen keys



Socket wrench and accessories



Presses and torque wrenches



Pliers and wire cutters



Pincers



Screwdrivers and bits



Tools for Torx® and Tamper Resistant Torx® screws



Tools for electrics and electronics



Insulated tools



Chisels and hammers



Cutting and filing



Drills and taps



Measuring and marking tools



Garage tools



Miscellaneous BETA



Consultez notre brochures BETA pour plus d'infos www.tvh.com/catalogues/beta.pdf



BETA clothes



- 1. Oxford Jack, water resistant
- 2. Jacket, fleece 250 gr/m²
- > 100% double layers polyester pile
- Oxford inserts for elbows and shoulders against wear



| | | • | 101 | _ | AL. | AAL |
|---|------|-----------|-----------|-----------|-----------|-----------|
| 7 | 7760 | 128TA2864 | 128TA2865 | 128TA2866 | 128TA2867 | 128TA2868 |
| 7 | 7620 | 128TA2869 | 128TA2870 | 128TA2871 | 128TA2872 | 128TA2873 |
| | | | | | | |

- 3. Shorts with several pockets
- 4. Workpants with several pockets
- 5. Sleeveless overall
- 6. Work overall
- 7. Work coat
- > T/C/Canvas 65% polyester, 35% cotton, 270g/m²
- Inserts made of "Oxford" polyester/ PU 240 g/m²







| | XS | S | M | L | XL | XXL | XXXL |
|------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| 7901 | 128TA2874 | 128TA2875 | 128TA2876 | 128TA2877 | 128TA2878 | 128TA2879 | 128TA2880 |
| 7900 | 128TA2881 | 128TA2882 | 128TA2883 | 128TA2884 | 128TA2885 | 128TA2886 | 128TA2887 |
| 7903 | 128TA2888 | 128TA2889 | 128TA2890 | 128TA2891 | 128TA2892 | 128TA2893 | 128TA2894 |
| 7905 | 128TA2895 | 128TA2896 | 128TA2897 | 128TA2898 | 128TA2899 | 128TA2900 | 128TA2901 |
| 7909 | 128TA2902 | 128TA2903 | 128TA2904 | 128TA2905 | 128TA2906 | 128TA2907 | 128TA2908 |

- 8. Rain overall
- 9. Rain pants
- 10. Rain coat
- > PVC material
- Adjustable elastic drawstring on hips
- > Superior quality!







BETA safety shoes

| REF | EU | UK | USA | J |
|-----------|----|------|------|------|
| 127TA2595 | 38 | 5 | 6 | 24 |
| 127TA2596 | 39 | 6 | 7 | 24.5 |
| 127TA2597 | 40 | 6.5 | 7.5 | 25.5 |
| 127TA2598 | 41 | 7 | 8.5 | 26.5 |
| 127TA2599 | 42 | 8 | 9 | 27 |
| 127TA2600 | 43 | 9 | 10 | 28 |
| 127TA2601 | 44 | 10 | 10.5 | 28.5 |
| 127TA2602 | 45 | 10.5 | 11.5 | 29.5 |
| 127TA2603 | 46 | 11 | 12 | 30 |
| 127TA2604 | 47 | 12 | 13 | 31 |

SUEDE ANKLE SHOE, WITH CORDURA INSETS (EN 20345 S1P)

- > 3D Fresh lining
- > Steel toe cap, 200 joule
- Elastic steel reinforced dual density polyurethane sole
- > Antistatic, fungicidal



| REF | EU | UK | USA | J |
|-----------|----|------|------|------|
| 127TA2605 | 38 | 5 | 6 | 24 |
| 127TA2606 | 39 | 6 | 7 | 24.5 |
| 127TA2607 | 40 | 6.5 | 7.5 | 25.5 |
| 127TA2608 | 41 | 7 | 8.5 | 26.5 |
| 127TA2609 | 42 | 8 | 9 | 27 |
| 127TA2610 | 43 | 9 | 10 | 28 |
| 127TA2611 | 44 | 10 | 10.5 | 28.5 |
| 127TA2612 | 45 | 10.5 | 11.5 | 29.5 |
| 127TA2613 | 46 | 11 | 12 | 30 |
| 127TA2614 | 47 | 12 | 13 | 31 |

SUEDE ANKLE SHOE, WITH CORDURA INSETS (EN 20345 S1P)

- > 3D Fresh lining
- > Steel toe cap, 200 joule
- > Elastic steel reinforced dual density polyurethane sole
- > Antistatic, fungicidal



| REF | EU | UK | USA | J |
|-----------|----|------|------|------|
| 127TA2615 | 38 | 5 | 6 | 24 |
| 127TA2616 | 39 | 6 | 7 | 24.5 |
| 127TA2617 | 40 | 6.5 | 7.5 | 25.5 |
| 127TA2618 | 41 | 7 | 8.5 | 26.5 |
| 127TA2619 | 42 | 8 | 9 | 27 |
| 127TA2620 | 43 | 9 | 10 | 28 |
| 127TA2621 | 44 | 10 | 10.5 | 28.5 |
| 127TA2622 | 45 | 10.5 | 11.5 | 29.5 |
| 127TA2623 | 46 | 11 | 12 | 30 |
| 127TA2624 | 47 | 12 | 13 | 31 |

SOFT SUEDE SHOE, PERFORATED (EN 20345 S1P)

- > Collar with 3D Fresh lining
- > Steel toe cap, 200 joule
- Elastic steel reinforced dual density polyurethane sole
- > Carbon inner sole
- > Antistatic, fungicidal



| REF | EU | UK | USA | J |
|-----------|----|------|------|------|
| 127TA2625 | 38 | 5 | 6 | 24 |
| 127TA2626 | 39 | 6 | 7 | 24.5 |
| 127TA2627 | 40 | 6.5 | 7.5 | 25.5 |
| 127TA2628 | 41 | 7 | 8.5 | 26.5 |
| 127TA2629 | 42 | 8 | 9 | 27 |
| 127TA2630 | 43 | 9 | 10 | 28 |
| 127TA2631 | 44 | 10 | 10.5 | 28.5 |
| 127TA2632 | 45 | 10.5 | 11.5 | 29.5 |
| 127TA2633 | 46 | 11 | 12 | 30 |
| 127TA2634 | 47 | 12 | 13 | 31 |

SOFT FULL GRAIN LEATHER 7291NNK ANKLE SHOE, HIGHLY BREATHABLE (EN 20345 S3)

- > Heavy duty
- > 3D Fresh lining
- > Polymer toe cap, 200 joule
- > Elastic steel reinforced dual density polyurethane sole
- > New fresh inner sole

| 100 many | ## |
|----------|-----------|

| REF | EU | UK | USA | J |
|-----------|----|------|------|------|
| 127TA2635 | 38 | 5 | 6 | 24 |
| 127TA2636 | 39 | 6 | 7 | 24.5 |
| 127TA2637 | 40 | 6.5 | 7.5 | 25.5 |
| 127TA2638 | 41 | 7 | 8.5 | 26.5 |
| 127TA2639 | 42 | 8 | 9 | 27 |
| 127TA2640 | 43 | 9 | 10 | 28 |
| 127TA2641 | 44 | 10 | 10.5 | 28.5 |
| 127TA2642 | 45 | 10.5 | 11.5 | 29.5 |
| 127TA2643 | 46 | 11 | 12 | 30 |
| 127TA2644 | 47 | 12 | 13 | 31 |
| | | | | |

SOFT FULL GRAIN LEATHER 7201N ANKLE SHOE, QUICK OPENING (EN 20345 S3)

- > Anatomic heavy duty
- > 3D Fresh lining
- > Polymer toe cap, 200 joule
- > Elastic steel reinforced dual density polyurethane sole
- > Carbon inner sole

| *OLARP | |
|--------|--|


| REF | EU | REF | EU |
|-----------|----|-----------|----|
| 127TA2645 | 36 | 127TA2651 | 42 |
| 127TA2646 | 37 | 127TA2652 | 43 |
| 127TA2647 | 38 | 127TA2653 | 44 |
| 127TA2648 | 39 | 127TA2654 | 45 |
| 127TA2649 | 40 | 127TA2655 | 46 |
| 127TA2650 | 41 | 127TA2656 | 47 |

INNERSOLES



SHOE-LACES

- > REF 127TA2657
- > Pack of 10 pairs of laces
- > Length: 120 cm



7399 A/

Accessories for aerial platforms



Power-Plates

To protect the surface

To provide a solid foundation on soft or fragile grounds

| Length (mm) | Width (mm) | Thickness (mm) | Weight (kg) | Handle | Reference |
|----------------|---------------|-------------------|----------------|--------|------------|
| 2000 | 1000 | 15 | 30 | 4 | 127TA2451* |

- Surface damage-free (completely damage-free up to 10 ton)
- > Unbreakable
- Lightweight
- > Made of synthetic material



The plates can be connected to each other with this connector REF 127TA2465







Hydraulic generator

Get 220V** in the basket of your aerial platform

- > No need for a stand-alone diesel generator, therefore reducing plant theft
- > No additional diesel costs
- Increases productivity potential and considerably reduces service and maintenance costs
- > Enhances the hire rate on the platform
- No more messing about with extension leads (cable mostly already in the telescopic arm)
- > To be fitted under the bonnet
- > Also available in 110V 4.1 kVA & 5 kVA

Exclusive distributor outside the UK!

Take a look at our website: www.tvh.com/hydraulic_generator









Wheel cover for aerial platforms

| Reference | Tyre size | lde |
|-----------|-----------|---------------|
| 125TA6262 | 23" - 33" | > s |
| 125TA6263 | 34" – 44" | > r |
| 125TA6264 | 45" - 52" | > e |

Ideal for:

- > show rooms
- > renovation & restoration works
- > exhibitions

Turn your tyre into a non-marking tyre

- > Set of 4 pieces. Also available separately.
- > Only for indoor use.
- > Maximum speed: 5 km/h.
- Intensive use will result in reduced life span.

Exclusive European distributor outside the UK!

Scale models

Komatsu BE-3R



Scale: 1/25

REF 127TA3881

Linde 39X



Scale: 1/50

REF 127TA3883

Still R70-25



Scale: 1/87

REF 127TA3882

Yale MTC Turret Truck



Scale: 1/25

REF 127TA3880

Haulotte Multijob MJX970



Scale: 1/50

REF 127TA3879

JLG Liftlux 260-25



Scale: 1/32

REF 126TA5960

Linde forklift with pedals



Dimensions: 130 x 57 x 107 cm

REF 127TA3884



This is just a small selection of our range! To find out more check on:

www.forkliftscalemodels.com 働

The O.E.M. references are only for indication and do not imply that the scale models are coming from the forklift manufacturer. Product sold only for collection purposes and not intended for children under 14 years of age.

Forklift Division

Second-hand forklift trucks



Via your browser on our website www.tvh.com/stock you can select different truck specifications. Send us your selection, and we will be pleased to reply with a firm offer.

Our export salesteam



Pascal Vanhalst Director

TEL +32 56 43 42 79 FAX +32 56 43 47 98

E-MAIL pascal.vanhalst@tvh.com



Patrice Vanhalst Director CC Heftrucks

TEL +32 53 84 90 92

FAX +32 53 84 90 94

E-MAIL patrice@cc-heftrucks.be





Rik Vandenheede Purchase Manager

TEL +32 56 43 43 79 FAX +32 56 43 43 37

E-маі rik@tvh.com



Wim Carlier Purchase & Sales **Aerial Platforms**

TEL +32 56 43 45 79 FAX +32 56 43 43 45

E-MAIL wim.carlier@tvh.com



Jos Moeyaert

TEL +32 56 43 42 36 FAX +32 56 43 43 45

E-MAIL jos.moeyaert@tvh.com



José Ornia UK + NL + D**Forklift Truck Purchase**

MOB +31 (0)6 47 60 52 34 TEL +32 56 43 43 11

FAX +32 56 43 43 45 E-MAIL jose.ornia@tvh.com



Benoit Bouve

Sales

TEL +32 56 43 45 35 FAX +32 56 43 46 36

E-MAIL benoit.bouve@tvh.com



Jan Odul Sales

TEL +32 56 43 48 19

FAX +32 56 43 48 98

E-MAIL jan.odul@tvh.com





> A global view on our second hand forklifts





Eric Goethals

Sales

+32 56 43 42 35

+32 56 43 45 36 E-MAIL eric.goethals@tvh.com



Olexiy Lyamtsev

TEL +32 56 43 47 19 +32 56 43 48 98

E-MAIL olexiy.lyamtsev@tvh.com



Used forklifts

Baumann EGX50-45-16-40

- > 5 ton > electric
- > 4 m duplex/

4 valves

- **)** 1998
- view



BT RRB2/4

- > 1.4 ton > 7 m triplex/ view/ff
- > electric > 1995 > sideshift

Caterpillar DP25K

> 2.5 ton) diesel

> 2002

- view
- > 3.3 m duplex/ > sideshift

Clark EM20

> 2 ton > electric

> 1992

> 5 m duplex/ view





REF KV020



Crown 15TSPTN-S

- > 1.5 ton
- > 8.61 m duplex
- > electric > 1998
- Daewoo D25S-2
- > 2.5 ton) diesel
- 3.9 m triplex/ view/ff
- > sideshift

Hyster H2.50XM

- > 2.5 ton > 5.5 m triplex/
- > LPG
- view/ff > 1995 > sideshift

Jungheinrich DFG20AS

- > 2 ton) diesel
- > 4.3 m triplex/



view/ff





REF KR010





Jungheinrich ETV 214

- > 1.4 ton > electric > 2001
- > 7.1 m triplex/ view/ff
- Kalmar LMV DC-500
- > 3 ton > LPG > 1994
- > 4.5 m triplex/ view/ff > cabin

Komatsu FD15T-20

- > 1.5 ton > 3 m duplex/
- diesel > 2005
 - view > transm. auto

Komatsu FB13M-3

> 1.3 ton > electric

> 2001

> 4.7 m triplex/ view/ff









Komatsu FG18HT-17

- > 1.8 ton > gasoline
- > 4.3 m triplex/ view/ff > sideshift

Linde H20D-03

- > 2 ton) diesel > 2001
- > 4.6 m triplex/ view/ff > sideshift

Linde H40D-03

- > 4 ton
-) diesel > 1999
- > 4 m duplex/
 - view

Linde R14

- > 1.4 ton > electric > 1994
- > 7.29 m triplex/ view/ff











Linde E16

- > 1.6 ton > electric
- > 3 m duplex/ view
- Linde H16T-03
- > 1.6 ton > LPG > 2001
- 3 m duplex/ view > windshield
- Manitou M426CP > 2.6 ton
-) diesel > 1997
- > 5.4 m triplex standard
- MIC WA15
- > 1.5 ton > electric > 2002
- > 6 m triplex/ view/ff









Used forklifts

Mitsubishi FD35T-F19C

- > 3.5 ton
- > 5 m duplex/
-) diesel view > 2003
- 4 valves

Mitsubishi FG15T-F25B

> 1.5 ton) gasoline

> 1998

> 3 m duplex/ view

REF KS517

> 3 m duplex/

view

Mitsubishi FD25T-F18B

> 2.5 ton) diesel

> 2002

- > 3 m duplex/
- view

Nissan YLO2A25 > 2.5 ton

> 2005

- > diesel
- 3 m duplex/ view







Nissan YGJ02A30

- > 3 ton
- > 4.5 m duplex/ view
-) diesel > 1999

- Nissan PJ02A20
- > 2 ton > dual fuel
- > 2003

Nissan QP02L20

- > 2 ton > 4 m duplex/

- > electric view
- > 2003

Nissan PJ01A15

- > 1.5 ton
-) gasoline > 2001
- > 3 m duplex/ view









Nissan BF03M35

- > 3.5 ton
- > 5.5 m duplex/ view
- > LPG > 1991
- - > electric

Nyk-Nichiyu FB18P-60B

- > 1.8 ton 3 m duplex/ view
- > 1997

Still FM14

- > 1.4 ton > 6.5 m triplex/ > electric view/ff > sideshift
- > 2000

Still R70-25T

- > 2.5 ton > LPG > 1990
- > 5.3 m triplex/ view/ff











TCM FD25T6H

- > 2.5 ton) diesel > 2003
- 3 m duplex/ view

TCM FB15-6

- > 1.5 ton
- > electric > 2000
- > 4 m duplex/ view

Terex 3517

- > 3.5 ton) diesel
- > 2005
- > 17 m boom telescopic

Toyota 02-7FD18

view







- > 1.8 ton > diesel > 2001
- > 3 m duplex/

- > 2.5 ton) diesel > 2001
- 3 m duplex/ view > sideshift
- Toyota 02-5FD45
- > 4.5 ton) diesel
- > 5.5 m triplex/ view/ff
- Toyota 6FG20
- > dual fuel **)** 1998





Toyota 62-7FD25

REF KR532

> 1998 4 valves

- > 2 ton
- 3 m duplex/ view



- Toyota 5FBE13
- > 1.3 ton > electric
- > 3 m duplex/ view > sideshift









Used forklifts / Used clamps

Toyota 7FB15

- > 1.5 ton
- > 4 m duplex/ view
- > electric > 1999

Toyota 7FBL15

- > 1.5 ton > electric > 2002
- > 3 m duplex/ view

Toyota FBMF16

- > 1.6 ton > electric
- > 3 m duplex/ view

Toyota 40-7FB25

- > 2.5 ton
- 3 m duplex/ view > sideshift











Toyota 40-3FGL7 demo

- > 0.7 ton) gasoline
- > 2.5 m duplex/ view
- > 2005

- Toyota 5FGL15
- > 1.5 ton
- 3 m duplex/) gasoline view
- > 1991

Toyota 7FG20 repainted

- > 2 ton
-) gasoline

- > 3 m duplex/ view
- > 1999

Valmet TD 1206A

- > 12 ton) diesel > 1991
- > 5 m duplex/
- view > sideshift











Yale 11-FG25PVIIFE

Valmet TD 1206A

- > 12 ton diesel
- > 5.5 m duplex/
- > 1992

Yale 11-FD25PVIIXA

- > 2.5 ton
- diesel > 2003
- 3 m duplex/ view

Yale 03-FG15PVIID5

- > 1.5 ton > dual fuel
- > 1998
- > 3 m duplex/ view
- > 2.5 ton > gasoline > 2003
- > 3 m duplex/ view > windshield









Used Clamps (latest edition)

Order now!

> A global view on our second hand clamps



REF 10845029



Used aerial platforms

Aichi SR123

-) diesel
- **>** ph 12 m
- > 1997



Genie Z-45/25J

- > bi-energy
- **>** ph 13.8 m **)** 1999

Genie Z-45/25DC J

- > electric
- **>** ph 13.8 m
- > 1999



Genie Z-45/25 RT

-) diesel
- **>** ph 13.9 m > 2001



Genie S-60

- > diesel
- > ph 18.3 m
- > 1993



Genie S-65

-) diesel
- **>** ph 19.8 m
- > 1999

Genie GS-1930

- > electric
- **>** ph 5.8 m
- > 2000

REF KM454

REF KR315



Genie GS-2646

- > electric
-) ph 7.9 m
- **)** 1998



Genie GS-5390 RT

-) diesel
- > ph 16.15 m
- > 2004



Grove TOUCAN 860

- > electric
-) ph 6.8 m
- **)** 1999

Iveco 35-11 BIZZOCCHI145VCL

-) diesel
- > ph 12.5 m
- > 2000

JLG E600JP

- > electric
- > ph 18.36 m
- > 2000



JLG 800AJ

-) diesel
-) ph 24.38 m



JLG 500RTS

-) diesel
-) ph 15.24 m
- > 2000



JLG 2646E3

- > electric
- **>** ph 7.9 m
- > 2000



Liftlux 17224X

-) diesel
- **>** ph 17.2 m
- **)** 1999



Manitou 165ATJ

-) diesel
- **>** ph 15.4 m > 2002
- REF KS300

Skyhigh 1800

- > electric
- **>** ph 16 m
- > 2001



Upright AB46RT

-) diesel
- **>** ph 14.1 m
- > 2001

REF KU046



Contact

REF KS559



REF KS252

Wim Carlier **Purchase & Sales**


+32 56 43 45 79 FAX +32 56 43 43 45 E-MAIL wim.carlier@tvh.com

Loading ramp LR TN 100 / Our used stock on-line



> Safety weight load: 10 ton
> CE compliant (machine directive)

TEL +32 56 43 40 19
E-MAIL friedel.d.haeyere@tvh.com



1 www.tvh.com/stock



Choose 1 or more of the brands you are interested in. Select lifting capacity, engine, transmission,...

With a simple click on "Find machines" you will find a range of available machines.

Handling Equipment Division

TVH Handling Equipment Division:The most complete range on material handling equipment

Trolleys, Trucks, Handpallettrucks, Electric handpallettrucks, Weighing equipment, Scissor handpallettrucks, Lifting tables, Stackers, Cranes, Jacks & Stands, Loading ramps, Safety accessories and Drum handling.



Handling your business!



TOTAL LIFTER.

Hand pallet truck

- > All dimensions possible
- > 2 years warranty on the pump
- > Qualitative and durable product
- > Durable and free of maintenance
- > Capacity: 2500 kg



Stainless steel hand pallet truck

- > Designed for use where water, moisture and salt are present
- > Low maintenance
- > Comply with safety and hygiene standards





Scissor hand pallet truck

- > Capacity: 1000 kg
- > Lifting height: 800 mm
- > With quicklift pump for lifting while unloaded
- > Single lift piston: prevents leaks



Weighing hand pallet truck

- > Capacity: 2000 kg
- > Fork length: 1 150 mm
- > Width: 550 mm
- > Steering wheels: polyurethane
- > Fork wheels: tandem polyurethane
- > Precision: 1 kg



REF 124TA4519

Stacking your business!

Choose from our large range of manual, semi-electric and electric stackers.



Loading & lifting your business!



Safety trestle >15T

> Length: 1200 mm

> Width: 550 mm

> Height: 1080 mm - 1300 mm


> 2 wheels: rubber - 200 mm

> 5 adjustables heights with the aid of pins

> Weight: 70 kg

REF 124TA2106





Ramps for forklift trucks

> Capacity: 4000 kg

> Simplifies the acces to the load.

REF 111TA9284



Safety jack

> Lifting capacity: 22700 kg

> Support capacity: 45500 kg

> Height: 1070 x 1350 mm

> Weight: 56 kg

REF 107TA8319

Loading & lifting your business!



Hydraulic jacks

- > Lifting capacity:
 - 1. 5000 kg
 - 2. 10 000 kg
 - 3. 25000 kg
- > Min. height:
 - 1. 25/368 mm
 - 2. 25/413 mm
 - 3. 58/470 mm
-) Max. height:
 - 1. 231/574 mm
 - 2. 258/646 mm

For the safe use of all jacks, see our wide-base props

- 3. 291/703 mm
- > Weight:
 - 1. 20 kg
 - 2. 27.5 kg
 - 3. 92 kg

Hydraulic jack > Lifting capacity: 4000 kg Hydraulic jack > Min. height: 60 mm Lightweight > Lifting capacity: 4000 kg Max. height: 360 mm 24 kg > Min. height: 65 mm > Weight: 31 kg > Max. height: 360 mm > Weight: 24 kg **REF 107TA8185 REF 127TA1826** With CE-Certificat Hydraulic jack > Lifting capacity: 7000 kg Min. height: 57 mm > Max. height: 406 mm **Stands** > Weight: 42 kg > Capacity: 9000 kg Minimum height: 240 mm **REF 107TA8190** > Maximum height: 420 mm **REF 105TA4047**

Large base area!

New products!



TOTAL LIFTER.

Mechanic lifter

- > Capacity: 300 kg
- > Lifting height: 145 mm
- > Width: 420 mm
- > Fork length: 1 100 mm
- > Width of 1 fork: 120 mm
- > Total height: 1 170 mm

REF 127TA1060



Lifting tables

- > Wheels: nylon
- > Capacity: 150 kg
- > Lifting height: 720 mm
- > Dimensions: 700 x 450 mm

REF 127TA1061

- > Wheels: nylon
- > Capacity: 300 kg
- > Lifting height: 880 mm
- > Dimensions: 850 x 500 mm

REF 127TA2350

- > Wheels: nylon
- > Capacity: 350 kg
- > Lifting height: 1300 mm
- Dimensions: 910 x 500 mm
 - REF 127TA2351

- > Wheels: nylon
- > Capacity: 500 kg
- > Lifting height: 880 mm
- > Dimensions: 850 x 500 mm

REF 127TA1062

- > Wheels: nylon
- > Capacity: 750 kg
- > Lifting height: 990 mm
- **>** Dimensions: 1 000 x 510 mm

REF 127TA2352





TOTAL LIFTER.

Hand pallet truck

- > Capacity: 2000 kg
- > Fork length: 2500 mm
- > Width: 540 mm
- > Steering wheels: polyurethane
- > Fork wheels: tandem polyurethane
- > Also available in other dimensions

REF 127TA1063







Parts Division - Why work with TVH? What can you expect from TVH Parts Division?

TVH is innovative, ambitious and focused on customer delight!

COLLABORATING WITH TVH = 25 EXPECTATIONS FULFILLED!

Orders

- 01. We guarantee you that express orders (max 40 order lines or 80 pieces per line) placed before the cut-off time, will be shipped the same day. Should the order not be sent for some reason, you will be notified by e-mail that same evening.
- 02. Every order you place, will be checked by your TVH contact person in order to detect possible irregular order lines, and to double-check them with you.
- 03. If you so wish, TVH can arrange the transport of the goods to your premises. In this case the transport cost will be calculated separately on your TVH invoice.
- 04. Parts that were incorrectly supplied by TVH can be returned without costs.
- 05. By default, back orders are sent with the next shipment, but we offer you the possibility of back order consolidation. If no new order is placed within 30 days for EU countries or 60 days for export countries, the back order is sent automatically.
- 06. We ship our goods in a suitable packaging.

TVH Quick Source

- **07.** Our on-line program TVH Quick Source is available free of charge.
- **08**. TVH Quick Source is available in 17 languages.
- 09. TVH Quick Source can be consulted 24/7.
- TVH Quick Source offers you the possibility of free identification of spare parts by means of the Quick Reference module.
- 11. Via TVH Quick Source you can quickly input and follow-up your complaints on-line.
- **12**. TVH Quick Source allows you to easily follow up your order processing.
- 13. TVH Quick Source offers you the possibility to trace your orders via the courier's site in real time.
- 14. Via TVH Quick Source you can visualize and print your invoices on-line at any given time.
- 15. Our catalogues can be consulted free of charge at any time by means of TVH Quick Source.

Communication

- 16. Your fixed contact person is always at your service during the office hours of your sales team. Changes to the office hours will be communicated to you separately. Should your fixed contact person be absent, a back-up is always available.
- 17. We can automatically and electronically provide you with the following documents in 18 languages: order confirmation, transport confirmation, shipment overview (for flat-rate transport cost), back order report (Monday), statement overview, invoices (pdf).
- 18. We offer you sales assistance in 31 spoken languages.
- 19. The flat-rate transport cost is immediately consultable so that you always know your transport cost in advance.

Research / Purchase

- **20**. Our technical department identifies parts for the most common lift truck and aerial platform brands.
- 21. The identification of parts by our technical department is free of charge.
- 22. You can look up a considerable number of brands and models yourself via the Quick Reference module.
- 23. In case of stock rupture an alternative (e.g. Service exchange...) is automatically offered if this is available.

Extra

- 24. You can request or order parts by means of different references: lift truck brand, manufacturer brand, TVH references.
- 25. We offer you the possibility to request or order parts by means of customised references: your own number or location.

Catalogues

TVHC BREEF

Labels & decals REF 12594102



Brushes REF 7901151



Relays REF 7083552



Exhaust systems RFF 10727802



LPG system parts REF 12410757



Filters: quick search REF 7543353



Seats & accessories REF 8821408



Paint & accessories REF 7882672



Key switches REF 10195714



Contacts & contact kits REF 10185471



Brake & Clutch cylinders REF 7072186



Hand Pallet Truck Parts REF 10550844



Mast rollers REF 7872482



Wheels, rollers & castors REF 6781097




Fuses, fuse holders REF 9103420



Starters & alternators REF 6252659



Bulbs REF 9103419



Engine parts REF 8255616



Replacement parts suitable for JLG RFF 12613028



Replacement parts suitable for Genie RFF 12726578



Potentiometers & REF 7835233



Brushes for sweepers & scrubbers REF 12206208



BFTA RFF 11960383

All catalogues are available in PDF-format on:



Our website (on request) www.tvh.com/catalogues



- > Our TVH Quick Source CD-ROM
- > REF 115TA7014

- > Our Infogate CD-ROM
- > All company info with TVH catalogues, presentation, movie, website, contact persons,
- documents,... > REF 10550851



TVHU

Master Catalogue

> Index in 6 languages: Dutch, French, English, German, Spanish and Italian > 1600 pages of references:

Technical info. Technical sheets. Pictures,...

> REF 9779984



Trade fairs



2008

Brugse Bedrijven Beurs

- **>** Date: 19/03/2008 20/03/2008
- > Location: Beurshalle Brugge (Belgium)
- > Stand: A33

Manutention 2008

- > Date: 11/03/2008 14/03/2008
- > Location: Paris-Nord Villepinte (France)
- > Stand: 6E072

Triënnale Verf & Decoratie

- > Date: 29/03/2008 30/03/2008
- > Location: Fabriekspand Roeselare (Belgium)
- > Stand: 34

Romexpo 2008

- **>** Date: 09/04/2008 13/04/2008
- > Location: Bucharest (Romanian)

Bedrijven contactdagen Gent 2008

- > Date: 16/04/2008 17/04/2008
- > Location: Flanders Expo Gent (Belgium)
- > Stand: 5316

SHD

- > Date: 22/04/2008 23/04/2008
- > Location: SECC Glasgow (UK)

Interclean 2008

- > Date: 06/05/2008 09/05/2008
- > Location: Amsterdam (Netherlands)

SED 2008

- > Date: 13/05/2008 15/05/2008
- > Location: Corby (UK)
- > Stand: 801

CeMAT 2008

-) Date: 27/05/2008 31/05/2008
- > Location: Hannover (Germany)
- > Stand: hall 25, Stand H11

- > Date: 03/06/2008 05/06/2008
- > Location: Amsterdam RAI Centre (Netherlands)

Taropak 2008

- **>** Date: 15/09/2008 18/09/2008
- > Location: Poznan (Poland)

Apex 2008

- > Date: 17/09/2008 19/09/2008
- > Location: Maastricht (Netherlands)
- > Stand: 1470

SHE

- > Date: 17/09/2008
- > Location: Kent Show ground Dettling (UK)

Machine Building 2008

- > Date: 29/09/2008 4/10/2008
- > Location: Plovdiv (Bulgaria)

СНГ

- > Date: 12/11/2008
- > Location: Westpoint Centre Exeter (UK)

2009

Intermat 2009

- > Date: 20/04/2009 25/04/2009
- > Location: Paris (France)

2010

IMHX 2010

- **>** Date: 2/03/2010 5/03/2010
- Location: NEC Birmingham (UK)

BAUMA 2010

- > Date: 19/04/2010 25/04/2010
- > Location: Munich (Germany)

Contacts Parts Division

| Department | Telephone number | Fax number | E-mail |
|---------------------------------------|---|---|---|
| General | +32 56 43 42 11 | +32 56 43 44 88 | info@tvh.com |
| Belgium / Luxemburg | +32 56 43 43 47 | +32 56 43 47 47 | sales.be@tvh.com |
| The Netherlands | +32 56 43 44 50 | +32 56 43 44 59 | sales.nl@tvh.com |
| France / Dom-Tom | +33 820 22 77 22 | +33 810 12 12 48 | contact@manupiece.fr |
| Germany | +32 56 43 45 50 +32 56 43 46 50 +32 56 43 47 50 | +32 56 43 45 54 +32 56 43 46 54 +32 56 43 47 54 | sales.de.nord@tvh.com sales.de.mid@tvh.com sales.de.sud@tvh.com |
| Austria | +32 56 43 47 50 | +32 56 43 47 54 | sales.de.sud@tvh.com |
| Switzerland | +32 56 43 47 50 | +32 56 43 47 54 | sales.de.sud@tvh.com |
| Hungary | +32 56 43 48 60 | +32 56 43 48 63 | marketing.hu@tvh.com |
| Ireland | +32 56 43 45 71 | +32 56 43 47 94 | sales.ie@tvh.com |
| United Kingdom | +44 24 76 58 50 30 | +44 24 76 58 50 31 | sales.uk@tvh.com |
| Spain | +32 56 43 42 69 | +32 56 43 43 95 | recambios@tvh.com |
| Portugal / Brazil | +32 56 43 45 70 | +32 56 43 44 94 | sales.pt@tvh.com |
| South-America | +32 56 43 45 40 | +32 56 43 45 49 | norma@tvh.com |
| Italy | +39 011 40 78 90 10 | Team Belgium +39 011 40 78 90 50 Team 1 Torino +39 011 40 78 90 51 Team 2 Torino +39 011 40 78 90 52 | sales.it@tvhitalia.com |
| Scandinavia | +32 56 43 43 60 | +32 56 43 45 88 | sales.nordic@tvh.com |
| Balkan countries | +32 56 43 44 39 | +32 56 43 46 88 | sales.bk@tvh.com |
| Poland / Czech Republic / Slovakia | +32 56 43 44 61 +32 56 43 45 73 | +32 56 43 46 88 | sales.pl@tvh.com sales.cz@tvh.com |
| Romania / Moldavia | +32 56 43 43 33 | +32 56 43 47 74 | sales.ro@tvh.com |
| Russia / Baltic States / C.I.S. | +32 56 43 48 73 | +32 56 43 48 74 | sales.cis@tvh.com |
| Asia | +32 56 43 43 34 | +32 56 43 43 83 | sales.asia@tvh.com |
| Greece | +32 56 43 49 73 | +32 56 43 41 71 | sales.med@tvh.com |
| Turkey / Cyprus / Malta | +32 56 43 43 91 | +32 56 43 49 71 | sales.tr@tvh.com |
| Middle-East | +32 56 43 44 71 | +32 56 43 49 71 | sales.mid@tvh.com |
| Oceania | +32 53 43 45 48 | +32 56 43 49 71 | sales.au@tvh.com |
| North-Africa | +32 56 43 43 71 | +32 56 43 48 71 | marketing.africa@tvh.com |
| South-Africa | +32 56 43 46 35 | +32 56 43 48 35 | marketing.africa@tvh.com |
| United States | +32 56 43 44 37 | +32 56 43 47 37 | sales.us@tvh.com |
| Canada | +32 56 43 44 37 | +32 56 43 47 37 | sales.ca@tvh.com |
| Other countries | +32 56 43 42 11 | +32 56 43 44 88 | sales@tvh.com |

