



Stylish and well connected

An amazingly chic, tiny 12x optical zoom camera with Wi-Fi for easy sharing, effortless touch screen control and HS System for incredible photos and Full HD movies even in low light.

The IXUS 510 HS is part of the Canon IXUS digital still camera range consisting of the below products:

**IXUS 510 HS, IXUS 500 HS, IXUS 230 HS, IXUS 240 HS, IXUS 125 HS**

**Sales Start date:** April 2012  
**Target Market:** Personal / Home

Key Features:

- Powerful 12x optical zoom (21x ZoomPlus) 28mm wide-angle lens in a tiny, chic metal body
- HS System: 10.1 MP CMOS and DIGIC 5 for premium image quality even in low light
- Intelligent IS adapts the optical Image Stabilizer to the scene (7 modes) for sharp shots
- Wi-Fi for easy image sharing including via smartphones\*
- Wide 8.0 cm (3.2") PureColor II Touch LCD (460k) with Touch Shutter
- Full HD movies (1080p) with stereo sound, optical zoom and HDMI
- Smart Auto (58 scenes) and Multi-area WB for point and shoot ease
- Face ID can recognise and prioritise your favourite people
- High-speed Burst, Super Slow Motion Movie captures action
- Movie Digest (720p)

\*Wi-Fi support varies by device and region. For more information visit [www.canon-europe.com/wirelesscompacts](http://www.canon-europe.com/wirelesscompacts)

Product Name	Mercury Code	EAN Code	Recommended Retail Price
IXUS 510 HS (Black)	6161B008AA	8714574580869	£349 / €399
IXUS 510 HS (White)	6164B007AA	8714574580906	£349 / €399
<b>What's in the box:</b> Digital Camera IXUS 510 HS, Wrist Strap WS-DC10, Battery Pack NB-9L, Battery Charger CB-2LBE, AC Cable, Interface Cable IFC-400PCU, User Manual Kit.			

Accessories	Mercury Code	EAN Code
Battery Pack NB-9L	4722B001AA	4960999676586
AC Adapter Kit ACK-DC70	4726B003AA	4960999676692
HDMI cable HTC-100	2384B001AA	4960999530383
European Soft Case DCC-60	1365V352	5026173428088
European Soft Case DCC-65	1361V694	8714574527635
High-Power Flash HF-DC2	5189B001AA	4960999782232

## Technical Specifications

<b>IMAGE SENSOR</b> Type Effective Pixels Colour Filter Type 5	1/2.3 type back-illuminated CMOS Approx. 10.1M (Total Pixels approx. 16.8M) Primary Colour
<b>IMAGE PROCESSOR</b> Type	DIGIC 5 with iSAPS technology
<b>LENS</b> Focal Length Zoom  Maximum f/number Construction  Image Stabilisation	4.0 – 48.0 mm (35 mm equivalent: 28 – 336 mm) Optical 12x ZoomPlus 21x Digital Approx. 4x (with Digital Tele-Converter Approx. 1.4x or 2.3x and Safety Zoom <sup>[11]</sup> ). Combined Approx. 48x f/3.4 – f/5.6 14 elements in 12 groups (1 double sided aspherical lens, 1 single sided aspherical UA lens and 1 single sided aspherical lens) Yes (lens shift-type), Approx. 3.5-stop. Intelligent IS
<b>FOCUSING</b> Type AF System/ Points  AF Modes AF Point Selection AF Lock AF Assist Beam Closest Focusing Distance	TTL AiAF (Face Detection / 9-point), 1-point AF (fixed frame) or Touch AF with Object and Face Select and Track Single, Continuous, Servo AF/AE <sup>[10]</sup> , Touch AF Size (Normal, Small) On/Off Selectable Yes 1 cm (W) from front of lens in macro
<b>EXPOSURE CONTROL</b> Metering modes  AE Lock Exposure Compensation  ISO sensitivity <sup>[13]</sup>	Evaluative (linked to Face Detection AF frame), Centre-weighted average, Spot (centre or Touch AF frame) On/Off Selectable +/- 2 EV in 1/3 stop increments Enhanced i-Contrast for automatic dynamic range correction AUTO, 100, 200, 400, 800, 1600, 3200
<b>SHUTTER</b> Speed	1 – 1/4000 sec. (factory default) 15 – 1/4000 sec. (total range -varies by shooting mode)
<b>WHITE BALANCE</b> Type Settings	TTL Auto (including Face Detection WB), Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom. Multi-area WB correction available in Smart Auto.
<b>LCD MONITOR</b> Monitor  Coverage Brightness	8.0 cm (3.2") PureColor II Touch (TFT), 16:9 aspect ratio, Approx. 461,000 dots Approx. 100% Adjustable to one of five levels.
<b>FLASH</b> Modes Slow Sync Speed Red-Eye Reduction Flash Exposure Compensation Flash Exposure Lock Built-in Flash Range External Flash	Auto, Manual Flash On / Off, Slow Synchro Yes. Fastest speed 1/2000 sec. Yes Face Detection FE, Smart Flash Exposure Yes 50 cm – 2.5 m (W) / 1.0 m – 1.5 m (T) Canon High Power Flash HF-DC1, Canon High Power Flash HF-DC2
<b>SHOOTING</b> Modes  Modes in Movie  Photo Effects  Drive modes Continuous Shooting	Smart Auto (58 scenes detected), P, Movie Digest, Portrait, Smooth Skin, Smart Shutter (Smile, Wink Self-Timer, FaceSelf-Timer), High speed Burst (2.5MP), Handheld Night Scene, Low Light (2.5MP), Fish-eye Effect, Miniature Effect, Toy Camera Effect, Soft Focus, Monochrome, Super Vivid, Poster Effect, Color Accent, Color Swap, Snow, Fireworks, Long Shutter Smart Auto (21 scenes detected), P, Portrait, Miniature Effect, Monochrome, Super Vivid, Poster Effect, Color Accent, Color Swap, Beach, Foliage, Snow, Fireworks, iFrame Movie, Super Slow Motion Movie My Colors (My Colors Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter Skin Tone, Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color) Single, Continuous, Auto Drive, Self-Timer Approx. 2.6 shots/sec., AF: Approx. 0.8 shots/sec., LV: Approx. 0.8 shots/sec. High-speed Burst (2.5MP): Approx. 6.1 shots/sec., (until memory card becomes full) <sup>[6][7]</sup>

Subject to change without notice.

[1] Depending on the image size selected.

[3] Standard Output Sensitivity / Recommended Exposure Index. According to ISO 12232:2006 (20th April 2006) which specifies the method for assigning and reporting ISO speed ratings for digital still cameras.

[6] Under conditions where the flash does not fire.

[7] Depending on memory card speed / capacity / compression setting.

[8] Using the batteries and memory card format supplied with the camera (where included), except where indicated.

[10] Some settings limit availability.

[11] The following Speed Class memory cards are required for maximum record time: (HD) 1280 x 720 Speed Class 4

or above. (Full HD) 1920 x 1080 Speed Class 6 or above. (iFrame) 1280 x 720 Speed Class 6 or above.

[15] Wi-Fi use may be restricted in certain countries or regions. Wi-Fi support varies by device and region. For more information visit [www.canon-europe.com/wirelesscompacts](http://www.canon-europe.com/wirelesscompacts)

<b>RECORDING PIXELS / COMPRESSION</b> Image Size   Compression Movies  Movie Length	4:3 - (L) 3648 x 2736, (M1) 2816 x 2112, (M2) 1600 x 1200, (S) 640 x 480 16:9 - (L) 3648 x 2048, (M1) 2816 x 1584, (M2) 1920 x 1080, (S) 640 x 360 3:2 - (L) 3648 x 2423, (M1) 2816 x 1880, (M2) 1600 x 1064, (S) 640 x 424 1:1 - (L) 2736 x 2736, (M1) 2112 x 2112, (M2) 1200 x 1200, (S) 480 x 480 Resize in playback (M2, S, XS)* *XS is half the length and width of S Superfine, Fine (Full HD) 1920 x 1080, 24fps, (HD) 1280 x 720, 30fps, (L) 640 x 480, 30fps Super Slow Motion Movie (L) 640 x 480, 120fps, (M) 320 x 240, 240fps Miniature Effect (HD, L) 6fps, 3fps, 1.5 fps iFrame Movie (HD) (Full HD & HD) Up to 4 GB or 10 min. 00 sec. <sup>[11]</sup> (L) Up to 4 GB or 1 hour <sup>[7]</sup> (Movie Digest) Up to 4GB or 29 min. 59 sec. (Super Slow Motion Movie) 30 sec.
<b>FILE TYPES</b> Still Image Type  Movies	JPEG compression, (Exif 2.3 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant MOV [H.264 + Linear PCM (stereo)] iFrame
<b>DIRECT PRINT</b> Canon Printers  PictBridge	Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print supported on SELPHY CP & ES printers only) Yes
<b>OTHER FEATURES</b> Red-Eye Correction My Camera / My Menu My Category Intelligent Orientation Sensor Histogram Playback zoom Self Timer Menu Languages	Yes, during shooting and playback Start-up image and camera sounds customisation Image tagging feature Yes Yes Approx. 2x – 10x Approx. 2 or 10 sec., Custom English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Simplified Chinese, Chinese (traditional), Japanese, Russian, Portuguese, Korean, Greek, Polish, Czech, Hungarian, Turkish, Thai, Arabic, Ukrainian, Romanian, Farsi, Malaysian, Hindi, Indonesian, Vietnamese
<b>INTERFACE</b> Computer Other  Computer/Other	Hi-Speed USB (MTP, PTP) dedicated connector (Mini-B compatible) HDMI Mini Connector (HDMI-CEC compatible) A/V output (PAL/NTSC) Wireless LAN (IEEE802.11b/g/n), (2.4 GHz only) <sup>[15]</sup>
<b>MEMORY CARD</b> Type	microSD, microSDHC, microSDXC
<b>SUPPORTED OPERATING SYSTEM</b> PC & Macintosh	Windows 7 SP1 / Vista SP2 / XP SP3 Mac OS X v10.6 – 10.7 For Ad-hoc Wireless LAN connection to a PC: Windows 7 SP1 only Mac OS X v10.6.8 or later
<b>SOFTWARE</b> Browsing & Printing Other	ImageBrowser EX PhotoStitch
<b>POWER SOURCE</b> Batteries Battery life  A/C Power Supply	Rechargeable Li-ion Battery NB-9L (battery and charger supplied) Approx. 190 shots <sup>[8]</sup> Approx. 180 min. playback Optional, AC adapter kit ACK-DC70
<b>ACCESSORIES</b> Cases / Straps Flash  Power Supply & Battery Chargers Other	Soft Leather Case DCC-65, IXUS Metal or Leather Strap Canon High Power Flash HF-DC1, Canon High Power Flash HF-DC2 AC Adapter kit ACK-DC70, Battery Charger CB-2LBE Canon HDMI Cable HTC-100
<b>PHYSICAL SPECIFICATIONS</b> Operating Environment Dimensions (WxHxD) Weight	0 – 40 °C, 10 – 90% humidity 85.8 x 53.5 x 19.8 mm Approx. 163 g (including battery/batteries and memory card)

## Logistics information

Pack Description	Quantity	Dimensions (L x W x H in mm)	Weight (Net/Gross in kg)
Each	1	159 x 138 x 61	0.333/0.422
Carton	15	447 x 326 x 202	6.33/7.12
Euro Pallet	375	1200 x 800 x 1160	-/181