

Product Specification

8-Port 10/100/1000Mbps with 2 Shared SFP
Web Smart PoE Switch

GSD-802PS

Version 1.0

This document contains confidential proprietary information and is property of PLANET. The contents of this document should not be disclosed to unauthorized persons without the written consent of PLANET.

Change History:

Revision	Date	Author	Change List
Version 1.0	2007/06/27	Kent Kang	Initial release

Author	Kent Kang	Editor:	Kent Kang
Reviewed by:		Approved by:	Tom Shih

1. PRODUCT DESCRIPTION

The PLANET GSD-802PS is an 8-Port 10/100/1000Mbps Web Smart PoE Switch, non-blocking wire-speed performance Ethernet Switch.

With a 16Gbps internal switching fabric, the Switch can handle extremely large amounts of data in a secure topology linking to a backbone or high capacity servers.

The GSD-802PS could recognize up to 8K MAC Address table and provides 176KB on-chip frame buffer.

They offer wire-speed packet transfer performance without risk of packet loss. With high data throughput, the GSD-802PS provides the most convenient for user to upgrade their network to Gigabit environment.

The GSD-802PS provides Web Smart management functions through the Web management interface. Functions such as per port speed, duplex, IEEE 802.3x Flow-control settings and QoS settings, Trunking and VLAN, Port mirroring, all can be found in the friendly user interface of your web browser. These features provide a cost-effective way to manage the devices from Internet whenever you are at work or at home.

2. PRODUCT FEATURES

■ Physical Port

- **8-Port** 10/100/1000Mbps RJ-45
- **2 SFP** slots, shared with Port-7 and Port-8

■ Generic Features

- Complies with IEEE 802.3, 10Base-T, IEEE 802.3u, 100Base-TX, IEEE 802.3ab, 1000Base-T, IEEE 802.3z Gigabit SX/LX, IEEE 802.3af, Power over Ethernet
- Each Switching ports support auto-negotiation-10/20, 100/200 and 1000/2000Mbps supported
- Auto-MDI/MDI-X detection on each RJ-45 port
- IEEE802.3x, full-duplex flow control compliant; back-pressure, half-duplex flow control
- Store and Forward switching architecture
- Non-blocking switch fabric
- 8K MAC address table, automatic source address learning and aging
- 16Gbps switch fabric, non-blocking switch architecture
- 9K Jumbo Frame support at all speed (10/100/1000 Mbps)

■ Layer 2 Switching

- Port-Based and 802.1q VLAN function, up to 64 VLAN groups
- 802.1w Rapid-Spanning Tree protocol support
- Port Trunking supports to optionally increase bandwidth between switches
- Link Aggregation support static mode and LACP (802.3ad) - up to 4 Trunk groups, each trunk for up to maximum 8 ports
- Ingress Rate Limit and Egress Shaping for bandwidth control in steps of 128kbps

■ **Multicast**

- IGMP Snooping for multicast filtering, supports v1 and v2
- IGMP Query Mode supports for multimedia application

■ **Quality of Service**

- 4 priority queues on all switch port
- Support for strict priority and weighted round robin (WRR) CoS policies
- Traffic class assignment based on 802.1p tag or DSCP field
- Multicast and Broadcast Storm Control as well as Flooding Control

■ **Security**

- Port Mirroring support for dedicated port monitoring
- 802.1X Port-Based network access control, RADIUS Server Authentication
- Static MAC Address assign destination MAC address at specifies port

■ **Power Over Ethernet**

- All Copper ports with IEEE 802.3af injector built-in
- Support 48VDC, 15.4 watts PoE power output to 8 IEEE 802.3af compliant Powered Devices
- Power feeding On/Off and priority configuration
- Power Limit function for PoE power management
- Powered Device Auto Detection
- LED PoE Status Monitoring

■ **Management**

- Remote Web management interface
- Firmware upgrade through web interface
- Cable Diagnostics technology
- Support SNMPv1 with RFC-1213/1573-Interface group and RMON Group 1 (Statistics)
- SNMP Trap
- Supports PLANET EASY-DISCOVERY Utility for deploy management

3. PRODUCT SPECIFICATION

3.1 MAIN COMPONENT

Switch ASIC:	VITESEE VSC 7398	X1
10/100/1000 PHY:	VITESEE VSC 8538	X1
Combo port PHY:	VITESEE VSC 8558	X1
Flash	SST 39VF040	X2

3.2 Functional Specifications

Product	GSD-802PS 8-Port Gigabit Web Smart PoE Switch
Hardware Specification	
Copper Ports	8 10/ 100/1000Base-T RJ-45 Auto-MDI/MDI-X ports
SFP/mini-GBIC slots	2 SFP interfaces, shared with Port-7 and Port-8
Switch Architecture	Store-and-forward
Switch Fabric	16Gbps / non-blocking
Switch throughput	11.90Mpps
Address Table	8K MAC address table with Auto learning function
Share data Buffer	176K bytes on chip
Flow Control	Back pressure for Half-Duplex IEEE 802.3x Pause Frame for Full-Duplex
Jumbo Frame	9K Bytes
LED	Power Status 1000 Link/Act , 100 Link/Act, PoE in Use Status per port
PoE Power Output	48V DC, 15.4W, 350mA (Ping 1, 2, 3, 6)
Layer 2 function	
Management Interface	Web Browser, SNMPv1, v2c monitor and SNMP Trap
Port configuration	<ul style="list-style-type: none"> – Port disable/enable. Auto-negotiation 10/100/1000Mbps full and half duplex mode selection. – Flow Control disable / enable. – Bandwidth control on each port.
VLAN	Port-Based / 802.1Q Tagged Based VLAN Up to 64 VLAN groups
Link Aggregation	Supports 4 groups of 8-Port trunk IEEE 802.3ad LACP
QoS	Traffic classification based on 802.1p priority, DSCP field in IP Packet
IGMP Snooping	IGMP (v1/v2) Snooping, up to 64 multicast Groups
SNMP MIBs	RFC-1213 MIB-2 RFC-1573-Interface MIB RFC-2819 RMON MIB (Group 1)
Standards Conformance	
Regulation Compliance	FCC Part 15 Class A, CE

Standards Compliance

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX
- IEEE 802.3ab Gigabit 1000T
- IEEE 802.3x Flow Control and Back pressure
- IEEE 802.3ad Port trunk with LACP
- IEEE 802.1d Spanning tree protocol
- IEEE 802.1w Rapid spanning tree protocol
- IEEE 802.1p Class of service
- IEEE 802.1Q VLAN Tagging
- IEEE 802.1x Port Authentication Network Control
- IEEE 802.3 af Power over Ethernet

Network Media

- 10Base-T – UTP/STP category 3, 4 or 5 cable
- 100Base-TX – UTP/STP category 5 cable
- 1000BaseT – UTP/STP category 5e/6 cable
- 1000Base-SX - 50/125 μ m, 62.5/125 μ m Multi-mode fiber cable
- 1000Base-LX - 50/125 μ m, 62.5/125 μ m Single-mode fiber cable

3.3 Physical Specification


■ **Dimensions**

330mm x 155mm x 43.5mm (W x D x H)


■ **Weight:**

1.8kg


■ **Front panel**



■ **Real panel**



■ One Reset button on front panel for Switch default load



■ LED definition

System

LED	Color	Function
PWR	Green	Lights to indicate that the Switch is powered on.

1000Base-T ports

LED	Color	Function
PoE In Use	Orange	Lights to indicate the port is providing 48VDC in-line power.
1000 LNK/ACT	Green	Lights To indicate that the Switch is successfully connecting to the network at 1000Mbps
		Blinks To indicate the Switch is receiving or sending data
10/100 LNK/ACT	Green	Lights To indicate that the Switch is successfully connecting to the network at 10Mbps or 100Mbps
		Blinks To indicate the Switch is receiving or sending data

3.4 Environmental Specification

Operating

Temperature: 0~50°C
Relative Humidity: 5~95%(non-condensing)

Storage

Temperature: -40~70°C
Relative Humidity: 5~95%(non-condensing)

3.5 Electrical Specification

Input Voltage: 100 - 240VAC, 50 – 60Hz, Auto-sensing
Power consumption: 8.7 watts / 27.31 BTU (Stand by)
Maximum Power output: 130 watts (with 8-Port PoE power output)

3.6 Regulatory Compliance

FCC Class A, CE.

3.7 BASIC PACKAGING

■ GSD-802PS	X1
■ User's manual (CD-ROM)	X1
■ Quick Installation Guide	X1
■ Power cord	X1
■ Rack mount accessory kit	X1

3.8 REALIABILITY

MTBF > 50,000 hrs @ 25°C

3.9 Packing Dimension

Dimension: 520 mm (W) x 210 mm (D) x 90 mm (H)

Weight: 2.30 KG (Gross Weight)

5 PCS in one Carton

Notice:

1. Cisco in-line/Legacy Power Device such as VoIP and Wireless AP are not supported.