HDTV RECORDER



User Manual

SAFETY WARNINGS

These safety warnings are provided to ensure the best user experience with the least inconvenience. Please read this user manual completely before installation and operation. It is advised that you keep the original packaging and protective material in case you need to safely transport the equipment in the future (e.g. for repair).

Maintain at least 2 cm around these devices during operations to ensure heat is properly dissipated; this will maintain and prolong the life of the product.

[WARNING]

Do not use these devices outdoors or in environments where they can be exposed to water and moisture (e.g. bathtubs, basins, water tanks, wet basements, swimming pools etc.). This warning is to prevent fire and electrical shock.



To further prevent electrical shock, do not, in any circumstance, open the cases. Only trained technicians are certified to repair these devices. If your device needs repair, please contact your dealer.

- Do not place containers holding liquid (e.g. flower vases, coffee mugs etc.) or material soaked with moisture (e.g. paper, cloth etc.) on the top of or in the vicinity of this product. Always leave 2 cm of open space around the periphery of the case and on top of the case.
- Do not block the air vents on the cases. Also, do not place this device on soft surfaces (e.g. sofas) where the product might sink into the surface. Also, do not place devices on carpets or rugs where the surrounding material can affect ventilation and heat dissipation.
- Do not place these devices on any surface that generates heat such as radiators, electric heaters, fire places etc.

[SAFETY INSTRUCTION]

- Before using this product, read the User Manual completely and pay attention to all safety measures concerning operations.
- Always keep this manual accessible for reference.
- Pay attention to all warnings and follow all the safety instructions closely.
- Only operate these devices in well ventilated areas (i.e. do not place in closets, cupboards, covered boxes etc.).
- Only use a dry cloth to wipe down the case. Do not use liquid cleaners or spray cleaners.

Do not place the devices in areas that are confined in a limited space (e.g. in the middle of a crowded bookshelf).

[ABOUT the POWER SUPPLY]

- If you do not expect to use the product for an extended period of time, unplug the device from the power socket. This is a precautionary measure because these products, as long as they are connected to a power socket, will maintain an electrical current even though they are "turned off" (i.e. using the power button). Unplug the power cable from the power socket by pulling from the plug; do not pull on the cable line.
- Power Cable Precautions
 - Do not wedge or clamp the power line between the case and surrounding items (e.g. walls, furniture, closets etc.).
 - > Do not place things on the power line or drag anything over it.
 - If the power line is damaged, replace it immediately to prevent electrical shock and fire.

[ABOUT the HDMI CONNECTOR]

- Improper use of the HDMI socket and connector will cause damage.
 - Before plugging in the HDMI cable into the HDMI socket, carefully check the orientation and shape of the ends of the socket and connector to make sure you are not inserting the connector upside down. Plug the cable carefully into the socket, making sure the head of the connector aims straight into the socket, without any tilt.
 - Remove the HDMI cables whenever you move or transport these devices.
 - Hold the HDMI cable line when you plug or unplug the HDMI cable. Do not twist or force the plug into the connector.

[ABOUT DISPOSAL]

- These devices should be disposed of properly according to national, regional recycling regulations.
- Components that are consumptive in nature (e.g. battery) are not included in the warranty and will incur a fee when replaced.

[ABOUT ABNORMAL OPERATIONs]

- If any smoke or odors emanate from these devices, turn off the device immediately. Unplug the power cable from the socket and contact your dealer; if you continue to utilize this product in these conditions, it may cause a fire or damage the product irreparably. Unauthorized repair by uncertified repair facilities is forbidden.
- If the device is accidently exposed to water or the case is damaged in any way, turn off the power switch and unplug the power cable. Failure to do so may result in electrical short and fire. If you are uncertain of your situation, please call your dealer immediately.

Contents

1.		INTRO	DUCTION	6
2.		PROD	UCT DESCRIPTION	7
	2.1		Panel Descriptions	
	2.2		ANEL DESCRIPTIONS	
3.		QUICK	SETUP GUIDE	9
4.			ATION GUIDE	
4.	4.1		E CONTROLLER	
	4.1 4.2		TE CONTROLLER BUTTON DESCRIPTIONS	
	4.3		IN SCREEN DISPLAY) MENU	
	т.Ј		File Viewer	
			Recordings	
			Timer Programming	
			System Setup	
			System Setup-Language Settings	
			System Setup-Time Settings	
		4.3.7	System Setup-Input Audio/Video Setup	27
		4.3.8	System Setup-Output Audio/Video Setup	28
		4.3.9	System Setup-USB Utilities	29
			System Setup-Software Update	31
			System Setup-Restore Factory Settings	
			Information	
			Information-Show Stream Information	
			JTTON RECORDING	
	4.5	SIMULT	ANEOUS RECORDING(1 INPUT SOURCE)	36
5		RECO	RDING TIPS	38
	5.1	CREATE	YOUR OWN VIDEO LIBRARY	
	5.2	Recori	D LIVE OR PRE-SCHEDULED TV PROGRAMS	39
	5.3	BACKU	P THE TV PROGRAMS IN A SET-TOP BOX PVR	40
	5.4	Recori	DING FOR SURVEILLANCE	40
6		PLAYE	BACK ON A PC/NB	41
•	יחר			
At	- 14	ΙΝΟΙΧΊ	TROUBLESHOOTING	42
AF	PE	NDIX 2	2 SYSTEM SPECIFICATIONS	45

1.Introduction

The HDTV Recorder employs HDMI[™] technology to receive video from various input sources (HDMI, Component and CVBS) in either digital or analog format. The HDTV Recorder then stores the video directly onto a portable USB hard disk or **high speed** pen drive. It uses H.264 TS format, which guarantees very efficient compression and timely delivery. Both digital and analog input/output audio are supported through HDMI or RCA interfaces. Recorded video can be played back on any media player, Blu-Ray Disc player or PC/NB that supports H.264 TS file format.

HDTV Recorder Kit Contents

The HDTV Recorder kit contains the components listed below. If anything in the list is missing or damaged, contact your dealer immediately.

Package Contents

A. HDTV Recorder x1
B. AC to DC Power Adaptor x1
C. Remote Controller x1
D. HDMI Cable x1 (optional)
E. YPbPr component cable x1 (optinal)
F. AV cable x1 (optional)



In addition to the kit, a USB hard disk or pen drive, a video player (DVD player, Blu-Ray Disc player, Set-top box, VHS player, etc.) and an HDTV are needed.

Note: Power adaptor specifications will vary, depending on country or region.

2. Product Description

2.1 Front Panel Descriptions



The diagram above shows the front panel layout, which is described, from left to right, as follows:

- POWER LED: Illuminates when the system is in use.
- USB Interface: Connects to an external USB storage device, such as a USB pen drive or USB HDD.
- CVBS Source LED: Illuminates when CVBS is the selected input source. It flashes when CVBS is selected but the CVBS video signal is unavailable from the source.
- YPbPr Source LED: Illuminates when the YPbPr (Component) input source is selected. It flashes when no YPbPr is selected but the video signal is unavailable from the source.
- HDMI Source LED: Illuminates when the HDMI is the selected input source. It flashes when HDMI is selected but the HDMI video signal is unavailable from the source.
- Source Selection button: Selects the input source from one of the three source selections; HDMI, YPbPr or CVBS.
- REC LED: Flashes when the system is recording.
- REC Start/Stop button: Starts and stops recording.
- IR Input: IR sensor for the remote controller.

2.2 Rear Panel Descriptions



The diagram above shows the rear panel layout and is described from left to right, as follows:

- DC-IN12V DC Input: For use with the power adaptor included in the package.
- Power On/Off switch
- CVBS input: Composite video input.
- L-Audio-R: Stereo audio input for use with component or composite video input.
- YPbPr input: Component video input.
- HDMI input: HDMI input interface.
- HDMI output: HDMI output interface.

3. Quick Setup Guide

The Quick Setup Guide section describes how to get your HDTV Recorder environment quickly installed. Once setup is complete, you will be able to record the video from a video source onto a portable USB storage device. For this setup you will also need:

- HDTV with HDMI or YPbPr connectors.
- Video player (e.g. Blu-Ray player, DVD player) with HDMI, YPbPr or CVBS connectors.
- USB Hard Drive or USB Pen Drive (with FAT32 file system)

Step 1: Connect the Video Player to the HDTV Recorder

Connect your Video player to the rear panel of the HDTV Recorder. The HDTV Recorder can use HDMI, YPbPr or CVBS cables for input. You must choose from one of those three cabling options as shown below.

- a) HDMI–The HDMI cable (shown right) uses a simple, single connection. Connect one end of the HDMI cable to the Input HDMI connector as shown (right).
 Connect the other end to your video player. Note: Audio is also delivered through this cable.
- b) YPbPr– YPbPr cables have 3 connectors, each color coded (green, blue and red). Simply match the colors on the connectors with the color coded adapters on the HDTV Recorder (top row - shown right).

Since YPbPr video cables do not carry audio, you must also attach an audio cable between the player and recorder (bottom row); this cable will have 2 connectors (left-right speakers, usually red and white). You will need to connect a total of 5 connectors. Attach the other ends to your Video Player.





c) CVBS– The CVBS cable is a single cable with a video connector (usually yellow). You will also need to attach two audio connectors (for L-R speakers, usually red and white). The CVBS cable may come as a single cable with the 3 connectors at each end. Attach the other ends to your Video Player.

Note: If your Video Player gives you a choice of using HDMI, YPbPr and CVBS, it is better to choose HDMI for ease of installation. Also, HDMI and YPbPr picture quality are both noticeably better than CVBS.

Step 2: Connect the HDTV set to the HDTV Recorder

Connect your HDTV Recorder to the HDTV. The figure to the right shows an HDMI cable connection to the HDTV Recorder's HDMI output port. Attach the other end to your HDTV.

Step 3: Connect the USB Storage Device to the HDTV Recorder

Connect your portable USB storage device to the USB port of the HDTV Recorder. The HDTV Recorder supports the FAT32 file system format only. You must confirm that your USB storage device is FAT32 compliant.

If you are unsure about FAT32, simply use an empty or new USB storage device and format it (ALL DATA WILL BE ERASED) using the USB

utility in the HDTV Recorder's OSD (On Screen Display) menu (explained later). **Note**: You must always plug in the USB storage device before turning on the HDTV Recorder. Also, you should power down the HDTV Recorder before detaching the USB device.

Step 4: Connect the power cable to the HDTV Recorder

Connect the DC power cable of the power adaptor to the HDTV Recorder. Connect the power adaptor to a wall socket with the appropriate voltage.









Step 5: Power on TV set and Video Player

Power on your TV set and Video Player in any order. Place a video disc into your player and begin playing video.

Step 6: Power on HDTV Recorder

Turn on the Power Switch on the rear panel of HDTV Recorder. Wait for about 10 seconds. A red Power Indicator LED will illuminate on the front panel of the HDTV Recorder. One of the Source LED indicators (HDMI, YPbPr or CVBS) will illuminate and should match the type of input source you have attached. If it doesn't match, press the Video Source Selector button on the front panel until the appropriate Source LED indicator illuminates.



If your Video Player is transmitting a video stream, you should begin to see it on your HDTV.

Step 7: Recording to USB Storage Device

Press the "REC" button on the front panel to begin recording to the USB Storage Device. The red "REC" LED should illuminate. The TV screen should display "Recording Started".



Step 8: Stop Recording

Press the "REC" button on the front panel again to stop recording. The TV screen should display "Recording Stopped".

A folder designated by date and a sequence number will be created on the USB storage device on the root:\\VSTOR directory of the device. For example, the folder name, "V1216000", represents a folder that was recorded on Dec 16; the three last digits "000" represent a sequence number. If you record a second video on the same day, the sequence number for a new folder name will be incremented (e.g. V1216001).

At least two files will be created in each folder, a DAT.TS (audio and video content) and a Meta.APV (playlist). Since the maximum file size is limited to about 4 GB, video recordings that extend past that file limit will be broken up into consecutive 4 GB files.

4. Operation Guide

4.1 Remote Controller

The HDTV Recorder package includes a Remote Controller unit that controls the HDTV Recorder. It can also bring up and navigate the OSD Menus on the TV.



Fig	Name	Description	
	Active/Power Saving	Toggles the state of the HDTV Recorder between Active mode and Power Saving mode. Active mode is the normal state when the HDTV Recorder is ON. Power Saving mode is the normal state when the system is not in use. In Power Saving mode, the HDTV Recorder stops sending video to the TV and then reverts to a low-power state.	
	Audio Mute	Audio Mute ON/OFF(on the HDTV Recorder)	
Vol Increase / Decrease Volume		Increases and decreases the audio volume.	
0 : wxyz 9	Numerical and alphabetical keys: 0- 9 / A-Z.	Used for character input when using the OSD menus.	

4.2 Remote Controller Button Descriptions

Fig	Name	Description	
HDMI	Select HDMI	Selects HDMI as the current input source.	
YPbPr	Select YPbPr	Selects YPbPr as the current input source.	
CVBS	Select CVBS	Selects CVBS as the current input source.	
	Information	Displays current status information	
File	File browser	Opens the file browser for browsing all files on your USB storage device.	
	Scroll up	Scroll-up button for OSD Menus navigation.	
	Move right	Move-right button for OSD Menu navigation.	
	Move left	Move-left button for OSD Menu navigation.	
	Scroll down	Scroll-down button for OSD Menu navigation.	
OK	Setting confirmation	Similar to an "Enter" key; used to confirm a setting selection.	

Fig	Name	Description
	Menu	Brings up the OSD Menu on the TV display
EXIT	OSD Exit	Exits the OSD Menu
REC	One button record	Begins video recording to the USB storage device.
Stop	Stop recording	Stops video recording.
	PLAY	Brings up the playlist where you can select a file for playback.
	STOP	Stops playback and returns to video play from the input source.
	NEXT	In playback mode, skips to the next file.
	Previous	In playback mode, skips to the previous file.
	PAUSE/PLAY	Toggles between Pause and Play
	Fast forward	Rapidly advances the video
	Fast rewind	Rapidly rewinds the video

Fig	Name	Description
Movie Recorded file list		To list the recorded files. Press the PLAY or OK buttons to play the selected file.
Photo	Photo file list	Enter into the file browser mode and list all the BMP and JPG files for preview.
	RED button	Function varies with OSD menus and screen applications. This button's usage will be indicated on the screen with a red circle and a function label indicating usage: (e.g. Back)
	GREEN button	Function varies with OSD menus and screen applications. This button's usage will be indicated on the screen with a Green circle and a function label indicating usage: (e.g. Del)
	YELLOW button	Function varies with OSD menus and screen applications. This button's usage will be indicated on the screen with a Yellow circle and a function label indicating usage: (e.g. Ins)
	BLUE button	Function varies with OSD menus and screen applications. This button's usage will be indicated on the screen with a Blue circle and a function label indicating usage: (e.g. Open)
F1	Snapshots	Takes a snapshot of the current frame displaying on the TV and saves the image file to the USB storage device. The file will be saved as a .bmp file with a date stamp. The file will be placed in a folder labeled "Snapshot".

Fig	Name	Description	
F2	Repeat	In playback mode, the current video can repeat automatically by pressing this button.	
Cutput resolution		Change output resolution.	
F4	Lip Sync	While in live monitoring or recording mode, you can use this button to re-sync audio and video manually.	

All other buttons not mentioned are reserved for future use.

4.3 OSD (On Screen Display) Menu

When the system is active, you can press the button on the remote controller to bring up the OSD menu on the HDTV attached to the HDTV Recorder. The OSD menu is used to configure various options as described below.



OSD Menu Items:

- File Viewer
- Recordings
- Timer Programming
- System Setup
- Information

Navigating the OSD Menu:

You can navigate the OSD Menus using the following keys on the Remote Controller.

- Press the webuild button to return to the previous OSD Menu
- Press the EXIT button to exit the OSD Menu.
- Press or the OK button to select an item on the menu, move to the

next menu item, or change a value setting.

Press or buttons toview the options available for a setting.

OSD Menu Descriptions:

Menu Item	Description	Options
File Viewer	This function allows you to browse files on the USB storage device attached to the HDTV Recorder. You can see all files (any format) that currently reside on the device. From this screen, you can playback a previously recorded file by selecting it in the browser and pressing the OK button (on the remote). To copy move, rename, or delete files, use the Yellow button (above F3 key on remote) to access a submenu with these operations.	File Browser
Recordings	This function displays a playback list of your previously recorded video files that currently reside on the USB storage device. The files are listed by date and time. You can playback, delete, rename or protect these files.	■ Play list
Timer Programming	This function allows you setup a recording schedule to automatically record video to the USB device at preset times. You can easily edit, add and remove multiple recording sessions.	Preset video recording timer
System Setup	Configures system settings	 Language Settings Time settings Audio/Video Setup USB Utilities Software Update Restore Factory Settings
Information	System information and stream information.	Free Disk SpaceStream Information

4.3.1 File Viewer

There are two ways to enter into the file viewer: (1) press the *File* button on the remote controller, or (2) press the *button* button on the remote controller and then choose File Viewer.

💻 H500G		
	♥ ♥ VSTOR ♥ SNAPSHOT	

You can navigate the left panel of the file viewer by pressing

the or buttons. Then, you can select a disc or sub-directory by

pressing the OK button on the remote controller. The right panel of the file

viewer will display a file list of the disc or sub-directory contents.

If the selected item has a video file that is known to the system (e.g. jpg or bmp), it will display the file's resolution, recording length and date/time or the firmware version in the right panel. You can organize the files and

sub-directories by pressing the yellow button on the remote controller to create, copy, move, rename, delete files and folders.

File Viewer	
a:/VSTOR/ V0413001 V0119001 V0131000 V0302000 V0302000 V0423002 V0302003 V0302003 V0309000 V0309000	V0413001 HDTV VIDEO 13.04.2011 10:07 2:14:33 New Folder Copy Move Rename Delete
MENU: Back EXIT: Close Menu	OK: Open Options

- New Folder: Creates a new folder, "Folder01", in the current directory.
- Copy: Copies files/folders from one place to another. You must select a source file or folder and then a destination sub-directory to copy into; use the
 button to copy the selection into the new location. A progress bar will indicate progress. If a file/folder already exists, there will be a warning dialog box before the "copy" is performed. You can press the
 button to cancel the copy operation.



- Move: Similar to the Copy command but the original file/folder will be deleted.
- Rename: Changes the name of the selected file or folder.

File Viewer	
a:/VSTOR/	V0309000
 ■ ● V0413001 	HDTV VIDEO 09.03.2011 12:13
String editor	
0309000	
	OIns OAbc123 123 Edit
MENUSave	EXIT Discard
✓ V0309000	
MENU: Back EXIT: Close Menu	OK: Rename Options
The and buttons can be used to r	nove the cursor. The 🔨
and white and be used to sel	ect numbers or characters. You can
also use the buttons 0~9 on the remote	e controller to input numbers or
characters directly. Press the ebu	tton to delete the previous
cursor-position character (backspace).	Press the button to delete the
character from the current cursor-posit	ion. Press the 🔵 button to add a
new position for editing. Press the	button to change the input mode.
Press the web button to save the mod	dification or Exm to discard any
changes. The maximum file/folder nam	
over 8 characters will not be saved with	
	folder. A confirmation dialog box will
pop-up; press OK to confirm or	to cancel (as shown below).
File Viewer	
H500G	V0309000
🗰 VSTOR	
SNAPSHOT V0309000 Delete Whole Folder 3	
OK Yes	
EXIT Cancel	
MENU: Back EXIT: Close Menu	OK: Open Options

4.3.2 Recordings

There are 3 ways to view the playback list of previously recorded videos: (1) press the button on the remote controller, (2) press the button on the remote controller, or (3) press the button on the remote controller and then select a recording.

Playback List							
Date	Time	Title		Length			
				2.23/57			
01-31	14:49:00	Knight and Day		2:01:07			
03-02	14:43:57	BRUCE_LEE		2:05:12			
03-02	18:15:36	RED_2010		1:52:21			
03-03	18:12:00	3_IDIOTS		2:51:15			
03-09	12:13:00	HDTV VIDEO		1:58:31			
04-13	10:07:58	HDTV VIDEO		2:14:33			
04-23	09:25:32	AVATAR		2:58:40			
OK MENU	: Playback : Remove : Back	exit	: Rename : Lock/Unlock : Close Menu				

The playback list will show all the recorded files on the external USB storage device. You can use the A and A buttons to move to a recorded file and then press the O button to play, press to delete the file, press to modify the file title (max. title length is 254 characters,) or press To lock/unlock the file (to protect from deletion or removal). Use the O button to return to the previous OSD menu. Press the Form button to close the OSD menus. During the playback mode, press the O button to bring up the following information table:

3_IDIC)TS		08:12:29
PLAY			
2:51:15	55:32	2011-03-03	18:12:00 19:07:32

The top-right corner displays the current time and the top-middle column shows the title of the playback file. The bottom line of the screen display is described below, from left to right: (1) Elapsed time from the beginning of the file.

(2) Total recorded time/length of the playback file

(3) Date and time that the file was recorded

(4) Actual time (during recording) from playback file.

Press the *button to pause or re-play the file.*

Press the \bigcirc or \bigcirc buttons to fast forward or fast rewind the playback file; press again to increase the speed (2x) of fast forward or fast rewind. In addition, you can press the \bigcirc and \bigcirc buttons for slow playback (1/2, 1/4 or 1/8 of normal playback speed).

During the playback mode, press the *D* or *b* buttons to jump to the next or previous recorded file in the list; if there are no more files in the list, you will be returned to the file list window.

Press the **E** button to repeat playback for a file or press the **E** button twice to repeat playback for all recorded files. If you want to disable the repeat playback function, press (and continue pressing) the **E** button until the repeat function label displays "OFF".

4.3.3 Timer Programming

The Timer Programming screen allows you to pre-schedule recordings in the future. Press the button and then choose the Timer Programming item to view the Timer Programmingscreen.

Timer I	Programming				
Date	Time 00:00:00	On	Program <empty></empty>	Title	
OK MENU	: Remove Item : Edit Timer : Back		• EXIT	: Activate / Deactivate Timer : Close Menu	

This screen lists anypre-scheduled recording sessions. To add a new recording session, cursor down to the line with the <Empty> label and then

press the OK button.

Title	
Start Date	2011-08-16
Start Time	09:58:00
End Time	11:28:00
Timer Mode	Single
Power Mode After Rec.	Power On

In the next window (above) you can configure the details for the new recording schedule session. You can enter a title of up to 254 characters (English alphabet). You can also edit the "Start Date" and "Start/End Time", which represent the desired start and end recording times (default is current date/time with a 1.5 hour recording duration). The "Timer Mode" allows for a one-time recording as well as daily, weekly, workday (Mon-Fri) and weekend recording intervals (for same time and duration per day). The "Power Mode After Rec." allows you to set the running/standby mode of the device after the

recording session ends. Press the REC

button to save the new session and

exit the timer editing window. Otherwise, press the without button to exit without

saving. Pressing the *sum* button will also not save the current item and will exit the OSD menus.

Date	Time		On	Program	Title
04-04	08:00:00	09:30:00	Yes	HDTV VIDEO	
	00:00:00			<empty></empty>	
OK	: Remove Item : Edit Timer	1		• : A	ctivate / Deactivate Timer

After you save your new recording schedule session, it will appear in the Timer Programming list. The system will automatically awaken and begin recording when the "Start Time" arrives. You can press the button to delete an

item, press the OK button to enable or disable an item, or press the OK

button to edit an item. The web button will return you to the previous OSD

26

menu. If you would like to exit the OSD menu altogether, press the Exit button on the remote controller.

4.3.4 System Setup

On the System Setup screens, you can adjust the system settings, such as OSD language, current date/time, display mode, video compression quality, lip sync mode. You can also format the external USB storage device, upgrade

firmware and restore the factory default settings. Press the (MENU) button and

then choose the System Setup item; a system setup window will display as shown below.

System Setup			
Language Settings			ОК
Time Settings			
Input Audio/Video Setup			
Output Audio/Video Setup			
USB Utilities			
Software Update			
Restore Factory Settings			
	EVIT		
MENU : Back	EXIT	: Close Menu	

4.3.5 System Setup-Language Settings

The OSD supports English, French, German, Japanese, Traditional Chinese, Simplified Chinese, Spanish and Italian. To change the OSD language option,

press the or buttons or press the	
window. Usethe And to	locate your selection and press the
button to save.	
Language Settings	
Lunguage Settings	
OSD Language	繁體中文 ← OK→
MENU : Back	简体中文
	日本語
100	English
	Deutsch Deutsch



4.3.6 System Setup-Time Settings

This option allows you to set the date and time for yourregion. These settings must be accurate in order for pre-scheduled recordings to function properly. To

edit the date and time, press the and buttons and numeric buttons to

change the date and time.

Date	2011-04-04	09 ← -
Time	08:03:02	
Daylight Saving Time	Off	
Region	Taipei,Beijing,HK	
GMT Offset	+ 08:00 H	

4.3.7 System Setup-Input Audio/Video Setup

In the Input Audio/Video Setup menu, you can modify the default settings for recording video quality, lip sync mode, loop recording mode, audio source and auto wake up.

	Input Audio/Video Setup			
	REC Quality		Normal	←OK→
	REC LIPSYNC		Mode1	
	Loop recording		Off	
	Continuous Recording Time		120 Min	
	Audio Source		By Video	
	Auto Wake up		Off	
ע	MENU : Back	EXIT	: Close Menu	

 REC Quality: Sets the video compression bit rate, which can be Excellent, High, Fine, Normal or Basic. Approximately 4 GB storage are needed to record 60 minutes of HD video, using the Normal setting (see table below):

Input Resolution	Video Quality	Recording Time
		for 4GB of data
HD video	Excellent	20 minutes
(1080i, 1080p24	High	30 minutes
or 720p)	Fine	40 minutes

Input Resolution	Video Quality	Recording Time for 4GB of data
	Normal	60 minutes
	Basic	100 minutes
	Excellent	40 minutes
SD video	High	60 minutes
(480p/576p or	Fine	80 minutes
480i/576i)	Normal	120 minutes
	Basic	200 minutes

REC LIPSYNC: This mode can be used if you encounter lip-sync issues that cannot be resolved with the (Lip Sync) button. Only HDMI input will encounter these problems, which result from video players or set-top boxes using different video clocks to output video. You don't need to change the lip-sync mode if you don't change the video player or set-top box. The (Lip Sync) button should resolve most temporary lip-sync issues when changing TV channels or jumping to a new chapter in a movie. The default setting is Mode1.

- Loop Recording: This option, when set to OFF, instructs the system to stop automatically when there is available storage space for recording. When set to ON, the system will begin deleting the oldest recorded files automatically to maintain a minimum of free storage space (10 minutes of space). However, it will not delete any protected files. If all the recorded files are protected, the system will stop recording when there is no free storage; a popup message will display in this case. Default is OFF.
- Continuous Recording Time: The one-button recording time could be changed through this setting. The minimal recording time is 30 minutes and the maximum time is 14,400 minutes (10 days.)
- Audio Source: Default is "By Video" source. This setting allows you to select different audio source for live viewing and video recording. For example, you could choose RCA Stereo RCA audio as the audio source when the video source is HDMI.
- Auto Wake up: If enabled, the system will be waked up by active video from the selected input source. Default is OFF.

4.3.8 System Setup-Output Audio/Video Setup

In the Output Audio/Video Setup menu, you can modify the default settings for display format, scaling method, video resolution, contrast, brightness and saturation.

ſſ	Output Audio/Video Setup			
	Display format		Auto	←OK→
	Scaling method		Fullscreen (zoom)	
	Video Resolution		1080i	
	TV System		Auto	
	Contrast		32	
	Brightness		50	
$\left \right $	Saturation		32	
٦	MENU : Back	EXIT	: Close Menu	

- Display format: Options include 4:3, 16:9, or Auto mode (default). Auto mode only applies for HDMI output.
- Scaling method: Maintain original video size and ratio (default) or to scale up to fill the entire video screen.
- Video Resolution: Output video resolution selection. The maximum video resolution is Full HD (1080i) and the minimum video resolution is SD (480/576i.)
- TV System: NTSC, PAL or Auto mode (default). Auto mode only applies for HDMI output.
- Contrast: adjust the video output contrast level. Default value is 32.
- Brightness: adjust the video output brightness level. Default value is 50.
- Saturation: adjust the video output color saturation level. Default value is 32.

4.3.9 System Setup-USB Utilities

The USB Utilities screen allows you to re-establish connections to your storage device, format your external USB storage device and check for free disk space information.

The "USB Reconnect now" is used when the system does not yet recognize your USB storage device, even though it is plugged in. This will be apparent when the "Free Disk Space" line does not display on the screen. Highlight

"USB Reconnect now" and press **OK** on the remote to re-establish connections to your USB device (the system will reboot).

Note: "Free Disk Space" checking may take a few moments when the USB drive is larger than 500 GB – on some storage devices an LED will flicker while free disk space is being evaluated.



The "Format USB" item can be used to format a USB HDD, a USB Pen drive or a memory card used with a USB card reader. The HDTV Recorder formats using the FAT/FAT32 file system format. (HDTV Recorder does NOT support other file systems).

Warning: Formatting will erase all data on the USB storage device. Please backup the data on the storage device before formatting.

Important Note: Since USB versions can vary significantly, it is strongly recommended that you acquire a recent or newer USB storage device to avoid compatibility and performance issues.

4.3.10 System Setup-Software Update

You can apply new firmware upgrades from the manufacturer for your HDTV Recorder. For these procedures, you will need:

- USB storage device with FAT/FAT32 file system.
- HDTV
- HDTV Recorder
- Latest upgrade firmware (.ahx file) distributed by the manufacturer or distributor.
- 1. Copy the new firmware (xxxxx.ahx) to the USB drive.
- 2. Plug the USB drive into the HDTV Recorder
- 3. Connect the HDTV Recorder to your HDTV (using HDMI or YPbPr cables).
- 4. Power on HDTV Recorder
- 5. Press the *menu* button on the remote controller. On the Main Menu, select

the "System Setup" menu item and press the OK button.

Main Menu	
File Viewer Recordings Timer Programming System Setup Information	ОК
MENU : Back EXIT : Close Menu	

6. In the System Setup menu, select the "Software Update" item and press



ſ	System Setup		
	Language Settings Time Settings Audio/Video Setup USB Utilities Software Update Restore Factory Settings		ОК
	MENU : Back	EXIT : Close Menu	

7. In the "Software Update" screen, select the "Update New Software..." item

an	d press or button.
	Software Update
	Update New Software
	Current Version: 0.99 build #: OEM-11-0205
Ч	MENU : Back EXIT : Close Menu

8. At the "Choose New System Software" screen, press the OK button

again to select the Disk Volume.

Choose New System Software:	
Volume	H500G VSTOR SNAPSHOT IMAGE.AHX
MENU: Back EXIT: Close Menu	OK: Open

9. Search for the firmware file (file extension is .AHX) on the USB drive;

arrow down to the file and press the OK button.



10. Press the OK button to confirm the update.

$\left[\subset \right]$						
ΠĹ	(e Undate Confirm				
	Update					
	Current	OK EXIT	Yes Cancel			
Ч	MENU	: Back		EXIT	: Close Menu	

Note: The upgrade process may take a few minutes to complete.

The system will reboot automatically after the firmware is upgraded. You have completed the upgrade firmware procedures.

*Important! Any interruption (especially power interruption) during the upgrade process may render the system unusable.

4.3.11 System Setup-Restore Factory Settings

You can use the "Restore Factory Settings" option to reset the system settings back to the factory defaults.

ĺ	System Setup					
	Language Setti Time Settings	Restore F	actory Settings?			
	Audio/Video : USB Utilities . Software Upc	OK EXIT	Save Changes Abort			
	Restore Factor	y Settings		ОК		
Y	MENU : Bac	k	EXIT : Close Menu			

Press the OK button to confirm the system reset operation.

4.3.12 Information

The Information window allows you to check free disk space, amount of time available for recording, firmware version or real-time video stream information.

1	Information		
	Free Disk Space Free Recording Time Current Version Show Stream Information	325 GByte 36:47:58 Ver: 0.99 build#: OEM-11-0205	OK
IJ	MENU : Back	EXIT : Close Menu	

4.3.13 Information-Show Stream Information

The stream information window will display the real-time input video stream and audio stream information, including the input video resolution, frame rate, compression format and bit rate, audio sampling rate etc.

Stream Information	
Video PID	4113
Picture Size / Aspect Ratio :	0x0 Invalid:0
Frame Rate :	Invalid : 0
Compression Format :	H.264
Max. Bit Rate :	0 kBit/S
Measured Bit Rate :	0 kBit/S
Audio PID	4352
Audio Format :	Invalid: -1
Mode :	Invalid: -1
Sample Frequency :	48kHz
MENU : Back	EXIT : Close Menu

4.4 One-Button Recording

The easiest way to record video is to simply press the REC button on front panel

or REC button on remote to record the video or TV program currently displaying

(i.e. One-Button Recording). An OSD message "Recording Started" will be shown on the screen, assuming the content is not protected and there is adequate disk space.

0001 HDTV VIDEO						11:53:01
HDMI						
RI	C Quali	ty : Normal				
0:1	7			2011-04-12	11:52:43	

The top-right corner displays the current time and the left column (second line) shows the current input source (e.g. HDMI). The middle row shows the recording quality or compression video bit rate. The bottom line is described as follows (from left to right):

- (1) Elapsed time from the start time
- (2) Start date and time for the current recording

The default recording time is 6 hours for One-Button Recording. If you don't

manually change its end time for the session, it will stop the recording after 6 hours or when the disk is full.

There are 3 ways to stop the One-Button Recording function:

- Press the REC button on the front panel the message "Recording Stopped" will be shown on screen.
- Press the stop button on the remote controller the message "Recording Stopped" will be shown on screen
- Press the button on the remote controller the following dialog box will be displayed on the screen:

Stop Re	cording ?			
HDTV VI	DEO - HDTV VIDEO			
OK MENU	: Stop Recording : Back	EXIT	: Close Menu	

Move to the selected item (default is HDTV VIDEO) and then press the OK button to stop the recording.

4.5 Simultaneous Recording(1 input source)

You can have two simultaneous, active recording sessions; however, you can only record from one input source at one time. This might happen if you have two pre-scheduled recording sessions overlapping each other's time slot (**note**: only up to 2 recordings can be active at the same time). This might also happen if you are recording with the one-button recording mode when a pre-scheduled session recording starts at the same time. In both cases two separate files will be created.

If two sessions are actively recording at the same time and you press the first button, the session with the earliest start time will be stopped first. Pressing the first button again will stop the second session. If you desire to "selectively" stop one of the sessions (i.e. stop 2nd session before 1st session), you can press the first button which will bring up a selection dialogue box. You can also bring up the Timer Programming window to selectively cancel a session that is currently recording.

Note: You **cannot** invoke two simultaneous one-button recording sessions by pressing the **REC** button twice on the remote control, nor can you do this by

pressing the REC button twice on the front panel. Pressing the REC button on the front panel a second time will simply stop the current one-button recording function and pressing the REC button on the remote controller a second time will display an error message on the screen.

5 Recording Tips5.1 Create Your Own Video Library

The HDTV Recorder recording quality allows you to archive your favorite TV programs, movies, family videos (etc.) from almost any media format (VHS tape, DV tape, DVD, VCD, etc.), using real-time AVCHD (H.264) compressed recordings at resolutions up to 1080i. Commercial applications are also available for making real-time training programs, video conference recordings, QA/QC records and more. With a portable USB storage device, you can demo or share your video library with others easily, anytime and anywhere.

First, you will need to prepare a VHS video recorder (if you would like to archive VHS tapes,) V8 or DV camcorder (if you would like to archive video or DV tapes,) or DVD player (if you would like to archive DVD or VCD discs.) Put the tape or disc into the player, find the scene you would like to start recording from, and then use One-Button Recording function. This method is almost the same as if you backed up your VHS tapes using two traditional VHS video recorders. If you are busy with other jobs while archiving your old video media, please follow the procedures as follows:

- (1) Put the tape or disc into the player
- (2) Find the scene you would like to start recording from and "Pause" the video (on video player).
- (3) Write down the elapsed time that displays in the status window of the video player
- (4) Go to the last scene you want to record to by using the fast forward button on the control panel of video player
- (5) Write down the elapsed time for the last scene.
- (6) Calculate the recording time by subtracting from the two elapsed times (ending scene time minus starting scene time).
- (7) Go back to the starting scene and then press the "Pause" button of video player
- (8) Press the REC button on the front panel (of the HDTV Recorder) or **REC** button on the remote controller (of the HDTV Recorder) and then press

the "PLAY" button of the video player

(9) Press the *wenu* button on the remote controller for HDTV Recorder and

then select the Timer Programming item. A Timer Programming window will display the session you had just started. You can set the end time, which is when the recording stops; it will be based on the total recording time calculated in step (6). You can also edit the title for the program/video. The title will become useful if ever you need to search for specific videos in the future. The system only supports titles with numeric or English character input.

5.2 Record Live or Pre-Scheduled TV Programs

The HDTV Recording can record TV programs currently showing on the TV ("Live") or it can pre-schedule a recording session for later viewing.

To record "Live" programs, simply press the REC button on the remote controller or the "REC" on the front panel of the HDTV Recorder.

To Pre-Schedule a recording session for a TV program you will need a TV Box or a Set-top box (analog or digital OK) to deliver the appropriate TV program to the HDTV Recorder. The TV Box/Set-top box must remain "on" and set to the correct channel when the HDTV Recorder begins recording at the designated time.

(**Note**: The HDTV Recorder only records video that it receives through its video cables – it does not have an internal TV tuner and cannot receive TV signals directly – i.e. a TV Box or Set-top box is required to deliver the TV programs).

To Pre-Schedule a recording session from TV Box or Set-top Box:

- 1. Turn on TV set
- 2. Turn on the TV Box or Set-top Box and the HDTV Recorder
- 3. On your TV set, select the TV channel for your TV Box or Set-top Box that will eventually show the desired program (only one TV channel can be set for recording).
- 4. Select the Timer Programming item through the OSD menu of the HDTV Recorder and set up a pre-scheduled recording session or sessions (refer to the chapter "Timer Programming")
- 5. Turn off the TV set (leave TV Box/Set-top Box on and leave your HDTV Recorder in Power Saving mode see Remote Controller descriptions).

The HDTV Recorder will automatically awaken and record your program when the pre-scheduled time arrives.

5.3 Backup the TV Programs in a Set-Top Box PVR

Even though some digital or satellite set-top boxes have a personal video recorder (PVR) functionality and supports pre-scheduled recordings, the recorded files typically cannot be played back on other video players or PCs. The HDTV Recorder can back up all the recorded TV programs to a portable USB storage device, which can be viewed at anytime from other players that support the video file types. With this feature, you can free up space in the original STB forother programs. Please refer to the user manual of your STB about the scheduled recording timer and playback functions. The backup procedures are almost the same as the procedures in sections 5.1 and 5.2. Playback the recorded files one by one and record them onto an external USB HDD using the one-button recording function or scheduled recording timer function.

5.4 Recording for Surveillance

The HDTV Recorder supports extended recording for surveillance applications:

- (1) Connect the surveillance multiplexer output or the HD camera to the HDTV Recorder and then connect the output of the HDTV Recorder to the surveillance monitor or HDTV
- (2) Setup each recording session's duration through scheduled recording timer
- (3) Select the timer mode for "daily" in the OSD Menu>>Timer Programming>>Timer Edit, if you would like to record at regular daily time slots. For a full day, set the start recording time at 00:00:00 and the end recording time for23:59:59.
- (4) Go to the OSD Menu>>System Setup>>Audio/video Setup and turn on the Loop Recording mode, which instructs the system, upon reaching full capacity on storage, to make room for new surveillance video by deleting older files. Otherwise, the system stops recording when the storage device is full.

6 Playback on a PC/NB

You can playback recorded video files on a PC/NB. The minimum PC/NB requirements are as follows:

- Intel Core 2 Duo 6300 1.86 GHz
- 2 GB RAM
- Windows XP SP2 or later
- Hardware GPU MPEG decoding capability is prefer

Not all software video players are able to adequately play high quality HD video recorded by the HDTV Recorder. The software media players should support H.264 TS file format. Commercial software video players are recommended, such as CyberLink PowerDVD or Corel WinDVD.

Appendix 1 Troubleshooting

If no video displays on the HDTV:

- Make sure all power connections are secure and power is supplied to all equipment.
- Inspect all cables and cable connections between the HDTV Recorder and the HDTV.
- Make sure the Video Player is in working order and confirm that video is being output; if necessary, connect a TV directly to the player to confirm this. Also, make sure the HDTV that is attached to the HDTV Recorder is in working order.
- Make sure that the Source LED indicator matches the physical connection of the video source input.
 - e.g.If you connected your Video Player to the HDMI input port on the HDTV Recorder, the HDMI Source LED should be illuminated on the front panel. If another Source LED light is illuminated, simply press the Video Source Selector Button until the matching Source LED indicator illuminates.

If the video fails to record onto the USB storage device:

- Make sure the USB storage device is partitioned with FAT32. The HDTV Recorder only supports FAT32.
- If you are not sure if it is partitioned with FAT32, you can reformat the USB storage device from the OSD menus. Go to Menu >> System setup >> USB Utilities >> Format USB. You can create an FAT32 partition from this option (Warning: all data will be erased!).

Reconnect the USB device or reboot the HDTV Recorder again, and retry the recording function.

Before you contact your dealer or distributor for customer service, make sure you first have reviewed the troubleshooting section below for ideas on how to resolve your problem.

Trouble Shooting Checklist				
Scenario	Possible Reason	Solution		
TV attached to the recorder displays "no video images".	 Power is switched "off" Cable connections are not secure The input source selection of the TV does not reflect the actual video input connection in back of 	 Make sure the power switches on the back panel are turned on. Make sure the power cable and video/audio cables are secured. Make sure the connections between TV and HDTV Recorder are correct and secure. 		
	 the TV The video format is not supported by the TV (e.g. the TV is not an HDTV) 	 Make sure the TV is an HDTV that supports 1080i video resolution in minimum. Press the F3 button on remote controller to change output resolution. 		
Power indicator LED is not illuminated.	 The system may shut down after the "sleep time" is invoked or when the system is not receiving video while in playback mode or in live/recording mode. 	 Press the U button on the remote controller, wait for a few seconds and check if the Power LED is illuminated. 		
	 Power not turned "On" 	Check the power switch on the rear panel to make sure it is turned "On".		
	 Device is not starting normally 	If there is no response from the remote controller, try turning the power switch "Off" and "On".		
	 Power supply damaged 	If the suggestions above do not remedy the problem, the power supply may be damaged. Unplug the power cords immediately and contact your dealer.		
The Source LED indicator on the front panel is flashing	 Media source player is not powered on or is in standby mode 	 Check to see if the media source player is turned on. Check to see if the media source player is sending video (may have to press the play button on the media source player). 		

Trouble Shooting Checklist				
Scenario	Possible Reason	Solution		
	 Unsupported video/audio format from the media source player 	Refer to the user manual of media source player and make sure it is sending a video format supported by the system, such as 1920X1080@60i, PCM audio (see Appendix 2 for Video Specifications).		
Cannot record or playback	 No USB storage device or the device is not detected by the system 	Plug in the USB HDD or Pen drive and then power-down, power-on the system		
	 The disk is full 	Use the Information on OSD menu to check for free disk space		
	 The disk format is not supported 	Backup all the data on the USB HDD or Pen drive and then use the USB Utilities in the OSD Menu>>System Setup to reformat the USB storage device. Power-down, power-on the system or reconnect the USB device after formatting the storage device.		
	 The speed of pen drive is too slow 	Check if the speed of pen drive is quick enough for recordings or not.		
Lip sync issues	 Recording frequency is not correct 	 Press the F4 button on remote controller to re-sync audio and video. Adjust the REC LIPSYNC mode in OSD Menu>>System Setup>>Audio/video Setup. The default setting is mode 1. Adjust the lip-sync mode if you encounter lip-sync issues. In general, different video players or set-top boxes will output different video clocks and it will cause the lip-sync issues. 		

Appendix 2 System Specifications

Video Specifications:

Interface	HDMI	CVBS	Component	
Resolution	TIDIVII	CVDS	Component	
1920 x 1080p/24, 23.98	\checkmark			
1920 x 1080i/60, 59.94	\checkmark		\checkmark	
1920 x 1080i/50	\checkmark		\checkmark	
1280 x 720p/60, 59.94	\checkmark		\checkmark	
1280 x 720p/50	\checkmark		\checkmark	
720 x 576p/50	\checkmark		\checkmark	
720 x 480p/60, 59.94	\checkmark		\checkmark	
720 x 576i/50	\checkmark	\checkmark	\checkmark	
720 x 480i/59.94	\checkmark	\checkmark	\checkmark	

Audio Specifications:

Interface	HDMI	Stereo RCA
Format	PCM	5.0Vpp-Max.
Sampling rate and resolution	44.1/48 kHz,16 bits	48 kHz,16 bits
Audio channel	2 channel	2 channel
Connector	HDMI	RCA

System Specifications:

Item	Input	Output	Note
HDMI Port	1	1	
Component port	1		
CVBS port	1		
Stereo audio port	1		
IR sensor port	1		— 38 kHz
Remote Controller	1		
DC Power Input	12V/2A		Power adaptor supports 100-240VAC
Power Consumption	12-20 W		average
Operation Temperature and Humidity	10~40°C ,30~80%RH		
Storage Temperature and Humidity	-20~80°C , 20~90%RH		