

Reveal

B-Vent Gas Fireplace Series



Reveal, The secret has been revealed: Enjoy the beauty of an open fire with the convenience of gas

- Open-hearth design eliminates the glass to recreate the experience of a woodburning fireplace
- Radiant, clean-face design enables the black metal front to be hidden behind a choice of non-combustible finishing materials for an authentic, traditional look
- Multi-colored stone refractory comes standard in a choice of traditional brick or herringbone patterns
- Three-tiered burner provides full, generous flames using 40,000 Btus per hour for 36" models and 43,000 Btus per hour for 42" models
- Six-log set is realistically detailed and easily assembled

Reveal shown with Bridgeport mantel, marron brown marble and bi-fold doors

• Limited Lifetime Warranty

IntelliFire[™]

- Eliminates a standing pilot, reducing fuel consumption, saving money and being environmentally friendly
- Dependable in a power outage with battery backup



Reveal shown with Sedona flush mantel, Englewood shelf, cast insert panels and hearth, and bi-fold doors

Exceptional Value

Dependa

Reveal Technical Specifications

					← (
PRODUCT DIMENSIONS				0.044			<u> </u>			
Model	A	В	С	8-3/4 in			 21-1/2 in.			
RBV42361	41 in.	36 in.	23-3/4 in.		A	$\overline{\mathcal{S}}$ \	21-1/2 III.			
RBV48421	47 in.	42 in.	29-3/4 in.		4	- h	\			
					← <i>μ</i>	<i>۹</i> —	>			
	 	► 8-1/4 in.								
Ĺ			<u>^^ ^ ===</u>			1		Д		
		ſ					•••			
(Ouside 39-1/2 in.									
	Air									
		• ↑ 18 in.				30-1/4 in.	Electric			
3-1/4 in.	⊙ ^{Gas}	18 in.			38 in.		/ 🖸			
↓										
		₩ <u>+</u> +		_		┵╶┵╧╘		-		
T (6-1/2 in. <mark>⊣</mark> ◄	►	←───	в ——	→	2-7/8 in.	←→ 5-7/8 ir	۱.		
		7-1/2 in.	I		I	2-1/0 111.				
FRAMING DIMENSIONS					APPLIANCE LOCATIONS					
	А	В	С		Model	А	В	С		
	Rough	Rough	Rough		RBV4236I	42 in.	48 in.	22 in.		
	Opening	Opening	Opening		RBV4842I	48 in.	51-1/4 in.	22 in.		
Model	(Width)	(Height)	(Depth)	4				·		
RBV4236I	42 in.	39-3/4 in.	22 in.	-						
RBV4842I	48 in.	39-3/4 in.	22 in.							
				1/2 in. min. appliance -	→ I← B					
				to combustible	s					
				Ť	1 Alexandre		A-			
						Drywall -	→ ← 1 in. — min.	→ 48 in. max.		
	B Alcove Installation									
~										
	·· · ·									

The rough framing dimensions shown represent the distance from stud to stud only and do not take into consideration the addition of drywall. Please refer to installation instructions for complete specifications and drawings when installing this product. Go to www.heatilator.com to download.

ability

Most Recognized Brand

Reveal Models Available*

Opening Sizes	Venting	Ignition System	Fuel
36"	B-Vent	IntelliFire	Natural Gas
42"	B-Vent	IntelliFire	Natural Gas

Options*



Operable Glass Doors



Fixed Glass Doors

Options Not Pictured*

Remote Controls and Wall Switches Thermal Damper LP Gas Conversion Kit Mantels and Surrounds

Venting*

B-Vent: 6" B-vent pipe

AVAILABLE FROM



a brand of Hearth & Home Technologies Inc. 1915 West Saunders Street Mt. Pleasant, Iowa 52641 800-927-6841 • heatilator.com

The information provided in this literature is for planning purposes only and subject to change. Please consult the installation manual for actual installation. Actual product appearance may differ from product images. The flame and ember appearance may vary based on the type of fuel burned and venting configuration used. For full warranty details, go to heatilator.com.

*Please consult the MSRP book for a complete list of models and optional accessories