

Epson EMP-X52



[click for larger image](#)

- ⌘ Affordable, reliable education and office projector
- ⌘ Easy to use, with 5 second set-up and 1 second shut down
- ⌘ A/V mute slide to pause presentations and protect the lens
- ⌘ Efficient and reliable, with extensive security features
- ⌘ XGA resolution

» [view full specification](#)

High-quality, affordable education and small business projector

Add performance, reliability and value to classroom or office presentations with this compact, versatile projector. It's easy to use, secure and packed with features to save you time and money.

The Epson EMP-X52 makes great presenting simple and affordable. It takes just 5 seconds to start-up, with Auto Keystone Correction for perfect pictures, and is ready to unplug and go in a second.

Take charge with the new Easy-Use remote, and pause instantly with the A/V mute slide. Maximise reliability, save energy and keep costs low with the Epson E-TORL lamp, which lasts over 4000 hours and produces bright, clear images at an excellent 2000 lumens. Add peace of mind with extensive security features.

Key Features

Combine quality with affordability – the perfect presenting partner for the classroom or office

Superb quality – excellent images whatever your subject with Epson 3LCD technologies and 8 colour modes

Save money and energy – low wattage lamp and low power use add efficiency but produce 2000 lumens brightness

Ready in an instant – start up takes just 5 seconds, unplug and go in just a second!

Keep in control - includes new Easy-Use remote control and A/V Mute Slide to pause presentations

Excellent reliability – the exclusive Epson ETORL lamp lasts up to 4000 hours

Quiet operation – at just 28db your audience will hear the presentation, not the projector

Added peace of mind – security features include a tough bar, lock and password protection

Epson EMP-X52 Specifications

[« back to EMP-X52](#)

Projection system

Projection system 0.63-inch without MLA (x3) TFT

Optical

Native resolution XGA (1024x768)

Brightness 2000 ANSI lm / 1600 ANSI lm
(High/Low brightness mode)

Contrast 400:1

Projection lens Manual focus and 1.2x optical zoom
F=1.60-1.74 / F=18.40-22.12mm

Lamp type / life 170W UHE / 4000 hours (3000h at high brightness mode)

Screen size 30 to 300 inch

(Projected distance) (0.84 to 10.42m)

Colour reproduction Full-Colour (16.77 million colours)

Keystone correction Vertical: -30 to +30 degrees
Auto Keystone Correction

AV Features

AV mute slide Yes

Instant off Yes

Input **Video** D-sub 15-pin x1, RCA x1, S-Video x1
Computer RGB x1
Audio RCA x 1 (White/Red)

Output **Computer** D-sub 15-pin x1

Control USB Type B x1

Speaker output 1 W monaural

Other functions

Other functions Direct Power On, Source Search, Auto Detection of RGB, Operation Panel Protected Function, 7 Colour Modes, High Altitude Mode, Theft Proof (Security bar), Kensington Lock, User Logo, Freeze, E-Zoom, Help

OSD language

OSD language 25 languages

Power

Power supply	100 – 240 V AC \pm 10%, 50/60 Hz
Power consumption	100 – 240 V AC 50/60 Hz 2.8 – 1.2 A

Physical

Weight	2.7 kg
Dimension (DxWxH)	245 x 327 x 92 mm (Excluding feet)
Fan noise	High brightness mode: 35 dB Low brightness mode: 28 dB

Operating conditions

Operating temperature	5°C to 35°C
Operating altitude	0 to 2,286m

Supplied accessories

Power cable	1.8m
Computer cable	1.8m D-sub 15pin (Male) – D-sub 15pin (Male)
Remote control	Includes 2 x AA type Alkaline batteries
Password protect sticker	Included
User's manual set	Included

Specifications are subject to change.