35 Custom Builder Direct Vent Gas Fireplace



Customise a beautiful gas fireplace to your taste and your decor!



Design your own fireplace to suit your individual style

- Enjoy realistic flames, with low cost & maximum heat!
- Zero clearance Easy installation
- The 35 Custom Builder ships complete with a standard arched or square metallic black face
- The Model 35 Custom Builder has 7 beautiful face collections to choose from



Neo Classic[™] - Brushed Nickel finish



35 Custom Builder Standard Arch™ - Black Painted Finish



French Country™ - Antique Gold Finish



Metropolitan Collection™ Black Painted Finish



Classic Arch[™] - 24 Karat Gold Plated
- Black Painted Finish

Mix and match to create warmth, atmosphere and ambience



35 Custom Builder Standard Square - Black Painted Finish



35 Custom Builder Standard Square - Bayswater Face Black Painted Finish



35 Custom Builder Standard Square - Black Painted Finish with 3 Sided Stainless Steel Fascia



35 Custom Builder Standard Square - Black Painted Finish with 3 Sided Stainless Steel Fascia



 ${\it 35 Custom Builder Standard Square - Black Painted Finish with 3 Sided Brushed Aluminium Fascia}$

24,000 BTU Model 35 Custom Builder (CB) Direct Vent Zero Clearance Fireplace

Heater Rated

low cost gas fireplace with high heat output. The unique look of Fireplace Xtrordinair is now incorporated into a

Lower Heat Output

clearances to combustible mantle. Allows for low cost installation, direct contact to drywall, and reduced

long life in a gas fireplace. Limited Warranty.

A thermocouple safety switch shuts off gas in 30 seconds if the

pilot goes out.

Safety In Mind

Easy Operation wall switch included

High Tech Direct Vent Combustion System
The combination of the multi-port, aluminized pan burner, SIT gas valve and direct vent system ensures great performance, ease of operation and durable long life in a gas fireplace. We back it all with our industry leading Seven Yea

Realistic Fire

combine to create a realistic wood-like fire The flickering flames, hand-carved four piece log set and embers

Variable Heat Output

130 CFM thermo controlled convection fan is a standard feature A finely detailed grill transfers heat efficiently into your home. Whisper quiet,

Large Ceramic Glass Fireview Area

42cm tall x 75cm wide ceramic glass (not tempered) is standard

Heating Specifications

Heating Capacity*

Mj per hour Input

(maximum vent configuration) Overall Efficiency*

> 25 Mj per hour (high) 15 Mj per hour (low) 43 to 95 Sq. M.

Overall Efficiency* (minimum vent configuration)

25 Mj per hour (high) 14 Mj per hour (low)

76.7% (NG)

78.5% (NG) 80.1% (LP)

78.6% (LP)

Heating Security

A millivolt system ensures continued use of your fireplace even if the power

Multiple Venting Approvals

and raised or floor hearth Install the 35 CB in any room in straight or corner placement, flush or recessed face

Install in: • Kitchens Bathrooms Family Areas Mobile Homes

Custom Options - 8 Different Faces Available

ALL 36 DV-XL faces require face upgrade kit

*Gas appliance performance can be affected by negative pressure in a home and by prevailing atmospheric conditions. Contact local building or fire officials about restrictions and installation requirements in your area. Heating capacity may vary depending on the degree of home insulation, floor plan and the ambient temperature zone of the area in which you live.

Clearances to Combustibles See Owner's Manual for non-combustible clearances


Edge of Glass Frame to Sidewall Floor to Mantle* Edge of Glass Frame to Side Facing 215 mm 1067 mm

Hearth Extension Front & Sides *300mm Maximum Mantle Depth

None Required 110 mm

The electrical connection is Dimensions:

NOTE: Improper installation of your gas appliance or failure to operate it in accordance to the guidelines detailed in the Owner's Manual may negate your warranty and endanger your home and family.



Gas line enters from lower right front corner.

made in the lower left front

Must be installed in accordance with all local codes if any, if not, follow ANSI Z223.1-1992 and NFPA 54(88) and the requirements listed in the Complies to AS 4553/A.G.A. 103 - Approval #6295 Owner's Manual.

The dimensions and clearances on this page are for reference only! Refer to the Owner's Manual for operation and exact specifications prior to installation



Kirkland, WA

www.fireplacextrordinair.com

Dragon Wholesaling Pty Ltd Ph 1-800-064-234 Distributed in Australia

Victorian Agent Heatmaster Pty Ltd Ph 03 9761 7130

A USTRALIAN HOME HEATING ASSOCIATION INC



Fireplace Xtrordinair reserves the right to alter or improve its products at any time without notification.