

WHIRLWIND EDB-1

MADE IN KOREA

IN: For input of the signal from the source. The source may be the output of any type of musical instrument or amplifier speaker output. **(WARNING! In speaker mode, the EDB-1 does not supply the proper amplifier load required by most tube type amplifiers. Do not use a tube amplifier's speaker output alone with the EDB-1. You must also have a speaker or appropriate dummy load connected to avoid possible damage to the amplifier.**

OUT A "Y" connection or "loop through" from the input.

OUTPUT: A male XLR, provides a balanced low impedance (150 Ohms) signal for connection to balanced, low-Z equipment (mixing console, workstation, etc.)

PAD: Most instruments will operate properly when set to the "0" position. Set to the "-20dB" position for use with very "hot" instrument signals. Set to "-40" or when connecting to the speaker output of an amplifier.

GND/LIFT: Disconnects the ground between the input and the XLR output when set to the LIFT position to help eliminate hum. Ground remains connected when set to the GND position.

This product is warranted to be free of defects in materials or workmanship to the original purchaser for a period of 90 days from the date of purchase. Should warranty service be required, return the unit postage paid along with the original sales receipt to:

Whirlwind Music Dist., Inc.
99 Ling Road
Rochester NY 14612

Whirlwind will, at its option, repair or replace the unit. This warranty does not cover damage resulting from abuse, unauthorized modifications or use of the product in unintended applications.