





Energy Management solutions for compressed air and industrial gases

VPINSTRUMENTS.COM

A vertical bar on the left side of the text box, composed of 15 horizontal segments in a gradient of colors: green, yellow, orange, red, and purple.

'VPVision is really a powerful tool to keep our compressed air consumption at the lowest possible level. It helps us to prevent leakage and to optimize our compressed air supply.'

- Kikkoman Europe

Our mission

VPInstruments develops, produces and supplies energy management solutions for compressed air and industrial gases. We show you where, when and how much you can save. Our solutions cover both supply side and demand side. We offer a unique product range consisting of:

- > Flow meters and other sensors for compressed air
- > Monitoring systems for total compressed air management
- > Easy to use tools for installation

VPInstruments is one of the most innovative companies in its industry. Our products and solutions are often unique in the market, easy to use, sustainably produced, and designed with two eyes for detail, which is reflected in our logo. Our products are sold through skilled distributors worldwide. Thanks to their skills and expertise, they can help you to get most out of our products.

We take quality and traceability very serious. Our calibration systems are traceable to the National Standards at NMI (Dutch Institute of Standards and Metrology). Our quality management system is certified to ISO 9001:2008.

Proudly serving leading companies worldwide

Through our distributors and dealers, we serve clients worldwide to save on compressed air energy costs. A small selection of end users: Astrum UK (Steel castings), Bolletje (Food), GSK (Medicines), Kikkoman Foods, Libbey (Glass), Mars (Food), Nedstaal (Steel production), Nestlé (Food), O&I (Glass), Philips (Consumer goods), Rexam (Glass), Toyota (Automotive).



History

In 1974, Anton van Putten develops world's first solid state flow sensor.

In 1999, VPInstruments is founded by Pascal van Putten, and wins the McKinsey New Venture '98 competition.

In 2007, The VPFlowScope product line is launched. For the first time, mass flow, pressure and temperature can be measured with a single probe.

In 2009, VPVision is introduced. The complete solution for compressed air energy management.

In 2011, The VPFlowScope Differential Pressure flow meter is introduced. Now you can perform air audits in wet, condensing air conditions.

In 2012, VPInstruments sets the new standard for web-based compressed air energy management. Open US Service center.

Technology

Thermabridge- leading sensor technology since 1974

Our co-founder Anton Van Putten invented world's first solid state thermal mass flow sensor back in 1974. We are proud to continue the heritage of making cutting edge products based upon this unique and patented sensor technology.

Working principle

The unique Thermabridge™ sensors are integrated circuits, just like computer chips. They combine a heater with a Wheatstone bridge. The heater keeps the sensor on a constant temperature. The Wheatstone bridge is used for temperature control and direction measurement.

Direction sensitivity. Invented by VPInstruments

The VPFlowScope combines an extremely large measurement range with integrated direction sensitivity. This patented feature enables you to measure in loop networks, and in systems with air receivers. These situations used to be very difficult to assess. With the VPFlowScope, flow direction is no longer a mystery.


Modbus - the industry standard

The VPFlowScope provides a Modbus-RTU interface, which opens the door to many energy management software packages and building management systems. No secret protocols or expensive configuration tools needed.

Sensing the future

Since 1974, the founders of VPInstruments have invested over 35 years in research and development. We will continue to do so, to enhance our products and our technology, in our effort to provide the best possible solutions for mass flow measurement of compressed air and technical gases.

The unique Thermabridge™ sensors combine a heating element with a Wheatstone bridge.



If you can measure it, you can improve it

Measure

p11



Use mass flow meters for:

- > Supply side air: pre-treatment wet oily dirty air
- > Demand side air - clean dry air
- > Piping systems from 0.5" up to 20", Measuring and recording mass flow, Temperature and Pressure in a single measuring instrument
- > Air audits, system checks

Monitor

p27



Leave measuring equipment in place to:

- > Continually know what is happening to your system
- > Proactively control leaks
- > Plan your maintenance, based on real-time actions
- > Monitor Dew point, power consumption and pressure loss to prevent downtime

Manage

p31



With VPVision you can:

- > Track and manage your leakage
- > Allocate compressed air costs to individual departments
- > Deliver cost evaluation and savings reports
- > Benchmark different plants around the world on efficiency and costs
- > Produce necessary documentation for utility incentives

Install

p35



We offer a line of tools and accessories for:


- > Hot tapping: Installation of flow meters under pressurized conditions
- > Leak detection
- > Measuring pipe wall thickness

Measure, Discover and Save!

Compressed air is a very expensive energy source. In fact, it is nearly 10 times more expensive than electricity.

Studies show that up to 50% of generated compressed air is still lost due to leakage, incompetent use and overdue maintenance. Our products enable you to chart these losses easily.

In many cases, compressed air demand can be reduced by optimizing the compressed air system with proper air management, pressure control, piping configurations and air leak control.



Maximize your ROI

Your return on investment can be a matter of months. Take a look at customer savings success stories on our website, and read how our products have helped companies save energy year after year.

kW	ANNUAL ELECTRICITY BILL			SAVINGS POTENTIAL		
	kW/Year	Euro	USD	Euro/Year	USD/Year	ROI (days)
25	109,500	€ 16,425	\$ 19,710	€ 4,928	\$ 5,913	365
37	162,060	€ 24,309	\$ 29,171	€ 7,293	\$ 8,751	247
55	240,900	€ 36,135	\$ 43,362	€ 10,841	\$ 13,009	166
125	547,500	€ 82,125	\$ 98,550	€ 24,638	\$ 29,565	73
250	1,095,000	€ 164,250	\$ 197,100	€ 49,275	\$ 59,130	37

Equipment investment	€ 5,000
Leakage/savings potential	30%
Production hours per day	12
kW price	€ 0.15

Did you know that a 2 inch in-line meter guards a cash flow of more than 10,000 Euro (\$13,000) per year? The ROI is in general a matter of months! See our website for more savings examples and calculators.

Compressed air applications

Virtually any production plant utilizes compressed air. Applications are packaging machines, offset presses, transport of granulate and food ingredients, cooling of products, and tank aeration.


- > Ceramic factories
- > Glass production
- > Cement and construction products
- > Paper
- > Food production, beverage and breweries
- > Life sciences
- > Automotive
- > Steel production



Other markets and applications

Our products are used successfully in various industrial applications, for example:

- > Aeration monitoring in water treatment plants
- > Airflow monitoring in large ducts
- > General test and measurement applications (like universities)
- > OEM applications
- > Combustion air mixing
- > Technical gas mixing
- > Welding gas, packaging gas
- > CO2 consumption metering
- > CO2 exhaust metering



Application examples and start kits

We offer start kits, which can be directly applied to your application. Each start kit contains all the items you need for the job.



Portable audit tools

The VPFlowScope® measures mass flow, pressure, temperature and features a built-in 500,000 point data logger. The device has a built-in display with keypad for configuration: no need to bring a computer on-site! The start kit is delivered in an heavy duty weather proof transport case. Complete with a portable power supply adapter, cables and VPStudio™ software.

Order codes

VPFlowScope®

VPS.R150.P400.KIT
VPS.R200.P4DP.KIT

VPFlowScope start kit for dry air
VPFlowScope start kit for wet air, high temperature

Demand side measurement

For small compressors, demand side and point of use measurement, we offer plug and play packages, consisting of an easy to install in-line flow meter and cable. Thanks to their unsurpassed measurement range, we offer three models that fit virtually all demand side applications. A wall mount power supply (IP54/ NEMA 3) is optional.

PIPE SIZES			CAPACITY			
DN	Thread ¹	Models	Qmin (m³ _n /hr)	Qmax (m³ _n /hr)	Qmin (scfm) ²	Qmax (scfm) ²
15	1/2 "	VPF.R060.M050.D1	0.32	60	0.2	35
25	1 "	VPF.R200.M100.D1	0.88	200	0.52	120
50	2 "	VPF.R01K.M200.D1	3.53	1000	2.08	590

- 1 All models supplied with BSP thread (straight).For US NPT, you can chase with die.
2 SCFM values are rounded off



Power supply and interface options

All power supplies are rated for 90 to 230 v input with 12 to 24 v output and supplied with correct plug for initial country shipped to.

ORDER CODE	DESCRIPTION	APPLICATION
VPA.0030.100	Power supply, in IP54 box	Fixed, heavy industrial
VPA.0000.100	Power supply with M12 connector	Light industrial, portable use
VPA.0000.102	Interface box JB1 with 5m / 16.4 ft cable / 12 VDC power supply	Air audits, portable use
VPA.0000.005	M12 cable, 5 meter	Fixed installations, control panels

Compressed air supply monitoring

For overall efficiency and cost monitoring we provide a complete solution. It consists of the VPFlowTerminal wall mount display, the VPFlowScope and an AC current sensor. With an optional dew point sensor, you can also monitor the dew point to make sure it is within the specified range.

Order codes

VPT.5110.000
VPT.5110.001

VPFlowTerminal display with 2 million point Data logger;
4 analog inputs 4 ... 20 mA option

Flow meters

VPS.R200.P4DP
VPS.R150.P400

Flow, pressure, temperature measurement, for wet air
Flow, pressure, temperature measurement, for dry air

Current sensors

VPA.8000.2100
VPA.8000.2200
VPA.8000.2400
VPA.8000.21K5

VPLog-i AC current sensor 100A-rms
VPLog-i AC current sensor 200A-rms
VPLog-i AC current sensor 400A-rms
VPLog-i AC current sensor 1500A-rms

Dew point sensors

APPLICATION	DEW POINT	CONNECTION	ORDER CODES
Adsorption dryer Refrigerant dryer	-100 ... +20°C -148 ... 68°F -40 ... +60°C -40 ... 140 °F	4 ... 20 mA 2 wire 4 ... 20 mA 3 wire	VPA.8000.1003 VPA.8000.1013

Example: VPFlowTerminal for local data logging

- > 1 VPFlowScope
- > 3 parameters on local display
- > Up to 7 parameters to be logged
- > Example: 4 analog inputs (4 ... 20 mA)
 - > 2 Current clamps (Amps)
 - > 1 Pressure sensor (Air treatment DP)
 - > 1 dew point meter (Air treatment Quality)
 - > VPFlowScope and all 4 ... 20 mA signals can be patched to DCS



Service & support

Service is provided from our main office in Delft and our Authorized Marketing and Service Center in the United States. As the market leader in compressed air flow measurement equipment, VPInstruments has developed unique calibration facilities.

Our pressurized calibration systems are state of the art, strictly maintained under the ISO 9001 certified Quality Management System.

For continual optimal service, we suggest the VPInstruments Full Service Subscription Program. No downtime: We send you a calibrated meter, and you return the used meter upon receipt.

Order codes

VPA.0001.920

Standard Service Subscription (SSP) 5 year subscription. Includes annual recalibration, firmware update and cleaning of your flow meter. Includes warranty extension up to 5 years.

VPA.0001.940

Full Service Subscription (FSP) Exchange Program. Receive annually a calibrated instrument and exchange it for the instrument in your possession. No service waiting time. Lifetime warranty extension. Includes shipment costs from VPInstruments to client, terms CIF* (Incoterms 2010). (Minimum for 3 years)

Special exchange programs available, check with your Distributor





Measure

'If you can measure it, you
can improve it'

- Lord Kelvin



VPFlowScope

- > Mass Flow, Pressure & Temperature
- > Display/data logger module for easy recording of data
- > Measures mass flow and direction



VPFlowScope

The VPFlowScope measures mass flow, temperature and pressure simultaneously. It's the ultimate compressed air audit tool, used by leading auditors worldwide. The bright blue display provides real-time information, and with the built-in data logger, recording is as easy as taking a picture.

VPStudio software can be used for real-time measurements on your PC, to process data and to print reports. The VPFlowScope product family consists of a wet and a dry air flow meter, which are fully interchangeable and compatible with the VPFlowScope display modules.

Applications

- > Air audits
- > Demand side monitoring, sub metering of compressed air
- > Ring networks (bi-directional)
- > Air, Nitrogen, Carbon Dioxide, Argon: Any dry and non-corrosive gas.

We offer the VPFlowScope for both wet and dry compressed air. You can combine both the wet and dry sensor module with the same display module. That's why the VPFlowScope is so exceptional for air auditors. With the VPFlowScope you can measure virtually any compressed air system with a single instrument.

Specifications – Thermal

VPFlowScope

Flow sensor

Measuring principle	Thermabridge™ Thermal Mass Flow sensor
Flow range	0 (0.5) ... 150 m _n /sec 0 ... 500 sfps Bi-directional option (calibrated in positive direction only).
Accuracy	2% of reading under calibration conditions; Please refer to the user's manual for details. Recommended pipe diameter: 25 mm (1 inch) and up.
Reference conditions	0 °C, 1013.25 mbar 32 °F, 14.65 psi
Gases	Compressed air, Nitrogen and inert, non condensing gases
Gas temperature range	0 ... +60 °C 0 ... +140 °F

Pressure sensor

Pressure sensor range	0 ... 16 bar 0 ... 232 psi gage
Accuracy	+/- 1.5% FSS Temperature compensated

Temperature sensor

Temperature sensor range	0 ... +60 °C 0 ... +140 °F
Accuracy	> 10 m/sec: +/- 1 °C 1.8 °F < 10 m/sec: + 5 °C 1.8 °F

Data outputs

Digital	RS485, MODBUS RTU protocol
Analog	4 ... 20 mA output, selectable via software to indicate flow, pressure or temperature

Display/data logger

Technology	Liquid Crystal (LCD)
Back light	Blue, with auto power save
Data logger	500,000 points


Mechanical & environmental

Probe lengths	400 mm 15 inch (other lengths on request)
Process connection	Compression fitting, 0,5 inch
Pressure rating	PN20, higher pressure on request
Protection grade	IP52 NEMA 12 when mated to display module, avoid upside down installation IP63 NEMA 4 when mated to connector cap, avoid upside down installation
Ambient temperature range	-10 ... +50 °C 14 ... 122 °F. Avoid direct sunlight or radiant heat Higher ambient temperatures: consult factory
Wetted materials	Anodized Aluminum, Stainless steel 316, Glass, Epoxy
Corrosion resistance	Highly corrosive or acid environments should be avoided

Electrical

Connection type	M12, 5 pin connector, female
Power supply	12 ... 24 VDC +/- 10 % Class 2 (UL)
Power consumption	2,4 Watt (no flow) 4,8 Watt (full flow) +/- 10% 100 mA (no flow). 200 mA (full flow) +/- 10% @24VDC
UL/ CUL	14 AZ, Industrial Control Equipment
CE	EN 61326-1, EN 50082-1

Technical drawings



Order codes

Flow meters

VPS.R150.P400.KIT

VPS.R150.P400.D1

VPS.R150.P400.D2

VPFlowScope start kit, for air audits, complete with software

VPFlowScope with data logger display module, for auditors and permanent installation (stand alone)

VPFlowScope with connector cap. For modbus networks

Other probe lengths

The standard P400 probe is acceptable for most air audits and installations. We offer P300 and P600 probes on request.

Accessories

VPA.5000.005

VPA.5001.105

VPA.5001.900

Cable, M12, 5 pole, for permanent connection


Interface box JB5 with 5m/ 16.4 ft cable + 12 VDC power supply

Connector cap with M12 socket for VPFlowScope sensor module

VPFlowScope R150.P400 flow range table

SCHEDULE 40 STANDARD SEAMLESS CARBON STEEL PIPE								SCHEDULE 10 STANDARD SEAMLESS CARBON STEEL PIPE					
Size (inch)	DN	ID (inch)	ID (mm)	Min flow (scfm)	Max flow (scfm)	Min flow (m ³ _n /hr)	Max flow (m ³ _n /hr)	ID (inch)	ID (mm)	Min flow (scfm)	Max flow (scfm)	Min flow (m ³ _n /hr)	Max flow (m ³ _n /hr)
2	50	2.1	52.5	2	688	4	1,169	2.2	54.8	2	749	4	1,273
3	80	3.1	77.9	5	1,516	9	2,576	3.3	82.8	6	1,712	10	2,908
4	100	4.0	102.3	9	2,610	15	4,435	4.3	108.2	10	2,923	17	4,966
6	150	6.1	154.1	20	5,924	34	10,065	6.4	161.5	22	6,508	37	11,057
8	200	8.0	202.7	34	10,259	58	17,429	8.3	211.6	37	11,173	63	18,982
10	250	10.2	259.1	56	16,756	95	28,468	10.4	264.7	58	17,487	99	29,709
12	300	11.9	303.2	77	22,953	130	38,995	12.4	314.7	82	24,724	140	42,004
16	400	15.0	381.0	121	36,237	205	61,565	15.6	396.8	131	39,315	223	66,794
20	500	18.8	477.8	190	56,996	323	96,832	19.6	496.9	205	61,643	349	104,729

The ranges apply only to compressed air and nitrogen. Contact us for other gases. The field accuracy of an insertion probe is typically +/- 5% due to installation conditions. Insertion probes may not be used for official compressor testing.



'The VPFlowScope enables us to perform air audits. quicker, easier and more cost effective. It is the Swiss army knife for any compressed air auditor'

- Air Energy Management, UK



VPFlowScope dP

- > Extreme resistance to pollution and water drops
- > Mass Flow, Pressure & Temperature
- > Display/data logger module for easy recording of data

VPFlowScope dP

The VPFlowScope dP is designed for wet air¹. When properly applied, it can be used in the discharge of the compressor. The VPFlowScope dP is fully compatible with the standard VPFlowScope, which means that it is easy to install and operate without additional training.

Typical applications

- > Wet air, untreated compressed air¹
- > High temperature up to 150 °C (302 °F)
- > High velocity applications (undersized pipes)

¹ The VPFlowScope dP can be used up to a high water content (saturated air). However, as it's based on the Pitot principle, some limitations apply: The rangeability is smaller, no vertical lines, no overflowing with water. See user manual for details.

Specifications

VPFlowScope dP

Flow sensor

Measuring principle	Differential pressure
Flow range	20 ... 200 m _n /sec 65 ... 650 sfps Bi-directional measurement
Accuracy	2% of reading over 1:10 range, under calibration conditions; Please refer to the user's manual for details. Recommended pipe diameter: 50 mm (2 inch) and up.
Reference conditions	0 °C, 1013.25 mbar 32 °F, 14.65 psi
Gases	Wet compressed air, Dry compressed air, Nitrogen and Inert gases.

Pressure sensor

Pressure sensor range	0 ... 16 bar 0 ... 232 psi gage
Accuracy	+/- 1.5% FSS Temperature compensated

Temperature sensor

Temperature sensor range	-40 ... +150 °C -40 ... +302 °F. Icing should be avoided
Accuracy	+/- 1 °C 1.8 °F

Data outputs

Digital	RS485, MODBUS RTU protocol
Analog	4 ... 20 mA output, selectable via software to indicate flow, pressure or temperature

Display/data logger

Technology	Liquid Crystal (LCD)
Back light	Blue, with auto power save
Data logger	500,000 points


Mechanical & environmental

Probe lengths	400 mm 15 inch (other lengths on request)
Process connection	Compression fitting, 0,5 inch
Pressure rating	PN20, higher pressure on request
Protection grade	IP52 NEMA 12 when mated to display module IP63 NEMA 4 when mated to connector cap - do not mount upside down
Ambient temperature range	-10 ... +50 °C 14 ... 122 °F. Avoid direct sunlight or radiant heat Higher ambient temperatures: consult factory
Wetted materials	Anodized Aluminum, Stainless steel 316, Epoxy
Corrosion resistance	Highly corrosive or acid environments should be avoided

Electrical

Connection type	M12, 5 pin connector, female
Power supply	12 ... 24 VDC +/- 10 % Class 2 (UL)
Power consumption	1 Watt +/- 10% 50 mA +/- 10% @24VDC, constant over the entire flow range
UL/ CUL	14 AZ, Industrial Control Equipment
CE	EN 61326-1, EN 50082-1

Technical drawings



Order codes

Flow meters

VPS.R200.P4DP.KIT

VPS.R200.P4DP.D1

VPS.R200.P4DP.D2

VPFlowScope dP start kit, for air audits, complete with software

VPFlowScope dP with data logger display module, for auditors and permanent installation (stand-alone)

VPFlowScope dP with connector cap. For Modbus networks

Other probe lengths

The standard P400 probe is acceptable for most air audits and installations. We offer P300 and P600 probes on request.

Accessories

VPA.5000.005

VPA.5001.105

VPA.5001.900

Cable, M12, 5 pole, for permanent connection


Interface box JB5 with 5 m/ 16.4 ft cable + 12 VDC power supply

Connector cap with M12 socket for VPFlowScope sensor module

VPFlowScope dP flow range table

SCHEDULE 40 STANDARD SEAMLESS CARBON STEEL PIPE								SCHEDULE 10 STANDARD SEAMLESS CARBON STEEL PIPE					
Size (inch)	DN	ID (inch)	ID (mm)	Min flow (scfm)	Max flow (scfm)	Min flow (m ³ _n /hr)	Max flow (m ³ _n /hr)	ID (inch)	ID (mm)	Min flow (scfm)	Max flow (scfm)	Min flow (m ³ _n /hr)	Max flow (m ³ _n /hr)
2	50	2.1	52.5	92	917	156	1,559	2.2	54.8	100	999	170	1,697
3	80	3.1	77.9	202	2,021	343	3,434	3.3	82.8	228	2,282	388	3,877
4	100	4.0	102.3	348	3,481	591	5,913	4.3	108.2	390	3,897	662	6,621
6	150	6.1	154.1	790	7,899	1,342	13,420	6.4	161.5	868	8,678	1,474	14,743
8	200	8.0	202.7	1,368	13,678	2,324	23,238	8.3	211.6	1,490	14,897	2,531	25,309
10	250	10.2	259.1	2,234	22,341	3,796	37,957	10.4	264.7	2,332	23,316	3,961	39,612
12	300	11.9	303.2	3,060	30,604	5,199	51,994	12.4	314.7	3,296	32,965	5,601	56,006
16	400	15.0	381.0	4,832	48,316	8,209	82,087	15.6	396.8	5,242	52,420	8,906	89,058
20	500	18.8	477.8	7,599	75,994	12,911	129,110	19.6	496.9	8,219	82,191	13,964	139,638


The ranges apply only to compressed air and nitrogen. Contact us for other gases. The field accuracy of an insertion probe is typically +/- 5% due to installation conditions. Insertion probes may not be used for official compressor testing.



'With the **VPFlowScope dP**, there is no more room for assumption.'

Get the complete picture!

Measure, monitor and manage your compressed air system to reduce your energy consumption. Our flow meters are used to establish baseline air flows and energy use. VPVision warehouses and analyzes flow data. It becomes the cornerstone of an energy management system for any plant seeking to sustain the energy efficiencies they have achieved.







VPFlowMate

The VPFlowMate can be used for point of use measurement and leakage management. It can also be used at the supply side, in small compressed air houses. We offer three types with different measurement ranges. All come standard with a yellow 2-line display, on which you can read the actual flow and totalizer simultaneously. The VPFlowMate is one of the first products we developed and has been on the market for more than ten years. It's the proven concept for compressed air and technical gas flow measurement.

VPFlowMate

- > Mass flow, total flow
- > Built-in 2-line display
- > Large measurement range

Applications

- > Demand side measurement
- > Point of use
- > Cost allocation
- > Leakage management

Specifications

VPFlowMate

Flow sensor

Measuring principle	Thermabridge™ Thermal Mass Flow
Flow ranges	See range table
Accuracy	<0.5% of full scale (when with ISO calibration and tubing kit)
Reference conditions	0 °C, 1013.25 mbar 32 °F, 14.65 psi
Gases	Compressed air, Nitrogen and inert, non condensing gases
Gas Temperature range	0 ... +50 °C 32 ... 122 °F
Pressure range	0 ... 16 barg 0 ... 232 psig
Humidity range	Up to 95% Relative Humidity, non condensing

Display

Technology	Liquid Crystal (LCD)
Back light	Yellow

Mechanical & environmental

Protection grade	IP65 NEMA 4, avoid direct sunlight and rain
Housing material	Aluminum, 2 component paint
Wetted materials	Epoxy, glass, stainless steel 316, anodized aluminum
Ambient temperature range	-10 ... +50 °C 14 ... 122 °F Higher ambient temperatures: consult factory
Corrosion resistance	Highly corrosive or acidic environments should be avoided

Electrical


Outputs	RS232, 4 ... 20mA (isolated), pulse (isolated)
Power supply	12 ... 24 VDC +/- 10 % Class 2 (UL)
Power consumption	< 100 mA. Peak power at start up may be 500mA, depending on actual flow and ambient temperature.
Connection type	M12 (8 pole)

Approvals/conformity


CE	EN 61326-1, EN 50082-1
UL/ CUL	14 AZ, Industrial Control Equipment

Technical drawings


VPF.R01K.M200



VPF.R060.M050



VPF.R200.M100



Order codes

Flow meters

VPF.R060.M050.D1
VPF.R200.M100.D1
VPF.R01K.M200.D1

Flow range

0.32 ... 60 m³_n/hr | 0.19 ... 35 SCFM¹
0.88 ... 200 m³_n/hr | 0.52 ... 117 SCFM
3.53 ... 1000 m³_n/hr | 2.08 ... 590 SCFM

Size

15 mm 1/2"
25 mm 1"
50 mm 2"

The complete solution, ready to install: VPFlowMate in-line, including display, 5 meter/16.4 ft M12 cable and ISO calibration report and tubing kit. Outputs: RS232, 4... 20mA and pulse.

Accessories

VPA.0000.100
VPA.0000.102

VPA.0000.005

VPA.0006.001

Power supply, with M12 connector, Real time read out via display.
JB1 interface box for PC connection via USB, includes 12V Power supply, USB converter, M12 connection cable 5 meter/ 16.4 ft.
Cable, 5 meter/ 16.4 ft, with M12 connector (8 pole) - on one side, open wires on other side. For permanent installation, connection with a compressor control panel, PLC, DCS system
USB PC connection cable for VPFlowMate

- 1 SCFM values are rounded off
- 2 All models supplied with BSP thread (straight).For US NPT, you can chase with die.

Dew point sensors

Maintaining the dew point of your air or gas system will prolong the lifetime of your equipment. Permanent monitoring enables you to detect and prevent problems on time.

VPInstruments' dew point transmitters are designed for ease of use, incorporating all the features needed to make installation and operation as simple as possible. The calibrated transmitters can be instantly incorporated into VPVision, or they can be connected to your air or gas management and control system.



Product highlights

- > 2-wire loop powered connection
- > Dew point or ppm moisture content
- > IP66 (NEMA 4X)
- > Excellent sensor protection
- > Fast response time

APPLICATION	DEW POINT	CONNECTION	ORDER CODES
extreme dry air moderate dry air	-100 ... +20°C -148 ... 68°F -40 ... +60°C -40 ... 140 °F	4 ... 20 mA 2 wire 4 ... 20 mA 3 wire	VPA.8000.1003 VPA.8000.1013

Specifications

VPA.8000.1003

VPA.8000.1013

Performance

Measurement range	-100 ... +20°C -148 ... 68 °F dew point	-40 ... +60°C -40 ... 140 °F dew point
Accuracy (dew point):	±2°C ±3.6 °F dew point	±2°C ±3.6 °F dew point
Response time	5 mins to T95 (dry to wet)	<10 sec typical (90% of the step change)

Electrical output/input

Output signal	4 ... 20 mA (2-wire) current source, configurable over the entire range	4 ... 20mA (3-wire)
Supply voltage	12-28VDC	8-30VDC
Current consumption	20mA max	9mA + load current
Supply voltage influence	±0.005% RH/V	±0.005 % RH/V

Operating conditions

Operating humidity	0 ... 100% RH	0 ... 95% RH (non-condensing)
Operating temperature	-40 ... +60°C -40 ... 140 °F	-30 ... +70°C -22 ... + 158 °F
Operating pressure	450 barg max.	20 barg maximum
Temperature coefficient	Temperature compensated across operating temperature range	±0.05 %/°C

Mechanical specifications

Ingress protection	IP65 NEMA 4	IP65 NEMA 4
Housing material	Stainless steel	Nickel-coated brass
Dimensions	L=132mm x ø27mm 5,2 x 1,1"	L=85mm, ø24mm (max) 3,3 x 0,9"
Filter	HDPE Guard <10 µm	HDPE front filter
Process connection	5/8" - 18 UNF	G1/2 (1/2" BSP)
Connection	DIN connector	2 m 6.5 Feet

Current sensors

The VLog-i measures AC currents up to 3200A (true-RMS on a single phase power cable). The VLog-i is very easy to use: just wrap around one of the three phases and close the snap fitting. It offers the best solution for your mobile power measurements. The VLog-i is the only sensor on the market that offers both 4 ... 20mA and pulse outputs.



Product highlights

- > Very easy and quick installation
- > Plug and play
- > For fixed and mobile measurements
- > Both 4 ... 20mA and pulse output
- > Loop powered

Usage

Easy does it: Just open the sensor and wrap around the power cable you want to measure. The LED on the device blinks when the VLog-i is powered. The rate at which it blinks is proportional to the output current. You can use one of the two outputs to get accurate measurement results.

Outputs

- 4 ... 20mA: The analogue output is proportional to the measured input and ranges from 4 to 20mA.
- Pulse: The pulse output generates a pulse frequency proportional to the current measured. This allows that the VLog-i can be used as a simple power meter.

Application examples:

- > Power consumption of compressors
- > General purpose power measurement
- > Electricity sub metering

The current sensor measures the input power of your compressor's electric motor. When combined with a flow meter, it can be used to determine the actual efficiency of the compressor.



Specifications

Accuracy	+/- 1% full scale.
Power supply	6 ... 30 Vdc
Power consumption	4 ... 20mA
Current input	100 ... 3200 A-rms (50Hz current)
Max Voltage	Insulated cables only! On open bus bars max 300 Volt
Pulse rate	0 ... 2.66 Hz
Coil length	170 mm 6.7", 250 mm 9.8", 350 mm 13.8"
Coil diameter	7 mm 0.28"
Coil bend radius	35 mm 1.38"
Housing W x H x D	26.7 x 41.4 x 13.6 mm 1.1 x 1.6 x 0.6 inch
Operation temperature range	-20 ... 70°C -4 ... 158 °F
Operational relative humidity	Max 95%, non condensing

ORDER CODES	MAX CURRENT - RMS	FREQUENCY	PULSES/AH	COIL LENGTH (MM)	INCH
VPA.8000.2100	100 A	50/60 Hz	10	170	6.7
VPA.8000.2200	200 A		10	170	6.7
VPA.8000.2400	400 A		10	170	6.7
VPA.8000.21K5	1500 A		1	250	9.84



Monitor

'If you monitor, you know
when, where and how
much you can save'



VPFlowTerminal

The VPFlowTerminal is a plug & play wall mount display with built-in power supply and 2 million point data logger. The VPFlowTerminal has five sensor inputs: one input for a VPFlowMate or VPFlowScope mass flow meter, and four generic analog inputs and can record up to 8 channels. This makes the collection and analysis of your compressed air data easier and quicker!

Product highlights

- > 2 Million data points
- > VPFlowMate / VPFlowScope input
- > 4 analog input channels

Applications

Efficiency: monitoring the efficiency of your compressor system. Measure with the VPFlowScope in the main pipe line of your system and measure with 4 power meters the power consumption of each compressor.

Air audits: the VPFlowTerminal can be used for air audits since you collect all data within one data logger. This makes the data collection, read out and analysis very convenient. Total package: Measure flow together with dew point, pressure and power consumption.

Order codes

For VPFlowTerminal

VPT.5110.000


VPFlowTerminal for VPFlowScope. Including display with built-in data logger. Pre-mounted connector for VPFlowScope. Built-in power supply. Includes Blac cap and 5 M / 33" for cable

VPT.5000.001 (option)

4 Analogue inputs for VPFlowTerminal. Data will be logged simultaneously. Configuration and read out with VPStudio.

Technical drawings


VPT.5110.00X



Specifications

VPFlowTerminal

Input voltage	100 ... 240 Vac mains (pre-wired)
Housing type	Painted Aluminum IP65 NEMA 4
Display	Liquid Crystal (LCD), 3 lines
Back light	Blue with auto power save.
Data logger	2.000.000 points.
Signal inputs	VPFlowScope + 4 optional 4 ... 20 mA sensors (non - isolated, loop powered)
Sensor power supply	24 VDC
Maximum sensor current	4 x 25 mA for analog sensors, 1 x 150 mA for VPFlowScope
Data outputs	USB for configuration and data retrieval
Ethernet interface	Modbus / TCP port
Basic configuration	Via key pad
Flow meter connection	M12, 8 pin
Additional connections	Cable glands for analog inputs, Ethernet connection.
Dimensions	l x b x h = 230 x 130 x 75 mm. 9.1 x 5.1 x 2.95"
Weight	1.6 kG 3.53 Lbs



VPStudio Software

With VPStudio, you can configure all VPInstruments products, view real time measurements and retrieve data log sessions. VPStudio enables you to view data in any unit both SI and Imperial. You can schedule your data log session, set logging intervals and adjust flow meter parameters. VPStudio communicates via your PC's USB port.



Applications

- > As configuration tool for all VPInstruments products
- > To read saved data log sessions
- > To extract recorded data to CSV files
- > Optional real time data logging on PC which can be saved as CSV

FUNCTIONS	FREE EDITION ¹	ADVANCED VPFLOWMATE	ADVANCED VPFLOWSCOPE	FULL / EVALUATION ²
Order codes		SFT.5003.200	SFT.5003.300	SFT.5003.400
Flowmeter configuration (all types)	✓	✓	✓	✓
Download data log sessions	✓	✓	✓	✓
Data Export	✓	✓	✓	✓
Real Time measurement VPFlowScope/VPFlowTerminal			✓	✓
Real time measurement VPFlowMate		✓		✓
Scheduler for display/VPFlowTerminal			✓	✓
CSV Studio		✓	✓	✓

¹ Free edition: basic configuration only

² Evaluation version is valid for one month from date of activation



Manage 'Beware of little expenses; a small leak will sink a great ship'

- Ben Franklin




VPVision

VPVision offers you the complete monitoring solution for compressed air and technical gases. It makes energy savings easy, quick, and rewarding. Using the latest web technology, VPVision enables you to view data anywhere, anytime. VPVision analyzes flow data and makes your savings potential transparent.

VPVision can be expanded to receive and consolidate data such as electric demand (compressor kW) and dew point. VPVision can also be fully integrated into a plant's existing SCADA system and linked to the Internet to allow access by designated company staff from anywhere.

Project approach

Although VPVision is a very user friendly software solution, preparation is key to a successful implementation. No compressed air system is the same. Therefore each VPVision system is customized to your needs and goals. Your return on investment can be a matter of months. With our VPVision project form, we can calculate the required investment and ROI. Ask your local distributor or go to our website for details.



With VPVision you can:

- > Maintain your efficiency
- > Allocate costs
- > Track and monitor leak level
- > Generate automated reports in PDF
- > Expand and adapt the system
- > Follow your system via IPad®, Smart PH, tablet and web browser
- > Centralize benchmark different plants on different locations.
- > Track Maintenance need points

Product highlights

- > Web based interface
- > Built in report tools
- > Early alert on leakage.
- > Direct insight in costs
- > Based on standardized hardware

VPVision project examples

Food production

In a Kikkoman soy sauce factory, a VPPVision system has been installed to monitor the demand side of the compressed air system. All individual cost centers are monitored by a flow meter. VPPVision logs all data and provides real-time feedback on actual use.

Cookie factory


Bolletje, a Dutch manufacturer of cookies and bakery products invested in a VPPVision system to allocate costs to various production lines. The system is linked to 3rd party energy monitoring and reporting software. VPPVision was part of a compressed air optimization project, which resulted in a cost reduction of 25%.

Steel factory

In a large steel plant, VPPVision is used to monitor 10 compressor stations. It guards a savings program which exceeds 250,000 Euro/ 300,000 USD per annum, and helps to make the right decision on where to save next.

Metal parts production

Astrum, a leading manufacturer of casted steel parts in the UK invested in a VPPVision system to monitor the overall compressed air supply and demand. The VPPVision system is part of a complete compressed air system re-design, with an ROI of less than 3 years.



Part numbers overview

The following table provides an overview of the available hardware and software. Please use the project preparation form, which can be supplied by your local distributor. This form is used to determine the complete list of required hardware and software for your project.

Order codes	
VPV.6001.M00	VPVision M. Main unit, with VPVision software, database, webserver, built-in power supply pre configured to display up to 8 VPFlowScope sensors. Can be read out on your own PDA, Tablet, PC or touch screen via the network. Powder coated steel enclosure, IP65.
VPV.HMI2.010	10" Panel mount touchscreen.
VPA.0030.100	Power supply module, built into IP65 plastic enclosure.
VPA.5030.020	Junction box for Modbus networks. Add one per VPFlowScope for a modbus RS485 multidrop network.
VPA.5030.011	Ethernet converter and power supply module (up to 8 VPFlowScopes), built into IP65 plastic enclosure, with space for optional ethernet module.
SFT.6001.M01	Additional measurement points implemented in the software. The software is designed to display up to 8 flow meters in a convenient way. Above 8, channels are grouped together. Ask us for a project specific quotation in this case.
SFT.6001.M02	Additional hardware Analog input module, 8 ports, 4 ... 20 mA. Add SFT.6001.M01 charge per channel.
SFT.6001.M06	Service Subscription for Monthly Report with energy savings tips for your system. Subscription for 5 years
SFT.6001.M05	Additional visualiation P&ID : overview of your compressed air system

Contact your local dealer for Job Sizing Template.



Install

'It all begins with proper installation'

Hot tap drill



The hot tap drill is the universal tool to install your insertion flow meter in any compressed air system. In only 30 minutes you can drill a hole and install your flow meter. Using a hot tap saddle and a hot tap drill, you can create a new installation point without depressurizing your installation. Compared to low-cost electrical hot tap drills, which are prone to jamming and breaking of the drill head, our hot tap drill is safe and easy to operate. See our instruction video for details.

Note: Hot tapping is a skilled task. Familiarize yourself with this task. VPInstruments also offers you training to become skilled. Once trained, you will be able to make process connections quickly, safe and economically. The average time to install is only 30 minutes.

Specifications	
VPA.8001.1002	
Max pressure	10 bar 145 psi, higher pressure ratings on request
Drill shaft diameter	16 mm 0.6 inch
Drill shaft length	345 mm 14 inch
Drill diameter	17 mm x M10 0.7 inch x M10

- Features:**
- > For application up to 10 bar
 - > 1" Hot tap drill size
 - > All accessories included
 - > Explorer® transport case included

Hot tap saddles

Hot tap saddles are available from DN44 to DN600 in the temperature range up to 70°C. For each installation point, you need the right saddle. The exact outer diameter is important to select the right saddle. For suitable hot tap saddles, ask the VPInstruments sales team. VPInstruments does not sell hot tap saddles into all countries. VPInstruments does not sell hot tap saddles into all countries. For specific countries, including USA, we can recommend local suppliers. Depending on local legislation, we will refer you to a local supplier. Order codes are available separately.

- Benefits:**
- > Make an installation point without taking the pressure of your system.
 - > Hand operated: no power tool needed on-site
 - > Safe and easy operation
 - > Versatile: For stainless and carbon steel



Specifications	
Carbon steel	
Fitting	1"
Saddle material	High grade Ductile Iron GGG 50, epoxy coated
Strap material	Stainless steel grade AISI 304
Gasket	NBR suitable for water and gas.
Temperature range	-30 ... 100°C -22 ... 212°F
Stainless steel	
Fitting	Fitting: 1"
Saddle material	Material: stainless steel grade AISI 304
Gasket	NBR suitable for water and gas.
Temperature range	-10 ... 70°C 14 ... 158°F

Thickness gauge



The ultrasonic thickness gauge is used to measure wall thickness, which is key information to calculate the exact inner pipe diameter.

It is important to know the exact wall thickness, especially in smaller pipes. In the table below, we show the influence of 1 mm | 0.04 inch error on your flow meter reading, for various pipe diameters.

Features:

- > Capable of performing measurements on a wide range of materials, including metals, plastic, ceramics, and glass.
- > High accuracy.
- > Integrated data logger.
- > One universal probe for a wide measuring range.
- > Includes transport case.

Disclaimer: The VP Thickness Gauge is only to be used to give an idea of wall thickness and not integrity or composition of the material.

DIAMETER (MM)	~INCH	ERROR (%)
50	2	4
100	4	2
150	6	1.30
200	8	1
250	10	0.80
300	12	0.70

Specifications

VPA.8001.1001

Measuring range (steel)	0.6 ... 400 mm 0.02 ... 16 inch (depending on probe type)
Accuracy	0.1 mm 4/1000"
Working temperature	-10 ... 50°C 14 ... 122 °F
Display	Back-lit display (128 x 64 pixel)
Connections	USB, probe
Power supply	2 x LR6 / AA - primary cell
Operating time	40 hours (backlight off)
Data logger	Max. 10,000 readings
Protection class Device	IP65 NEMA 4
Probe	IP67 NEMA 6P
Software	Software included, Windows

Leak Detector



The VP Leak Detector is a practical tool for any leak detection program. Simple to use - find compressed air leaks and prevent machinery failure with this unique instrument.

Leak detectors are a beneficial addition to mass flow meters for your leakage management program. The two instruments together make your leakage management system efficient. Measure and manage your ROI when repairing leaks. Use your flow meters to establish a leakage level before you repair the leaks and report the savings after.

The VP Leak Detector features a sensitivity dial with decibel indications. In addition, it features an LED bar graph display in which each LED equals approximately 3 dB - ideal for calculating decibel levels.

Application examples:

- > Compressed Air Leak Detection
- > Pressure and Vacuum Leak Detection
- > Exhaust system leaks
- > Tanks, pipes, Leak testing
- > Electrical Inspection

Order codes	
VPA.8000.1010	Ultrasound leak detector basic
VPA.8000.1011	Ultrasound leak detector start kit for air audits, with data logger

Specifications	
Construction	Hand-held ABS pistol type ultrasonic processor, stainless steel sensor enclosures
Peak frequency response	36-44 kHz
Indicator	10 segment LED Bar Graph (red)
Power	9 Volt Alkaline Battery
Low Battery Voltage Indicator	LED
Response time	Response time: 300 msec
Operating Temperature Range	0 ... 50 °C (32 °F ... 120 °F)
Relative Humidity	10-95% non-condensing at up to 30 °C (86 °F)
Dimensions	13.3 x 5 x 20.3 cm (5.25" x 2" x 8")
Weight	0.3 kg (11 oz)
Carrying Case	Nylon soft carrying case

Savings tips

1. Shut off sections and machines that you do not use

A simple manual or motorized valve can save you thousands of euros/dollars. Make sure that air is not lost through leaks or machines standing in idle mode. Flow meters help to determine to which sections air is flowing.

2. Breathe cool, fresh and clean air

A compressor converts 90% of its power into heat. The compressor room heats up, while a compressor uses less energy to compress cold air. 3°C cooler air, already results in 1% energy savings.

3. Invest in an efficient control system

Have insight in your compressed air usage profile, so you can optimize your compressor control system. Ask an air audit specialist to perform an air audit, and make an improvement plan based upon the results.

4. Think about the required air quality

Clean compressed air is important for the life span of your compressed air installation. Choose the right quality carefully for specific processes whenever possible, as higher air quality results in higher energy costs.

5. Reduce offload hours

Electricity consumption of a compressor in offload stage costs 10-35% of the consumption during load hours. At >80% use of the capacity, the offload-load control is considered efficient. Choose the right control system.

6. Manage your leakage

In general there is 20-40% of leakage in a compressed air installation. VPVision can be used as a global leakage management system and helps you to rank the leaks on savings potential. Invest in an ultrasound leak detector to find the leaks.

7. Balance your system

Is your compressor oversized? In some applications the compressor is bigger than necessary, for instance after changes in the production process. The payback time of the investment in a smaller compressor is often short.

8. Reduce the pressure

Every bar pressure reduction gives an instant win of 7% on your energy consumption. Invest in pressure regulators per production area, use buffer vessels and reduce pressure swings in your network.

9. Think of alternative uses

Compressed air is 8 times more expensive than electric power. However compressed air is often used, simply because it is present. The VPFlowScope offers insight in the usage and helps you to select the right solution.

10. Choose the right pipe size and material

A proper pipe system is crucial to limit your pressure drop. Iron pipes tend to rust. Too small piping creates pressure loss. Use angular feed-ins on the main header to reduce pressure loss.





Corporate Headquarters
Van Putten Instruments BV
Buitenwatersloot 335
2614 GS, Delft, The Netherlands


T +3115 2131580
F +3115 2130669
Email: info@vpinstruments.com

US Marketing & Sales office
T +1 740-862-0084
Email: sales@vpinstruments.us

© 2012-2013 Van Putten Instruments.

Subject to change without prior notice. All dimensions stated in drawings are indicative. For actual specifications, always consult factory. Our core intellectual property and brand names are protected by Dutch, US and international patents trademark rights, copyrights, and exclusive licenses. All artwork and 3D images in this catalog are copyright material and exclusively made for promotion of VPIstruments. Violators will be prosecuted to the maximum extent possible, by the respective owners. Nothing from this catalog may be re-printed or reused in any way without prior permission. Our general terms and conditions of sale apply on all sales transactions. A copy can be downloaded from our website.

VPIstruments only sell and distributes through authorized dealers
Your local dealer:



www.vpinstruments.com