PRODUCT SPECIFICATIONS Left & Right Corner (624WBCL/624WBCR) Radiant Wood Burning



INTERIOR DIMENSIONS

Front opening width: 36" Front opening height: 22-11/16" Rear wall width: 17" Firebox depth: 22-1/2"


TECHNICAL INFORMATION

Flue Series (Std.): "S" Series Double Wall Flue Size: 8" Inner; 11" Outer Clearance to Flue: 2" Firestop Framing**: 14-1/2" x 14-1/2" Minimum Flue Height: 13' Maximum Flue Height: 86' Minimum Height with 2 Elbows: 13' 8" Minimum Height with 4 Elbows: 21' Clearance to Fireplace: 1" (Back) 1/2" (Side) Minimum Hearth Size: 16" UL Design Certified ** Clearance reduces to 1-3/4"

FIELD INSTALLED ACCESSORIES

Glass Door: WB36LR (required and sold seperately) Outside Air Kit: AK4, FP4U, 403 Terminations (Std.): "S" Series SC, SCL, CF8, SQ8, LFSQT, SPC

Air Space 32' 16' 10" 23-1/2" FRAMING DIMENSION 23" TOP VIEW 38" 38" FRAMING DIMENSIONS 1/2" Air Space 8" 45 1/4 FRAMING 45" 42' 22 11/16" 30 3/8" 5 3/4' 34 3/4" 36" FRONT VIEW 23" 22"



Framing dimensions in illustrations accommodate 1/2" finishing material.



A Brand of Monessen Hearth Systems Co. 149 Cleveland Drive, Paris, Kentucky 40361 www.monessenhearth.com



To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. © 2007 Monessen Hearth Systems Co.