

PRODUCT SPECIFICATIONS REVEAL (ILDV) Direct Vent Insert System



GLASS VIEWING AREA

25 1/4"W x 16 3/16"H (409 Square Inches)

TECHNICAL INFORMATION

Max. Btu Input: 30,000 BTU/HR

FE Ratings (Cdn. Fireplace Efficiency): 71.9% NG/ 83.7% LP

Afue Efficiency: 66% NG/ 69% LP

Thermal Efficiency: Up to 88%

CSA Design Certified

FIELD INSTALLED ACCESSORIES

Surrounds: Bevelled & Colonial in Iron Age & Black Texture

Clean face design

Natural Flame™ burner with fiber ceramic log set





Cottage Clay firebrick

Thermostat blower (160 cfm) standard

3" flue outlet

18" flex line with On/Off shut-off valve

CSA design certified



A Brand of Monessen Hearth Systems Co.
149 Cleveland Drive, Paris, Kentucky 40361

www.monessenhearth.com



To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. © 2007 Monessen Hearth Systems Co.