

# GHX-10

**User Manual** 

Version 2.2

Compliant with GHX-10 Firmware version 1.4.0 and Doremi Universal Interface version 4.0.2

# **Table Of Contents**

1	Introduction	5	5
	1.1 Contact Information	5	5
2	GHX-10 Overview	6	3
	<ul> <li>2.1 GHX-10 Description</li></ul>	6 6 7	\$ \$ 3
3	GHX-10 Front Panel Controller	9	)
	<ul> <li>3.1 Menu Items Overview.</li> <li>3.2 Input Menu.</li> <li>3.3 Output Menu.</li> <li>3.1 Color Space.</li> <li>3.4 Image Menu.</li> <li>3.5 Sync Menu.</li> <li>3.6 Audio Menu.</li> <li>3.7 OSD Menu.</li> <li>3.8 System Menu.</li> <li>3.9 Status Menu.</li> </ul>	9 10 11 14 14 15 15 17 18 18	)   L + 5 5 7 8 8
4	Infrared Remote Controller	19	)
	<ul> <li>4.1 Remote Controller Overview.</li> <li>4.2 Remote Controller Functions.</li> <li>4.3 Quick Input Format Setting.</li> <li>4.4 Output Format Setting</li></ul>	19 20 21 21 21 21	)     !
5	Doremi Universal Interface Software (duis)	.22	<u>&gt;</u>
	<ul> <li>5.1 Doremi Universal Interface Software Installation.</li> <li>5.2 Doremi Universal Interface Software Overview.</li> <li>5.3 Settings Window.</li> <li>5.4 Tabs Description.</li> <li>5.4.1 Input Tab.</li> <li>5.4.2 Output Tab.</li> <li>5.4.3 Image Tab.</li> <li>5.4.4 Sync I/O Tab.</li> <li>5.4.5 Audio Tab.</li> <li>5.4.6 OSD Tab.</li> <li>5.4.7 System Tab.</li> </ul>	22 24 25 26 26 26 26 27 28 29 30 31	215557 8001
6	Firmware Update	32	2
	<ul><li>6.1 USB Update</li><li>6.2 SD Memory Update</li></ul>	32 32	2
7	Annex A: Specifications	.33	3
	7.1 Inputs 7.2 Outputs	33 33	3

	7.3 Audio	. 33
	7.4 Video	. 34
8	Acronyms	. 35
9	Document Revision History	.36

### Software License Agreement

The software license agreement can be found at the following location: <u>http://www.doremilabs.com/support/proav-support/proav-warranties/</u>

# Hardware Warranty

The hardware warranty can be found at the following location: <u>http://www.doremilabs.com/support/proav-support/proav-warranties/</u>

#### HDMI

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.

# **1** Introduction

This document provides guidance on how to use the GHX-10 device. It explains the front panel, the infrared remote control, and the Doremi Universal Interface usage. It also details how to upgrade the firmware on the GHX-10.

# 1.1 Contact Information

If in need of help or assistance, please contact Doremi Labs Technical Services at **+ 1-818-562-1101** or email at proavsupport@doremilabs.com.

# 2 GHX-10 Overview

# 2.1 GHX-10 Description

The GHX-10 is a Universal Cross Converter that incorporates High-Definition Multimedia Interface technology, and SDI connectors that allow for any input to be converted to any output format or scan rate. It supports both SD and HD video and employs high quality 12 bit bi-cubic interpolation to ensure the highest quality picture. The GHX-10 can tackle many conversion tasks. It can be used as a computer DVI to HD-SDI converter (using a DVI to HDMI® adapter cable), HDMI resolution converter, or as an HD video up-converter or down-converter. It supports up to 8 channels of AES, HDMI and SDI audio. A two lines LCD display and scroll wheel simplify navigation through the GHX-10's menus.

# 2.1.1 GHX-10 Front Panel

This is a snap shot of the front panel:



Figure 1: GHX-10 Front View

An LCD screen is available in the middle of the front panel to facilitate controlling the GHX-10 without using the On Screen Display.

The scroll wheel with built in Select button and the ESC button can be used to navigate the menu structure and setup the unit.

The four LED indicators reflect the status of the various input signals:

- SDI-A LED
- SDI-B LED
- HDMI LED
- SYNC LED

The "PWR" LED lights up when the GHX-10 is powered ON.

The infra-red sensor can be used to remotely control of the GHX-10, see Section 4.

A SD Memory connector is available and can be used to perform firmware update.

### 2.1.2 GHX-10 Rear Panel

Below is a snap shot of the GHX-10 rear panel:



Figure 2: GHX-10 Rear Panel

The rear panel has the following connectors:

Connector	Description	
USB USB connector		
HDMI in	HDMI input connector	
HDMI out	HDMI output connector	
SDI-A out	SDI output connector – Link A	
SDI-B out	SDI output connector – Link B	
SDI-A in	SDI input connector – Link A	
SDI-B in	SDI input connector – Link B	
SYNC in	Sync input connector	
SYNC out	Sync output connector	
AES-12 in	AES audio input connector for audio tracks 1 and 2	
AES-12 out	AES audio output connector for audio tracks 1 and 2	
AES-34 in	AES audio input connector for audio tracks 3 and 4	
AES-34 out	AES audio output connector for audio tracks 3 and 4	
AES-56 in	AES audio input connector for audio tracks 5 and 6	
AES-56 out	AES audio output connector for audio tracks 5 and 6	
AES-78 in	AES audio input connector for audio tracks 7 and 8	
AES-78 out	AES audio output connector for audio tracks 7 and 8	

# 2.2 Supported Formats

The table below summarizes all supported inputs and outputs available on the GHX-10.

Suppor	ted Input(s)	Supported Output(s)		
SD-SDI: NTSC, I	PAL	SD-SDI: NTSC, PAL		
HD-SDI: all HD + 274, SMPTE296	2K formats (SMPTE , SMPTE372)	HD-SDI: all HD +2K formats (SMPTE 274, SMPTE296, SMPTE372)		
HDMI/DVI:		HDMI/DVI:		
640x480	= VGA	640x480	= VGA	
720x480i	= 480i	720x480i	= 480i	
720x480p	= 480p	720x480p	= 480p	
1440x480i	= 480i	720x576i	= 576i	
720x576i	= 576i	720x576p	= 576p	
720x576p	= 576p	800x600	= SVGA	
1440x576i	= 576i	1280x720	= 720p	
800x600	= SVGA	1024x768	= XGA	
1280x720	= 720p	1366x768	= WXGA	
1024x768	= XGA	1280x1024	= SXGA	
1280x768	= WXGA	1400x1050	= SXGA+	
1364x768	= WXGA	1680x1050	= WSXGA+	
1366x768	= WXGA	1920x1080i	= 1080i	
1536x768	= 1536x768	1920x1080p	= 1080p	
1152x864	= XGA+	1920x1200	= WUXGA	
1280x960	= SXGA-			
1280x1024	= SXGA			
1364x1024	= 1364x1024			
1400x1050	= SXGA+			
1680x1050	= WSXGA+			
1920x1080i	= 1080i			
1920x1080p	= 1080p			
2048x1080	= 2Kp			
1600x1200	= UXGA			
1920x1200	= WUXGA			

# 3 GHX-10 Front Panel Controller

Throughout this chapter "press Select" refers to pressing the front panel scroll wheel button of the GHX-10 – see Figure 1.

### 3.1 Menu Items Overview

Press "Select" to enter the GHX-10 menu system then turn the "Wheel" to access the different menus:

- Input
- Output
- Image
- Sync
- Audio
- OSD
- System
- Status

Press "Select" to navigate one of the above menu items and access the list of available submenus. Browse the list of available sub-menus by turning the "Wheel", then press "Select" to change settings of a given sub-menu.

Browse the available values by turning the "Wheel". To choose the desired value, press "Select". The selected value should be flagged with the # sign on its right which is the current setting indicator.

To go back to a higher level in this menu tree, press on the "ESC" button – Keep pressing it to exit the menu system.

The following tables list all GHX-10 setup parameters, items in bold are factory defaults. All video formats show frame rates and not the field rates, so 1080i-60 fields per second will be shown as 1080i-30 frames per second.

# 3.2 Input Menu

Sub-Menu	Value	Description
Interface	<b>SDI</b> HDMI/DVI Pattern	Input interface setting. Pattern produces a color pattern with 16 channels of audio at different frequencies
SDI Color	Auto RGB RGB ext YCbCr 601 YCbCr 601 ext YCbCr 709 YCbCr 709 ext XYZ'	SDI input color setting. Auto: Single Link (1.5Gbps) inputs will be treated as 601 (SD) or 709 (HD). Dual link (1.5Gbps) inputs will be treated as RGB. Ext: designates extended color range (full bandwidth) as opposed to limiting the color spectrum to comply with ITU standards.
HDMI/DVI color	Auto RGB RGB ext YCbCr 601 YCbCr 601 ext YCbCr 709 YCbCr 709 ext	HDMI/DVI input color setting Auto: Detected using meta-data, if not present the default is RGB Ext: designates extended color range (full bandwidth) as opposed to limiting the color spectrum to comply with ITU standards.
Default EDID	720p 50 720p 60 1080i 25 1080i 30 1080p 50 <b>1080p 60</b> WUXGA 50 WUXGA 60	DVI input default setting. When you feed a signal to the HDMI input, the GHX-10 has to report a native resolution over EDID. This menu allows the user to change the default resolution of the GHX-10 between the available formats. <u>CAUTION</u> : You must disconnect HDMI/DVI source before changing this setting.

# 3.3 Output Menu

This menu can be used to s	etup the output parameters.
----------------------------	-----------------------------

Sub-Menu	Value	Description
Interface	HDMI/DVI SDI	Set the active output. For common video formats, both outputs can be active simultaneously
SDI color	Auto RGB RGB ext YCbCr 601 YCbCr 601 ext YCbCr 709 YCbCr 709 ext XYZ'	Set the SDI output color mode Auto: 601 (SD) 709 (HD), RGB (2K) "ext" designates extended color range (full bandwidth) as opposed to limiting the color spectrum to comply with ITU standards.
SDI Resolution	NTSC PAL 720p <b>1080i/sf</b> 1080p 2Kp 2Kp Flat Match Input	Set the SDI output pixel resolution. Match Input: In this mode, the SDI output will have the same resolution as the input source.
SDI Frequency	23.98 24 25 <b>29.97</b> 30 47.95 (1080p only) 48 (1080p only) 50 (720p & 1080p only) 59.94 (720p & 1080p only) 60 (720p & 1080p only) Match input	Set the SDI output frame rate Match Input: In this mode, the SDI output frame rate will be equivalent to the input source
SDI Force Interl	<b>Off</b> On	Force the SDI output to interlaced (or Segmented Frame)

Sub-Menu	Value	Description
Ancillary out	Off	Off: No VANC on SDI output
	Bypass SDI	Bypass SDI: Pass Ancillary data from SDI input to SDI output
HDMI/DVI color	Auto RGB RGB ext YCbCr 601 YCbCr 601 ext YCbCr 709 YCbCr 709 ext	Set the HDMI/DVI output colors Auto: RGB unless otherwise communicated over EDID. "ext" designates extended color range (full bandwidth) as opposed to limiting the color spectrum to comply with ITU standards.
DVI Resolution	Auto         VGA         SVGA         XGA         WXGA         SXGA         SXGA+         WUXGA         480p         480i         576p         576i         720p	Set the DVI output pixel resolution. Auto: In this mode, the unit will read the default resolution of the connected monitor using EDID and sets the output to match Match Input: In this mode, the unit will set the DVI output resolution to match the input resolution – or to the closest output resolution if the exact input resolution is not available. VGA= 640x480 SVGA= 800x600 XGA= 1024x768 WXGA= 1280x800
	1080i 1080p Match input	SXGA= 1280x1024 SXGA+= 1400x1050 WSXGA+= 1680x1050 WUXGA= 1920x1200

Sub-Menu	Value	Description
DVI Frequency	Auto	Set the DVI output frequency .
	23.98 24 25 29.97 30 47.95 48 50 59.94 60 Match input	This list shows all possible frequencies but the GHX-10 menu will only show the allowed frequencies for the DVI output format selected. Auto: In this mode, the unit will read the default frequency of the connected monitor using EDID and sets the output to match Match Input: In this mode, the unit will set the DVI output frequency to match the input resolution.
	Match input *2	Match input *2: The output is set at double the input frame rate.
Color Depth	Auto 8 bits 10 bits 12 bits	Set the color depth <u>Note</u> : If the input is 10bit and the output is set to 8bit for example, the GHX-10 will dither (NOT truncate)
Time Code	Off <b>Bypass SDI</b> Free wheel	Off: No embedded timecode on SDI output Bypass SDI: Pass embedded timecode from SDI input to SDI output Free wheel: Generate embedded Time Code starting at the moment this option is enabled.

#### 3.3.1 Color Space

The ITU-R BT.709-5 (HD formats) and ITU-R BT.601-5 (SD formats) Standards define the range of color values in a digital signal to be:

- 16 to 240 for 8bit coding
- 64 to 960 for 10bit coding

The GHX-10 color space conversion supports these standards, but it also supports full range by allowing the color values to be between:

- 0 to 255 for 8bit coding
- 0 to 1023 for 10bit coding

On the GHX-10 the full range modes are designated by the "ext" following the color space conversion mode.

#### 3.4 Image Menu

This menu can be used to	setup the image	parameters.
--------------------------	-----------------	-------------

Sub-Menu	Value	Description	
Brightness	0% to 100% default <b>50%</b>	Brightness value setting	
Contrast	0% to 100% default <b>50%</b>	Contrast value setting	
Scaling	One to One	Scaling value setting	
	Aspect Ratio Fill	Aspect Ratio: Maintain input aspect ratio	
	Aspect Fit H Aspect Fit V	Fill: Scale to fill the output resolution	
		Aspect Fit H (V): Scale Horizontally (Vertically) to fill the output resolution	
		One to One: No Scaling	
Deinterlacing	Off	Set the Deinterlacing mode	
	On Motion	Motion: Deinterlacing is based on motion.	
SD Ratio	4:3 Analog	The pixel aspect ratio for standard	
	4:3 Digital	definition signals is not square and it depends on the material used.	
	16:9 Analog	Choose the proper pixel SD ratio	
	16:9 Digital	based on the source material.	

Sub-Menu	Value	Description
Input LUT	User Defined 0.1 to 4.0 default <b>1.0</b>	Set the Gamma Curve from 0.1 to 4.0 or choose User Defined to use a custom LUT table uploaded using Doremi Universal Software Interface
Output LUT	User Defined 0.1 to 4.0 default <b>1.0</b>	Set the Gamma Curve from 0.1 to 4.0 or choose User Defined to use a custom LUT table uploaded using Doremi Universal Software Interface

# 3.5 Sync Menu

This menu can be used to setup the sync parameters.

Sub-Menu	Value Description	
Input	Auto	Sync input setting
	SDI HDMI/DVI	Auto: Sync is derived from the input source
	Extern	Extern: Sync is derived from the Sync Input connector.
Output	Auto	Sync output setting
	Force Bi-Level	Auto: Tri-Level for HD and 2K formats and Bi-Level for SD formats.
H offset	X pixels default 0	Horizontal Sync offset in pixels
V offset	X lines default 0	Vertical Sync offset in lines

# 3.6 Audio Menu

This menu can be used to setup the audio parameters.

Sub-Menu	Value	Description
Input	Auto SDI DVI/HDMI AES	Audio input format setting Auto: Audio input is the same as video input
Delay	X frames default 0	Audio delay setting from -1 to +2 frames

Sub-Menu	Value	Description	
Level	-18, -12, -6, <b>0</b> , +6, +12, +18 dB	Audio Output level setting	
HDMI Channel out	Auto 2 4 6 8 Off	Set the HDMI audio output mode Auto: All audio inputs will be present on the HDMI output 2, 4, 6, 8: Total number of audio channels to be present on the HDMI output Off: No audio on HDMI output	
SDI Out Groups	Auto 1 1+2 1+2+3 1+2+3+4 Off	Set the embedded SDI active audio groups Auto: All audio inputs will be present on the SDI output Each group has 4 audio channels, when 1+2+3+4 is selected, all 16 audio channels will be present. Off: No embedded audio on SDI output	
Swap Audio Channels 3 and 4	On Off	Channels 3 and 4, commonly used for sub-woofer and central channel can be swapped if needed.	

# 3.7 OSD Menu

This menu can be used to setup the OSD parameters.

Sub-Menu	Value	Description		
OSD Enable	<b>Yes</b> No	Enable or disable On Screen Display		
OSD timeout	X s (seconds) <b>default</b> 30s Infinite	On Screen Display timeout in seconds. Set to Infinite to keep it always on.		
OSD H Position	1% to 99% default 25%	OSD horizontal position in percentage		
OSD V position	1% to 99% default 25%	OSD vertical position in percentage		
OSD Status The OSD Status will show the burn-in window timecode, I/O status and audio levels when the menu OSD is not active. OSD Status Position can only be set using the Doremi Universal Interface Software	Off TC BIW Input Status Output Status	Burn In Window and Status display - Off: BIW and Status not displayed - TC BIW: Timecode is shown in a burn-in window on the GHX output - Input Status: In addition to the BIW timecode, the GHX output will display the Input Status including Audio levels, Closed Caption presence, Input Format and CRC errors (flashing red dot) - Output Status: In addition to the BIW timecode, the GHX output will display the Output Status.		
OSD/TC Color	White/Black W/B Zoom Black/White B/W Zoom	Burn In Window type setting		

# 3.8 System Menu

This menu allows to access the system parameters.

Sub-Menu	Description
Save	Save current settings to flash.
	Select to Save, when you get the "?" Select again to confirm, you should see "#"
Firmware: v.x.y	Firmware version
Serial: zzzzzz	Serial number
License: uuuuuuuu	License number
Temp: vv C	Temperature (in degree Celsius)
Standby	Standby mode. Put the unit in Power Down mode
Auto Standby <b>Off</b> , 60minutes, 120minutes	Auto Standby mode. Set the idle time duration before the unit goes in power down mode automatically
IR 0 to F <b>default is 0</b>	Infra-Red. To avoid IR interference when you have multiple GHX units, you can assign each a different IR code from 0x0 to 0xF (16 total). You need to set the DIP switch on your Doremi IR remote accordingly.
MicroSD or SD Memory update	Depending on your unit, you might see "Micro SD" or "SD Memory" firmware update

# 3.9 Status Menu

This menu can be used to view the Input and Output status.

Sub-Menu	Description
In: Out:	Input and Output format status information

# 4 Infrared Remote Controller

The buttons on the IR remote are used to access the unit while observing the On Screen Display (OSD). Left and Right arrows are used to navigate between menus and sub-menus. Select is to make a selection, Exit is to go one level up or exit the menu structure.



# 4.1 Remote Controller Overview

#### Figure 3: Infrared Remote Controller

The remote controller is divided into Four different areas:

- RESET/IR Lock buttons
- Navigation or Menu System
- Input Format
- Output format

# 4.2 Remote Controller Functions

Remote Control	Function
Input format selection	Select HD-SDI, SDI, HDMI/DVI (through the DVI- D/HDMI button) or Pattern
	Note: The DVI-A button is not used.
"IR Lock" button	Not used
"RESET" button	Not used
"Menu" button	Invoke the Menu System. Pressing this button on the IR is similar to pressing the scroll button on the GHX-10 front panel
"Exit" button	Back one menu level. Similar to Front Panel ESC button
Output format area	Set the SDI or HDMI/DVI output resolution to: HDMI/DVI: Auto, 720p, 1080i, 1080p, 1024x768, 1280x768, 1366x768, 1280x1024, 1920x1200 SDI: 480i, 576i, 720p, 1080i, 1080p
"Up Arrow" button	Not used
"Down Arrow" button	Not used
"Left Arrow" button	Navigate left. Similar to Wheel counter clockwise
"Right Arrow" button	Navigate right. Similar to Wheel clockwise
"Select" button	Ok/Select, Similar to Select on Front Panel
"InRes" buttons	Force the output resolution to match the input resolution. There is one for SDI and one for HDMI/DVI
"InFPS" buttons	Force the output frame rate to match the input frame rate. There is one for SDI and one for HDMI/DVI
"Scaling" button	Navigate between the available scaling options
"De-Int Filter" button	Toggle De-interlacing Filter ON or OFF
"Status OSD" button	Toggle on screen display ON and OFF
"Save" button	Save settings
OUT-HDM	Set the output interface to HDMI/DVI
OUT-SDI	Set the output interface to SDI

# 4.3 Quick Input Format Setting

To select the input format, press one of the buttons available at the top of the remote controller.

Press one of the available input formats



#### Figure 4: Quick Input Format Setting

You have the choice between: SDI, HDMI (using the DVI-D/HDMI button) and Pattern. The "Pattern" button will generate color bars with 16 channels of audio at different frequencies.

Note: The DVI-A button is unused.

# 4.4 Output Format Setting

Since not all formats are common between SDI and HDMI/DVI, the output interface must be selected.

- If the output interface is set to SDI and if the selected output format is a valid HDMI resolution, both SDI and HDMI outputs will be active with proper colors on both outputs. This is due to the presence of a dedicated color space converter on the HDMI output.
- If the output interface is set to DVI (HDMI) and if the selected output format is a valid SDI resolution, both HDMI and SDI outputs will be active but the SDI output colors might be wrong. This is due to the presence of a dedicated color space converter on the SDI output (this might change in future releases).

#### 4.4.1 HDMI/DVI Output Format

To set the output format to a specific HDMI/DVI format, press "OUT-HDM" on the IR controller, then press the corresponding output format: Auto, 720p, 1080i, 1080p, 1024x768, 1280x768, 1366x768, 1280x1024, 1920x1200. More formats are available through the menu system.

#### 4.4.2 SDI Output Format

To set the output format to a specific SDI format, press "SDI-OUT" on the IR controller, then press the format you want to set: 480i, 576i, 720p, 1080i, 1080p. More formats are available through the menu system.

# **5** Doremi Universal Interface Software (duis)

### 5.1 Doremi Universal Interface Software Installation

To install the Doremi Universal Interface software, follow the steps below:

- 1. Plug the provided USB cable between the GHX-10 and an available USB port on your PC see Figure 2 for USB connector location
- 2. Power on the GHX-10 by pressing the PWD button
- 3. If you get the "Found New Hardware Wizard" window at this stage, click "Cancel"
- Run the installation package by double-clicking on a file like "Doremi\_Universal\_Interface\_Software-4.0.2.0.exe" which can be downloaded from our web site: <u>http://www.doremilabs.com/</u>.
- 5. After the installation is over, if you get the "Found New Hardware Wizard", go through all the steps shown below:
  - Step 1: Select the "No, not this time" option and click on "Next >"



Figure 5: "Found New Hardware Wizard" Window - Step 1

• <u>Step 2</u>: When asked for software installation, choose the option "Install the software automatically (recommended)"



Figure 6: "Found New Hardware Wizard" Window – Step 2

• <u>Last step</u>: Wait for the driver installation to be completed. Click on the "Finish" button when done.



Figure 7: "Found New Hardware Wizard" Window – Last Step

• Run the Doremi Universal Interface GUI and verify that you have a proper connection by looking at the "Devices" tab which should show the Model and Serial numbers.

**<u>Note</u>**: If you get the following message during the installation:



#### Figure 8: Hardware Installation Warning Window

• Click on the "Continue Anyway" button.

**Note**: If during the automatic installation you get a message asking you to search for a specific file,

- Hit cancel then uninstall duis.
- While the GHX-10 unit is still connected, go to the Device Manager > Universal Serial Bus Controllers and uninstall Doremi GhX Board.
- Install duis again and recycle power on the GHX-10 which should take you back to Step 1 or Step 2 above.

## 5.2 Doremi Universal Interface Software Overview

The Doremi Universal Interface Software (duis) consists of a GUI that can control one or more GHX-10 device(s) connected to your workstation through USB.

When starting the Doremi Universal Interface, the following GUI should appear:



Figure 9: duis – Input Tab

This GUI is composed of the following parts:

- The "Devices" section: Can be used to select one connected GHX-10 from the drop down menu click on the "Refresh" button to be sure all the connected GHX-10 units are visible.
- The "Information" section: Provides information about the input and output interfaces and resolutions, the current timecode and the audio input level of the connected GHX-10 device.
- The "Control" section: Has tabs that can be used to view or modify various settings on the connected GHX-10 unit: Input settings, Output settings, Image settings, Sync I/O settings, Audio settings, OSD (On Screen Display) settings and System settings. These tabs are presented in Section 5.4.
- The "Settings" window located on the left of the GUI: Can be used to manage the settings files (loading, saving, importing, exporting etc ...). This "Settings" window is presented in the Section 5.3 below.

### 5.3 Settings Window

The "Settings" window can be used to manage settings files

• To save the current duis settings into a file, enter a settings filename in the top left corner field as shown in below, then click on "Save".

The saved settings file should appear in the "Settings" window:

	Doremi_Universal_Interface_Software - Master	• X	
	Eile Logs Help		
	Settings         Devices           Settings_1         Image:		
"Settings file" saved	SDI2HDMI         Input :         SDI 1080p 29.97           Imput :         SDI 1080p 29.97         Imput 22.38:55:15           Output :         DVI WUXGA 60		
"Settings files"	Input       Image       Image       Sync I/O       Audio       Image       System         Output selection :       Image		
	SDI HDM//DVI		
"Load" button	HDMI Output Settings     HDMI Output Settings     HDMI Output Settings     HDMI Output Settings     Resolution : 1080     Frame rate : 29.97     Frame rate : 60	•	
"Save" button	Save Color: Auto Color: Auto	•	
"Delete" button	Bypass		
"Import" button	Export Color Depth		
"Export" button	Update		
"Update"			
button			

Figure 10: duis – Settings Section

- To export this saved "settings file" so you can use it for another GHX-10 device, select it in the "Settings files" area see figure above and click on the "Export" button. You should be asked to confirm where you want to export this file using a standard "Save as" dialog box.
- To import an existing "settings file" from a .ghx file to the connected unit click on the "Import" button. Then browse the files to select the appropriate "settings file" you want to import. The imported file should appear in the "Settings files" area on the left part of the GUI. To apply the settings to the connected GHX-10 unit, you need to select this file then click on the "Load" button. The GHX-10 settings should be updated.
- To delete a settings file present in the "Settings files" area see figure above select it and click on the "Delete" button.
- Click on the "Update" button to update the "Settings" window to reflect the content of the "User Settings" folder of the duis (folder where all the settings files are stored).

### 5.4 Tabs Description

### 5.4.1 Input Tab

The input tab is presented in Figure 9 above. All parameters are explained earlier in this manual in the chapter titled "GHX-10 Menu".

#### 5.4.2 Output Tab

Below is a screen shot of the "Output Tab":

ettings	Devices	
Settings_1 Filename	0. Doremi GHX 10 SN : 01000202 🕥 🕢 Refresh	
SDI2HDMI	Input : SDI 1080p 29.97 Timecode Input Audio	1
Settings_1	Output : DVI WUXGA 60	
	🛄 Input 🕎 Output 🔀 Image 🛷 Sync I/O 💿 Audio 🔤 OSD 📀 System	"Output selection"
	Output selection :	window
	SDI HDM/DVI	"HDMI/DVI of selection"
•	- SDI Output Settings	window
👔 Load	Frame rate : 29.97 V Frame rate : 60 V	
Save	Color: Auto  Color: Auto  Color: Auto	
Delete	Timecode mode : Bypass Anciliary Data	
Import	Color Depth	"OD! 1
🖕 Export	Auto	selection"
Update		window

Figure 11: duis – Output Tab

#### 5.4.3 Image Tab

This is a screen shot of the "Image Tab":

duis Doremi_Universal_	Interface_Software - Master	
<u>File Logs H</u> elp		
Settings Settings_1	Devices           0. Doremi GHX 10 SN : 01000202	Brightness
Settings_1	Input :         SDI 1080p 29.97         Timecode         Input Audio           Output :         DVI WUXGA 60         22.47.39:00         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0         0	related "Reset" button
	Image	Brightness cursor
		Contrast cursor
Load	Scaling	
Save	Aspect Ratio     Image: Constraint of the second seco	
Import	C User Gamma Curves	
Update		

Figure 12: duis – Image Tab

### 5.4.4 Sync I/O Tab

Below is a screen shot of the "Sync I/O Tab":

duis Doremi_Universal_I	interface_Software - Master	×
<u>File Logs</u> <u>H</u> elp		
Settings_1 Filename	Devices           Image:	
SDI2HDMI	Input :         SDI 1080p 29.97         Timecode         Input Audio           Output :         DVI WUXGA 60         22:47:59:14         Image: Control of the second	- "Input Sync Reference" window
	Image	
	Auto Mode     C HDMI/DVI     C SDI     C Extem     C Force Bi-Level	"Output Sync
	Sync Voffset	window
Load	Sunc Hoffset	"Sync V offset" cursor
Save	0 pixels	
- Delete		"Sync H offset" cursor
Export		
Update		

Figure 13: duis – Sync I/O Tab

#### 5.4.5 Audio Tab

This is a screen shot of the "Audio Tab":

duis Doremi_Universal_I	Interface_Software - Master
<u>File Logs H</u> elp	
Settings_1	Devices           Image: Contract of the second seco
SDI2HDMI	Input :         SDI 1080p 29.97         Timecode         Input Audio           Output :         DVI WUXGA 60         22:48:13:19         Image: Control of the second
	🌉 Input 🛛 🔤 Output 🚘 Image 🛛 🛷 Sync I/O 🛇 Audio 🖉 OSD 🔯 System
Load Load Save Delete planet Export	Audio Input Source Audio Mode AES SDI HDMI/DVI HDMI Channels Audio Swap Audio Groups : Auto HDMI Channels Audio Swap Swap audio channels 3 and 4

Figure 14: duis – Audio Tab

#### 5.4.6 OSD Tab

Below is a screen shot of the "OSD Tab":

Settings Settings_1	Devices           Image: Contract of the second seco	
Filename /	Input :         SDI 1080p 29.97         Timecode         Input Audio           Output :         DVI WUXGA 60         22:48:26:12         Image: Control of the second	
	Image	"OSD Timeouť cursor
↓ →	OSD Vertical Position	
Save	OSD Horizontal Position 25 % 50 %	
Export	Status Window BIW Type : Black  BIW TC : Off	

Figure 15: duis – OSD Tab

All parameters are explained earlier in this manual in the Section 3 titled, "GHX-10 Front Panel Controller."

The Status Window Vertical and Horizontal positions are available only through duis. They set the position of the Status OSD window that shows only when the main OSD is off and the Status OSD is ON.

#### 5.4.7 System Tab

This is a screen shot of the "System Tab":



Figure 16: duis – System Tab

All parameters are explained earlier in this manual in the Section 3 titled, "GHX-10 Front Panel Controller."

In addition this tab can be used to perform the following actions:

- To save the current settings to flash, click on the "Save Settings" button
- To restore the factory default settings, click on the "Restore Default Settings" button
- To enter a new license number, click on the "Enter New License Number ..." button and type the new license number in the pop-up window.
- To perform a firmware upgrade, click on the "Firmware upgrade (Current: x.yy)" button note that this button provides the current firmware version installed on the connected unit, after "Current: ". On the above picture, the current firmware is version 1.2.15 for example. See Section 6.1 for detailed upgrade steps to follow.
- To display the logs, click on the "Display Logs" button. A window containing the logs will appear. Select "Auto Update" from that window to see all messages.

# 6 Firmware Update

The firmware can be updated through USB or SD Memory. This section presents both methods. In case you miss one of the files listed in the procedures below, please contact Doremi Labs (see Section 1.1).

# 6.1 USB Update

The firmware can be updated through USB using the Doremi Universal Interface Software as presented in Section 5.4.7.

To perform such update, follow the steps below:

- 1. Connect the GHX-10 to your computer using the USB cable provided with the unit,
- 2. Start the Doremi Universal Interface Software see Section 5
- 3. Go to the "System Tab" see Section 5.4.7
- 4. Click on the "Firmware upgrade" button
- 5. Select the firmware file (e.g: "ghx\_firmware\_1.3.11.bin") and click on the "Upgrade now" button

86)/DoremiLabs/Doremi_Universal_Interfa	ace_Software/Firmwares/ghx_firmware_1.3.11.bin	Browse
		0%
Please do not turn the unit off u	ntil the upgrade process is over.	

Figure 17: Firmware Update Window

6. Once the update is completed, re-cycle power on the GHX-10 unit. Newer GHX-10 models recycle power on their own.

# 6.2 SD Memory Update

The SD Memory must be formatted as FAT or FAT32.

This is the update procedure:

- 1. Copy the firmware file (e.g: "ghx\_firmware\_1.3.11.bin") on the SD Memory card
- 2. Plug the SD Memory into the SD port of the GHX-10 (see Figure 2).
- 3. Power On the GHX-10 and go to the menu "System" see section 3.8
- 4. Select the "SD Memory update" sub-menu.
- 5. Select the file you want to use for the update using the menu scroll wheel, see Figure 1 and confirm the update.
- 6. Once the update is completed, re-cycle power on the GHX-10 unit. Newer GHX-10 models recycle power automatically.

# 7 Annex A: Specifications

### 7.1 Inputs

- HDMI without HDCP
- Single or Dual Stream HDSDI (For dual stream HDSDI, the two inputs must comply with SMPTE Standard S372M, i.e., genlocked with no more than 2 to 3 pixels of difference)

# 7.2 Outputs

- Single or Dual Stream HDSDI
- Single HDMI Output without HDCP

# 7.3 Audio

- 16 channels of audio supported embedded in HDSDI
- 8 channels using HDMI
- 8 channels of AES audio de-embedded
- Audio delay can be set from the GUI, front panel or IR Remote Control -1 to +2 frames

# 7.4 Video

Suppor	ted I	nput(s)	Supported Output(s)
SD-SDI: NTSC,	PAL		SD-SDI: NTSC, PAL
HD-SDI: all HD (SMPTE 274, SI SMPTE372)	+2K MPT	formats E296,	HD-SDI: all HD +2K formats (SMPTE 274, SMPTE296, SMPTE372)
			HDMI/DVI:
640×480	_	VGA	640x480 = VGA
720×480i	_	VGA 480i	720x480i = 480i
720x480n	_	480n	720x480p = 480p
1/202480p	_	480p 480i	720x576i = 576i
720x576i	_		720x576p = 576p
720x576n	_	576n	800x600 = SVGA
1440x576i	_	576j	1280x720 = 720p
800×600	_	SVGA	1024x768 = XGA
1280x720	_	720n	1366x768 = WXGA
1024x768	_	XGA	1280x1024 = SXGA
1280v768	_	WXGA	1400x1050 = SXGA+
1364x768	_	WXGA	1680x1050 = WSXGA+
1366x768	=	WXGA	1920x1080i = 1080i
1536x768	_	1536x768	1920x1080p = 1080p
1152x864	=	XGA+	1920x1200 = WUXGA
1280x960	=	SXGA-	
1280x1024	=	SXGA	
1364x1024	=	1364x1024	
1400x1050	_	SXGA+	
1680x1050	=	WSXGA+	
1920x1080i	=	1080i	
1920x1080p	=	1080n	
2048x1080	=	2Kp	
1600×1200	=	UXGA	
1920x1200	=	WUXGA	

# 8 Acronyms

Term	Definition
DVI	Digital Visual Interface
HDMI	High-Definition Multimedia Interface
HD-SDI	High Definition Serial Digital Interface
IR	Infra Red
OSD	On Screen Display
SDI	Serial Digital Interface

# 9 Document Revision History

Date	Version	Description
10/31/2008	1.0	First version.
11/10/2008	1.2	Editorial changes.
12/11/2008	1.3	GHX Control Panel GUI documented.
04/09/2009	1.4	All sections revised.
04/10/2009	1.5	All sections revised.
09/09/2010	1.6	All sections revised and modified. Old images updated to reflect current version of the Doremi Universal Interface Software. New picture of the IR Doremi remote updated.
10/22/2010	1.7	Section 3.6.1 added to reflect supported audio sample rates.
03/02/2011	1.8	New pictures added.
03/04/2010	2.0	Updated to comply with GHX-10 firmware version 1.4.0 and Doremi Universal Interface version 4.0.2.
07/26/2012	2.1	Logo updated and contact information added.
02/12/2013	2.2	Minor revisions made to Section 1 and Section 2.1.