

Makita®

18V LXT LITHIUM-ION ANGLE IMPACT DRIVER

COMPACT RIGHT ANGLE IMPACT DRIVER FOR FASTENING AND LOOSENING IN TIGHT SPACES

Makita Built Motor and Impact Mechanism Produces 531 in. lbs. of Maximum Torque and 0-3,000 IPM

Variable Speed (0-2,000 RPM) for a Range of Applications from Auto Repair to Cabinet Installation

Large Conveniently Located Paddle Switch for Comfortable Operation

Over One Foot of Tool Extension for Extra Reach Into Deep Tight Spaces

L.E.D. Light Illuminates the Work Area


Soft Grip Handle Provides Increased Comfort on the Job

POWER



Makita built motor and impact mechanism produces 531 in. lbs. of torque and 3,000 IPM

CONVENIENCE



Compact angle head design for use in close quarter applications

COMFORT



Large conveniently located paddle switch for comfortable operation

INNOVATION



LXT battery and optimum charging system produces 430% total lifetime work

LXT
LITHIUM-ION

Models
BTL061
BTL061Z

18V POWER.
12V WEIGHT.™

POWER DRIVING IN TIGHT SPACES

18V LXT LITHIUM-ION ANGLE IMPACT DRIVER

Models BTL061 / BTL061Z

FEATURES & BENEFITS

- Compact right angle impact driver for fastening and loosening in tight spaces
- Makita built motor and impact mechanism produces 531 in. lbs. of maximum torque and 0-3,000 IPM
- Variable speed (0-2,000 RPM) for a range of applications from auto repair to cabinet installation
- Large conveniently located paddle switch for comfortable operation
- Over one foot of tool extension for extra reach into deep tight spaces
- L.E.D. light illuminates the work area
- Soft grip handle provides increased comfort on the job
- Convenient belt clip mounts on either side of the tool
- Phosphorescent bumper ring for locating tool in dark work areas
- LXT Lithium-Ion battery provides longer run time, 5x lower self-discharge (for use any time) and 16 firm holding contact terminals (for constant high power)
- 30-Minute Rapid Optimum Charger communicates with the battery's built-in chip throughout the charging process to optimize battery life by actively controlling current, voltage and temperature
- 3-year warranty on tool and 1-year warranty on battery & charger




STANDARD EQUIPMENT

- Tool belt clip and screw (324705-1 and 251314-2)
- Contractor bag (821007-X)
- 2 ea. 18V LXT Lithium-Ion 3.0Ah battery (BL1830)
- 30-Minute Rapid Optimum Charger (DC18RA)
- Plastic battery cover (450128-8)

SPECIFICATIONS

Hex shank	1/4"
No load speed	0 - 2,000 RPM
Blows per minute	0 - 3,000 BPM
Max torque	531 in.lbs.
Lithium-Ion battery	18V DC (3.0Ah)
Overall length	15-1/4"
Net weight (w/ battery)	3.7 lbs.
Shipping weight	12.4 lbs.
Master carton quantity	2
UPC	(BTL061) 088381-085250 (BTL061Z) 088381-085236



Model BTL061



Model BTL061Z



OPTIONAL ACCESSORIES

- Straight attachment (192440-7)
- Ratchet attachment (192439-2)
- 17 piece bit set (T-00153)
- 28 piece bit set (T-00169)



192440-7



192439-2



T-00153



T-00169

For a complete listing of Makita tools and accessories please refer to the Makita General Catalog, or visit our website at makitatools.com, or call 1-800-4MAKITA.

All specifications subject to change without prior notice. All models and accessories subject to stock on hand.
NTF-1107-5M MA-0897-07 For more information, call 1-800-4MAKITA or visit makitatools.com



Makita U.S.A., 14930 Northam St., La Mirada, CA 90638