

SPECIFICATIONS

WRIGHT SENTAR[®] SPORT™



Cutting Width	36"	42"	48"	52"
Cutting Height Range	1.0 - 5.0	1.0 - 5.0	1.0 - 5.0	1.0 - 5.0
Deck Lift System	Rapid-Hite™	Rapid-Hite™	Rapid-Hite™	Rapid-Hite™
Deck Construction Heavy-Duty Commercial Fabricated	7 Gauge	7 Gauge	7 Gauge	7 Gauge
Blades (1/4" thick, high-lift wings)	(2) 18"	(2) 21"	(2) 16.5"	(3) 18"
Blade Tip Speed (fpm at 3584 rpm)	19,000	19,000	19,000	19,000
Spindles 1" Shaft with precision ball bearings	Cast Iron Housings	Cast Iron Housings	Cast Iron Housings	Cast Iron Housings
Blade Clutch/Brake Maintenance-Free; Rated Heavy Duty	Warner™	Warner™	Warner™	Warner™
Discharge Systems	Side, Rear & Mulch			
Makes Available	Kawasaki™	Kawasaki™	Kawasaki™	Kawasaki™
Horsepower	17, 19	17, 19	19	19
Cylinders	2	2	2	2
Starting	Electric	Electric	Electric	Electric
Hour Meter	Included	Included	Included	Included
Ammeter	n/a	n/a	n/a	n/a
Operator Controls	Quad Lever™	Quad Lever™	Quad Lever™	Quad Lever™
Hydro Pumps	10 cc	10 cc	10 cc	10 cc
Fuel Capacity	6.4 Gal.	6.4 Gal.	6.4 Gal.	6.4 Gal.
Drive Tires	18 x 8.0 x 10			
Caster Tires	11 x 4.0 x 5			
Speed Forward (mph)	7.5	7.5	7.5	7.5
Speed Reverse (mph)	4.3	4.3	4.3	4.3
Overall Length	63"	66"	58.5"	59.5"
Overall Width - Deflector Up (Down)	37" (48")	42.5" (62.5")	49" (59")	53" (64")
Dry Weight	710	720	750	790

RAPID HITE DECK LIFT



RUBBER CHUTE DEFLECTOR



REINFORCED DISCHARGE



TWIN 10cc PUMPS



Warranty 2-year Limited Warranty: Covers parts and labor. For further details, see your local Wright dealer. To find the name of your nearest dealer, please visit www.wrightmfg.com.

COMING SOON TO A WRIGHT DEALER NEAR YOU!

For more information, call 1.301.360.9810 or find our dealer locator at www.wrightmfg.com.

THE WRIGHT WAY TO MOW.

