



CyberPower®

Model #: CP825LCD

UPC: 649532018253

MSRP: \$114.99

The Intelligent LCD Series CP825LCD UPS is ideal power protection for individuals running a stand-alone PC in their home, or office.

Real-time system vitals can be viewed from the Intelligent Crystal-Blue LCD display, and the unit can be conveniently mounted in a workstation cabinet or directly on the desktop. LCD diagnostics include: Input Voltage Level, Output Voltage Level, Battery Capacity, Runtime, Load Level, On Battery, Overload, Wiring Fault, and Silent Mode.

It also includes PowerPanel PE™ Power Management software, which monitors the vitals of the UPS and will safely shutdown your system in case of a power outage. Composite integrated circuitry offers advanced lightning protection and also guards against surges, spikes, sags, brownouts and other power abnormalities. This rugged unit is equipped with a RJ11/45 port which protects against surges from phone, modem, network, and broadband disruptions.

The small footprint design is ideal for horizontal or vertical placement, and is even designed for wall-mountability. An HID-compliant USB port allows for connectivity with both PC and Mac systems. The unit is also perfect for protecting other electronics such as monitors, printers, scanners, speakers, fax machines, CD/DVD players, and iPods.

Cyberpower guarantees this product for 3-years, and has a \$225,000 connected equipment guarantee.

- **Intelligent LCD Diagnostic Display:** The innovative front panel LCD can be used to display detailed information on the UPS status and current power conditions. The LCD displays 9 different diagnostics: Input voltage level, Output voltage level, Battery capacity, Runtime estimate, Load level, On battery, Overload, Fault Condition, and Silent mode.
- **EMI/RFI -** Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or “humming” that occurs over telephone lines or stereo electronics.
- **Transformer-spaced Outlets -** Widely spaced outlets allow you to conveniently add large transformer-based plugs without compromising the utility of other outlets.
- **USB Connectivity -** An HID-compliant USB port enables full integration with built-in power management and auto shutdown features of Windows, Linux, and Mac OS X.
- **PowerPanel PE™ Smart Management Software –** In event of a power outage, PowerPanel PE saves your open files and will “Hibernate” your PC to increase the run-time on the UPS unit. PowerPanel is quickly and easily installed on any Windows-based PC and is designed to utilize minimal system resources. Diagnostic screens give immediate visuals of the UPS’s status, and also include the following features: Silent operation mode, configurable system notifications, automatic self tests, adjustable high/low voltage warnings, event/data logging, and scheduled shutdowns.
- **LED Indicators -** LED status lights indicate Power-On and wiring faults.
- **Audible Alarms -** Audible tones identify when the unit is running off battery power, unit overloads, and low battery.
- **Convenient Mounting –** Multiple mounting options: horizontal, vertical, cabinet, and wall.
- **Resettable Circuit Breaker -** Convenient unit reset switch in case of an overload.
- **3-year Warranty -** CyberPower will replace damaged units if within 3 years of purchase date. We stand behind our products and guarantee quality. CyberPower also offers a #1 rated technical support team that will assist you with product, installation, or warranty concerns --- Free of Charge!
- **ISO & Safety Certifications -** All CyberPower manufacturing facilities are ISO-9001 Quality Tested. Our products are also certified by the FCC, cUL, and UL.
- **Windows Vista™ compatible -** Our Power Management software has been fully tested and is compatible with Windows 200x, Server, XP, and Vista.

Technical Specifications

General	
Model #	CP825LCD
UPS Topology	Standby
Input	
Voltage	90 - 140V
Frequency	57 - 63Hz
Plug Type	NEMA 5-15P
Cord Length	6 ft
Output	
VA	825
Watts	450
Automatic Voltage Regulation	No
On Battery Waveform	Simulated Sine Wave
Outlets - Total	8
Outlets - Battery & Surge	4 x NEMA 5-15R
Outlets - Surge-Only	4 x NEMA 5-15R
Transfer Time	4 ms
Battery	
Runtime at Full-Load	2 Minutes
Runtime at Half-Load	8 Minutes
Battery Specification	1 x 12V/8.5Ah
Surge Protection and Filtering	
Surge Suppression	1030 Joules
Phone / Ethernet RJ11 / RJ45	1 x RJ11/45 Combo (One-in/One-out)
Coax Protection RG6	None
Management & Communications	
Indicators	LED Indicators
USB Port	1 x HID Compliant
Serial Port	None
Software	PowerPanel Personal Edition
SNMP / HTTP Remote Monitoring	Not Available
Physical	
Dimensions (WxHxD)	11" x 6.5" x 3.5"
Weight	13.5 lbs.
Warranty	
Product Warranty	3-year warranty. Free Tech Support.
Connected Equipment Guarantee	Lifetime
CEG Amount	\$225,000