



3C1100 – COBB Nissan VR38 1000cc Fuel Injector Kit
2008+ Nissan GT-R



WARNING

A vehicle modified with COBB products will not always meet the legal requirements for operation on public roads and highways. It is the purchaser's responsibility to check and comply with all local, state and federal laws prior to operating vehicle. Installation and use of performance products may also affect and void warranty and insurance policies. In general, COBB performance products carry no warranty. COBB Tuning Products, LLC shall not be liable for direct, indirect, incidental or consequential damage or injury to persons or property that might be claimed as a result from the installation, improper installation, and failure of part including claims.

DISCLAIMER

We recommend the COBB fuel injectors are installed by a knowledgeable and experienced certified mechanic. If attempting the installation yourself, please refer to the factory service manual for the correct removal and installation instructions. Be sure to release any pressure in the fuel system before disassembly. After installation, be sure to check for fuel leaks by priming the fuel system **BEFORE STARTING THE ENGINE**. Be sure not to use matches, lighters, or any other source of fire or spark when working with fuel. If working on a car within a residential garage, be sure to turn off gas water heater or gas drying machine pilots before any fuel spills occur. COBB is not responsible for any damages, injuries, or any other accidents during the installation of or as a result of the installation of these fuel injectors.

COBB has teamed up with Injector Dynamics to supply these injectors that are precision matched to work specifically with the COBB Accessport and the COBB OTS maps for COBB Staged Power Packs. Of course the injectors can be used with any other ECU solution as well. Please review the data on the following page for suggested map changes in Accesstuner Race and Pro. COBB's OTS maps for the Accessport are available for download at cobbtuning.com. Choose the appropriate OTS map for your COBB Power Package and flash the map in before starting the vehicle (and after checking for fuel leaks of course). Or visit your local COBB Tuning Retail Store or a certified COBB Pro-Tuner for custom dyno tuning. Thanks for the purchase and happy tuning!

Suggested changes for COBB Accesstuner Pro software @ 3 bar fuel pressure:

Fuel – Injector Scalar for E10 = 965

Fuel – Injector Scalar for E85 = 690

Fuel – Injector Latency Offset = 1.11

Fuel – Economy Display Injector Size for E10 = 965

Fuel – Economy Display Injector Size for E85 = 690

If you have any questions on injector scaling or latency, please do not hesitate to contact the COBB Nissan Expert Group at gtr.experts@cobbtuning.com or contact our Customer Service Representatives at 866.922.3059 between the hours of 9AM and 6PM Monday through Friday.