

Pill Splitter, Pill Pulverizer Pill boxes and Pill Timer

These easy tools are ideal for elderly people, children and hospital attendants. Great also for medicating pets. They avoid dispersion of medicine and guarantee integrity of the dose. Easy to clean, also in dishwasher. Made in non-toxic, unbreakable material. Packed in single cardboard box with instruction sheet.

Code 25731 PILL PULVERIZER

Powerful pulverizing point powders pills of any shape and size, with an easy twist of the wrist.

minimum order: 6 pcs.









Code 25734 WEEKLY PILL-BOX - white colour - 7 compartments Supplied with a set of labels for each day in 6 languages: English, French, German, Italian, Portuguese, Spanish. minimum order: 24 pcs.

Code 25735 DAILY HANDY PILL BOX - yellow colour With 6 compartments. Packed in a cardboard box.

Drugs of Abuse, Urine and Oral Fluid Tests in few minutes



GIMA retains all rights of reproduction, in whole or in part, of this catalogue, and, by law, no reproduction by third parties may be made without the prior written consent of the Company. Owing to its policy of continuous product development, GIMA reserves the right to amend specifications without notice.

HEALTH-CARE - PHARMACY

Thermofocus[®] professional "no contact" Thermometers



THERMOFOCUS THERMOMETERS

The most advanced thermometers in the world! Thermofocus read infrared radiation from the surface of the skin to accurately calculate the core body temperature.

- without touching: never in contact to avoid any risk of

- non invasive: do not require patient collaboration, advised for

- accurate: a sophisticated microprocessor warrants high precision

- economic: no need of expensive probes
- few seconds: time for pointing and reading temperature
- 1°C-55°C (25571 only): for measurement of vast range of objects

- body temperature scan (25571): can be done quickly Code 25570 THERMOFOCUS - mod. 0700 - forehead Totally hygienic, without touching. Simply hold the thermometer close to the center of the forehead and release the activatig button. It can also be used to take the temperature of objects such

Code 25571 THERMOFOCUS - mod. 1500 - multi-use For the professional user or family that requires maximum accuracy and flexibility of temperature taking. Same as code 25570 with an additional button to allow the user to read the ambient temperature and the one of other areas of the body as well as objects within a range from 1 to 55°C (33.8 to 131°F). Code 32200 "AAA" BATTERIES

> A patented optic-aiming system allows to immediately find correct distance for measurements.

Contact Thermometer

Code 25583 IR CONTACT THERMOMETER -**Code 32212 SPARE BATTERY** Innovative new system of taking fever: just place it near forehead and scan temperature. Fully meet "ASTM" standards in measurement accuracy (22 °C to 42.2 °C \pm 0.3 °C).All other features and technical specifications are same as code 25580. Packed in deluxe carton box. Just place on forehead no need of probe covers

25583

25583





HEALTH-CARE - PHARMACY



Oval, Prismatic, Rectal and Coloured thermometers



Code 25600 OVAL THERMOMETER °C Individually packed in plastic case. minimum order: 12 pcs. Code 25601 OVAL THERMOMETER - dual scale °C and °F Code 25602 OVAL THERMOMETER °C Same as 25600 but made in Germany. High quality.



Code 25605 COLOURED CLINICAL THERMOMETERS Oval °C thermometers in 5 colours: green, blu, lilac, yellow, red with transparent plastic case, and same colour cap. minimum order: one box of 10 pcs.



Code 25590 PRISMATIC THERMOMETER °C - oral Individually packed in plastic case. minimum order: 12 pcs.

Code 25592 RECTAL THERMOMETER °C Individually packed in plastic case. minimum order: 12 pcs.

Code 25606 PRISMATIC THERMOMETER °C - oral Same as code 25590, but made in Germany. High quality.



Code 25610 ECOLOGICAL OVAL THERMOMETER °C Precise, non toxic and ecological, with gallium instead of mercury. Glass structure, individually packed in plastic case. Made in Germany minimum order: 10 pcs.

STREP-A rapid test, accurate results in 5 minutes



Cardiac Marker rapid test: Myoglobin+Ck-Mb+Troponin I



FOB-Fecal Occult Blood Test for early detection

Code 24530 FOB TEST - box of 25 tests Provides accurate results in few minutes. It facilitates patient treatment decision early. Simple procedure, easy to perform and interpret. No additional equipment required. It includes 25 pcs of collection stick, device test and one buffer bottle.

pack) and 20 droppers



One-Step Test for Prostate Screening - PSA

Code 24533 PSA TEST - box of 40 tests - (∈ - for doctor/hospital use Provides accurate results in few minutes, it can be performed by doctors or directly by the consumer at home.

- Over 98% correlation to lab tests
- Simple, easy to use whole blood test
- Detects PSA as low as 4ng/ml
- Contains everything needed to perform test



Visual Strips for self Test Glucose and Cholesterol

Code 24520 GLUCOSE STRIPS - box of 30 pcs. Code 24521 CHOLESTEROL STRIPS - box of 2 pcs. A new, convenient, CE marked line of strips for visual reading of cholesterol and glucose in whole blood. No meter is needed to measure the results. The special color chart allows an easier comparison of the colors for a better quantification of the result. Cholesterol is offered in a 2 tests/ tube package inclusive of fingertips, color chart and instructions for use.

Glucose is offered in a 30 tests/tube package inclusive of colour chart and instructions for use. Box and instructions in English, German, Italian.





GIMA

Cholesterol, Triglycerides and Glucose pocket monitor

Code 23950 MULTICARE

Unique diagnostic device for self-check of glucose, cholesterol and triglycerides.

Multi-parameter technology allows to measure, with the same reflectometer, different parameters simply changing kind of strips: in fact, there is a chip in each pack of strips that is specific for each analyses. Regular measuring of these three parameters **to prevent cardiovascular pathologies** is important if we consider that intolerance to glucose, hyper-cholesterolemia and hypertriglyceridemia are three of the principal cardiovascular risk factors, along with the age, obesity, lifestyle, smoking and arterial hypertension. Multicare is supplied in carton box with a nylon bag, 25 glucose strips, lancet device, 25 lancets and user manual.

Spare strips for MULTICARE

codeSpare strips for WEETTCARE23955Glucose strips - tube of 25 strips + 1 chip23956Glucose strips - tube of 50 strips + 1 chip23957Cholesterol strips - tube of 5 strips + 1 chip23958Cholesterol strips - tube of 25 strips + 1 chip23959Triglycerides strips - tube of 5 strips + 1 chip23960Triglycerides strips - tube of 25 strips + 1 chip



	Technical Specifications		
Measuring range:	25-500mg/dl (1.4-28 mmol/l)	Batteries:	2 batteries
Display:	LCD		Cr 2032 3 Volts
Temperature:	10-40°C	Size:	48x105x22 mm
Memory:	255 test results with date and time	Weight:	70 g

Easv sample

application with capillary action

Glucose Monitor for daily diabetes testing

Advanced technology glucose monitors available in two versions. For each model is available the unit only or the complete kit that includes 15 strips, code chip, control solution, 15 sterile lancets, lancet device, clear cap (for testing on forearm or palm), carrying case, user manuals in English, Italian, French and Greek (Spanish, Portuguese on request), logbook.

		Tech	nical Specifications					
	Measuremen	t Range 8 n	mmol/L (20 to 600 mg/dL)					
	Sample Sites	Finger tips, Forearm or palm						
	Sample Size	1μ	Ĺ					
	Test Time	Ap	proximately 10 seconds					
	Power Sourc	e On	e 2032 or equivalent 3.0V coin cell battery					
	Battery Life	e 12 months or approximately 1,000 tests						
	Memory 2	to 300 records with time and date						
	2	.3900/1 Las	Last 30 results, no averaging, no date/time					
	Meter only Complete kit Glucose monitor and consumal							
	Meter only	Complete kit	Glucose monitor and consumables					
_	ĩ							
	23900 23905	Complete kit 23901 23906	Glucose monitor EZ Glucose monitor Plus					
	23900	23901	Glucose monitor EZ Glucose monitor Plus Glucose Strips - box of 25 strips					
	23900 23905	23901	Glucose monitor EZ Glucose monitor Plus Glucose Strips - box of 25 strips					
	23900 23905 23910	23901	Glucose monitor EZ Glucose monitor Plus					
	23900 23905 23910 23912	23901	Glucose monitor EZ Glucose monitor Plus Glucose Strips - box of 25 strips Glucose Strips - box of 50 strips					
	23900 23905 23910 23912 23914	23901	Glucose monitor EZ Glucose monitor Plus Glucose Strips - box of 25 strips Glucose Strips - box of 50 strips Control Solution					

- Biosensor technology - 10 second test time - only 1 μl blood sample



Safety Automatic Lancets Lancets and Lancet Device

website)

ONE-STEP SAFETY AUTOMATIC LANCETS Multi purpose capillary blood sampling devices for all testing requirements.

The one-step safety lancet is easier to use, no arming is required, and safer, once lancet is used it is rendered inoperable. High-speed delivery and penetration method minimizes patient pain and operator error. Latex-free, hypo-allergenic.



One-Step Safety Automatic Lancets								
GIMA code	Туре	Depth of penetration	Gauge	Blood Flow	Finger Stick	Glucose	Hematocrit	Minimum order
24513 24515		1.0 mm 2.2 mm	G26 G22	5-10 μl 20-40 μl	•	•	•	box of 100 box of 100



HEALTH-CARE - PHARMACY

Portable Whole Blood Test System

	•
Code 24000 BLOODLAB - instrument only Code 24002 BLOOD BASIC - same as code 24000 but without LIPID PANEL readings. Code 24001 BLOODLAB - complete system A powerful diagnostic tool to test for blood chemistry parameters while your patient is in the office. Lipid panel test: Lipid profile determination (15 multitest strips) of Total Cholesterol, HDL Cholesterol, Triglycerides, calculated LDL Cholesterol and TC/HDL ratio 6 single tests: Total Cholesterol, HDL Cholesterol, Triglycerides, Creatinine, Glucose, Ketones. Accurate, convenient, fast	CE 24001
- Clinical Laboratory accuracy and precision	GIMA Bloodlab accessories
- Results in 2 minutes or less	code Diootnab accessories
- Internal memory for 400 results	24004 Lipid Panel (total cholesterol, HDL cholesterol,
- Two button easy-to-use device	triglycerides, calculated LDL chol. and TC/HDL ratio)
- Performs both panel and single tests	- box of 15 test strips (not for 24002)
- No refrigeration required for strips 24000	24005 Total Cholesterol 100-400 mg/dL - box of 25 test strips
Technical Specifications	24006 HDL Cholesterol 25-85 mg/dL - box of 25 test strips
Size: 76x145x25 mm Weight: 122 g	24007 Triglycerides 50-500 mg/dL - box of 25 test strips
Strip storage: at less than 30° C (room temperature)	24008 Glucose 20-600 mg/dL - box of 25 test strips
Battery operated: 2xAAA 1.5 V, alkaline - life for 300 tests FDA, CE, CLIA professional approved Made in USA	24009 Ketones 2-70 mg/dL - box of 25 test strips
TDA, CE, CEAT protessional approved Made in USA	24010 Creatinine 0.2-10 mg/dL - box of 25 test strips
Standard accessories of system kit (24001)	24015 Thermal Printer (18x9x14 cm - 1 kg - 100-240 V)
The man set has 50 minutes $(1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,$	24016 Roll of 500 labels
Transport bag50 micropipettes6 total Cholesterol strips	
Plexiglass workstation 50 blood lancets 6 HDL Cholesterol strips	24017 Micropipettes $15 \mu l$ - box of 50 pcs.

Urine analysis System with printer and urine strips



Code 24050 URINE LAB Code 33250 PRINTER PAPER - box of 5 rolls

Urine Lab is a small urine test strip reader with modern CCD measurement technology and many features that facilitate daily routine operations. To be used with urine strips 24062 only. Manual in English, German, Italian.

Technical Specifications

	reclinear Specifications
Measurements	: 40 meas./hour in convenient mode 120 meas./hour in fast mode
Memory:	500 measurements with date and time
Display:	2 x 24 character LCD-Display
Printer:	Low noise thermal printer with paper roll for more than 300 meas.
Printout:	Current number measurement, Date and time, Serial No. of the
	meter, patient-I-D, Asterisk on pathological results, Parameters
	can be printed in SI-units, Conventional units and arbitrary units
Accuracy:	Meter adjustment in 5 levels according to individual requirements
Instrument of	check: 2 control strips for check of calibration of urine lab (included)
Power supp	ly: 100-240 V, 50-60 Hz



Code 24060 URINE STRIPS - 3 parameters - tube of 100 strips - Glucose - Protein - pH

Results can be read directly on the strip (after about 60 seconds) and compared with the label on the bottle. Supplied in metal tube in single carton box. This product is made in EC Manual in English, French, Greek, Italian, Spanish,

Portuguese. Dutch and German available on request.

Code 24061 URINE STRIPS - 10 parameters - tube of 100 strips

- Same as code 24060 with 10 parameters.
- Leucocytes

- Protein (albumin)

NitriteUrobilinogen

- pH

- Specific gravity
- Ketones (acetoacetic acid)
- Bilirubin

- Blood

- Glucose

Code 24062 URINE STRIPS - 11 parameters - tube of 150 strips Same as code 24061 plus one parameter: ascorbic acid Results can be read on the strips or printed through code 24050.

Centrifuges for Plasma and Microhematocrit

Code 24030 ULTRA 8 CENTRIFUGE Strong and very stable plasma centrifuge made of aluminium alloy. Ideal for routine separation of blood, urine and other fluids. Provided with a variable speed selector at fixed speeds (800, 1500, 1800, 3300 rpm) and a 30 minutes timer. It includes holder to accomodate 8 tubes, any size, from 15 ml to 3 ml. Impact resistant



Technical Specifications
Nominal RCF: 1327 g
8 tube capacity (2-15 ml)
Maximum volume 120 ml
Safety off switch in lid
On/Off indicator light
Plastic rotor husing
Clear Locking lid
Power: 220 volt
Weight: 7 Kg
Dimensions: 330x330xh260 mm

Code 24035 XC-2000 CENTRIFUGE Very silent plasma centrifuge with 6 tube positions, provided with electronic counter to allow precise speed setting from 1000 rpm to 4000 rpm (500 rpm increments). It is supplied with holder for 6 tubes of 10 ml and holder for 6 tubes of 15 ml. Operating time is adjustable from 1 to 60 min. Strong ABS structure.



Code 24040 TEST TUBE 10 ml box of 100 pcs

Technical Specifications					
Power Supply:	220V - 50hz				
Power:	80 W				
Speed: Approx	1000-4000 rpm (increased in				
	increments of 500 rpm's)				
Time:	1-60 min				
Capacity:	15 ml or 10 ml x 6				
Max. RCF:	1790 g				

pieces

Code 24025 MICROHEMATOCRIT CENTRIFUGE - 180 sec.

Economic system, easy to use, fully automatic with led indicators, no vibration, silent, rapid and provided with rechargeable battery.

Useful for: small labs, office labs, blood drawing areas, pediatric, neonatal settings, dialysis centers, emergency room labs, veterinarians, sample prep for stat chemistries.



Saliva Alcohol Strips

Code 24502 SALIVA ALCOHOL TEST STRIPS - box of 25 GIMA Saliva Alcohol Test Strip is a rapid highly sensitive test for the determination of relative blood alcohol concentration in saliva specimens.

- Results in just 2 minutes
- Color chart provides approximate relative blood alcohol
- concentrations (BAC) from 0.02% to 0.30%
- No instrumentation required
- Saliva testing avoids urine collection
- CE Marked for sale in the European Union



2. Read results in 2 minutes

Breath Alcohol Tester

Code 24500 ALCOHOL TESTER

Compact device to measure your blood alcohol concentration. Digital/graphic interface and animation, one-hand operation. ‰ BAC and mg/l values. Supplied in carton box with 3 blowing tubes Ø 7 mm and one cleaning cap. **Code 24501 BLOWING TUBE - box of 12 pcs. Code 32200 "AAA" BATTERIES - blister of 4** /

Large display to read exact value of your breath (3 colour backlight)

Technical SpecificationsRange: Low & $0.15 \sim 1.50$ % BAC or $0.075 \sim 0.75$ mg/lAccuracy: ± 0.2 % BAC full range under alert levelBattery: $3 \ge 1.5V$ AAA batteries (not included)Display: Graphic & Digital display with 3 decimal points (eg. 0.025%BAC)Tolerance compensation: Pre-alert function together with tri-colour backlightingAuto power off: 2 minutes - Real time clock: 12 /24 hour formatBreath sampling: less than 5 seconds continuous breath sampleRecycle time: about 20 secondsUnit Dimensions: $107 \ge 45 \ge 25$ mm approx.Weight: 50g (without batteries)Alert level calibrated: 0.5 % BAC or 0.25mg/l

Protective Goggles



Code 25661 POLYSAFE MEDICAL - bulk Code 25660 POLYSAFE MEDICAL - with box

They are a vital part of any infectious disease control program for eye protection. They provide a wide field of vision and excellent optical quality. Designed with top and side shields to protect eyes from every angle. They can fit all head sizes comfortably, and have superior optical clarity. Autoclavable. Norms EN 166.

0194 25664

Code 25664 MILLENIA GOGGLES - black - fog resistant The best quality of protection goggle according to a positionable and innovative design.



Code 25662 SANTA CRUZ GOGGLES - blue Due to their linear frame design they give total protection to the eyes and a uninterrupted panoramic vision. 5-stop adjustable side arms fit a variety of head sizes with ease. Packed in a nice plastic bag. Autoclavable. Anti-scratch. Norms EN 166 and EN 170

Visor Face Mask and Shield



Code 25654 GIMA FACE SHIELD Code 25656 VISOR HEAD MASK Great features

- faceshield with 90° max rotation (25656 only)
- inner and outer surface treated against mist
- superior coverage to protect against droplets and splashes of liquids (25656)

Superior materials

- elastic ritention band in anallergic material
- rotation systems in anodized aluminium
- soft support in anallergic foam
- faceshield in heat-formed acetate with anti-fog treatment

Easy and comfortable use

- fitting headbands adjustable by velcro fasteners
- usable over ophthalmic glasses

Visor Shield "Protector"



Quality product: made in USA

Code 25642 VISOR SHIELD "PROTECTOR"

The ultra-light face shield that combines function with style:

protection: a waterproof plastic barrier will protect you

comfort: fast and easy to wear and remove convenience: reusable and replaceable shield optical quality: superior optical quality, the best you can buy

Medium adjustable size: fits over 90% of healthcare professionals. Fits over glasses. White or green colour.

Supplied with 2 face transparent shields + 1 head shield.

Code 25643 REPLACEMENT SHIELD KIT Includes 2 face transparent shields + 1 head shield





99% Filtering Masks made in Italy - EN 14683:2005



Code 25648 MASKELLA - face mask with ear loops

- 3 layers of non-allergenic woven-non woven
- Size 90x180 mm
- Weight 3 g
- Non allergenic and nuisance-free
- polyester and elastomer ear loops - Tensile strenght extra-long ties: 80 cm
- Comfortable, shapeable nose clip
- Filtering efficiency > 99%
- Resistance to breath (MM H_2O/cm^2) < 2
- Latex and glass fibres free
- Non sterile min. order : 18 packs of 50=900



Code 25649 MASKERITA - surgical face mask

- 3 layers of non-allergenic woven-non woven - Size 90x180 mm
- Weight 3 g
- Tensile strenght extra-long ties: 80 cm
- Comfortable, shapeable nose clip
- Filtering efficiency > 99%
- Resistance to breath (MM H_2O/cm^2) < 2
- Does not contain glass fibres
- Does not contain latex
- Non sterile



Code 25652 MASKOP Surgical mask with wrap-around visor

- Anti-misting, antistatic wrap-around visor
- 4 layers of non-allergenic woven-non w.
- Weight 10.5 g
- Atraumatic and conformable nose-clip
- Filtering efficiency > 99%
- Resistance to respiratory flow (MM H,O/cm²)<2.5
- Latex and glass fibres free. Not sterile
- Fluid permeability: impermeable
- External/Internal polyethylene anti-
- misting strip

mininum order : box of 50

Code 25651 SURGEON'S MASK - 2 PLY Made in soft TNT, with plastic ear loop. Non-sterile. Light blue colour. Supplied in 50 pcs. Dispenser. minimum order: 2,000 pcs (box of 40 dispenser)



Code 25675 BOUFFANT CAP

min. order: 12 packs of 50=600

Made of soft TNT non sterile. Light blue colour. Supplied in 100 pcs box. Minimum order: 1000 pcs (10 bags of 100 pcs)



Code 25672 BIBS - roll of 80 Made of 2 plies, one of highly absorbent cellulose tissue and one of waterproof polyethylene. Extremely soft and comfortable, they assure an excellent protection to the patient. Each roll has 80 bibs with pre-cut and comfortable ribbons or

bi-adhesive. Minimum order: box of 6 rolls

6 0373

Folded Napkins

FOLDED NAPKINS

Pre-coated folded napkins, made of 2 plies of pure wadding of cellulose partially laminated on 1 ply of polyethylene. The special features of materials offer high absorbency and waterproofness, to assure a high comfort to the patient.



GIMA code	Folded Napkin	ns - pack of 500 pcs.
25230 25231 25232 25240	Napkins 33x48 cm - Napkins 33x48 cm - Napkins 33x48 cm - Plastic dispenser	light blue colour
25239	Chain for napkins	Other colours and size available for quantitie

Disposable Gowns

DISPOSABLE GOWNS

Disposable non woven gowns, suitable when comfort and light protection are required. Colour: dark green Grams: 27 g/sqm Size: large only (suitable for all sizes)

Code 26100 DISPOSABLE GOWNS - non sterile - with cotton cuffs

minimum order: polybag of 10 pcs

Code 26099 DISPOSABLE GOWNS - sterile Sterilized by ETO

minimum order: box of 50 pcs

26100

HEALTH-CARE - OPERATORS PROTECTION

Doctors White and Surgery Coats, Jackets, Trousers



sizes for	men and women, made in high	Doctor's white Coats It			100 % 000	Jack			lets	
quality 1	Size			Women	Men	Size	White	Green	Light Blue	
Âll prod	lucts conform to 89/686/CEE.	Europe	USA	France			S	26130	26140	26150
Sı	urgery Room Coats - green	42	S	38	26111	-	Μ	26131	26141	26151
Size	Men-women	44	S	40	26112	-	\mathbf{L}	26132	26142	26152
		46	Μ	42	26113	26101	XL	26133	26143	26153
52-56 58-62	26162 26163	48	Μ	44	26114	26102	XXL	26134	26144	26154
		50		46	26115	26103		Trou	isers	
	165 FANTASY CAP	50	Ē	48	26116	26103	S	26135	26145	26155
1	Code 26166 GREEN CAP						Μ	26136	26146	26156
100% cotton surgical cap with fantasy		54		50	26117	26105	\mathbf{L}	26137	26147	26157
pictures on 3 mixed background colours		56	XL	52	-	26106	XL	26138	26148	26158
(light blu	ue, red, beige) or green.	58	XXL	54	-	26107	XXL	26139	26149	26159

Antistatic Clogs - autoclavable at 135°C

GIMA PROFESSIONAL CLOGS

- active arch support to stimulate circulation
- antistatic material directly injected in the polymeric blend
- perforated sole for breathability and transpiration
- antislip grooved sole safe on wet floor
- machine washable, sterilizable at 135°C



Other colours

available

		Unne	r without p	ores		Un	per with p	ores	
<u> </u>	W/h:4a				Enchric				
Size	White	Green	Electric Blue	Orange	Fuchsia	White	Yellow	Blue	
34-35	26311	26331	-	26371	-	26411	-	26451	
35-36	26312	26332	-	26372	-	26412	-	26452	
36-37	26313	26333	-	26373	-	26413	-	26453	at a second s
37-38	26314	26334	26354	26374	26394	26414	26434	26454	
38-39	26315	26335	-	26375	-	26415	-	26455	Salar
39-40	26316	26336	-	26376	-	26416	-	26456	
40-41	26317	26337	-	26377	-	26417	-	26457	
41-42	26318	26338	26358	26378	26398	26418	26438	26458	
42-43	26319	26339	26359	26379	26399	26419	26439	26459	
43-44	26320	26340	26360	26380	26400	26420	26440	26460	
45-46	26321	26341	-	26381	-	26421	-	26461	
47-48	26322	26342	-	26382	-	26422	-	26462	

Wood and plastic flavoured tongue depressors



Code 25500 PLASTIC COLOURED TONGUE DEPRESSORS CE

Plastic tongue depressor with child pictures, strawberry aromatic flavour and bright colour. Individually packed, in plastic envelope. Packed in box of 50 pieces. For minimum 50,000 pcs we can pack in personalized boxes of 20, 30, or 50 pcs. Made in Italy



Code 25616 WOOD TONGUE **DEPRESSORS** - Non sterile. High quality tongue depressors manufactured with selected and seasoned wood. Edges accurately finished. 150x18 mm. Made in France.

minimum order: 50 packs of 100= 5,000 pcs. Code 25618 WOOD TONGUE **DEPRESSORS** - sterilized Same as code 25616, individually packaged in a paper envelope. Made in France. minimum order: 40 packs of 50= 2,000 pcs.



Code 25510 WOOD TONGUE DEPRESSORS - non sterile Wooden medical tongue depressors made of quality birch wood. Edges accurately finished. Size: 152 x 17 x 1.6 mm Made in China.

Supplied in boxes of 100 pcs. minimum order: 50 boxes of 100 = 5,000 pcs

Vinyl and Latex Gloves

VINYL GLOVES: Sensitivity and protection. Ideal gloves for hospital attendants, for everyday use

they warrant protection and sensitivity. Medium weight, designed for many applications, including

laboratory procedures and hospital ward use.

Packed in dispenser box 100 units. EN455-EN347-AQL<1.5

With Powder	Powder free elasticised	Vinyl gloves - non sterile (box of 100)
25701	25716	Small size - NON sterile
25702	25717	Medium size - NON sterile
25703	25718	Large size - NON sterile

Sterile Surgical Gloves

Latex sterile surgical gloves with low content of latex proteins. The micro textured surface assures a very good grip in any different condition of use. Lightly powered. Anatomic shape assuring a very good comfort. Sterilized by ETO.

GIMA code	Latex surgical gloves - sterile box of 50 pairs	NOC THE R
25685	Size 6.5 - sterile	m a
25686	Size 7 - sterile	Higher and a second
25687	Size 7.5 - sterile	1111
25688	Size 8 - sterile	att a
25689	Size 8.5 - sterile	and the second



put your logo here

Code 25700 DRACULA

Universal holder for glove and tissue boxes, with little sharp teeth automatically adjust to tightly hold any size of box. It's an universal holder that allows one-hand operation.

LATEX GLOVES

ambidextrous - with hem Pure latex gloves, non sterile. hypoallergenic, packed in dispenser box 100 units. EN455-EN347-AQL<1.5

With Powder	Powder free	Latex gloves - non sterile (box of 100)
25706 25707 25708	25712	Small size - NON sterile Medium size - NON sterile Large size - NON sterile

Nytrile Gloves - no powder

Disposable nitrile examination gloves, powder free and latex free, conform EN455 - EN374 - AQL<1,5 Suitable for end users with sensible skin, medical, labs, final industry use. It assures a great protection.



GIMA code	Nytrile gloves - non sterile (box of 100)	
25680 25681 25682	Small size - non sterile Medium size - non sterile Large size - non sterile	€

COPOLYMER GLOVES ON PAPER Examination gloves, elasticised, medium size, for ginecology use. Code 25710 COPOLYMER GLOVES - non sterile

minimum order: 5 pack of 100 pieces = 500 pcs. Code 25709 COPOLYMER GLOVES - sterile minimum order: pack of 100 pieces **C E** 0373

Sterilized by ETO. AQL <1.5

HEALTH-CARE

Security System GIMA to fuse needles up to Ø 1.6 mm

Code 25820 SECURITY SYSTEM - needle destroyer To avoid accidents from used injection needles, GIMA has

developed and patented Security System.

This Needle Destroyer generates a temperature of **1,000°C**, hot enough to destroy stainless steel and all known bacteria/ viruses. It fuses in 1-2 seconds needles up to a diameter of 1.2 mm. and with some more seconds needles **up to 1.6 mm Safe for nurses, doctors, cleaning staff and patients.** Most of accidents by sticks with needles takes place in the following circumstances that are avoided by use of Needle Destroyer: placing the needle in its protective sheath, discarding a needle from a used syringe, carrying hospital residues. Destroyed needle material is sterilized and stored in a drawer in the base of the unit.

Long life and easy maintenance

It is sturdy, over 4 kg weight, and manufactured in best quality material. Only maintenance necessary is to change fusing spare parts every 4,000 needles.

Code 25821 FUSING SPARE PARTS minimum order: 2 pcs. Security System eliminates accidental contagion of infectious diseases caused by needle-sticks

Technical specifications

Size: cm 22x14x h 9 Weight: 4 kg Operating voltage: 220 V - 50 Hz Fusion temperature: 1,000°C Power: 400 Watt Fuses: 2x2,5 A T Norms: CEI 62-5 - IEC 601-1 Made in Italy: GIMA S.p.A.



Tourniquets in latex, rubber-cotton and latex-free



Code 25722 JETPULL 2° - with gradual adjustment Code 25723 JETPULL 2 - with gradual adj. - latex free Code 25724 JETPULL BABY - with gradual adjustment Easy to use, 2 choices for pressure release: instant or gradual release, thanks to the button on the lock. Ribbon in special material to avoid any skin inflammation. Blood proof. Made in Germany. Code 25725 STRIP-VELCRO TOURNIQUET Self applicable tourniquet made of a nylon band threads

through plastic "D" buckle. Washable and autoclavable.





	IMA ode	Description	Material	Colour	Lenght cm.	Fastening systems	Minimum order	Origin
25	5720	TUBOLARE Tourniquet	Latex	Yellow	33	Manual	200 pcs.	Europe
25	5721	GIMA Tourniquet	Rubber-cotton	Yellow	40	Velcro	10 pcs.	Asia
25	5722	JETPULL 2° Tourniquet	Rubber-cotton	Blue	56	Double lock system: quick and slow release		Europe
25	5723	JETPULL 2° Tourniquet	Rubber-cotton	Green	56	Double lock system: quick and slow release		Europe
25	5724	JETPULL BABY Tourniquet	Rubber-cotton	Child design	56	Double lock system: quick and slow release	-	Europe
25	5725	STRIP-VELCRO Tourniquet	Velcro	Green	45	Velcro+ring: use with one hand only	-	Asia
25	5727	FAST Tourniquet	Rubber-cotton	Red	40	Single lock system: quick release	-	Asia
25	5728	FAST Tourniquet	Rubber-cotton	Green	40	Single lock system: quick release	-	Asia



Syringes, Hypodermic and Mesotherapy Needles, Scalp Vein Sets

2(010						Cather 26053 26056 1de in taly	er needle	Hypoo Mesotherapy new Scalp Vei		(€ 0123
26005 CE	In	suline syring			e in Italy	260		STERIL		ade in Italy
Capacity	Gauge	3 pieces Syringes	3 pieces Syringes	2 pieces Syringes	Minimum	GIMA code	Hypoder Gauge	rmic Needles Gauge mm	- Sterile Colour code	Minimum Order
ml		with needle	without needle	with needle	order	26050	18G 1 1/2"	1.20x40	pink	box of 100
	30G 1/3" R0	26000	-	-	box of 100	26051	19G 1 1/2"	1.10x40	cream	box of 100
1	30G 1/3" R0	26002	-	-	box of 100	26052	20G 1 1/2"	0.90x40	yellow	box of 100
1	25G 5/8"	26005	-	-	box of 100	26053	21G 1 1/2"	0.80x40	green	box of 100
2	22G 1 1/4"	-	-	26040	box of 100	26054	22G 1 1/4"	0.70x30	black	box of 100
2.5	22G 1 1/4"	26010	-	-	box of 100	26055	25G 5/8"	0.50x16	orange	box of 100
5	22G 1 1/4"	26012	-	26041	box of 100	26056	27G 1/6" MESO	0.40x4	grey	box of 100
10 CEN	21G 1 1/2"	26015	-	-	box of 80	26057	27G 1/4" MESO	0.40x6	grey	box of 100
10 L/L	-	-	26030	-	box of 80	Scalp	Vein Sets (But		sterile- tube 3	
10 ECC	21G 1 1/2"	26016	-	26042	box of 80	26060	21G L/L	0.80x19	green	box of 100
20 ECC	21G 1 1/2"	26020	26032	26043	box of 80	26061	23G L/L	0.60x19	dark blue	box of 100
30 L/L	-	-	26034	-	box of 80		1 1	ther Needles		
60 CAT	-	-	26036	-	box of 55	26067	20G L/L	32 mm	pink	box of 100
100 CAT	-	-	26038	-	box of 50	26068	22G L/L	19 mm	dark blue	box of 100
	ed space (no residi er (large cone)	ual)	L/L: Luer Lo ECC: Eccent				V. Solution Ad		Set - without	
CAT: catheter (large cone) ECC: Eccentric Luer 1/3": lenght in of stainless needle (cannula) CEN: Central Luer				26070		pvc tube 150 cm		box of 50		
SYRINGES AND NEEDLES: Gima propose a vast range of					2(070				0123	
	sterile, latex free syringes with or without needle made in					26070				
1	pylene and ca		/							X
	products are				+CO ₂ 90%				- 11	
method	and made in	Italy. Box	in 15 langua	ges.		With drip c	hamber and closure	piercing device, ai	filter, flow regula	tor, roller and L/L

Vol. 3 l

B-D Sharps Collectors

SHARPS COLLECTORS BECTON-DICKINSON WALL MOUNTED SYSTEM - 3 l.

Outer fixed wall-mounted support and inner disposable sharps container. Transparent inner to monitor fill level.

Code 25824 INNER DISPOSABLE SHARPS COLLECTOR Code 25825 OUTER GUARDIAN SHARPS COLLECTOR Code 25826 DESK CONTAINER - 1.4 l.

Disposable and space saving container

supplied with adhesive support.



Biological Collectors



HEALTH-CARE - SURGICAL INSTRUMENTS

GIMA: disposable s/s scalpels & stainless or carbon steel blades

"GIMA" DISPOSABLE BLADES - sterile

Standard surgical blades are available in both high carbon and stainless steel and manufactured in accordance with the requirements of British Standards BS 2982:1992, BS 5194: 1992 and ISO 7740:1985. Each blade is hallmarked. Each blade is individually packed in aluminium foil. Carbon Steel blades are VPI paper protected. Blade size are clearly identified on the reverse side of the foil

Blade size are clearly identified on the reverse side of the foll peel-pack and by a colour coded sticker on unit boxes. Supplied sterile in unit dispenser boxes of 100.

"GIMA" DISPOSABLE SCALPELS - sterile

S/S blade fitted on an ABS plastic handle. Individually paked in sterilized envelope. Safety blade guard. Box of 10 pcs.







graduated ABS body

perfectly sonic-welded balanced sandwiched blade

Anti skid blade guard

"GIMA" SAFETY DISPOSABLE SCALPELS - sterile Scalpels with stainless steel retractable blade with steadfast disposal lock. Supplied in box of 10 pcs.





GIMA code	Sc	alpel Handles - stainless steel	Minimum order
26913	Scalpe	l Handle N° 3 for blades 10-15	10 pcs.
26914	Scalpe	l Handle N° 4 for blades 20-25	10 pcs.
Carbon	Stainless	GIMA sterilized	Minimum
steel	steel	blades (pack of 100 pcs.)	order
27000	27020	Sterilized stainless steel blades No.10	▲
27001	27021	Sterilized stainless steel blades No.11	
27002	27022	Sterilized stainless steel blades No.12	
27003	27023	Sterilized stainless steel blades No.15	10 packs
27004	27024	Sterilized stainless steel blades No.20	also
27005	27025	Sterilized stainless steel blades No.21	assorted
27006	27026	Sterilized stainless steel blades No.22	
27007	27027	Sterilized stainless steel blades No.23	
27008	27028	Sterilized stainless steel blades No.24	. ↓
Standard Model	Safety Model	GIMA Sterilized disposable scalpels stainless steel (pack of 10 pcs.)	Minimum order
27040	27050	Disposable scalpels - blade 10	
27040	27050	Disposable scalpels - blade 11	T I
27042	-	Disposable scalpels - blade 12	
27043	27053	Disposable scalpels - blade 15	10 packs
27044	-	Disposable scalpels - blade 20	also
27045	-	Disposable scalpels - blade 21	assorted
27046	-	Disposable scalpels - blade 22	
27047	-	Disposable scalpels - blade 23	
27048	-	Disposable scalpels - blade 24	¥

Paragon stainless steel scalpels and blades made in UK

GIMA code	Paragon sterilized stainless steel blades (pack of 100 pcs.)	Minimum order
26901 26902 26903 26904 26905 26906 26907 26908 26909	Sterilized stainless steel blades No.10 Sterilized stainless steel blades No.11 Sterilized stainless steel blades No.12 Sterilized stainless steel blades No.15 Sterilized stainless steel blades No.20 Sterilized stainless steel blades No.21 Sterilized stainless steel blades No.22 Sterilized stainless steel blades No.23 Sterilized stainless steel blades No.23 Sterilized stainless steel blades No.24	10 packs also assorted
GIMA code	Paragon Sterilized disposable scalpels (pack of 10 pcs.)	Minimum order
26920 26921 26922 26923 26924 26925 26926 26926 26927 26928	Disposable scalpels - blade 10 Disposable scalpels - blade 11 Disposable scalpels - blade 12 Disposable scalpels - blade 15 Disposable scalpels - blade 20 Disposable scalpels - blade 21 Disposable scalpels - blade 22 Disposable scalpels - blade 23 Disposable scalpels - blade 24	10 packs also assorted



"PARAGON" DISPOSABLE SCALPEL BLADES - sterile These high quality blades are manufactured with best British stainless steel. They guarantee excellent sharpening and perfect cut control. Individually packed in metal foil in cardboard box of 100 units. Gamma rays sterilized. "PARAGON" DISPOSABLE SCALPELS - sterile Grip on the handle allows stability for long straight incisions. Individually packed in sterilized envelope, reinforced with blade protection, in cardboard box of 10 units.



Single-use Sterile Dermal Curettes



Stainless steel semi-sharp cutting edge for abnormal soft or weak tissue. Size embossed on each curette for easy identification. Sterile ready-to-use, use once and discard. Eliminates need for re-sharpening and sterilization. Wide range of sizes.

(E⁰¹⁹⁷

Used in the following minor surgical skin procedures: Curettage of a basal cell carcinoma, curettage of a verruca and curettage of any other benign neoplasms of the skin. **Clinical Areas.** Dermatology, surgical, podiatry, veterinary

GIMA code	Dermal Curettes	Minimum order
26950	Dermal Curettes Ø 2 mm	20 pcs.
26951	Dermal Curettes Ø 3 mm	20 pcs. 20 pcs. 20 pcs. 20 pcs.
26952	Dermal Curettes Ø 4 mm	20 pcs.
26953	Dermal Curettes Ø 5 mm	20 pcs.
26954	Dermal Curettes Ø 7 mm	20 pcs.

Single-use Sterile Biopsy Punches

Stainless steel sharp cutting edge, ribbed handle for sure grip. Size embossed on each punch for easy identification. Suggested for dermatology, ginaecology, podiatry. Each punch is individually sealed in a peel-apart see-through package.

I	2	1 1	0 1	0
GIMA code	With plunger	Biopsy Punches	Blade length mm	Minimum order
26939	-	Biopsy Punches Ø 1 mm	7	20 pcs.
26940	-	Biopsy Punches Ø 1.5 mm	7	20 pcs.
26941	26972	Biopsy Punches Ø 2 mm	7	20 pcs.
26938	-	Biopsy Punches Ø 2.5 mm	7	20 pcs.
26942	-	Biopsy Punches Ø 3 mm	7	20 pcs.
26943	-	Biopsy Punches Ø 3.5 mm	7	20 pcs.
26944	-	Biopsy Punches Ø 4 mm	7	20 pcs.
26946	-	Biopsy Punches Ø 5 mm	7	20 pcs.
26947	-	Biopsy Punches Ø 6 mm	7	20 pcs.
26948	-	Biopsy Punches Ø 8 mm	7	20 pcs.



Sutures - Fine Wound Closure Material

CLINISILK STERILE BLACK BRAIDED SILK SUTURE B.P. Non-absorbable sutures made from pure natural silk, braided to form a multifilament thread, double treated with a silicone coating to prevent capillarity and to enhance ease of passage through tissue. Silk sutures are considered to have the best handling and tying characteristics.

CLININY STERILE BLUE MONOFILAMENT NYLON SUTURE B.P.

Non-absorbable synthetic monofilament suture made from Polyamide 6.6. No tissue reaction, excellente tensile strenght and handling characteristics. Nylon is a highly favoured material for skin closure.

GIMA code		Clinisilk	and Clining	y sutures - pack of 12 pcs.		
Silk	Nylon	Gauge	Needle	Type of needle		
25910	25920	2/0	26 mm	Reverse cutting		
25911	-	3/0	22 mm	Conventional cutting		
-	25921	3/0	20 mm	Conventional cutting		
25912	25922	3/0	24 mm	Reverse cutting		
-	25923	3/0	25 mm	Fine conventional cutting		
25914	25924	4/0	19 mm	Reverse cutting		
-	25925	5/0	16 mm	Reverse cutting		
25916	25926	5/0	19 mm	Reverse cutting		
-	25927	6/0	12 mm	Reverse cutting		
25918	25928	6/0	16 mm	Reverse cutting		

CLINISORB STERILE BRAIDED SYNTHETIC ABSORBABLE SUTURE

CliniSorb is a synthetic absorbable braided suture made from a polymer of Glycolic acid. This material is inert, non collogenous, non-antigenic, non-pyrogenic and has a high tensile strength and predictable absorption rate, allowing wound support for approximately 21 days. It is treated with a surface coating to ensure smooth tissue passage and enhance knot sliding.

It is not affected by infection, inflammatory processes or

exposure to protein digesting enzymes in the gastro intestinal tract. Suitable for both skin closure and where non-permanent wound support is indicated.



GIMA	Clin	res - pack of 12 pcs synthetic	
code	code Gauge Needle		Type of needle
25900 25901 25902	2/0 3/0 4/0	24 mm 19 mm 19 mm	Reverse cutting Reverse cutting Reverse cutting

Round Sterilizer Drums

ROUND STERILIZER DRUM for autoclave and hot air sterilizer manufactured from stainless steel AISI304 . Sliding removable band and drop down clasps.

Shufing temovable ballu and urop down clasps.					
GIMA code	Round sterilizer drums				
26673	Ø 120x h 120 mm				
26674	Ø 140x h 140 mm				
26676	Ø 160x h 120 mm				
26678	Ø 180x h 180 mm				
26680	Ø 190x h 160 mm				
26681	Ø 240x h 160 mm				
26682	Ø 240x h 240 mm				
26683	Ø 290x h 160 mm				
26684	Ø 290x h 240 mm				
26685	Ø 340x h 340 mm				
26686	Ø 390x h 250 mm				



Stainless Steel Boxes

Aluminium Boxes





HEALTH-CARE - HOLLOWARE

Stainless Steel Holloware



Tungsten Carbide Instruments - Gold Line



Stainless Steel Retractors



Medication s/s Forceps



HEALTH-CARE - SURGICAL INSTRUMENTS

Stainless Steel Surgical instruments

CE



Beauty Instruments



Dermatology Instruments and Kit Instruments Catalogue



Gynaecology Instruments and Kit

CE





ENT Stainless Steel instruments and Kit

CE



Laryngeal Mirrors and Spirit Lamp

31612	GIMA code Laryngeal mirror - straight				Minimum order
And a second sec	31600	Mirror number	000	diameter 10 mm	
	31601	Mirror number	00	diameter 12 mm	
	31602	Mirror number	0	diameter 14 mm	
1921 Harrison	31603	Mirror number	1	diameter 16 mm	10 pcs.
	31604	Mirror number	2	diameter 18 mm	mixed
	31605	Mirror number	3	diameter 20 mm	sizes
	31606	Mirror number	4	diameter 22 mm	
CE	31607	Mirror number	5	diameter 24 mm	
31614	31608	Mirror number	6	diameter 26 mm	•
Code 31616 ADJUSTABLE MIRROR HANDLE	Code 31	612 SET 9 LARY	NGEAI	MIRRORS 000-6)
Code 31615 FIXED MIRROR HANDLE	Set of 9 laryngeal mirrors from 000 to 6, all mirrors have a				
	different diameter: from 10 mm to 26 mm.				
31616	Code 31	614 SPIRIT LAM	P - 120	inimum order: 1 set of CC	9 mirrors
31615					23

SURGICAL INSTRUMENTS

Otoscillo Electrical Irrigation Device

Code 25815 OTOSCILLO

Otoscillo is designed for automated ear rinsing both in hospitals and during private consultations. Innovative, compact, efficient and rapid, the Otoscillo combines the most sophisticated operating qualities with the best security guarantees, all in a single device.

Anywhere, anytime

Otoscillo is an electrical irrigation for simplified rinsing of the ear canal. The pulsating stream system makes it easier to remove cerumen, even at low pressure control, Otoscillo is particularly adapted to the treatment of sensitive ear canals. It looks less alarming and it is easier to use, with greater accuracy and security, than the alternatives. The water basin is removable to allow easy filling and emptying.

The device is readily usable and easy to clean. Can be mounted on a wall or a cupboard. Made in Germany

Operating power: 220V - 50/60 Hz Code 25816 SPARE SET (2 tips + disk)

Code 25817 SPARE HANDLE + TUBE



Water temperature

Glass-metal, all-metal, and single-use Ear Syringes



BAGS

Utility Bag



Code 27127 UTILITY DOCTOR BAG - empty Practical doctor bag for easy transport of instruments and medications provided with 8 internal movable divisions, 3 external pockets, 8 elasticated retaining, 1 internal pocket with zip, 1 removable mini bag. Size: 36 x 22 x h25 cm.

Thermal Bag



Code 27209 THERMAL BAG - Colour yellow - nylon Thermal bag with pockets. Its temperature pack maintains cold or hot temperature for prolonged periods. Beautifully crafted, durable, insulated bag with detachable shoulder straps. 3 temperature packs included. Internal size: 30 x 23 x 21 cm. Made in Italy **Code 27219 THERMAL BAG TEMPERATURE PACK**

Instrument Bags, Vial bags,



Code 27139 DIATERMO BAG - Colour black - cordura Designed to carry small electrosurgical units, audiometers, spirometers, ECG with their accessories. One division to separate device from accessories and one zip pocket.





Code 27129 MAXI VIALS BAG Colour red - cordura The best way to protect, identify and organize up to 9 phials of any size. Made of two parts, with elastic strips for holding big and small ampoules. Central partition with transparent polyvinyl window for documents. Size: 29 x 22x h 7 cm

Code 27133 MEDICATION BAG - Colour blue - cordura Compact cordura bag made in water-proof anti-scratch material: 2 internal zip pockets and 9 elasticated retainers for more instruments. Size: 34 x 24 x h 7 cm.



Code 27255 DIABETIC BAG - empty - blue Code 27254 MINI DIABETIC BAG - empty- blue Thermal pharmaceutical bags made specifically for transporting medications that must be kept at cool temperatures, ideal for diabetics.

Temperature pack included to provide a temperature of about 10°C for up to 10 hours. Exterior material is a water repellent vinyl nylon with a foam backing. Made in Italy

BAGS

Emergency Bags - 4 Models, 7 Sizes



Shoulder straps included with medium and large bag.





Safe metal buckles

27156

Removable lining for easy cleaning

	GIMA code	Model	Material	Colour	Size	Internal modular spaces	External pockets
	27150	Small	Cordura	red	45x28xh28 cm	3	4
	27151	Medium	Cordura	red	55x35xh32 cm	6	4
	27152	Medium	Cordura	blue	55x35xh32 cm	6	4
i	27153	Large	Cordura	red	65x35xh35 cm	6	5
1	27156	Pediatric	Cordura	red	55x25xh30 cm	3	2

27153

SMART BAGS - empty

Professional emergency bags extremely capacious with internal adjustable compartments which permit personalized organization of the space. Provided with external pockets, internal divisions, and one (2 for code 27154) removable pouch with transparent window. Made in strong, waterproof cordura material, provided with double yellow refractive strips. Internal lining is removable for easy cleaning. Waterproof rubber bottom to prevent water infiltration. May be carried on shoulder or hand.

Shoulder belt has colour sections. Colour resulting by child height, allows immediate entification of same colour pouch with correct products for that height/age

27151

Padded

frontal

pocket

ottom and

Code 27156 SMART PEDIATRIC BAG - cordura - empty Made of same material and with same finish as smart line. This bag includes 7 colour-coded removable pouches (model E6) with transparent windows and one ampoule kit. Colour-coded pouches (E6) are designed to well organize products (size,) related to child's height. Shoulder belt has colour sections, same as pouches, and centimeters to allow immediate identification of correct product pouch depending on child's height. Size: 55x25xh 30 cm. With 2 external pockets.



27165



27165

Code 27136 EMERGENCY BAG Colour orange - nylon - 35x50x23 cm Code 27165 EMERGENCY BAG Colour red - cordura - 35x45x21 cm

Capacious bag, despite compact size. Large central compartment, 1 front and 3 lateral pockets. May be carried on shoulder (braces) or hand (2 handles). Made in strong, waterproof material with yellow refractive strips and rubber bottom (only 27165) 27161







Code 27160 LIFE-1 BAG Code 27161 LIFE-2 BAG

2 section first-aid bag with double opening zip: bottom side with shockproof inner basin, upper side with 4 (27160) or 5 (27161) removable coloured pouches (model E1) with transparent window. Made of strong, waterproof cordura material provided with refractive yellow strips. Shoulder or hand portable. Size 35x20xh 35 cm (Life-1), 48x25x30 cm (Life-2).

2716



Professional Emergency Rucksacks in Waterproof Cordura



27171

Code 27170 LOGIC-1 RUCKSACK medium 40x20xh47cm Code 27171 LOGIC RUCKSACK large 40x25xh47cm

Supplied with 6 (27171) or 5 (27170) coloured pouches with transparent window and velcro strips (model E1), 2 frontal pockets and 2 lateral pockets. Internal velcro strips and elastics, to retain instruments. Central division with zip and elastics (only 27171). Provided with vellow refractive strips

27174

Code 27174 AMBULANCE RUCKSACK

Modular extra large rucksack provided with 8 internal pouches, 4 coloured with handle (model E5) and 4 coloured with transparent window (model E2). Velcro internal strips for pouches fixing. Provided with double yellow refractive strip. Size: 40x30xh57 cm

Large 10 mm zips

Code 27175 SILOS RUCKSACK Professional, resistant rucksack.

The Silos bag has a semi-stiff yet padded external structure.

A special rubber layer bottom enhances the sturdiness of this product. Innovative shoulder strap design provides extra comfort to the back. Inside features: 5 see-through pouches (3 E2 pouches and 2 E4 pouches) and bottle holder, 2 frontal pockets. Size 35x28xh53 cm.



PHYSICIAN BAGS

High Quality Leather Bags - made in Italy



27119

External dimensions: 41x17x h31 cm.

Code 27119 PILOTA leather - colour chestnut Designed for Professionals requiring extra storage capacity. Rigid bottom, 3 inside partitions, two locks.



Code 27126 PRIMATO prime leather - colour leather 2 inside partitions, one with articles-holder, and large zip- fastener pocket. External large zip-fastener pocket, burnished locks.



27114

External dimensions: 38 x 20 x h20 cm

Code 27114 AOSTA leather - colour bordeaux Rigid bottom, inside zip fastener central pocket, lateral inside pocket, burnished lock.



Code 27110 TEXAS leather - colour: chestnut

Rigid bottom, inside pocket with button fastening, burnished lock.

27110



External dimensions: 42 x 20 x h25 cm

Code 27112 ARIZONA leather - chestnut Folding bottom, inside partition, inside zip fastener pocket, outer pocket, 2 burnished locks.



Code 27117 DIPLOMATICA leather - colour black Professional leather bag with two compartment inside and internal zip pocket. Quality lock.



External dimensions: 34 x 17 x h21 cm.

27120

PRIME LEATHER

Code 27120 VALIGETTA prime leather - colour: leather Rigid bottom, inside zip-fastener pocket and inside folding pocket, burnished lock.



External dimensions: $42 \times 21 \times h25 \ cm$

27112

Code 27115 SUPERTEXAS leather - colour: black Code 27116 SUPERTEXAS leather - colour: chestnut With outer pocket and inside zip fastener pocket, 2 burnished locks, inside transversal partition 8 cm. from side, large central area.



Simulated Leather Bags - made in Italy





27102

Code 27100 TEXAS skay - colour: black Code 27101 TEXAS skay - colour: cognac Rigid bottom, inside pocket with button fastening, burnished lock.



External

dimensions: 42 x 20 x h25 cm

Code 27102 ARIZONA skay - colour: cognac

Folding bottom, inside partition, inside zip fastener pocket, outer pocket, burnished lock.



27106

External dimensions. 41x17x h31 cm.

Code 27106 PILOTA skay - colour: cognac Designed for Professionals requiring extra storage capacity. Rigid bottom, 3 inside partitions, two locks.



External dimensions: 38 x 20 x h20 cm

27105

Code 27104 INFERMIERA skay - colour: cognac Rigid bottom, inside zip fastener pocket and inside folding pocket, burnished lock.



Code 27105 SUPERTEXAS skay - colour: cognac With outer pocket and inside zip fastener pocket, 2 burnished locks, inside transversal partition 8 cm. from side, large central area.



27108

External

External dimensions: 45 x 20 x h25 cm

Code 27108 LARGE POLUS skay - colour: cognac Rigid bottom, inside zip fastener folding pocket elasticated retainers for instruments on both inside sides.



MEASURING

GIMA Skinfold Calipers: mechanical and digital



Code 27320 PLICOMETRO - SKINFOLD CALIPER - mechanical Code 27346 PLICOMETRO - SKINFOLD CALIPER - digital with PC CABLE for data transfer

This high precision instrument measures the thickness of a fold of skin with its underlying layer of fat giving physicians the situation of the subcutaneous tissues of the patient. Possibility of re-calibration

Produced to meet International Standards, the Gima "Skinfold caliper" has springs which exert a pressure of 10 g/mm" on the skinfold and an accurate scale which measures thickness in mm. With possibility of re-calibration of the pressure it solves the major problem of traditional skinfold caliper that is reduction of the tension of the spring in the time.

Easy to use and read

With double reading scale (code 27320) or digital display (code 27346), it is supplied with picture showing advised positions for measurement. Tables will help to obtain correct % of bodyfat from measured data and make a correct evaluation of the patient. **Stylish and user-friendly**

A special nylon finish makes the device feel skin, avoiding trouble of contact with metal. Made in metal and sold in an attractive wooden box. Made in Italy. User manual in English, French, Italian, Spanish. **Data management on PC (only 27346)**

Compatible with windows 2000 and XP, does not work with windows 98

Body fat Analyzer with carrying case

Code 27322 GIMA BODY FAT ANALYZER

Ideal for dieticians, gymnasia and sports centres, it is perfect also for homecare. It will help manage nutrition, fitness and weight control and can indicate if you are at the right weight and also whether or not you are nutritionally healthy. Advanced technology in your hands.

GIMA Body Fat Analyzer measures the flow of electrical signals (total body electrical resistance or impedance) as they pass through FAT, LEAN (muscle, bones, vital organs) or WATER. When the amount of fat, lean or water changes, so does the Body Fat signal, giving you a highly reliable and accurate measure of the amounts of each of these components that make up your total weight. Specifically, 4 electrodes are placed over metacarpus and metatarsus where a 50 kHz current is introduced. The detected signal level will be an index of total body water and fat free mass.

Only 2 minutes for an accurate and easy test

Testing and results take less than two minutes and have the same accuracy as other more expensive devices.

A lot of meaningful data

FAT: actual weight of fat on the body

LEAN: actual weight of lean, mostly muscle and vital organs WATER: water content in the body % FAT: percent of fat weight in total body weight

% LEAN: percent of lean weight in total body weight BMR: basal metabolic rate

Target Weight: weight goal under optimal condition Target % Fat: normal percent for sex and age Portable, for performing test everywhere

Small size and light weight for portability.

Body Fat Analyzer helps to get and stay fit.

It helps maximize personal level of fitness if you want to lose weight, build muscle, tone and trim, or simply be sure you are maintaining your current level of fitness:

- enables you to check effectiveness of weight loss program, telling exactly where your weight loss is coming from (fat-lean-water).

- it helps monitoring improvements in muscle mass as a result of exercise and/or diet.

 - establishes a baseline for your body composition, so that nutritional and fitness improvements can be regularly monitored. Body fat is sold with a carrying case, kit of 2 sensor cable, sensor pads (box of 20), 2 x 9V batteries, transformer and manual (English, Italian) Code 27331 SPARE SENSOR CABLES (kit of two) units sold before 06/02 Code 27323 SENSOR PAD (box of 20)- replacement Each sensor can be reused 5-6 times. Code 32205 9V ALKALINE BATTERY

Code 27324 CALIBRATION KIT

Technical specifications Size: 66 x 176 x208 mm Test frequency: approx. 50 kHz Test current: less than lmA Weight: 1500 g (unit, battery and probe). Power source: two 9 Volt DC batteries or 230V (by transformer) Norms: 89/336/EEC/ (it is not a medical device)









m Size: 345x92x28 cm Power supply: 2x1.5V AA batteries 27333

Code 27328 TAPE HEIGHT MEASURE Clear scale 0-200 cm. Easily secured to a wall. Code 27333 ELECTRONIC HEIGHT ROD - Soehnle Measuring range: 50-300 cm (20-118 inch), division: 1 cm. Code 27326 BABY MEASURE "CALIBRO" Weight 300 g. Made in oxidized aluminium, metric graduation 0-900 mm, every 5 mm. Certified by Italian "weights and measure office".



27326



Code 27325 BONE MEASURE

Slip-knot caliper in anticorodal for knee, shoulder, wrist, elbow...measuring. Measuring capacity: 150 mm. Burner length: 100 mm. Tested by Italian "weights and measures office"

Code 27327 CRANIOMETRO - HEAD MEASURE

27345

30 cm

In special, soft, plastic material. Measures diameter of child head up to 60 cm. Code 27341 BMI - TAPE MEASURE

Pocket retractable tape measure 150 cm. BMI (Body Mass Index) calculator on front panel.



Evaluating the Spine and

Code 27345 BRIEFCASE - instrument set

Includes: inclinometer and support, goniometer with arms, gibbometer, cirtometer, torsiometer, ruler with visual-analogue scale, retractable tape measure, dermographic pencil For the most precise and complete (functional, postural, clinical and radiological) measurement of analytical motility and scoliosis.

Code 27350 SCOLIOSOMETER - ask for brochure

Code 27330 INCLINOMETER - gravity goniometer (patent) Used for precise measurement of analytical motility angles of various parts of the body. The instrument can be fixed to the body parts, avoiding the need for propping to the limbs. Can be used to rapidly measure radiographs (tolerance 0.5°)

Code 27336 GIBBOMETER

Gives a measurement in mm of the gibbus in the scoliosis of the spinal column (tolerance 1 mm)

Code 27332 TORSIOMETER

Used with radiographs for the evaluation of metameric rotation (Cobb's) and cunation of the vertebrae by simply overlaying it on the radiograph.

Code 27334 CIRTOMETER

For the measurement of the sagittal and spinal curves and the lumbopelvic region by placing the instrument on the spinous process. Can also be used to evaluate the shape of the gibbus in scoliosis. This graduated flexi-curve holds any position given to it. **Locomotor System**



Consists of two perspex arms (3mm thick) that will remain open at any given position due to the friction at the joint between them

27338

Two graded scales: one increasing scale and one decreasing scale. Arm length: 30 cm

Code 27338 GONIOMETER WITH ARMS (tolerance 1°) For measuring analytical motility of various body segments in

For measuring analytical motility of various body segments in degrees (from 0 to 360 in a clockwise or anti-clockwise direction)



MEASURING



Technical specifications Capacity: 160 kg Dial Ø: 180 mm Sensitivity: 1000 g Dimension: 430 x 380 x 70 mm Weight: 3 kg

professional doctor's scales.

Capacity: 150 kg (330 lb)

Sensitivity: 500 g (1 lb) Warranty: 3 years

The oversized dial shows your weight in

increments of 500 g. Individual certification.

Mechanical Scales

Code 27287 SOEHNLE PROFESSIONAL SCALE Mechanical flat scale with pure design: a large and clear dial, a robust housing made of steel with a classic design characterise this new product by Soehnle.



Code 27285 SECA 762 SCALE

Traditional model with large easy-to-read dial. Pointer professional scale in strong metal structure white painted. Consistent accuracy on any surface. Spacious platform design with no slip rubber mat, stable for safety. Made in Europe.

Technical specifications

Bathroo Bathroo Other States of the platform of this scale is inspired by the best features of

> **Code 27317 SOEHNLE 61220 SCALE** Traditional bathroom scale with non-slip easy to clean surface. Individual certification.

27317



Code 27280 DIGITAL DIET SCALE With large weighing base. Easy-to-read large display. Weight indicated in 1 g increments. Up to 5 kg

Lithium 3V battery-included

Function: tare



Digital Bathroom Scales

90/384/EEC



Technical specificationsCapacity: 150 kg (330 lbs)Sensitivity: 100 gSize: 34x35x h 6 cmPower: 2 lithium batteries (included)



Code 27315 VERONA DIGITAL SCALEODigital bathroom scale with easy-cleanDplastic platform cover and bright LEDDdigits. Automatic Start.D



Code 27314 COLUMBIA BODY SCALE Provided with high-tech crystal platform. LCD display with measuring of weight, fat and water % of the body. 10 memories.

WEIGHT + WATER+FAT





Electronic Infant Scale



Code 27303 DIGITAL DANY SCALE

Advanced design, high precision electronic baby scale. Provided with a large LCD display and baby measure line both in cm and inch. Multilingual user manual.



Home Care Baby Scale

Seca Baby Scale



Code 27299 SECA 725 - mechanical

The sturdy classic: with its softly curved weighing tray, the stable all-steel casing and the precise, smooth running weights, this model is the indestructible original baby scale.

Mains or batterv

Technical specifications Capacity:16 kg Dimensions: 550x190x305 mm Sensitivity: 5 g Weight: 6 kg Made in Europe



Keys to symbols:

Manual zero adjustment

MEASURING

Mechanical Scales

27308 Steel platform with non slipping 27308 ABS cover Pillar separated by platform to enlarge space for feet Code 27308 BISA SCALE-150 kg

with height meter (95-200 cm) Compact scale of modern design for medical use. Solid base made of steel with tempered spindles of 6 mm and reinforced bearings in V shape. Weighing headstock with ABS cover and hidden balancing bars. Calibrated and verified to secure a precision of 100 g. Easy recalibration on site. Galvanized inner levers. Height rod in mm up to 2 metres. Finish of furnaced electrostatic shellack.

Technical specifications Capacity: 150 kg Sensitivity: 100 g Base measures: 500 x 310 x 70 mm Platform measures: 300 x 300 mm antiskid Height: 950 mm Made in European Community



Code 27305 FERT SCALE - 200 kg Code 27307 FERT SCALE - 150 kg Code 27265 FERT SCALE classIII Same as code 27307 but with (III) M All Fert supplied with height meter (95-200 cm). Solid base made of steel with tempered spindles of 6 mm and reinforced bearings in V shape. Chromed balancing arm with easy reading graduation. Easy recalibration on site. Height rod graduated in millimetres

Technical specifications Capacity: 150 kg/200 kg Sensitivity: 100 g Base measures: 500 x 310 x 70 mm Platform measures: 300 x 300 mm antiskid Height: 1400 mm Made in European Community



Code 27310 ASTRA SCALE - 200 kg mechanical with height meter (75-200 cm) Traditional scale with robust lever system, powder coated platform and column, provided with wheels for easy transport. User manual in English, Spanish, French, Italian, German, Greek, Portuguese, Arabic.

Technical specifications Capacity: 200 kg Sensitivity: 100 g Weight: 15 kg Dimensions: 275 x 1485 x 530 mm Platform: 375 x 275 mm



34

(($\overline{(m)}$ = Calibration according to class III sensitivity required by 90/384/EEC

Seca Professional Scales



Code 27284 SECA 756 - mechanical with height meter

Tradition combined with modern design. With a very sensitive precision mechanism to show weight by the aid of a highly visible red pointer on the circular dial.

User manual in English, Spanish, French, German, Italian.

Technical specifications Capacity: 160 kg Sensitivity: 500 g Weight: 18 kg Dimensions: 628 x 360 x 1000 mm Platform: 360 x 350 mm with wheels

Code 27296 NEW SECA 711 - mechanical **Code 27298 HEIGHT METER** Mechanical column scale with weight

adjustment at eye level. Weight can be measured in a conventional way: by aligning two chrome plated indicators. User manual in English, Spanish, French, German, Italian. **Technical specifications**

Capacity: 220 kg Sensitivity: 100 g Weight: 23.5 kg Dimensions: 520 x 1556 x 520 mm Platform: 350 x 360 mm

Fitness Scale



Technical specifications Capacity: 200 kg Sensitivity: 100 g Dimensions: 535x275x940 mm Platform: 372x275 r Weight: 15 kg Power supply: 220 V - 50 Hz Battery accumulator: 6V 5AH Recharging time: 4-5 hours Operating time when fully charged: 36 hours



Code 27257 ELECTRONIC VET SCALE Robust metal platform with a separate digital display.



Chair scale - see page 36

Keys to symbols:

■ = Metrological Approval for use in medical field **(€** (Ⅲ) = Calibration according to class III sensitivity required by 90/384/EEC

Technical specifications

300-500 kg: 200 g/0.4 lb

Dimensions: 860 x 480 x 1050 mm - 25 Kg

Capacity: 500 kg /1100 lb

Power supply: 230V/50Hz

Sensitivity: 0-300 kg: 100 g/0.2 lb

PROFESSIONAL

Made in Germany



35

Hydraulic and Electrical Lifters

Weight

50 Kg

Sling support

min H 88 cm max H 177 cm

27751

Code 27751 HYDRAULIC LIFTER

Lifting movement by a hydraulic pump operated by adjustable side control lever. Descent movement by independent exhaust-valve. Adjustable base 63 to 105 cm controlled by a manual device for easy access to narrow places. Painted steel frame. Anti trauma push-handle. 4 pivoting wheels of Ø 100 mm, two of which are fitted with stand-still brakes. Equipped with universal sling. Made in Italy. **Code 27754 ELECTRICAL LIFTER** Same as code 27751 but with electrical controls.

Up and down movements by an electric actuator 24 V D.C. and push button. Battery fed by current transformer with an emergency push-button for the immediate stop of the movement and free up/down piston-stroke. **Code 27757 UNIVERSAL SLING - spare**

Made of polypropylene, anti-allergic, non toxic, washable



Raised Toilet Seats

Code 27741 RAISED TOILET SEAT HEIGHT cm 10 with lateral fixing system. Code 27743 RAISED TOILET SEAT HEIGHT cm 10 with central fixing system and armrest



Walker Aid and Rollator

Sling support

min H 88 cm max H 177 cm

Maximum load 160 Kg

27754

Adjustable base

63-105 cm

Length 123 cm



brakes on wheels. Size 71x64 c adjustable. Height 81-93 cm. Seat at 55 cm. Weight 8 kg.

Shower and bath chairs





PAEDIATRIC

- Aluminium type

- flip up arm-rest

- pneumatic rear wheels

- fixed foot-rest

- solid castors

- folding

27708

CE

Folding Wheelchairs and Commode Chair



ECONOMY

- Economy type
- fixed armrest and footrest
- folding
- solid castors
- solid rear wheel
- 27709

Code 27709 STANDARD WHEELCHAIR - chromed



Code 27715 ROYAL WHEELCHAIR - chromed



LIGHT - ONLY 13 kg



- Aluminium type - detachable armrest, footrest and brake
- folding

Code 27708 PEDIATRIC WHEELCHAIR EXTRA LARGE - 56 cm - super width - flip up armrest - detachable footrest - PU castors - pneumatic mag wheel 27716 Code 27716 EXTRA LARGE WHEELCHAIR - Steel



Code 27718 LIGHT WHEELCHAIR - Aluminium

	GIMA code	f.			Ð.	C.	Ċ.	(JA	Co	E C	4	۵	
	27709	65	24	46	59	20	50	87	106	40	45	100	93x24x88 19 21
	27708	51	32	35	57	15	48	89	97	36	40	100	87x33x70 13 15
	27715	61	28	46	60	15	45	90	106	40	45	100	80x28x72 14 16
27702	27716	72	32	56	60	20	54	93	109	45	46	125	80x33x93 21 23
	27718	61	28	46	40	15	45	90	100	40	45	100	72x28x72 13 15
Code 27702 COMMODE		69	36	46	61	15	52	91	105	40	45	120	80x33x92 17 19
WHEELCHAIR - painted	27702/3	55	-	44	12.5	12.5	51	92	90	44	42	100	54x53x53 17 19
Code 27703 COMMODE Code 27706 TABLE for wheelchair - Universal connector													

WHEELCHAIR - stainless Code 27705 IV STAND for wheelchair - Suitable for all models - universal connector steel

Code 27707 FIRE RESISTANT PVC BACKREST AND SEAT - spare for 27715 only

PATIENT AIDS

Soft and Rigid Collars

SOFT CERVICAL COLLARS

This collar is made of soft expanded polyurethane lined with an anti - allergic 100% cotton fabric. Velcro fixing on the back. Available in 3 sizes.

RIGID CERVICAL COLLARS

Made of polyethylene, with comfortable resting support in vinyl leather and height adjustable. Velcro straps on the back. Available in 3 sizes. Soft



GIMA code	Soft and rigid neck collars
34600	Rigid cervical collar 32-40 cm (neck circumference)
34601	Rigid cervical collar 41-46 cm (neck circumference)
34602	Rigid cervical collar 47-52 cm (neck circumference)
34610	Soft cervical collar 43 x 8 cm - small (h 7 cm)
34612	Soft cervical collar 46 x 8 cm - medium (h 8.5 cm)
34614	Soft cervical collar 49 x 10 cm - large (h 10.5 cm)



Code 27780 ALUMINIUM WALKING STICK-silver Adjustable height: 68-90.5 cm - weight 0.3 kg Code 27781 ALUMINIUM WALKING STICK - black Adjustable height: 66-90.5 cm - weight 0.3 kg **Code 27782 FOLDABLE ALUMINIUM WALKING STICK** Adjustable height: 82-92 cm - weight 0.3 kg **Code 27790 TRIPODS - FOUR LEG** Aluminium made, height adjustable 72.5-95 cm - 1.1 kg **Code 27793 FOREARM CRUTCHES** Light weight aluminium tube. Anatomic handgrip. Height adjustable 95.5-118.5 cm. Weight 0.95 kg. Max load 130 kg **Code 27798 T-BAR CRUTCHES** Stainless steel type. Adjustable height: 118-130 cm. Max load 130 kg

Arm Slings



Suitable for supporting a sprained or broken arm during recuperation. The shoulder strap is adjustable to allow correct positioning of the arm. Stitched from cotton fabric requiring normal laundry care. Fits any arm. Available in 3 sizes.

GIMA code	Pouch arm slings
28620	Arm sling - small
28621	Arm sling - medium
28622	Arm sling - large

Invalid Rings



Quality	invalid	rings	made	of latex-
free rub	ber.			

	GIMA code	Invalid rings Latex - free rubber
ſ	28610	Invalid ring Ø 35 mm
	28611	Invalid ring Ø 40 mm
	28612	Invalid ring Ø 45 mm

Walking Sticks-Crutches Quality Sticks made in Italy



WOOD STICKS:

Code 27760 GIOTTO CURVED HANDLE - man - brown Code 27761 GIOTTO CURVED HANDLE - woman - brown Code 27762 RAFFAELLO "T" HANDLE - man - brown Code 27763 RAFFAELLO "T" HANDLE - woman - brown

Code 27764 TIZIANO CURVED HANDLE - unisex - brown Code 27765 TIZIANO "T" HANDLE - unisex - brown

Code 27768 LEONARDO METAL CURVED HANDLE - unisex - black Code 27769 LEONARDO METAL "T" HANDLE - unisex - black

Code 27772 TIEPOLO CHROMED "DUCK" HANDLE - unisex - black


PATIENT AIDS

Anti-Decubitus Cushions



28524

Prevention for medium decubitus risk

28522

28526

Prevention for medium-high decubitus risk

Prevention for low decubitus risk

Code 28520 ANTIDECUBITUS GEL CUSHION 40x40x4 cm

Fluid gel grants a perfect distribution of patient's weight by sensibly decreasing the pressure on capillars and avoiding their eventual occlusion. It also gives a pleasant sense of freshness. **Code 28522 VISCOELASTIC CUSHION with hole 40x40x3 cm**

Code 28524 VISCOELASTIC CUSHION without hole 40x40x3 cm

It is composed by a Polyurethane gel layer with high pressure absorbing capacity and by a layer of Polyurethane expanded foam. The two layers are wrapped and protected by a special cover easily removable, with transpirant sitting side and waterproof and anti-slip bottom side. Thanks to the Polyurethane gel the contact pressure decreases and improves the distribution of the same. Cover is made of polyammide threaded with PU, water-proof, transpirant to steam, elastic hypoallergenic and washable in washing machine up to 40° .

Code 28526 AIR FLOATING CUSHION 40x40x6.5 cm Code 28528 AIR FLOATING CUSHION 44x44x6.5 cm Latex cushion with communicating cells. The particular shape of the air cells allows a perfect body positioning and a correct pressure distribution. The alveolar cells allow an optimal adaptation to human shape increasing perspiration and air circulation thus reducing skin maceration. Particularly suitable for patient with skin wounds, medullary lesions, multiple sclerosis, bifid spine. The device is supplied with an anti-slip cover, a pump for inflation and a reparation kit. Available with single valve.

Electric Heating Pad Urine Bags made in Europe

Sold in 4 languages box (English, French,		GIMA code	Urine bags	Minimum order
Italian, Spanish)		28700	Urine bag 2000 cc, tube 90 cm	box of 180
		28701	Urine bag 2000 cc, tube 90 cm	box of 180
	OUGS OF SUP		with non-return/exhaust value	
			18 pouches of 10 pcs.	
		28702	Urine bag 2000 cc, tube 130 cm	box of 180
		28703	Urine bag 2000 cc, tube 130 cm	box of 180
Size: 38x30 cm External cover in cotton (94%) and	14-15-		with non-return/exhaust valve	
nylon, internal bag in PVC	2.20		18 pouches of 10 pcs.	
Code 28655 ELECTRIC HEATING PAD		28706		box of 300
Suitable for many applications. Code 28656 ELECTRIC "SAND" HEATING PAD		AL.	complete with lacets and buttons	
The use of purified marine sands make it possible to	the second s		30 pouches of 10 pcs.	
naturally transmit their beneficial warmth.	1	28710	Men's external catheter Ø 30 mm	box of 30
Operating power:	28700		- latex	
230V-50/60 Hz - 75W (28656) - 55W (28655)		28715	Biadhesive tape	box of 30



Code 28600 HOT WATER BAG 100% made of rubber, latex free blue colour Two side ribbed. Packed in plastic bag with multilanguage user manual



Code 28605 ICE BAG - cap Ø 28 mm Made of rubber fabric (cotton/polyester), latex free. Blue colour. Single packed in carton box, with multilingual manual.



Code 28720 TRAVELLING ENEMA Supplied in carton box with cannula and tubes. Made in Italy. **PATIENT AIDS**

Therapeutic Antidecubitus Mattresses up to level IV



Code 28505

Prophylaxys and therapy of bedsores up to level II° (NPUAP classification). Low-Medium risk patients (Norton classification)

Code 28500 EURO SOFT ANTIDECUBITUS SYSTEM - Overlay with 17 interchangeable elements, to be put on

- traditional mattress. - Washable elements (up to 60° C) made of nylon/polyurethane.
- Bi-elastic cover, flame retardant, antifungine, antibacterial,
- washable, perspirant and impermeable to liquids.
- CPR (Cardio-Pulmonary Reanimation) function allows the quick deflation of system in case of emergency.

- The three-way pump working at alternating pressure allows pressure regulation according to the patient's body weight, up to 130 kg (up to 200 with a little modification).

- Pump machine is equipped with alarm led.

System includes pump, overlay and cover.



Code 28505 EURO SOFT PRO ANTIDECUBITUS SYSTEM

- Mattress with 20 interchangeable elements, replaces traditional mattress.
- Washable elements (up to 60° C) made of nylon/polyurethane.
- Bi-elastic cover, flame retardant, antifungine, antibacterial, washable, perspirant and impermeable to liquids.

- CPR (Cardio-Pulmonary Reanimation) function allows the quick deflation of system in case of emergency.

- The three-way pump working at alternating pressure allows pressure regulation according to the patient's body weight, up to 150 kg (up to 250 with a little modification).

- Pump machine is equipped with alarm led.
- Static/dynamic function.

System includes pump, mattress with inflatable elements, cover, polyuretane foambase and carry-bag

Code 28510 Technical specifications Code 28500 Code 28505 Code 28510 Mattress Size: 200x90x23cm 200x90x23cm 200x90x11cm 6.2 Kg Mattress Weight: 3.8 Kg 7.2 Kg Mattress Material: non toxic nylon/PU Base material: PU-foam, flame resistant (1 IM Class) Pump material: ABS 230V Power supply:

Treatment and prevention of bedsores up to level IV° (NPUAP classification). High risk patients (Norton classification)

Code 28510 EURO PULSE ANTIDECUBITUS SYSTEM

Euro Pulse is a therapeutical real-air-loss system, that prevents patient's skin maceration, thanks to the air loss of mattress elements. The system is equipped with a digital pump machine and a 20-element mattress, divided in three sections (head, chest an legs) working at different pressure levels. The mattress base, made of polyuretane foam, avoids the patient to sink even without pump machine. The pulse therapy can be set both in duration and in amplitude. In each cycle, the three inflatable sections inflate and deflate, then producing a micro-massage stimulating venous and lymphatic circulation.

An electronic sensor reacts to the change of position of the patient's back, preventing the sinking of the sacral zone. Quick inflation function allows to inflate the mattress at the maximal pressure. An acoustic and visual alarm warns on the bad functioning.

CPR (Cardio-Pulmonary Reanimation) function allows a very simple and quick emptying of the mattress, as to promptly reanimate the patient in case of emergency.

System includes pump, mattress with inflatable elements, cover, foambase and carry-bag





Anti-Decubitus Air Mattresses to prevent sores

Code 28482 MASTER PUMP SYSTEM - with pressure adjustment Code 28483 KIT MASTER (AIR MATTRESS 28492 + MASTER PUMP 28482) Made of stiff and strong ABS, it may be placed on the ground, as it has rubber feet, or hung at the edge of the bed. A control handle makes pressure regulation easy: air amount is adjustable to suit patient weight from 40 to 150 kg. The mattress should inflate totally in about 20 minutes. Air output 2.5 l/min. Master pump can be used with bubble or interchangeable section mattress.

Size: 330x150x120 mm Weight: 1.95 Kg Operating voltage: 230 V - 50 Hz Power Consumption: 8 W - CLASS II Working pressure: 60-135 mm/Hg

Technical specifications for Master Pump - Rint Plus Pump Suitable for mattress: bubble or section Regulations: IEC-601-1 class II Type B Made in Italy User manual in English Spanish, French, Italian, German





Code 28492 AIR MATTRESS WITH BUBBLES

This air mattress is divided in bubble sections which inflate and deflate alternatively latitudinally through the alternative compressor. The continual movement given by the pressure pumped inside is useful to prevent minor bedsore problems.

Technical specifications Mattresses										
Code 28488 Code 28492 Code 28493 Code 28495										
Size:	190x85 cm	190x85 cm	190x85 cm	200x90x10.5 cm						
Weight:	2.5 Kg	3 Kg	5.2 Kg	5.5 Kg						
PVC thickness:	0.3 mm	0.4 mm	0.4 mm	0.4 mm						
Number of elements:	-	-	20	17						
Suitable for persons up to	o: 80/90 kg	80/90 kg	100 kg	130 kg						

28495 11 Thanks to height of cells, Rint Plus can be used also with medium risk patients. lasting pump made with high quality materials

CE

50kg - 110 lbs 40 mm/Hg 50-80 kg - 110-176 lbs 70 mm/Hg 80-150 kg - 176-330 lbs 100 mm/Hg

28493 **Code 28493 AIR MATTRESS - with interchangeable sections** It has 20 sections which can be inflated or deflated alternatively. Easy and practical to use, it is ideal for patients with minor bedsore problems. Elements are jointed in-between and fixed to a PVC sheet. Code 28494 INTERCHANGEABLE CELL - spare for 28493 Press studs which attach each section to the supporting sheet

make for easy exchange in case of damage.

Welfare Kit launch Offer - minimum 10 pcs Code 28489 - PUMP WITH PRESSURE ADJUSTMENT + BUBBLE MATTRESS Quality, reliable and economic kit with hook, made in Italy. Code 28487 WELFARE BUBBLE MATTRESS - beige

Code 28495 RINT PLUS AIR MATTRESS - interchangeable cells Rint Plus Mattress is made of a strong and soft PVC, realized with 17 big interchangeable bars. The integrated CPR function (Cardio Pulmonary Reanimation) allows the immediate emptying of the 17 bars. It is supplied with bi-elastic, liquid proof and permeable to water-steam cover.

Code 28498 RINT PLUS PUMP SYSTEM - with pressure adjustment Same as Master pump but with special valve for use with Rint Plus Mattress.

Code 28496 INTERCHANGEABLE CELL - spare for 28495 Code 28497 COVER - spare for 28495

Anti-Decubitus PVC Water Mattress

Code 28499 WATER MATTRESS

It is made in PVC with a stabilising inflatable external structure to prevent excessive water "wave motion" and of 3 independent units. The water mattress distributes the total pressure on the whole supporting surface, making this less than the average arterial pressure, avoiding the exposure of the skin to pressure risk. Easy to use, it is placed over the usual mattress and is washable. It is sold with a manual pump, 2 disinfectants and a filling tube.

Size: 190x85 cm. Weight 4 kg. PVC thickness 0,4 mm



Patient beds with 1 or 3 joints, manual or electric



Specialist bed 3-joints/4 sections, electrical, with adjustable height

electric



2 cranks

electric

Code 27675 SPECIALISTIC BED

All-welded mainframe made of rectangular steel tube. Each section of the mattress platform is fitted with welded grids made of 5 mm. diameter steel rods in rectangular mesh. Foursections mattress platform. Backrest-section and leg-section adjustable by means of two independent electric motors 24V D.C. and push-button. Foot-section adjustable by means of a rack device. Fixed pelvis-section. Removable head and footend frames made of natural solid wood with rounded corners and edges, available with integrated guide for telescopic safety rails.

27671 Bed side table

Legs fitted with 4 castors with simultaneous central brake. Comes complete with support for IV stand, lifting pole and side rails



Code 27677 BEDSIDE TABLE

Manufactured from high density chipboard panels, borders made from solid wood with rounded edges. With drawer, door and removable inner shelf.

Size: 45 x 45 x h75 cm. Made in Italy.

Movement:

1 crank



Mattresses, Covers and Pillows

27682		Mattress, Covers and Pillow	Size 190x80x12	Size 195x85x14
		Mattress foam density 30 kg/mc with Trevira [®] fire-retardant, transpirant, polyester cover. Validation RE1535D20D1 IM00002	-	27682
		Mattress - foam density 30 kg/mc	27690	27680
27680	Flame resistant Size of section 63x85x14 cm	Trevira [®] transpirant, polyester, fire- proof (class 1) cover for mattress	27691	27681
	HILLIN	100% cotton cover for mattress	27693	27683
	111111111	Waterproof cover - universal	276	95
Special structure provides good air ventilation for better perspiration	HHH	Pillow (foam density 21 kg/mc) with Trevira [®] fire-retardant, transpirant, polyester cover	276	
of patient skin.	27697	Antidecubitus mattress and cover	Size 19	0x85x14
11114	4	Antidecubitus expanded polyurethane mattress (density 30kg/mc) - class 1 IM	276	97
	B	Cover Plus bielastic, flame retardant (norms BS7175: 1989), transpirant to steam, waterproof.	276	98
Dmogeneous and optimal listribution of patient weight	27698			43

27696

Trendelenburg Patient Trolley - Stretcher



Professional Ward Stretcher



Code 27819 WARD STRETCHER

Main features:

- **Platform:** all-welded mainframe made of different sections steel tube. Section frame made of oval steel tube 50x25x1.5 mm.
- Push/Pull handle: Made in steel tube Ø 32x1.5 mm.
- Surface finish: Epoxy gloss finish standard grey 7035

- Mattress platform section: Two section mattress platform fitted with removable chrome-plated grids made of 5 mm. Ø steel rods and rectangular mesh 100x50 mm.

- Backrest: Adjustable by means of a rack device. Fixed leg section.
- Castors Four castors Ø 200 mm. made of grey synthetic
- rubber two of which with independent brake.

- **Bumpers:** Four bumpers at the corners made of anti-acid and anti-shock grey resin.

- Delivery stretcher with trolley: If necessary the upper part is detachable to enter ambulance or other use. Made in Italy.



Detachable upper part



For Solaris, it is moveable by four large antistatic castors, 2

base is completely made of stainless steel to ensure perfect stability. It is provided with a locking system to the floor

one pivoting and 2 directional.

- Longitudinal translation

- Movements

encumbrance

Table top size

directional and 2 pivoting with brake. For Gima and Gima TR

through a foot bar. Transport is allowed by 3 antistatic wheels,

For Solaris: Trendelenburg and Reverse/Trendelenburg with

"quick action" by a gas spring and lateral tilt right-left 20° by

model Gima TR offers manual longitudinal translation of table

Technical specifications

Code 27560

200x48 cm

crank. For Gima and Gima TR same table movements as

above, work through a mechanical system moved by two

top of about 300 mm to allow total elimination of column

cranks, positioned at the side, easily retractable.



Designed to satisfy surgical functionality, practicality, quickness and easy maintenance. They allow, with proper accessories, to satisfy every basic surgical activity

- Table top

Divided in 5 sections (head, back, pelvis, 2 indipendent leg sections) with stainless steel structure and plexiglass to allow x-ray permeability and easy cleaning.

Table top is pre-arranged for the insertion of x-rays holders all over its length.

Accessories holder (25x10 mm) in stainless steel, covers table top length on both sides.

- Telescopic column

Square and of limited size, covered by anodized aluminium (27560) or stainless steel (27562/4)), it allows up and down movement (70-100 cm) by a foot pedal placed at the base through a closed oleodynamic circuit with oil-tight pump avoiding any oil leakage.

- Mattresses

They cover all the table top lenght. Made in a long lasting material, sterilizable in autoclave, x-ray translucent and Thou are independently r

elasti	cs. They are independently removable.	Height	70-100 cm	75-105 cm
GIM code	Onerating tables	Hydraulic lifting system - Trendelenburg	200	250
	1 0	U U	30°	35°
2756	O Solaris operating table	- Reverse Trendelenburg	30°	25°
2756	2 Gima operating table	- Lateral tilt right-left	20°	25°
2756	1 8	Table top composition		
2750		- Head section	extractable and inclinable (+25	/
	translation of table top - 100% radiotransparency	- Back section	inclination: $(-40^{\circ} + 80^{\circ})$ by gas	1 0 (
GIM	On susting tables according 1000/ stainlass stal		(-20° +80°) by gas	spring (Gima)
code	Operating tables accessories - 100% stainless steel	- Pelvis section size	size 48x51 cm	
2757	Two-hook adjustable IV stand (needs clamp 27571)	- Leg section	size 48x49 cm	
2757	•	- Leg section	divided in two independent see with following manual movem	
2757	1 1 11		• opening right/left of 0°/90°	lents
			• inclination +30° -90°	
2757				1 41 4 4 - 1- 1 -
2757	4 Leg holder with radio transparent valve and	Table weight:	• both parts are easily independ	
	cushion - couple (needs clamp 27575)	Operating table capacity:	90 kg 200 kg	160 kg 250 kg
2757		Made in Italy	200 kg	230 Kg

Code 27562-27564

200x48 cm

Gynaecological Chair, Stool and Work Station





Gynaecological and **Delivery Beds**



Code 27500 DELUXE GYN BED - quality leg holders Code 27501 GYNAECOLOGY BED - standard leg holders Strong structure in chrome-plated. Rectangular steel tube. Adjustable head and leg sections. Simulated leather, black colour, washable upholstery, self extinguishing. Complete with s/s bowl Ø 30 cm and leg holders. Made in Italy. Code 27510 DELUXE DELIVERY BED - quality leg holders Same as above, but with three sections with independent controls and Trendelenburg position. Code 27503 STANDARD LEG HOLDERS - couple Code 27504 QUALITY LEG HOLDERS - couple

Kit leg holders include 2 leg holders and arm.

Wood Couch for Cardiology and Physiotherapy



Code 27416 WOODEN EXAMINATION COUCH Code 27417 WOODEN EXAMINATION COUCH - with hole Comfortable couches, ideal for physical therapy, cardiology and wellness centres. Superior quality beech wood from the Black Forest. Back rest adjustable in 13 positions. Resilient foam padding covered with washable and fire-proof weave. Available in cream colour. Size: 190 x 70 x h70 cm. Delivered in kit form. Easy assembly, tool provided.

Made in Italy.

Code 27409 COUCH ROLL HOLDER for 27416 and 27417

Electric Height-adjustable Examination/Treatment Tables



Examination Couches and Foot Stools

Backrest adjustable through different

positions

Couch size **Code 27401 EXAMINATION COUCH - chromed - black mattress** Code 27402 EXAMINATION COUCH - white painted - grey mattress^{180 x 61 x h 75 cr}

27402

27404

27401

Suitable for medical office or small surgeries. Easy to assemble, following enclosed instructions. Comes complete with mattress. Upholstery in two sections: one 130 x 61 x h 5.5 cm fixed and a 50 x 61 x h 5.5 cm backrest

adjustable through different positions.

Delivered in kit form. Universal couch roll holder (code 27418, not included)

Made in Italy.

Code 27418 COUCH ROLL HOLDER

Adjustable roll holder suitable for round (Ø27-30 mm) or square (27-30 mm x 27-30 mm) metal couch leg.

Code 27980 FOOT-STOOL - one step Code 27981 FOOT-STOOL - two steps Mounting steps with tubular frame and plastic foot board. Load 90 kg. Non slipping platform 40 x 20 x 1.5 cm Made in Italy

Code 27404 CLASSIC EXAMINATION COUCH - beige - chromed **Code 27405 CLASSIC EXAMINATION COUCH - blue Backrest with hole - chromed**

27981

Chromed mainframe and legs constructed in chrome-plated steel. Legs fitted with plastic feet. The two-section top has resilient foam padding covered with washable and fire-proof plastic material. Backrest fully adjustable. Available in cream or blue colour. Other colours on request, minimum 10 pieces. Size: 180 x 57 x h73 cm. Delivered in kit form. Made in Italy.

Suitcase Couch

Code 27407 SUITCASE COUCH Chromed steel and folding legs. Upholstered covering in washable material. Padded in resin. Available in black colour. Weight 17 kg. - Max load: 95 kg Supplied with a velvet bag for easy transport. Made in Italy. CE 27407 Couch size: 185 x 64 x h 70 cm (open) 95x65x16 cm (folded)

Aluminium Suitcase Couch

Simulated leather, black/grey colour

washable upholstery in two sections

CE

CE

27980 25 cm

27405

Code 27406 ALUMINIUM SUITCASE COUCH with hole Light, foldable, two sections, suitcase couch with aluminium frame. Central double legs for improved safety and block system on the hinges. Head rest with mouth/nose hole. Upholstered and covered with simulated leather. Maximum load: 110 kg Weight: 12 kg Made in Italy. F



Size: 62x182 cm



Couch paper - rolls and Hand Paper Rolls/Towels



Pharmacy Cabinet



Code 27915 MEDICINE CABINET - with inner dangerous drugs compartment. Entirely constructed from bilaminate 20 mm thick,



standard colour grey (ABET 478). Base made of 4 legs diam. mm 60 with adjustable ABS feet. Two lockable doors turning through 270° fitted inside with 2 ABS thermoformed containers with 16 medicine compartments; perimetrical anti-dust gaskets. Inside cabinet: two double ABS thermoformed containers turning through 90° with 32 medicine compartments complete with transparent plexiglass rings; 5 shelves adjustable; **dangerous drugs compartment provided with lock** and drop front to be used as working top. Dimensions 100x60x h. 190 cm. Made in Italy.

.

Doc	ctor Cabinet			
27970		27988 27903 27990		
27403		27429 27932	27991 27991 Code 27991 STUE LIGI Metal tubolar fram plastic base with 5 wheels (one with	HT ne with 5 plastic brake).
27985	27980		Technical specific 100 Watt lamp (not in Power supply: 220 V	
GIMA code	Product	Description	Size	Weight
27920	DESK - with 2 drawers	Desk with 2 side drawers with locking top drawer and enamelled tubular steel frame	1 120x70x76	27
27403	EXAMINATION COUCH	Single-hinged examination table with chromed steel tubular fram Comes complete with simulated leather mattress (grey), backrest adjustable throught different positions. Delivered in kit form.		22
27984 27985	WASTE BIN - enamelled steel - stainless steel	Made of enamelled steel with plastic inner bucklet - capacity 7 1 Made of AISI 304 stainless steel with plastic inner bucklet - capacity	71 30x25x28 30x25x28	2 2
27988	COAT HANGER	Free-standing coat hanger with chromed tubular steel frame and spoke base - 6 knobs		8
27990	LIGHT	Not medical. 100 W Itallumag tubular frame with 5 spoke base 40 mm castors. Adjustable height. Lamp not included.	on	3

Illuminated and not Illuminated Optometric Charts

HB U	N X V	đi		E B	GIMA luminous optot according to clinical re extra white light to giv reading of any detail.M screen, and according Shuko plug, green light	ecommendatio ve an accurate Manufactured v to safety norm	ns for an and precise with acrylic
				0 L U H C P & T T T T T T T T T T T T T T T T T T T	Technica Viewing Area: 24 x 62 cr External dimensions: 29.5 Weight: 6 kg / 2 kg Mad Other specifications like r	5x67.5x12 cm / 29 le in Italy	
		1444244	3 400000 A	====	Optometric charts	Illuminated GIMA code	Not illuminated GIMA code
MIXED DECIMAL 3m Code 27382	MONOYER 3m Code 27381	CHILDREN 3m Code 27383	ANIMALS 5.5m Code 27384	ARMAGNAC 5m Code 27380	Armagnac - 5 m Monoyer - 3 m Mixed decimal - 3m Children - 3 m Animals - 5 m Spare Tube 700	27380 27381 27382 27383 27383 27384 27388	27390 27391 27392 27393 -



X-ray Illuminators - Negativoscopes

Bipolar light switch

Deptl

12

12

12

12

12

12

12

12

12

Weight

6

8

11

14

18

28

36

11

14

NEGATIVOSCOPES - X-RAY ILLUMINATORS GIMA negativoscopes have been designed according to

to safety norms (fuses, Shuko plug, green light On/Off, ...). They may be used on the table placed horizontally,

Body composed of oven-fired epoxy powder coated aluminium and injected ABS (colour RAL 7035).

> Colour temperature: Cool white 6500 °K Power supply: 230 V - 50 Hz

Technical specifications

All components UL, DVE, IMQ approved Made in Italy

lengh

43

67

97

127

158

127

158

43

43

External dimensions (cm)

Height

43

43

43

43

43

2x43

2x43

97

127

accurate and precise reading of any detail.

vertically, or wall mounted.

Protection fuse: 2x1A Schuko plug with 2 m cable

X-ray illuminators - negativoscopes

Negativoscope 38 x 38 cm

Negativoscope 38 x 62 cm

Negativoscope 38 x 92 cm

Negativoscope 38 x 122 cm

Negativoscope 38 x 153 cm

Negativoscope 76 x 122 cm

Negativoscope 76 x 153 cm

Negativoscope 92 x 38 cm

*Products not in stock, available in 30 days

27373* Negativoscope 122 x 38 cm

GIMA

27364

27365

27366

27367

27368

27369

27370*

27372

clinical recommendation for an extra white light to give an

Light source:straight daylight fluorescent tubes

CE



GIMA code X-ray illuminators - negativoscopes External dimensions (cm) Weight Lenght Height Depth Depth 27360 35 x 43 cm 44 39 13,5 6 I panel 27360 25 x 42 cm 44 39 13,5 6 I panel	GIMA clinic an acc Manu safety The u	NDARD AND ADJUST A negativoscopes have l al recommendations for curate and precise readi afactured with metacryla norms (fuses, Shuko p unique film gripping sys White colour. Made in	been de r an ext ng of a ate scre lug, gre tem giv	esigne ra wh ny det een, an een lig	d follo ite lig tail. id acco ght On	owing ht to g ording v/Off, .	ive to).		Cool white 6500°K d fluorescent light source supply = 220 V - 50 Hz	ADJUSTABLE
		X-ray illuminators - negativoscopes				Weight				
272(1) 25 - 42	27360	35 x 43 cm	44	39	13,5	6		1 panel	(E	
2/301 35 X 43 cm - adjustable 44 59 15,5 6 1 I panel	27361	35 x 43 cm - adjustable	44	39	13,5	6		1 panel		

Ultra Slim Negativoscopes

The n LCD best v	A NEGATIVOSCOPE new generation of negati technology and colour t vision and interpretation ole support for horizonta	ivoscop temper of rad	ature o iograpl	f 850 hy.	0°K f	or			
	Technica Colour temperature: Cool Power supply: 230 V - 50 LCD Technology Bulb life: 60.000 hours All components UL, DVE Made in Italy	white 85 /60 Hz	500 °K						
GIMA code	X-ray illuminators - negativoscopes	Externa Lenght	l dimension Height	ns (cm) Depth	Weight			STREET, STOR	1222222 100015
27374	Negativoscope 41 x 36 cm	44	49	3	4		l panel	Designed 18.2.3	1992
27375	Negativoscope 41 x 72 cm	80	49	3	6		2 panels	100	CONTRACTOR OF STREET
27376	Negativoscope 41 x 109 cm	118	49	3	10		3 panels		CALL CONTRACTOR OF CALL OF CAL
27377	Negativoscope 41 x 145 cm	154	49	3	12		4 panels		

Cabinet with 1, 2, 4 doors



GIMA CABINETS Choice of cabinets with enamelled sheet steel structure and temperated glass. Rack-mounted adjustable glass shelves. Code 27901 CABINET - 1 door Code 27905 CABINET - 2 doors Code 27903 CABINET - 4 doors Code 27911 WALL CABINET - sliding door

Technical specifications	27901	27905	27903	27911
Door:	1	2	4	2
Adjustable shelves:	3	4	3	2
Weight kg:	26	49	42	12
Size cm:	53x36x144	75x38x169	75x38x169	

3 or 4 Wings Ward



Chairs

27911



27932

Code 27930 CHAIR plastic seat Enamelled steel frame chair with laminated plastic seat and back Stackable. Load 120 kg. Code 27932 CHAIR padded seat

Itallumag frame chair with grey padded seat and back. Stackable. Load 120 kg. Code 27933 CHAIR padded seat with armchairs

Same as 27932 but with padded armrests.

Made in Italy

Stools



Code 27950 STOOL - s/s seat - foot Code 27951 STOOL - s/s seat - castors 50 mm Height adjustable seat in AISI 304 stainless steel. Ø 28 cm. Height 44/56 cm. Weight 5 kg. Code 27948 STOOL - s/s seat- foot aluminium Same as code 27950 with aluminium base Code 27952 STOOL - padded seat - foot Code 27953 STOOL - padded seat - castors Adjustable height seat in washable grey padded simulated leather, Ø 31 cm. Adjustable height 49/61. Weight 5 kg. Delivered in kit form. Made in Italy

Doctor Trolley



Code 27446 DOCTOR TROLLEY Useful trolley made of plastic material (ABS) provided with 9 drawers of different sizes. Height of drawers: two 8.5, five 5.5, two 2.7 cm. Size: 38x30xh72 cm. Made in Europe



Office Chairs with Armrest



Code 45070 CUNEO - fabric - red Code 45071 CUNEO - fabric - grey Code 45075 CUNEO - leatherette black - fireproof

Functional office upholstered chair, with armrests and polypropylene swivel base, movable backrest with permanent contact. Perfect solution for consulting rooms/offices.

Weight	Backrest height			Depth
12 Kg	98/111 cm	42/52 cm	56 cm	49 cm



Code 45081 CREMONA - fabric - grey Code 45082 CREMONA - fabric - blue Superior quality chair with neat linens, upholstered seat and backrest for greater comfort, swivel base, armrests, permanent contact movement of the backrest. High density and thick foam. ENI 1335/1/2/3.

Weight	Backrest height	Seat height	Width	Depth
12 Kg	90/107 cm	45/52 cm	58 cm	44 cm



Code 45090 REGGIO GREY - fabric - red Stylish chair with armrests, swivel base, upholstery with comfortable foam, permanent contact of the back and gas height adjustment. Modern round grey frame make it suitable for any environment. ENI 1335/1/2/3.

Weight	Backrest height	Seat height	Width	Depth
12 Kg	95/108 cm	45/57 cm	62 cm	45 cm

Executive Chairs Visitor Chairs



Code 45120 SALISBURGO executive swivel chair - leather - black Code 45122 SALISBURGO visitor cantilever chair - leather - black High and low back stylish executive chairs. Refined lines and maximum comfort. 2 positions tilting movement, swivel base, polypropylene armrests, height adjustable by gas jump.

GIMA Code	Weight	Backrest height	Seat height	Width	Depth
45120	17 kg	118/128 cm	43/53 cm	62 cm	55 cm
45122	14 kg	95 cm	45 cm	62 cm	55 cm

Visitor Chairs



Code 45030 ISO - fabric - red Code 45032 ISO - fabric - blue Code 45035 ISO - leatherette - black fireproof

Comfortable upholstered chair with 4 legged frame. Can be used for patient and waiting rooms, with Cuneo and Cremona chairs.

Comfortable seat made of expanded polyurethane hit injected heliocell foams.

Weight	Backrest height	Seat height	Width	Depth
7 Kg	82 cm	45 cm	53 cm	43 cm

Chairs



Code 45050 CUNEO B - fabric - red Code 45051 CUNEO B - fabric - grey Code 45055 CUNEO B - fabric - black Low back swivel chair, without armrests. Permanent contact of the backrest and height adjustable by gas pump.

Weight	Backrest height	Seat height	Width	Depth
11 Kg	85/98 cm	42/52 cm	56 cm	49 cm



Operating Room Inox Cabinets



27917

Code 27917 INOX CABINET Made of AISI 304 stainless steel. Two lockable doors (10/10 thickness), 4 adjustable shelves (8/10 stainless), 4 adjustable feet, with stainless steel cover.

Size: 100x48xh190 cm. Made in Italy



Code 27918 GLASS-INOX CABINET Made of AISI 304 stainless steel with two lockable doors in temperated glass 5 mm thick, 4 shelves in temperated glass 6 mm thick and 4 adjustable feet. Size: 100x48xh190 cm. Made in Italy

Anaesthetic Trolley



Code 27437 ANAESTHETICS TROLLEY

Made of satined AISI 304 stainless steel, with 6 drawers (internal 26x37xh7 cm), a vertical compartment and an open space. Top with 3.5 cm upstand. 4 revolving castors Ø 80 mm Size: 60x40x h 110 cm Weight: 41 kg Made in Italy

Instruments Trolleys



Code 27438 TRIS TROLLEY A practical trolley for ECG, Electrobisturi or any other device, with 4 nylon castors and 2 lateral handle for easy moving. Revolving castors Ø 50 mm. Size: 49 x 37 x h 77 cm. Shelf size: 40 x 30 cm. Colour: RAL 9002 **Delivered in kit form.** Made in Italy



27441 Castors Ø 100 mm (2 with brake).

produced without upstands at four sides for an easier cleaning of the trolley.

Code 27441 EXCEL TROLLEY -4 shelves (60x45cm) Size: 60x45x h110 cm. Code 27440 EXCEL TROLLEY -3 shelves (60x45cm) Size: 60x45x60 cm. Delivered in kit form. Made in Italy

Professional Cart





Multifunctional Cart

I.V. Stands



SUPER EASY CART: A new stylish and quality cart you can build according to your needs

Build up your favourite cart

Technical specifications Dimensions: 470 x 426 x 790 mm	GIMA code	Super Easy
Shelf: 320 x 260 mm Load capacity: total load 120 kg shelf 10 kg 4 castors Ø 80 mm	27870	Standard cart with handle and 1 shelf
Material: - extrusions in aluminium - plastic parts in ABS Made in Italy	27872 27873 27874	Extra shelf Basket Infusion stand

Easy Cart



Technical	l specifications	
Dimensions (WxDxH):	500 x 450 x 790/880/1120 mm	
load capacity:	total load 140 kg	Ι.
	shelf 25 kg	
helves:	400 x 360 mm	
castors Ø 80 mm		
Aaterial: - vertica	al aluminium extrusions	
- plastic	parts in ABS	
Iade in Italy	•	

D

L

S

4

Ν

A complete stylish line with 4 carts for all your needs

GIMA code	Easy Cart Line
27880	Cart h79 cm 3 shelves 40 x 36 cm
27881	Cart h88 cm 4 shelves 40 x 36 cm
27882	Cart h112 cm 5 shelves 40 x 36 cm
27883	Cart h79 cm 3 shelves 40 x 36 power



Smart Cart



27896 Cart h90 cm 4 shelves 40 x 36 cm **27897** Cart h115 cm 5 shelves 40 x 36 cm

Stainless Steel, Instrument and Dressing Trolleys



27430

Code 27430 INOX TROLLEY

AISI 304 Stainless steel trolley with plastic drawer internally divided in 4 sectors. 2 shelves with upstands (3,5 cm) on four sides. Revolving rubber castors Ø 80 mm (two with brake). Size: 70x50x h. 82 cm **Delivered in kit form**. Made in Italy



Code 27433 MEDICAZIONE TROLLEY - small Size: 60x40x h 81 cm - weight 9 kg Code 27434 MEDICAZIONE TROLLEY - medium Size: 70x50x h 82 cm - weight 10 kg Code 27435 MEDICAZIONE TROLLEY - large Size: 90x60x h 85 cm - weight 15 kg AISI 304 stainless steel trolleys, with push handle, 2 shelves with upstands (3,5 cm) on four sides, 4 revolving rubber castors Ø 60/80/100 mm.

Delivered in kit form. Made in Italy



Code 27431 TER TROLLEY AISI 304 Stainless steel trolley, with push handle. 3 shelves with upstands (3,5 cm) on four sides 4 revolving rubber castors Ø 80 mm Size: 70x50x h 82 cm - weight 13 kg **Delivered in kit form**.

Made in Italy



Code 27436 DRESSING TROLLEY Dressing trolley made of AISI 304 stainless steel with 2 70x50 cm shelves, 1 drawer (40x50x h 15 cm), basin holder and basin. 4 revolving castors Ø 100 mm Size: 70x50x h 80 cm Weight: 18 kg Delivered in kit form Made in Italy



Code 27460 DELUXE TROLLEY Code 27461 DELUXE TROLLEY with drawer 62 x 42 cm Size: 65 x 45 x h 80 cm Top quality Trolleys made of lightweight anodized special alloy, with detachable stainless steel shelves. 4 revolving rubber castors Ø 80 mm. **Delivered in kit form.** Made in Italy.



Code 27429 GIMA 2 TROLLEY - small: 60x40x h 77 cm - Weight 15 kg Code 27425 GIMA 2 TROLLEY - medium 70x50x h 77 cm Practical trolleys with aluminium body and handles. With 2 white bilaminated shelves 18 mm thick, black PVC bordered, with guard-rail. Two large lateral handles facilitate transport or lift up of the trolley. 4 revolving nylon castors Ø 80 mm Code 27426 GIMA 3 TROLLEY - medium 70x50x h 77. Same as GIMA2, but without guard rail. Delivered in kit form. Made in Italy.

Mayo tables





Code 27453 MAYO TABLE - 5 spoke Code 27454 MAYO TABLE - s/s base S/s tray size $68 \times 46 \text{ cm}$ (removable for code 27454). With 5 spoke with castors, 50 mm Ø (27453), or AISI 304 s/s base with 4 castors, 50 mm (27454). Adjustable height: 70 to 110 cm Weight: 9.3 kg (27453 and 27454) Code 27455 MAYO TABLE with pump Similar to 27454, but with pump. Removable s/s tray, size 75 x 54 cm, s/s AISI 304 base with 4 castors (50 mm) Adjustable height: 85 to 120 cm Weight: 23 kg Size: 68x44x h85/120 cm Delivered in kit form Made in Italy

Overbed table



Bowl Stands

Code 27456 SINGLE BOWL STAND Code 27457 DOUBLE BOWL STAND

Chrome plated steel stand with stainless steel base and 5 plastic wheels, one with brake. Adjustable height from 60 to 95 cm Stainless steel bowl Ø 32 cm Available with one or two bowls. Delivered in kit form.



Laundry trolley

Rex trolley



Code 27439 REX TROLLEY

Complete stainless steel dressing trolley. Supplied with 3 shelves, waste bin, drawer, support for bottles, guard rails on the two bottom shelves, 4 wheels (2 with brakes). Size: 90x80x h 80 cm. Delivered in kit form.

Soiled linen trolley



Code 27458 OVERBED TABLE Chrome plated steel stand, painted steel base. Tiltable and sliding serving tray made of thermoformed anti-shock plastic material with retaining edges and incorporated bottle, glass and cutlery holder.

Base with 4 \emptyset 50 mm castors. Adjustable height: 80 to 115 cm Size: 42 x 65 x h80/115 cm. Delivered in kit form. Made in Italy



Code 27465 LAUNDRY TROLLEY This trolley allows to collect dirty laundry while distributing clean linen at the patient bedside. Stainless steel frame. Equipped with 4 Ø 125 mm castors (2 with brake) and 4 rubber bumpers at corners. Size: 1330x650x h 1040 mm. Made in Italy



Code 27467 SOILED LINEN TROLLEY Chrome plated frame with 3 castors Ø 80 mm. Removable bag. Size: Ø 46x h 95 mm. Delivered in kit form.



Record Holders, X-Ray Film Holders, Pharmacy



Code 27491 RECORD HOLDERS TROLLEY **Code 27492 RECORD HOLDERS TROLLEY - 2 large drawers**

Record trolleys are designed to hold clinical writing surface. Frame is in painted steel reports in A3/A4 format or specific format. Frame in painted steel base, working surface and panels in tecnopolimer plastic. Equipped with 4 Ø125 mm revolving rubber castors (2 with brake). Made in Italy. 4 Ø125 mm revolving rubber castors Size: 820 x 640 x 1000 h mm(code 27491) 820 x 640 x 1150 h mm (code 27492) **Code 27493 FILE RACK**

Code 27488 X-RAY FILM HOLDER

This trolley has 32 extractable compartments, a wide top surface, 4 side document holders, and a sliding out with sliding-in bilaminated doors with a 270 ° opening.

Base and lateral cabinets are made in tecnopolimer material. Equipped with (2 with brake). Size 820x640x1200 h. mm

Made in Italy.

58

Code 27497 PHARMACY TROLLEY large - 30 3-compartment partition A portable pharmacy, allowing to manage daily or weekly treatment of patients, with 20/30 3 compartments small drawers for easy drug storage (60-90 spaces). Painted steel frame, tecnopolimer surface and panels. Can be completely closed by safety key lock. Provided with 4 revolving castors Ø 125 (2 with brake); Size 820/1150 x 640 x 1000 h mm. Made in Italy.

Code 27498 PARTITION - 3 compartments



ELECTROMEDICAL DEVICES

Iono Base

Code 28316 IONO base - Galvanic Ionophoretic generator Local administration of medicines by Ionophoretics, electric osmosis and treatment of hyper hydrosis and cellulitis. Current generator for hydro galvanization and aesthetic shaping. IONO base has been developed for users with limited technical knowledge and it is characterized therefore by its simplicity and safety of use, although it maintains characteristics of a professional equipment. Complete kit of accessories for treatment (see photo). It comes with ABS case and velcro elastic Velcro bands, rubber conductive electrodes 80x120mm and 50x50mm elastic and envelopes sponges for electrodes. hand

Technical specifications Operating Voltage: 230 V - 50 Hz Absorbed Max Power: 3 VA Max Output Current: 20 mA Safety class: II BF - **(€** 93/42/EEC. Made in Italy.

Domiciliary Electric Stimulator

Code 28319 STIM base - 2 channels

Medium frequency bipolar electric stimulator. Invigorating and rehabilitative treatment subsequent to prolonged immobilization due to traumas or fractures. Useful for the muscle building up in the athletic and for treatment of the cellulitis, hypotonic gluteus, pectoral and abdominal muscles. High intensity current provided for therapeutic hyperstimulation. Supplied in ABS case with all standard accessories shown in this picture.

Code 28317 KIT OF 4 ELECTRODES - spare

Technical specifications Operating Voltage: 230 V - 50 Hz Absorbed Max Power: 10 VA Max Output Current: 60 mA Safety class II BF - **C€** 93/42/EEC Made in Italy

GIMA TENS

Code 28360 TENS E-701 - dual channel Code 28352 GIMA TENS with L.C.D. display

GIMA Tens are transcutaneous electrical nerve stimulators controlled by a micro-processor. They relieve the symptoms of muscular pain, poor circulation, peripheral numbness, fatigue, stiff shoulder, neuralgia. Supplied in rigid case with instructions, 9 V battery, 2 patient leads, 4 adhesive electrodes. **Code 28351 ELECTRODES FOR TENS - single patient** 40 x 40 mm - pack of 4 electrodes Code 28354 CABLE FOR TENS sold before 04.2002

Code 28353 CABLE FOR TENS sold after 04.2002 **Code 32205 9V ALKALINE BATTERY**

Technical specifications 28360/28352 Channel: dual, isolated between channels Wave form: asymmetrical bi-phasic square pulse Voltage: adjustable, from 0 to 4.2/5 Vrms (max output) Pulse Rate: adjustable, from 2 (28360) or 1 (28352) Hz to 150 Hz Pulse Width: adjustable, from 30 uS to 260 uS



Size 125x67x25 mm

Infrarex: Therapeutic Heating device

Code 28650 INFRAREX 230V-50/60 Hz Code 28651 SPARE BULB 7.5W

Envelopes

electrodes

sponges for



(€ 0051

Infrarex is a modern scientifically electronic therapeutic heating

device which provides deep, infrared heat that can penetrate far below the surface of the skin to produce a shooting, comforting effect upon the nerves. It relieves muscular tension, reduce inflammation and provides pain relief without medication for many conditions such as: arthritis, bursitis, sinusitis, tennis elbow, back ache, neuralgia, muscular pains, aches, sprains, and other musculoskeletal aches.

Infrarex provides pain relief without medication, you will experience pain relief within 10-15 minutes. No concern for side effects, simple to be used.







28360

(🗲 0197

Precise adjustmen of amplitude: intensity is increased by 1mA each step from 1 to Weight 150 g 80 mA

ELECTROMEDICAL DEVICES

GIMA UT Automatic: Ultrasound Therapy Unit



ultrasound therapy unit without head GIMA UT Automatic is an automatic system for ultrasound therapy which makes possible the use of any ultrasound head with oscillation frequency from 0.5 MHz to 3 MHz. Pulse frequency is 2 pulses/second. Pulse time is selectable from 10% to 100 %, through a digital keyboard.

Technical specifications

Treatment time: programmable from 1 to 99 minutes Selectable pulse/time%: 10%-20%-30%-50%- 100% Pulse frequency: 2 pulses/second Max. power: 3 W/cm² Operating voltage: 115/230 V - 50/60 Hz - switchable Size: 360 x 265 x 150 mm Weight: 8 kg Safety class I BF - C€ 93/42/EEC Norms: EN 60601-1 (CEI 62-5)/IEC 601-2-5 (CEI 62-23)

Maximum output power is: 37.7 W (3 W/cm²) for standard head, 5.28 W (3 W/cm²) for thin head.

Luminous read-out for distributed power.

Gima UT is recommended for: ultrasound lipoclasia, sports medicine, arthritis, artrosis, neuralgie and lumbago. Supplied with power cord and user's manual. Made in Italy.

Code 28312 1 MHz ultrasound head Ø 60 mm Code 28314 1 MHz ultrasound thin head Ø 15 mm Automatic ultrasound head with 1 MHz oscillation frequency. Recommended for physiotherapy.

Code 28313 3 MHz ultrasound head Ø 60 mm Code 28315 3 MHz ultrasound thin head Ø 15 mm Automatic ultrasound head with 3 MHz oscillation frequency. Recommended for aesthetics.

Electrotherapy: GIMA ET2 programmable



GIMA code	GIMA ET 2 spare parts	Minimum order
28332	Connecting cable	-
28333	Rubber electrodes 120x80 mm	box of 10
28334	Sponge bags for electrodes 120x80 mm	box of 10
28335	Rubber electrodes 50x50 mm	box of 10
28336	Sponge bags for electrodes 50x50 mm	box of 10

Code 28330 GIMA ET 2 programmable - 2 channels ET 2 is a modern apparatus for electronic diagnosis and a vast field of low frequency electrotherapy applications. The varied impulsive current delivered by this unit can be used for therapy in painful syndromes and circulatory throngs as well as in the rehabilitation of muscular tissues and for invigorating hypertrophizating treatment in passive gymnastics for aesthetic purposes.

Standard accessories	
Power cable 2 m	
4 cables for electrodes connections	
4 rubber electrodes 120 x 80 and 4 rubber electrodes 50x50)
4 cushioned bags for electrodes 120 x 80: and 4 bags 50x5	0
3 velcro elastic belt in para rubber, length 1 m - 60 cm and	40 cm
User Manual	
Technical specifications	
Channels: 2	
Current adjustment independent for each channel	
Programmable treatment from 1 to 99 minutes	
Action time: 1 ms - 5 sec (10 ms - 50 sec for FAR4)	
Repetition frequency: 1 - 500 Hz.	
Max current intensity impulsive: 60 mA - galvanic: 25	mA
Operating voltage: 115/230 V - 50/60 Hz	
Size 470 x 250 x 150 mm weight: 6 Kg	
Norms: EN 60601-1 (CEI62-5)/IEC601-2-10 (CEI62-2	24)
Class I type BF 93/42 EEC	



Magnetotherapy Units: Domiciliary and Professional models



Code 28326 MAGNETOTHERAPHY PROFESSIONAL - unit only Code 28327 KIT: 1 BELT + 2 PLATE TRANSDUCER - 100 Gauss Code 28323 VELCRO ELASTIC BAND 100x8 cm - spare Code 28325 CYLINDER Ø 24 cm - 100 Gauss Code 28329 CYLINDER Ø 50 cm - 80 Gauss Code 28328 CYLINDER Ø 60 cm - 80 Gauss

MAGNETOMED is an ELF magnetotherapeutic unit designed for ambulatory or at patient home professional applications. It is useful in the therapies that require treatments repeated for a long period and/or long duration accessions, or therapies on traumatized or immobilized patient that have difficulty to reach a physioterapeutic ambulatory. **Applications**

The principal effects of the ELF magnetic therapeutic fields are: - antiaedemic, antalgic, antiflogistic, regenerative Main field of application are: traumatology, rheumatology,

angiology, neurology, dermatology, endocrinology

Technical specifications Working frequencies: 2, 5, 10, 20, 30, 40, 50, 60 Hz.

Intensity control: 20, 40, 60, 80, 99% Waveform: rectangular Time of treatment: 1-99 min Active channels: CH1 - CH2 - CH1+CH2 Operating Voltage: 115/230V - 50/60 Hz switchable Power: 220 VA Norms: EN60601-1 (CE162-5) - **(€**93/42 EEC



Plates and Cylinder are not included in standard configuration.

Code 28321 GIMA MT BASE PLUS - magnetotherapy

Magneto Base + is an ELF low frequency magnetotherapic unit designed for domiciliary applications. The most important effects of the magnetic fields are: Antiedemigen / Analgesic / Antiphlogistic / Regenerative and have applications in: traumatology, rheumatology, angiology, neurology, dermatology, endocrinology. The magnetic field produced is impulsive. Internal generator of square waveform electrical current with frequency varying from 10 to 99 Hz and impulse time varying so to obtain a field's intensity determinated from 10 to 80 Gauss. Internal sound sensor of magnetic field and safety system in the case of short-circuit. Two transducers can be connected in the same time (the field produced by each transducer is half of total).

GIMA code	Accessories for Magnetotherapy	Minimum order
28322	Plate transducer 70 x 120 mm	1 pc.
28323	Velcro elastic band 100 x 8 cm	1 pc.

GIMA MT base: standard accessories GIMA MT base unit power cable 1 velcro elastic band 100 x h. 8 cm 2 plate transducers 80 gaus - 120 x 70 mm 1 velcro elastic band 60 x h. 8 cm Manual (English, Italian)

tis supplied with all accessories in a plastic case.

Technical specifications Waveform: square Max. ratio emission/pause: 50% Selectable magnetic field from 10 to 80 Gauss Selectable frequency: from 10 to 99 Hz. Intensity of magnetic field: 80 Gauss (8mT) Operating voltage: 230V/50-60 Hz Size: 193 x 138 x h. 68 mm. Weight: 1 kg Safety class: II BF - Norms: EN60601-1 (CE162-5)

ELECTROMEDICAL DEVICES

Nebulizers for Domestic Use



Eolo Nebulizer - piston

Code 28097 EOLO NEBULIZER - piston

Innovative portable, easy to use nebulizer for home use, recommended to nebulize antibiotics and bronchodilator drugs.

Plastic body with high thermal insulation. Supplied with adult and pediatric face mask,

bulb, mouthpiece, air tubing and air filter. Made in Italy

Betaneb Nebulizer - piston

Code 28098 BETANEB II - piston, light green colour 230 V Stylish and portable nebulizer for a quick and efficacious aerosol therapy. Supplied with adult and paediatric face mask, nebjet bulb,

mouthpiece, nasal prong and connection tubing. 5 language box and manual.





	Technical specifications		
	28097 Eolo Nebulizer	28098 Bet	
perating voltage:	230V/50Hz/170VA	230V/50 H	
perating pressure:	0.9 bar	0.65 bar	
ir flow:	12 l/min	14 l/min	
ax Pressure:	2.5 bar	2 bar	
imensions:	22x14.5x12 cm - 1.7 kg	14x25.5x1	
oise level	59 db	55 db	
emporary use:	30/30 min. ON/OFF	20/40 min	
lass of risk	IIa	IIa	
orms:	Class II, Type B	Class II, T	
rigin:	Italy	Italy	

taneb II Hz/140VA 19.5 cm - 1.7 Kg n. ON/OFF Гуре В

28097



Nebulizers for Professional and Hospital Use

HOSPINEB PROFESSIONAL NEBULIZER Code 28134 HOSPINEB PROFESSIONAL 230 V-50 Hz Code 28136 HOSPINEB PROFESSIONAL 230 V-60 Hz Code 28137 HOSPINEB PROFESSIONAL 110 V-60 Hz This aerosol theraphy appliance is designed principally for clinical use and embodies all the dictates of modern aerosol theraphy techniques. Reliable and simple to use, can even be operated by unexperienced persons.

Technical specification	18	
Operating voltage: 230 V - 50 Hz - 50 VA		
100 V - 60 Hz on request		
Size: 19 x 17 x 28 cm.	Weight: 2.6 kg	
Max pressure: 350 kPa (3.5 bar)	Air Flow: 15 l/min	
Noise level: 60 db	Made in Italy	
Operating pressure: 0-130 kPa (0-1.3 bar).	Class: I type A	
	<i>.</i>	

Standard Accessories

Sterilizable Fasterjet bulb in polypropylene Sterilizable nasal prong in polypropylene Sterilizable mouthpiece in polypropylene Plastic adult and paediatric face mask Tubing and connectors





Code 28103 CORSIA NEBULIZER - piston

The right choice for prolonged use. Ideal for clinic. Piston type.

Technical specifications

Operating Voltage: 230 V - 50 Hz (available also 60 Hz) Max pressure: 2.5 bar. Max flow: 16 l/m Nebulization: 0.5 ml/min Operating pressure: 0.9 bar Power consumption: 200 VA. Weight: 2.3 kg Size: 235x190x165 mm Made in Italy

Standard Accessories

Nebulizer bulb in polycarbonate Nasal prong in polycarbonate Mouthpiece in polycarbonate Plastic adult face mask. Tubing and connectors Support for nebulizator

Vapinal inhaler

Code 28110 VAPINAL INHALER

Warm jet mineral water inhaler ideal **for home spring water inhalation treatment.** Made of plastic material to facilitate electric and thermal insulation. The hot boiler chamber in stainless steel has a high armoured resistance and a safety thermostat. Supplied with polycarbonate ampulla, in a 4 colour deluxe box. Made in Italy

Code 28112 VAPINAL AMPULLA - spare part



Famiglia Nebulizer

Code 28101 FAMIGLIA NEBULIZER diaphragm (membrane) Economic, compact lightweight nebulizer, perfect for homecare. Ideal to nebulize antibiotics and bronchodilators. Plastic case shock resistant. Made in Italy Standard accessories: bulb, mouthepiece, adult and pediatric face masks

Technical specifications Weight: 1.8 kg Max pressure: 0.9 bar Operating pressure: 0.6 bar Air flow: 11 l/min Particle: from 0.5 to 5 micron Power consumption: 115 VA Operating voltage: 230 V - 50 Hz. Size: 280x170x120mm Class: II type B Temporary use: 30/30 min ON/OFF

CE 0470

28110



Respira and Pingoo Ultrasonic Nebulizers



Heat and Ultrasonic Humidifiers



Nebulizes 400 ml in 1 hour

Automatic mist-stop when tank is empty

Adiustable steam direction

64

Operating voltage: 230V-50/Hz.

Protection fuse. Made in Italy

Medical Grade Silicone Tubes for external use



SILICONE TUBES for external medical use - silicone 100% Suitable for autoclaving (135°C - 2.2-2.5 bar) and Gamma Sterilization. Heat resistant in hot air up to 200°C. Infra-red vulcanization. Hours treatment at 200°C temperature in special oven. Anti-adherent, avoid incrustation and coagulation.

Medical Grade - Transparent - Odourless

Technical specifications
Raw material: HTV-R-402/60 E - WACKER (D)
Colour: translucent
Hardness: 60° +/-5% Shore - DIN 53505
Density: 1.17 g/ccm - DIN 53479A
Tensility: 10.8 N/mm ² - DIN 53504 S1
Stretch: 490/530% - DIN 53504S1
Tear resistance: 34-35 N/mm - ASTM D 624 B
Reverse pull elasticity: 51% - DIN 53512
Compression set: (22h/175°C): 30-15% - DIN 53517

Made in European Union according to: US PHARMACOPEA XXI EUROPEAN PHARMACOPEA DIN 58367 - DIN 58362 - DIN 13098- FDA 177.2600 - BGA XV part A and B - BGA IX part B

GIMA code	Internal diameter x external diameter	Thickness mm	Minimum order
25830	1x3 mm	1 mm	100 m
25831	2x4 mm	1 mm	100 m
25832	3x5 mm	1 mm	100 m
25833	4x6 mm	1 mm	100 m
25835	6x8 mm	1 mm	30 m
25840	4x7 mm	1.5 mm	30 m
25841	5x8 mm	1.5 mm	30 m
25842	6x9 mm	1.5 mm	30 m
25843	7x10 mm	1.5 mm	30 m
25844	4x8 mm	2 mm	30 m
25845	6x10 mm	2 mm	30 m
25846	8x12 mm	2 mm	30 m
25847	10x14 mm	2 mm	30 m
25848	5x10 mm	2.5 mm	30 m
25849	7x12 mm	2.5 mm	30 m
25850	6x12 mm	3 mm	30 m
25855	7x13 mm	3 mm	30 m
25851	8x14 mm	3 mm	30 m
25852	9x15 mm	3 mm	30 m
25853	10x16 mm	3 mm	30 m
25854	12x18 mm	3 mm	30 m
25857	8x15 mm	3.5 mm	30 m
25860	made to	order	500 m
MADE	TO ORDER	SILICONE 1	TUBES
V	<mark>Ve can manufa</mark>	cture any size	

(minimum order 500 m - delivery 30 days)

Accessories for any brand of nebulizer

all nebulizers

bulb 28107

bulb 28107

28109

ACCESSORIES FOR NEBULIZER

28107

28109

28111

Gima offers different nebulizer bulbs with their line of accessories, suitable for any brand of nebulizer.



Nebulizer bulb - polycarbonate

Facemask - adult

Facemask - paediatry

FASTERJET BULB with Valve SystemA new designed Jet Nebulizer capable of
delivering any medication in a very short time
with a high amount of respirable particles.Faster-
For del
any medication
in a very
in a veryThe Valve System makes theraphy extremely
efficient by reducing the ammount of wastedin a very
in a very

Faster-jet bulb: For delivering any medication in a very short time

28164	28166 28168	28169 28145
GIMA code	Nebulizer accessories	To be used with
28163	Fasterjet bulb*	all nebulizers
28164	with Valve System Nebjet bulb ** with Double Venturi Effect	all nebulizers
28165	Mouthpiece bi-valve bulb 28163	
28166	Mouthpiece	bulb 28164,
28167	Nasal Prong bulb 28164, 28163	
28168	Facemask-adult	bulb 28164, 28163
28169	Facemask-pediatry bulb 28164, 28163	
28145	Hidrofobic, 99% antibacteric filter	28130/1/2/3/4/5
	ard with Happyneb II, Hospyneb dard with Happyneb I, III, Betane	b

ACCESSORIES

Autoclavable/Disposable Jars, Filters and Silicone Tubes



GIMA code	Suction Aspirators accessories	To be used with	
28257 28258	Bottle 1 I - autoclavable (without cover+valve) Cover+valve for bottle 1 l Bottle 1 l with cover - autoclavable Disposable suction liner	28241, 28244, 28245, 28246 sold up to december 2006 28256 28241, 28244, 28245, 28246 since 2007 28258	T
28227 28236 28272 28273 28228	Bottle 1 I - autoclavable at 120°C - with cover Cover + valve for bottle 1-2 I - spare Bottle 2 I - autoclavable at 120°C - with cover Bottle 2 I autocl. w/o cover, for disposable bag Cover + disposable bag 2I Bottle 4 I - autoclavable at 120°C - with cover Cover + valve for bottle 4I - spare	28226, 28236 28205, 28211, 28214, 28217, 28218, 28224, 28231, 28232, 28235, 28240, 28243	28272 28273
28229 28237 28239	3229 Hydrophobic, 99% bacterial filter 28210, 28211, 28220, 28221, 28222, 28224, 28230, 28240, 28243, 28148 3237 Hydrophobic, 99% bacterial filter 28210, 28211, 28220, 28221, 28222, 28234, 28230, 28240, 28243, 28148 3239 Hydrophobic, 99% bacterial filter 28214, 28215, 28216, 28231, 28217, 28218 3255 Hydrophobic, 99% bacterial filter 28241, 28244, 28245, 28246		
25850	Silicone tube 6 x 10 mm Silicone tube 6 x 12 mm Silicone tube 8 x 14 mm	28252 Adaptor for catheter 28210/211/220/221/222/224/240 28253 Adaptor for catheter 28210/211/24/245/246 28205/207/215/216/217/218/231/232/233/23 28205/207/215/216/217/218/231/232/233/23	34/235

Accessories for any Suction Aspirator

Autoclaval at 134 °C up to 100 t		GIMA code	28248 Available on request other sizes and length 60 cm Suction Catheter-Sterile	
GIMA code 29980 29981	Silicone Vacuum Suction - Autoclavable Silicone vacuum suction Ø 60x210 mm Silicone vacuum suction Ø 70x210 mm	28247 28248 28249 28250	 7 Suction catheter CH 14 Ø 4.66 mm x 48 cm 8 Suction catheter CH 16 Ø 5.33 mm x 48 cm 9 Suction catheter CH 18 Ø 6.0 mm x 48 cm 	
GIMA	26797 26799 26798 26795 26796 26807 Stainless Steel Cannula	28260		
code 26795 26796 26793 26794	Stainless steel Frazier suction cannula Ø 2 mm Stainless steel Frazier suction cannula Ø 3 mm Stainless steel Frazier suction cannula Ø 4 mm Stainless steel Frazier suction cannula Ø 5 mm	GIMA code 28262 28264	Stainless Steel Aspiration Tube S/S Bierer Aspiration tube Ø 8 mm S/S Bierer Aspiration tube Ø 12 mm Supplied with removable connection cannula	
26797 26798 26799 26807	Stainless steel Rosen suction cannula Ø 1.5 mm Stainless steel Rosen suction cannula Ø 3 mm Adaptor with Luer tip and thumb valve Stainless steel Novak suction cannula for Gyn	28260	Set of uterine aspiration cannulas: each set is composed of 3 cannulas with side suction end (Ø 5,6,8 mm), 3 cannulas with front suction end (Ø 7,10,11 mm) and one handle	



ELECTROMEDICAL DEVICES



anytime, anywhere. Precision and solidly built to assure long service life. Polycarbonate suction bottle with capacity 400cc, autoclavable at 120°C and spill-over protection. Bacterial filter included.

Code 28219 BOTTLE 0.4 l - spare

Technical specificationsWeight: 1.2 kgSuction power: 22 l/min.Size: 225 x 165 x 85 mmBottle capacity: 400 ccMax suction - 0.40 barMade in Italy

Breast pump - Mamilat GIMA

Code 28148 MAMILAT - BREAST PUMP

Easily transportable from one maternity ward to another, or for use at home. To be used for aspirating mother's milk. Easily portable equipment. Made of highly heat-resistant, electrically insulated plastic material in conformity with the latest European safety standards. Supplied with 2 polycarbonate milk bottles (150 cc and 250 cc) antibacterial and hydrofobic filter, set of tubes 6x10 mm, breast shield, PVC air tube. Suction adjustment knob on the front panel.

Code 28149 SPARE KIT

28220

1000

Includes two plastic bottles (125 cc and 250 cc) and bacteriological filter.

Code 28229 SPARE FILTER

Technical specifications Regulator for suction intensity - max suction -0.33 bar Operating voltage: 230 V - 50 Hz Max flow (air litres/min): 14 l/min Power consumption: 184 VA Size: 235x190x165 mm Weight: 2.2 kg Norms: CEI 62-5 (IEC601-1). Made in Italy 5 languages manual: Italian, English, Spanish, French, German.

> Supplied with anti-bacterial filter

28148

(E0470

ELECTROMEDICAL DEVICES

Suction Aspirators High Vacuum, Low and High Flow



Code 28222 TOBI - suction aspirator

Portable, particularly recommended for tracheotomy and small surgery. Continuos adjustable vacuum with vacuum indicator. Has unbreakable 1,000 ml standard bottle autoclavable at 120°C with safety float control valve to prevent overflow. Silicone connection tube. ABS plastic case.

Suction power: 18 air litres/min. - Max suction: - 0.75 bar Supplied with antibacterial



Code 28224 SUPER TOBI - suction aspirator 230V - 50Hz Code 28225 SUPER TOBI - suction aspirator 110V - 60Hz Portable suction aspirator, ideal for small surgery in hospital ward. Vacuum continuously adjustable with vacuum indicator. Has unbreakable 1,000 ml standard bottle (2,000 ml optional) autoclavable at 120°C with safety float control valve to prevent overflow. Silicone connection tube.

Suction power: 30 air litres/min. - Max suction: - 0.80 bar Code 28221 TOBI UNO - suction aspirator

Portable suction aspirator. Vacuum continuously adjustable with indicator supplied with 1 liter Makrolon bottle, autoclavable at 120°C. With safety float control valve to prevent overflow.

Standard Accessories			
	Tobi-Uno	Tobi	Super-Tobi
Bottle 1000 ml with co	over 1	1	1
Antibacterial Filter	1	1	1
Suction catheter	1	1	1
Silicon Tube set	1	1	1
User manual*	User manual* 1 1 1		
* User manual is pro	vided in 5 languag	es: English, Spani	sh, French,
German and Italian	1.		
	Technical spe	ecifications	
	28221 Tobi-Uno	28222 Tobi	28224 Super-Tobi
Operating voltage:	230 V - 50 Hz	230 V - 50 Hz	230 V - 50 Hz
			110 V - 60 Hz
Power consumption:	184 W	184 W	106 W
Bottle capacity:	1000 ml	1000 ml	1000 ml

-0.75 bar (563mm/Hg)

37x22xh21 cm

3.5 kg

Italy

IEC 601-1

-0.80 bar (600mm/Hg)

37x22xh21 cm

5.25 kg

Italy

IEC 601-1

-0.75 bar (563mm/Hg)

19x23xh16 cm

2.3 kg

Italy

IEC 601-1

Max suction:

Size (cm):

Weight:

Norms:

Origin:

"Vega" Professional Aspirators with 1 or 2 litres Jar





Supertobi Suction Aspirator on Trolley





High Vacuum, High Flow Hospital Suction Aspirators





Code 28231 TOBI CLINIC - suction aspirator - 2x2l jar 230 V Code 28214 TOBI CLINIC - suction aspirator - 2x2l jar 230 V + foot switch Code 28215 TOBI CLINIC - suction aspirator - 2x4l jar 230 V Code 28216 TOBI CLINIC - suction aspirator - 2x4l jar + foot switch Code 28232 TOBI HOSPITAL - suction aspirator - 2x4l jar 230 V Code 28233 TOBI HOSPITAL - suction aspirator - 2x4l jar 230 V Code 28235 TOBI HOSPITAL - suction aspirator - 2x4l jar 230 V Code 28235 TOBI HOSPITAL - suction aspirator - 2x4l jar + footswitch Code 28235 TOBI HOSPITAL - suction aspirator - 2x4l jar + footswitch Code 28235 TOBI HOSPITAL - suction aspirator - 2x2l jar 110V Ideal for hospital, these suction aspirators are manufactured in ABS. Four antistatic castors, two of which with brakes, to allow perfect mobility. Vacuum gauge for the control of vacuum (1 bar). 2 or 4 litre jar made of autoclavable makrolon, with 200/400 ml. graduation. Each jar with double security valve. Pump piston type, lubrication and maintenance free. With anti bacterial filter. On request available footswitch and other operating voltage (110 V). User manual available in English, French, German, Italian, Spanish.

Technical specifications		
	Hospital (28232-28233-28234/5)	Clinic (28231-28215-28216)
Size:	55 x 45 x h 65 cm	46 x 42 x h 60 cm
Weight:	20 Kg	13 Kg
Operating voltage:	110 V or 230 V - 50/60 Hz	110 V or 230 V - 50/60 Hz
Maximum suction:	- 0.90 bar (675 mm/Hg)	- 0,90 bar (675 mm/Hg)
Flow:	90 l/min	60 l/min
Norms:	CEI 62-5 (IEC 601-1)	CEI 62-5 (IEC 601-1)
	93/42 EEC. Made in Italy	93/42 EEC. Made in Italy

Code 28205 TOBI HOSPI PLUS - suction aspirator - 2x2l jar 230 V with foot switch and flow direction regulator

Code 28207 TOBI HOSPI PLUS - suction aspirator - 2x4l jar 230 V with foot switch and flow direction regulator

Ideal for hospital, these suction aspirators are manufactured in ABS. Four antistatic castors, two of which with brakes, to allow perfect mobility. Vacuum gauge for the control of vacuum (1 bar). 2 or 4 litre jar made of autoclavable makrolon, with 200/400 ml. graduation. Each jar with double security valve. Pump piston type, lubrication and maintenance free. With anti bacterial filter. On request available other operating voltage (110 V). User manual available in English, French, German, Italian, Spanish.

	Technical specifications	
	Hospi Plus (28205-28207)	
Size:	47 x 43 x h 74 cm	
Weight:	20 Kg	
Operating voltage:	230 V - 50/60 Hz (110 V on request)	
Maximum suction:	- 0.90 bar (675 mm/Hg)	
Flow:	90 l/min	
Norms:	EN60601-1 Class II type B 93/42/EEC	
	Made in Italy	





GYNAECOLOGY

GIMA Foetal Pocket Dopplers - Made in U.K.



Code 29502 GIMA FOETAL DOPPLER G2002

Small, lightweight, hight sensitivity pocket Doppler, with 2 MHz foetal probe, ideal for use by a General Practitioner or Midwife for routine antenatal foetal detection.

Pocket Doppler can be used to detect the beating foetal heart from about 10th week of gestation. It may be used to locate the position of the placenta, thus aiding in the early diagnosis of placenta praevia, to survey blood flow of the umbilical cord and to diagnose multiple pregnancies. Foetal signal are easily located using the lightweight narrow beam transducer while internal signal processing minimises noise artefacts. Audio foetal heart signals are available to the user via the built-in loudspeaker or option headset, with output level controlled by rotary volume control. Code 29511 ON/OFF MEMBRANE SWITCH for code 29502

Code 29503 GIMA FOETAL DOPPLER D2003 with display Pocket foetal doppler with same specification as code 29502 but with built-in foetal heart rate processing. Foetal heart rate (FHR) is displayed on a large LCD display whilst internal signal process minimises noise artefacts.

Code 29505 GIMA FOETAL DOPPLER D2005 with display and waterproof probe

Same as code 29503 but waterproof (probe and main unit). All units are supplied in a nice bag with a tube of coupling gel and user manual in English, Spanish, French, German, Italian, Greek, Portuguese.



(EN (46002

Technical sp	ecification (codes 29502 - 29503 - 29505)
Ultrasound	Frequency: 2 MHz continuous wave
	Transducer: 2 crystal narrow beam
	Output power: <10mW/mm ² SATA
	Audio Response 300Hz -1 KHz
	Fetal heart rate: multipoint real time
	autocorrelator (only code 29503 and 29505)
Unit Controls	Keys: 1 Key (for unit on/off)
	Controls : rotary volume
Indicators:	3 digit FHR LCD display (codes 25903, 29505)
	FHR pulse icon (codes 25903, 29505), Battery low icon
Power supply	Battery 9 V Alkaline Manganese
	Expected battery life: >6 hours (codes 29503, 29505)
	>9 hours (codes 29502)
Output	Headset: Audio output to optional headset
	Serial: RS232 interface (codes 29503, 29505)-jack 35 mm
Material:ABS	/ Noryl
Size 150 mm	by 75 mm Weight: 295 g (with transducer)
Classification	Class I Type B - IEC 60601-I C € 0120
Warranty: 1 y	ear Made in UK

Fetatrack Foetal Monitors - Made in U.K. MANUFACTURED ACCORDING TO



Colour display, Single or Twins Foetal Monitors



Cost-effective single Foetal Monitor



Code 29520 FOETAL MONITOR GIMA FC 700 Cost-effective single fetal monitor

Extreme ultrasound doppler sensitivity

- High-accuracy with 1 Mhz frequency
- Automatic/manual Foetal Movement detection
- Auto NST (Non-stress test) function from 10 min. to 1 hour.

Data printout

- A4 size chart paper with

- perforation line
- Plain thermal fax paper usable
- Print speed 1, 2, 3 cm/min

Easy-to-use

- One- touch operation and
- easy setup
- Alarm function (FHR high-low)
- s/w upgrade via internet

Standard accessories (29520, 29530, 29531)
Doppler transducer (2 for Twins Foetal Monitor)
Toco transducer Event maker Gel Printer naper Belts Manual

Technical specifications Foetal Monitors (29520, 29530, 29531)

Doppler	Indicators
Pulsed Doppler	Heart rhyth
Ultrasound frequency: 1.0 MHz	Alarm, prin
Intensity: <10mW/cm ²	AC power
FHR range: 50-240 bpm (± 1 bpm)	Set-up
Fetal movement	Alarm uppe
Detection source: Ultrasound	Record spe
pulsed doppler	Movement
UC	contrast, Au
Frequency response: DC 0.5 Hz	Power
Reference (zero) control	INPUT: AC
Measurement range: 0~99 units	296(W)x30
Printer	Approx 2.9
Thermal array type	3.2
Print speed: 1, 2, 3 cm/min	External li
Paper feeding function	RS-232C: I
Display	
7-segment LED (29520)	
2 channels (HR, UC) (29520)	
320x240 Colour LCD (29531)	

Indicators
Heart rhythm with signal quality
Alarm, printing on/off state
AC power
Set-up
Alarm upper/low limit value
Record speed, paper grid, Fetal
Movement On/Off, Time/Date, Print
contrast, Auto print period
Power
INPUT: AC 100-240V (50/60 Hz)
296(W)x305.5(H) x 92.5(D)mm,
Approx 2.9kg (29520),
3.2kg (29530-29531)
External link
RS-232C: Program Download
-

For 29520	For 29530-31	Accessories for foetal monitors
29522	29528	Paper pack
29523	29532	Doppler transducer - spare
29524	29533	Toco transducer - spare
29519	29519	Trolley with 2 baskets (adjustable height)
-	29534	Battery NI-MH, 12V, 2600 mA
33747	33747	AC adaptor
29525	29525	Belt
For 29520	For 29530-31	Network systems for foetal monitors
29518	29518	Software + cable for connection to PC
		For real time data graphic transfert to a PC with database storing (PC not included)
		with database storing (PC not included)
29527	29527	Central station (PC, monitor, software,
		connection kit for 2 foetal m.) to manage up to
29526	20526	8 monitor (kit 29526) Same function as 29518
29520	29526	Connection kit to Central Stat. for each
_	29521	additional foetal monitor (up to 8 monitors)
-	29321	Wireless connection kit (foetal monitor to central station) for 1 monitor (up to max 8 monitors)





central system (distance 10-100 m)



GYNAECOLOGY

Pregnancy Tests: Midstream and Strip Type



Code 29104 HOME PREGNANCY TEST - midstream (€ 0197 Deluxe box of one midstream test with multilingual manual. Code 29107 HOME PREGNANCY TEST - midstream (€ 0197 Box of two midstream tests with multilingual user manual. Code 29108 DOCTOR PREGNANCY TEST - midstream (€ Box of 25 midstream tests. With multilingual user manual.

Personalised box - minimum 3,000 pcs.

Menopause Test



Code 29109 MENOPAUSE TEST - midstream $\zeta \in O^{197}$ Deluxe box of two midstream tests with multilingual user manual and box (English, Spanish, French, Portuguese, Greek, German, Italian, Arabic).

Vaginitis Test Kit



Code 29111 VAGINITIS TEST KIT

A unique, easy-to-use and revolutionary test for gynecologists and operators. Finds the causes of the inflammation/vaginal infection in just 10 minutes. It replaces traditional bacterial tests that take days and costs only a tenth. When necessary dilute vaginal fluid specimen in a buffer solution and then transfer to reagent pad. The instruction manual contains a result guide and can be used to recognize: Trichomoniasis, negative gram bacteria, Gardnerella, Chlamydia, serious bacterial vaginitis.



Code 29100 HOSPITAL PREGNANCY TEST - strip 4 mm (€ Box of 50 strip tests, with multilingual manual (English, Italian, French, Spanish, Greek, Portuguese)

- Main features of pregnancy tests:
- Each test is individually packed
- Very quick, some positive can be detected in 1 minute
- Reliability: 99%
- Sensibility: 25 mlU/ml

Ovulation - Fertility Test



Code 29112 OVULATION TEST - midstream $(\in ^{0197})$ Deluxe box of 5 midstream test with multilingual user manual Code 29113 OVULATION TEST - strip 4 mm $(\in$ Box of 50 strip tests with multilingual user manual

Vaginal Ph Test

Code 29110 VAGINAL PH TEST - box of 10 pcs. Quick test to determine vaginal PH. An easy routine test to check vaginal PH in just 1 minute to make sure it is within the physiological limits (< 4.5).

An increase in the Ph level may indicate a change in the vaginal environment. This could mean there is a possible vaginitis. The test is ideal for pregnant women and for women with particular diseases such as diabetes.




Amnioscope: tubes and set Schultze Salpingograph



Code 29970 AMNIOSCOPE SET

Set of three amnioscopes tubes with shutter 200 mm length, 12, 16 and 20 mm diameter, and a clamp for fibre optic light. All tubes are graduated in centimetres, have a rounded end and are sterilizable with any method. To light amnioscope set you can use GIMA 150 light source (code 30801), adapter (code 30830), F.O. cable (code 30818) and adapter for clamp (code 30840). **Code 29971 AMNIOSCOPE TUBE 12 x 24 x 200 mm Code 29973 AMNIOSCOPE TUBE 16 x 24 x 200 mm Code 29975 AMSIOSCOPE TUBE 20 x 24 x 200 mm Code 29975 ANGLED CLAMP FOR LIGHT CONNECTION**

Obstetric Stethoscopes

32501 SHORT OBSTETRIC STETHOSCOPE - beech-wood 32502 LONG OBSTETRIC STETHOSCOPE - beech-wood These stethoscopes are hand-craft manufactured, made in beechwood accurately selected and sesasoned for at least 3 years. They have a perfect finish with a special transparent varnish. **32505 PINARD STETHOSCOPE - aluminium**



Pap Test Kits Ready for Use



Code 29700 PAP TEST KIT - sterile

Pap-Test is a painless examination to detect the presence of any anomalous cells on the cervix. It allows an early diagnosis of uterus neck cancer. The functional configuration of the kit allows a ready to go operation. The kit includes:one latex glove, one perno speculum (medium size), one GIMA brush, one Ayre spatula (wooden), two slides and one box for them. Individually packed in sterile pouch. Made in Italy.



Code 29780 SALPINGOGRAPHC € 0124Instrument for hystero-salpingography and tubal insufflation,
Prof. Gunter K. F. Schultze from Berlin type. Made in Germany.

Hysterosalpirograph: standard accessoriesWatch for hysteroHystero syringe 20 cc. Luer LockRack-bar3 interchangeable cones (small-medium-large)

Latex Probe Covers

Code 29513 LATEX PROBE COVERS For ecography and doppler probes. Individually packed in single plasic bag. minimum order: box of 50 pcs.





Code 29701 PAP TEST KIT - not sterile Economic kit that includes: one GIMA brush, one Ayre spatula, one slide, all packed in a carton box specifically designed for laboratory delivery.

On the box there is a space to write the name of patient, date and other info.

minimum order: box of 25 kits

Disposable Sterile Vaginal Speculum



CUSCO SPECULUM - with gradual adjustment - sterile Disposable speculum with gradual screw-action adjustment. It is manufactured with the best non-toxic transparent material, comes in a single transparent vacuum packing and is sterilized with ethylene oxide. Sterilization is guaranteed by the special quality control label on each pack. Available 3 sizes distinguishable through screw color. Made in Italy.

GIMA code	Vaginal Speculum disposable - sterile	Minimum order
29950	CUSCO Speculum - small 85 x 20 mm	120 pcs.
29951	CUSCO Speculum - medium 90 x 28 mm	120 pcs.
29952	CUSCO Speculum - large 100 x 36 mm	120 pcs.

PERNO SPECULUM - with central key adjustment For dilation of the vaginal canal to expose the uterus neck. It allows the adjustment of the vaginal opening by positioning the blades and locking the central key. The smooth surface and rounded edges aid a comfortable introduction. The central key can be bent down for an easier introduction of cumbersome instruments 3 sizes distinguishable through key colour. Made in Italy.

num ler	GIMA code	Vaginal Speculum disposable - sterile	Minimum order
pcs.	29954	PERNO Speculum - small Ø 20 mm	120 pcs.
pcs.	29955	PERNO Speculum - medium Ø 26 mm	120 pcs.
pcs.	29956	PERNO Speculum - large Ø 30 mm	120 pcs.

Stainless Steel Vaginal Speculum - Cusco and Collin



GIMA code	Stainless steel Speculum		
29770	Cusco stainless steel speculum - small 100 x 30 mm		
29771	Cusco stainless steel speculum - medium 110 x 34 mm		
29772	Cusco stainless steel speculum - large 125 x 36 mm		
29773	Cusco stainless steel speculum - virgin 110 x 17 mm		
29763	HF Cusco stainless steel speculum - medium		
	with insulation for HF applications		
29768	Collin stainless steel speculum - medium		
All speculum are individually packed in carton box			

Gynolight



Code 29962 GYNOLIGHT

It allows illumination of the vaginal canal. It fits both central key and side-screw specula. It is provided with two points light source for a proper illumination of the vaginal canal, and its upper point light source can be adjusted by the operator. It's easy to set and remove thanks to spring sideholders. Gynolight does not come into contact with mucosa. Cold sterilization. Made in Italy.

Lubrigima: lubrificant gel

Code 29960 LUBRIGIMA - 250 ml For an easy insertion of instruments during gyn examinations. Its special composition and high transparency does not alter the visual image when optical instruments are used. It does not contain spermicides, it does not grease or stain. It has an acid Ph and a good electrical conductivity. It is soluble in water. The gel is well absorbed by the skin and does not cause irritations to the mucosa. Made in Italy.



minimum order: 6 pieces



Ayre Spatulae, GIMA Brush and Cotton Swabs



Code 29738 WALLACH PAPETTE

The logical choice for conventional PAP smears as well as the **new fluid-based technology**. With Wallach papette all it takes is a simple rotating motion to collect a total sampling endocervical and ectocervical cells, including the transformation zone, with less tissue trauma Mian o Mur methods. It is a simplified procedure that eliminates the two-steps brush and spatula combination. Made in USA. **minimum order: 1 box of 100 pcs.**

29743 CE A 29744 B 29746 Used for ecto-cervical and posterior fornix cells sampler in uterus neck cancer screening procedures. GIMA Minimum Product **Material** order code Ayre Spatula A Wood 29743 500 pcs. Packed in box of 100 pcs., in carton of 500 29744 Ayre Spatula B Wood 500 pcs. Packed in box of 100 pcs., in carton of 500 29746 Avre Spatula Polyprophylene 400 pcs. Packed in plastic bags of 25 pcs, in carton of 400



29740 (€

Code 29739 GIMA BRUSH - conical - bag of 25 pcs. Code 29740 GIMA BRUSH - conical - box of 400 pcs. These single-use endocervical brushes are an efficient method of collecting vulval, endocervical and nasal surface samples for cytological/microbiological examinations. Non sterile. Packed in plastic bags of 25 units, in carton of 400 units.

minimum order: 400 pcs. **Code 29742 GIMA BRUSH - conical - STERILE** As code 29740, individually packed in sterile plastic bag. Both codes are made in Italy

Dom coc	ies are made in mary		11111111	ium or ue	r: 500 pcs.
29754		_	_		CE
29755					
		_	-	-	
-	_	_			
29750					and the second se
		Shaft	Cotton	Shaft	Minimum
GIMA code	Product	Shaft Material	Cotton Ø	Shaft lenght	Minimum order
GIMA code		Material	Ø	lenght	
GIMA code 29750 Packed i	Cotton Swab n plastic bags of 25 p	Material Plastic cs., in ca	Ø 1 cm rton of 4	lenght 20 cm 00	order 400 pcs.
GIMA code 29750 Packed i	Cotton Swab	Material Plastic cs., in ca	Ø 1 cm rton of 4	lenght 20 cm 00	order 400 pcs.
GIMA code 29750 Packed i 29754	Cotton Swab n plastic bags of 25 p	Material Plastic cs., in ca Wood	Ø 1 cm rton of 4 0.5 cm	lenght 20 cm 00 15 cm	order 400 pcs.
GIMA code 29750 Packed i 29754 Packed i	Cotton Swab n plastic bags of 25 p Cotton Swab	Material Plastic cs., in ca Wood pcs., in c	Ø 1 cm rton of 4 0.5 cm arton of	lenght 20 cm 00 15 cm 500	order 400 pcs. 1,000 pcs.

Spray for Citology Fixation and Accessories

Code 29778 GIMAFIX SPRAY FOR CITOLOGY FIXATION

Fixer for cytology. Composition: isopropanole, poly-ethylenglycole. It doesn't contain propellants destructive for the ozone. 250 cc bottle. minimum order: 12 bottles

Code 29775 MICROSCOPE SLIDES

Size 76 x 26 mm, 1.2 mm thick, glass made with polished edges and sandblasted band

Code 29776 BOX FOR SLIDES

Plastic, transparent box for storage of up to three slides.



Cups for Hysterography and SIFT screw Syringe



Pessary for Uterine Prolapse



Membrane Perforator

29945 Code 29945 AMNIOTIC MEMBRANE PERFORATOR-sterile Disposable amniotic perforator. This system is thought to be completely safe to avoid lesions to the foetus. Supplied in single sterile envelope. (© 0373 minimum order: 600 pcs.

	ROMETER with slider - single use - sterile ed reading on the handle, flexible	C € 0120
-	-	29930-32
GIMA	HYSTEROMETER	Minimum
code	single use - sterile	order
29930	Hysterometer CH 10	25 pcs.
29931	Hysterometer CH 12	25 pcs.
29932	Hysterometer CH 14	25 pcs.

CUPS FOR HYSTEROGRAPHY

The device consists of a rigid, transparent tapered cup with a central conical cannula; it is equipped with a 25 cm long flexible, pliable manipulator joined to the cup and two tubes equipped with clamps. One of these provides the vacuum, while the other injects the radiopaque medium. Perfect adhesion to the cervix by self-centering is ensured by the tapered shape of the cup and the progressive application of a vacuum to the cup.

The suction cup/cannula unit is radiotransparent and allows the proximal area of the endocervix to be controlled. The radiologist is able to manipulate at a distance from the radioactive field while at the same time comfortably immobilizing the uterus.

SIFT SCREWTHREAD SYRINGE

Contrast medium is injected by turning the position of the syringe which is equipped with a thread, to enable easy and regular injection of the contrast medium.

If cup is used on our SIFT syringe, connector is not needed.

Amniocentesis Needles

For transabdominal sampling of amniotic fluid for prenatal diagnosis of genetic disorders of the foetus. It is also used for cytogenetic and biochemical studies. Accurate sharpening of the needle allows an easy and atraumatic insertion. Its mandrel is provided with an ultrasound detectable tip allowing an echoguided insertion, and it is colour coded for an easy identification of the needle size. The needle is provided with an adjustable stopper to determine insertion depth, and with a female luer lock connector to collect the amniotic fluid through a syringe. Made in Italy.

GIMA code	Amniocentesis Needles - sterile
29630	Needle 20 G x 100 mm
29631	Needle 20 G x 120 mm $\mathbf{C} \in 0373$
29632	Needle 20 G x 150 mm
29633	Needle 20 G x 180 mm
29634	Needle 21 G x 120 mm

Umbilical Cord Clamp



Code 29943 X-SAFE UMBILICAL CORD CLAMP - sterile Disposable large size umbilical cord clamp to allow a proper clamping of all umbilical cords and prevent their outcoming from the closing comb. Individually packed in coupled cellophane (nylon/poliethilene) and medical paper to ensure safe hygienic conditions to user. Sterilized by ethylene oxide. Made in Italy. Minimum order: 600 pcs.

Code 29944 UMBILICAL CORD CLAMP - sterile

Disposable umbilical cord clamp with side fasteners to avoid the outcoming of the umbilical cord from the closing comb. Supplied in single sterile envelope.Sterilisation by ethane oxide under high temperature. minimum order: 600 pcs.





"Karman" and "Berkeley" style intrauterine suction curettes

ADAA AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA	C € 0373	5
GIMA code	"KARMAN" STYLE CURETTES flexible - single use - sterile	Minimum order
29810 29811 29812 29813 29813 29814 29815 29816	Karman Curette N° 6 - 6 mm x 24 cm Karman Curette N° 7 - 7 mm x 24 cm Karman Curette N° 8 - 8 mm x 24 cm Karman Curette N° 9 - 9 mm x 24 cm Karman Curette N° 10 - 10 mm x 24 cm Karman Curette N° 11 - 11 mm x 24 cm Karman Curette N° 12 - 12 mm x 24 cm	10 pcs. 10 pcs. 10 pcs. 10 pcs. 10 pcs. 10 pcs. 10 pcs.
(€	20 cm long	



Special syringe with adaptor suitable for use with Karman and Berkeley curettes of any brand.

One-way self-blocking valve for safety and easier use. Single use and sterile, 60 ml capacity. minimum order: 10 pcs.

Cannulas for endometrial sampling



29850

It is used for procedures where uterus manipulation and/or injection of contrast media is requested (e.g. diagnostic and operative laparoscopy, fertility examinations, etc.). It has a curved shape for an easy insertion and a stiff handle allowing a firm safe manipulation. Ext. $\emptyset = 5$ mm

Silicone Suction Cup

Code 29980 SILICONE SUCTION CUP Ø 60x210 mm Code 29981 SILICONE SUCTION CUP Ø 70x210 mm Prodotto in silicone medicale



Disposable rectoscope, proctoscope, anoscope

Code 25953 F.O. ILLUMINATION HEAD

This head perfectly fits and illuminates the disposable anoscopes, rectoscopes, proctoscopes for GIMA, HEINE, WELCH ALLYN, GPS. It can be connected to a light source by a F.O. cable or to a LED illumination system. See at page 92

Code 25950 DISPOSABLE ANOSCOPE - sterilized

Lenght 10 cm, with stylet diameter of 17 mm, suitable for treatment of haemorrhoids. minimum order: pack 60 pcs.

Code 25951 DISPOSABLE PROCTOSCOPE - sterilized Lenght 16 cm, with stylet diameter of 17 mm minimum

minimum order: pack 50 pcs.

Code 25952 DISPOSABLE RECTOSCOPE - sterilized

Length 25 cm, with stylet diameter of 17 mm, scale in cm, illumination in distal exit thanks to the opaque black tube placed inside the transparent body which enables the light to shine without shadow. minimum order: pack 50 pcs.





LIGHTING SYSTEMS

All products in this page are supplied with Acmi/Wolf light connection. To bring the light to these connection it is necessary to buy a Wolf adaptor (30841) a F.O. cable (30818-30826) a light source adaptor (30830) and a light source (30801-30802). See page 92. To better hang the instruments during the use we suggest below handle that can be placed between the instrument and F.O. cable.

Code 30798 HANDLE for Ano/Procto/Rectoscope and Sigmoidoscopes Alternatively you can choose a more economic solution, for illumination, inclusive of handle **Code 30799 ILLUMINATED HANDLE 6.0 VOLT - HALOGEN BULB**

Works as an indipendent light source for F.O. instruments

F.O. Anoscopes, Proctoscopes



F.O. Sigmoidoscopes









Adjustable height

CE

Gima Colposcope

Code 29600 COLPY - GIMA COLPOSCOPE Easy to use halogen colposcope mounted on a 5 wheels base.

Technical specifications

Magnifying: 6.2X with standard 10X eyepieces Optic system: stereo with inter-pupil adjustment and optic head at 45° Illumination: halogen dicroic bulb 12V - 12W Working distance: 26 cm Operating voltage: 230 V (available on request 115) Norms: CLASS I Type B - IEC 601-1 CE 93/42/EEC. Made in Italy

Code 29601 CAMERA CONNECTOR

To connect a camera with standard "C mount" to GIMA colposcope. (see cameras at page 93)

Video Colposcope system

Code 29605 NETSCOPE - COLPOSCOPE - 8X

All in one system for videocolposcopy applications: the system includes a CCD camera with integrated 150 watt light source, F.O. cable, ergonomic handle and colposcopy probe. Main features:

- Excellent image quality

A microprocessor controls the brightness, resolution at 440,000 pixel gives a clear and sharp image. Optical part made in Germany - Easy to use and handle

The ergonomic probe design and the trolley make the use of this

device really easy - High magnification

Fine adjustment for various applications by focus knob, without the necessity to change the lens

- Flexibiliv

This device can be turned into videodermatoscope or videotoscope, just by changing the probe. Easy lamp replacement through door.

Code 29610 IMAGE SOFTWARE

This software allows to store images and data in a PC database and print them (English language only) Code 72705 LCD MEDICAL MONITOR - 15" - flat type Code 29606 TROLLEY CART - easily fits Netscope and

every kind of flat monitors compliant with VESA 75 standard. Code 29607 FLEXIBLE ARM with stand - this arm is fixed on a tripod support and allows to hang the probe in fixed and stable position.

Technical specifications Netscope Camera sensor: 1/3 CCD Sony Cable length: 200 mm Horizontal resolution: 480 lines Minimum illumination: 0.5 lux Power supply: 90-250 V - 50-60 Hz Digital signal processing ACG white balance: AUTO/FIXED Basic unit size: 210x92x240 mm Light intensity: adjustable 0-150 W Weight: 3kg Video out: Y/C (S-VHS), composit (BNC) Made in Germany



Image freeze function allows to freeze up to 4 images on the screen and immediatly review one of them



Display: 15"/38,1 cm

TFT active matrix



in full screen size



Videodermatoscope



Code 29608 VIDEODERMATOSCOPE PROBE - 20X This probe added to our code 29605 turns the system into a videodermatoscope. Made in Germany.

Videotoscope

Active area: 304,1x228 mm

Size: 375x356x210 mm

Resolution: 1024x784 (XGA)





E 0197

Code 29609 VIDEOTOSCOPE PROBE - Ø 4 mm - 0° This probe added to our code 29605 turns the system into a videotoscope. Made in Germany.

Change-A-Tip[™] Cauteries with High Temperatures



High Temperature Electrocauteries



6 0197

Histofreezer® Cryotherapeutic aid for the treatment of warts

Code 30585 HISTOFREEZER® - mini kit One 40 ml aerosol bottle, 2 applicators 2 mm and 3 applicators 5 mm. Code 30586 HISTOFREEZER® - mix kit One 150 ml aerosol bottle, 25 applicators 2 mm and 25 applicators 5 mm. Code 30587 HISTOFREEZER® - kit 2 mm One 150 ml aerosol bottle and 50 applicators 2 mm. Code 30588 HISTOFREEZER® - kit 5 mm One 150 ml aerosol bottle and 40 applicators 5 mm.

Electrodepilator

800°C - Thick tip

Code 28340 ELECTRO-DEPILATOR 400

This device ensures a definitive depilation with thermolitic method. It delivers a current of radiofrequency to cause the heating and consequent coagulation of the papilla, reached through the introduction of a needle into the follicle of the hair. Provided with highly reliable electronic integrated components, with RF intensity adjustable with continuity and luminous working signal.

Technical specifications RF output frequency: 1.9 +/-10% MHz Modulation: sinusoidal Maximum output power: 7 +/-2Watt Size: 260 x 265 x 110h mm Weight: 4 kg Operating voltage: 115/230 V - 50/60 Hz. switchable Norms: CEI 62-39 Class: I-BF

It comes complete with footswitch, handpiece for depilation, depilation needle and power cable (2 m) **30552 HANDPIECE FOR DEPILATION 30560 DEPILATION OR MICROSURGERY NEEDLES 30568 FOOTSWITCH**

Histofreezer





Monopolar electrosurgery units - 50W and 80W



Code 30516 DIATERMO 106 - 50W - monopolar Code 30517 DIATERMO 108 - 80W - monopolar These HF electrosurgery units, are particularly suitable for small operations and are recommended for veterinary, dentistry, first aid and dermatology work. They offer precision of cut and immediate coagulation and give excellent results in a large range of applications: from uterine coagulation to microcoagulation

TT 1	• 1 • • • • •						
I ech	nical specification	s 30517 - MB 108					
Output nowor: CUT							
Output power: CUT	40W/400 ohm						
	45W/400 ohm	60W/400 ohm					
MICRO		20W /600 ohm					
Working frequency:							
	180 x 180 x h 100 mm	180 x 180 x h 100 mm					
Weight:	2.8 kg	4 kg					
Operating Voltage: 115/	/230 V - 50/60 Hz s	witchable					
Electric input power: 90 VA 230 VA							
Fuse: 2 x 1 AT 2 x 2 A							
Alarm for overheating	Footswitch operat	ing					
Norms: EN60601-1Class I (CF, EN 60601-1-2 93/42	2/EEC (Class IIb)					
Made in Italy Warranty: 12 months							
Diatermo 106 and 108 standard accessories							
KIRKY single-use handle without buttons							
Operative foot-switch							
Flat neutral plate with c	able (30563)						
Kit of 6 short autoclavab		mm, length 5 cm					
Power cable 2 m - Shuko plug							
Tower cable 2 m - Shuko plug							

User manual: available in English, Italian, Spanish, French

in dermatology. Moreover you can choose from a wide variety of electrodes for any need. The modes of operation, CUT, COAG BLEND and MICRO(30517 only), can be easily selected by a

switch on the front panel. The complete isolation between patient and the unit and strict respect of international norms guarantee total safety.



Diatermo MB 132 mono-bipolar - programmable - 120 W



Code 30544 DIATERMO MB 132 - mono-bipolar - 120 W HF electrosurgical unit suitable to perform middle monopolar or bipolar electrosurgery. By selection of the modes of operation MB 132 provides pure cut, coagulated cut, forced coagulation, soft coagulation and, with forceps, bipolar coagulation. The use of either split or normal neutral plate are allowed. **Technology and precision:** Using the digital keyboard MB 132 enables the user to regulate the HF emission time in cut or coagulation mode with great precision, and to reproduce a previous intervention. Moreover it includes a useful "**repeat**" function which enables the user to repeat set impulses from 2 to 9 times, and a timer to monitor the elapsed time of the treatment or the whole operation.

Complete safety: an acoustic alarm (intermittent beep) and a blinking red led on front panel warns user that the neutral plate is

Diatermo MB 132 mono-bipolar: standard accessories Two-button handle (autoclavable code 30547) MB operative foot-switch (usable in alternative to handle) MB flat plate (neutral electrode) Kit 10 short standard electrodes, diam. 2.4. mm. Power cable 2 m Microsurgery handle - Microsurgery needle Manual: available in English, Italian, Spanish, French unplugged or not in contact with the patient or he cable is disconnected. In this condition HF emission for cut and coagulation operation is switched off.

OVH Alarm: the unit incorporates an internal circuit protection to warn when the current delivery lasts too long.

Minimum preselectable power0Level step1Maximum output power CUT (W)120 250Ω Maximum output power BLEND (W)90 250Ω Maximum output power COAG FORCED (W)80 250Ω Maximum output power COAG SOFT (W)60 250Ω Maximum output power COAG SOFT (W)60 250Ω Maximum output power BIPOLAR (W)40 250Ω Crest Factor CUT1.5 1.5 Crest Factor BLEND2.1 1.5 Crest Factor COAG FORCED2.0 1.5 Working frequency 600 kHzWeight Kg8Size LxHxD mm $360x150x265$ Operating voltage (switchable) $115/230V-50/60$ HFuses 230Vac (5x20) TIMED $2x$ 6.3AFive steps adjustable sound level (from 55- to 75 dBA) 500 Self-check $$
Maximum output power CUT (W)120 250Ω Maximum output power BLEND (W)90 250Ω Maximum output power COAG FORCED (W)80 250Ω Maximum output power COAG SOFT (W)60 250Ω Maximum output power BIPOLAR (W)40 250Ω Crest Factor CUT1.5Crest Factor BLEND2.1Crest Factor COAG SOFT1.7Crest Factor COAG SOFT1.7Crest Factor BIPOLAR1.5Working frequency600 kHzWeight Kg8Size LxHxD mm $360x150x265$ Operating voltage (switchable) $115/230V-50/60$ FFuses 230Vac (5x20) TIMED $2x$ 6.3AFive steps adjustable sound level (from 55- to 75 dBA) \cdot
Maximum output power BLEND (W)902500Maximum output power COAG FORCED (W)802500Maximum output power COAG SOFT (W)602500Maximum output power BIPOLAR (W)402500Crest Factor CUT1.5Crest Factor BLEND2.1Crest Factor COAG FORCED2.0Crest Factor COAG SOFT1.7Crest Factor BIPOLAR1.5Working frequency600 kHzWeight Kg8Size LxHxD mm360x150x265Operating voltage (switchable)115/230V-50/60 HFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA)Self-check
Maximum output power COAG FORCED (W)802500Maximum output power COAG SOFT (W)602500Maximum output power BIPOLAR (W)402500Crest Factor CUT1.5Crest Factor BLEND2.1Crest Factor COAG FORCED2.0Crest Factor COAG SOFT1.7Crest Factor BIPOLAR1.5Working frequency600 kHzWeight Kg8Size LxHxD mm360x150x265Operating voltage (switchable)115/230V-50/60 HFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA)Self-check•
Maximum output power COAG SOFT (W) 60 250Ω Maximum output power BIPOLAR (W) 40 250Ω Crest Factor CUT 1.5 Crest Factor BLEND 2.1 Crest Factor COAG FORCED 2.0 Crest Factor COAG SOFT 1.7 Crest Factor BIPOLAR 1.5 Working frequency 600 kHz Weight Kg 8 Size LxHxD mm $360x150x265$ Operating voltage (switchable) $115/230V-50/60 \text{ F}$ Fuses 230Vac (5x20) TIMED $2x 3.15A$ Fuses 115Vac (5x20) TIMED $2x 6.3A$ Five steps adjustable sound level (from 55- to 75 dBA)Self-check \bullet
Maximum output power BIPOLAR (W)40250ΩCrest Factor CUT1.5Crest Factor BLEND2.1Crest Factor COAG FORCED2.0Crest Factor COAG SOFT1.7Crest Factor BIPOLAR1.5Working frequency600 kHzWeight Kg8Size LxHxD mm360x150x265Operating voltage (switchable)115/230V-50/60 FFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA)Self-check
Crest Factor CUT1.5Crest Factor BLEND2.1Crest Factor COAG FORCED2.0Crest Factor COAG SOFT1.7Crest Factor BIPOLAR1.5Working frequency600 kHzWeight Kg8Size LxHxD mm360x150x265Operating voltage (switchable)115/230V-50/60 FFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA)Self-check
Crest Factor BLEND2.1Crest Factor COAG FORCED2.0Crest Factor COAG SOFT1.7Crest Factor BIPOLAR1.5Working frequency600 kHzWeight Kg8Size LxHxD mm360x150x265Operating voltage (switchable)115/230V-50/60 HFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA)Self-check
Crest Factor COAG FORCED2.0Crest Factor COAG SOFT1.7Crest Factor BIPOLAR1.5Working frequency600 kHzWeight Kg8Size LxHxD mm360x150x265Operating voltage (switchable)115/230V-50/60 HFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA).Self-check.
Crest Factor COAG SOFT1.7Crest Factor BIPOLAR1.5Working frequency600 kHzWeight Kg8Size LxHxD mm360x150x265Operating voltage (switchable)115/230V-50/60 HFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA)Self-check•
Crest Factor BIPOLAR1.5Working frequency600 kHzWeight Kg8Size LxHxD mm360x150x265Operating voltage (switchable)115/230V-50/60 HFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA).Self-check.
Working frequency600 kHzWeight Kg8Size LxHxD mm360x150x265Operating voltage (switchable)115/230V-50/60 HFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA).Self-check.
Weight Kg8Size LxHxD mm360x150x265Operating voltage (switchable)115/230V-50/60 FFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA).Self-check.
Size LxHxD mm360x150x265Operating voltage (switchable)115/230V-50/60 FFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA).Self-check.
Operating voltage (switchable)115/230V-50/60 FFuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA)•Self-check•
Fuses 230Vac (5x20) TIMED2x 3.15AFuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA)•Self-check•
Fuses 115Vac (5x20) TIMED2x 6.3AFive steps adjustable sound level (from 55- to 75 dBA)Self-check
Five steps adjustable sound level (from 55- to 75 dBA) • Self-check •
Self-check
Power accuracy output warning •
Split or not split patient plate allowed •
Repetition of timed delivery da 2 a 9
Timed delivery 1-999ms
Last working condition storing •
Electrical Class (EN60601 - 1) I CF
MDD 93/42/EEC Class II b
Patient circuit F

Diatermo MB 122 and MB 160 mono-bipolar - 120W - 160 W



Code 30540 DIATERMO MB 122 - mono-bipolar - 120 W Code 30541 DIATERMO MB 160 - mono-bipolar - 160 W MB 122 and 160 are HF electrosurgical units suitable to effect middle monopolar or bipolar electrosurgery. By selection of the modes of operation they provide pure cut, coagulated cut, forced coagulation, soft coagulation and, with forceps, bipolar coagulation. The use of either split or normal neutral plate is allowed. MB 160 is recommended in case of operational fields damp for instance mucous, or tissue whose composition is varying, with consequent need to have reserve of usable power. For these reasons, MB 160 is suggested for Gynecological and orthopedic surgery.

Leading-Edge Technology. This advanced concept device enables highly professional surgery intervention thanks to ergonomic and safety features derived from high power theatre apparatus.

Complete safety. Open Circuit (OC) Alarm warns the user that connection into the neutral plate has not been made or that the cable is disconnected or the neutral plate is not in contact with the patient. The alarm is signalled by an intermittent beep together with a flashing red light on the front panel. In this condition HF emission for cut and coagulation operation is switched off.

Diatermo MB 122 - MB 160 standard accessories MB single-use two button handles MB operative foot-switch (usable as alternative to handle) MB flat neutral plate Power cable 2 m Kit of 6 short autoclavable electrodes, diam. 2.4 mm. User manual: available in English, Spanish, Italian, French, Polish

Technical specifications	MB122		MB160	
Minimum preselectable power	0		0	
Level step	1		1	
Maximum output power CUT (W)	120	250Ω	160	250Ω
Maximum output power BLEND (W)	90	200Ω	120	200Ω
Maximum output power COAG FORCED (W)	80	150Ω	100	150Ω
Maximum output power COAG SOFT (W)	60	100Ω	80	100Ω
Maximum output power BIPOLAR (W)	40	100Ω	60	100Ω
Crest Factor CUT	1.5		1.5	
Crest Factor BLEND	2.1		2.1	
Crest Factor COAG FORCED	2.0		2.0	
Crest Factor COAG SOFT	1.7		1.7	
Crest Factor BIPOLAR	1.5		1.5	
Working frequency	600 kHz	z	600 kHz	z
Weight Kg	7		7	
Size LxHxD mm	260x110)x265	260x110)x265
Operating voltage (switchable)	115 -23	0	115 -23	0
Mains frequency (Hz)	50-60		50-60	
Fuses 230Vac (5x20) TIMED	2x 3.15	A	2x 3.15	A
Fuses 115Vac (5x20) TIMED	2x 6.3A		2x 6.3A	
Electrical input power (VA)	300		350	
Electrical input current (230Vac) (A)	1.3		1.5	
Electrical input current (115Vac) (A)	2.6		3	
Five steps adjustable sound level (from 55- to 75dBA)	•		•	
Self-check	•		•	
Power accuracy output warning	•		•	
Split or not split patient plate allowed	•		•	
Last working condition storing	•		•	
Electrical Class (EN60601 - 1)	I CF		I CF	
MDD 93/42/EEC Class	II B		II B	
Patient circuit	F		F	
Conform to EN60601-1-4 (1998)	•		•	

OVT Alarm. The unit includes an internal circuit protection warning when the current delivery lasts too much long. **Code 27139 DIATERMO NYLON BAG - black** See page 25

FOOT	SWITCHES AND BOARD	It allows selection
GIMA code	Footswitches for MB 122, 132, 160, 200, 202	Antiexplosion and
30568	Standard footswitch	And and a state of the state of
30571	Waterproof MB footswitch	Constant of the local division of the local
30570	Double MB footswitch - antiexplosion, water proof Footswitches for MB 240, 250, 380, 400	
	Footswitches for MB 240, 250, 380, 400	10000
30569	Double antiexplosion, water proof footswitch - MB240-380	All and a second second
30572	Double antiexplosion, water proof footswitch - MB250-400 Main Board	In Il
	Main Board	
30557	Main board - specify model and serial number of diatermo with order	

It allows selection from pedal of CUT and COAG functions Antiexplosion and waterproof.





Diatermo MB 200 and MB 202 - mono-bipolar - 200 W



Code 30542 DIATERMO MB 200 - 200 Watt Code 30546 DIATERMO MB 202 - 200 Watt

DIATERMO MB200 and MB202 are HF electrosurgical units suitable to effect middle monopolar or bipolar electrosurgery. The available waveforms and peak voltage value, as well as the accurate HF leakage current operation for polypectomy, TURP, intrauterine resections, endometriosis excision, etc.

The units allow the accurate preset of the output power with as low as 1 Watt resolution and to perform coagulation with high crest factor current, to get an elevated thermal effect, as well as with low voltage low crest factor current, to get coagulation in absence of carbonization. Ten different programs related to ten different operative conditions could be stored and easily recalled by the surgeon.

The use of either split or normal neutral plates are allowed. A special electronic circuit (Skin Plate Electronic Control) continuously warns the plate to patient contact safety and unwanted short circuit in the connecting cable.

An over time warning (OVT) is provided to prevent excessive heating of the tissue around the surgical target due to too long current delivery time.

DIATERMO MB202, furthermore, can be used with current delivery time equal to that of actuation of the output power switch as well as with preset current delivery time in the range from 1 ms up to 999 ms. The output pulse can be automatically repeated 1 to 250 times. The presetting of the current delivery time is propre for collecting of bioptic samples and for microsurgical dermatologic operationy like treatment of telangiectasias, spider nevus, angiomas, etc. Bipolar cable and forceps are not included in standard accessories.



Technical specifications	MB200		MB202	
Minimum preselectable power	0		0	
Level step digital	1		1	
Maximum output power CUT (W)	200	250Ω	200	250Ω
Maximum output power CUT 90% (W)	200	250Ω	200	250Ω
Maximum output power CUT 80% (W)	200	250Ω	200	250Ω
Maximum output power CUT 70% (W)	200	250Ω	200	250Ω
Maximum output power BLEND (W)	120	200Ω	120	200Ω
Maximum output power COAG FORCED (W)	150	150Ω	150	150Ω
Maximum output power COAG SOFT (W)	90	100Ω	100	100Ω
Maximum output power BIPOLAR (W)	-		100	100Ω
Maximum output power BIPOLAR COAG(W)	100	100Ω	-	
Maximum output power BIPOLAR CUT (W)	120	250Ω	-	
Crest Factor CUT	1.5		1.5	
Crest Factor CUT 90%	1.6		1.6	
Crest Factor CUT 80%	1.7		1.7	
Crest Factor CUT 70%	1.8		1.8	
Crest Factor BLEND	2.1		2.1	
Crest Factor COAG FORCED	2.0		2.0	
Crest Factor COAG SOFT	1.7		1.7	
Crest Factor BIPOLAR	-		1.5	
Crest Factor BIPOLAR CUT (W)	1.5		-	
Crest Factor BIPOLAR CUT (W)	1.5		-	
Working frequency	600 kHz	:	600 kH	z
Weight Kg	8		8	
Size LxHxD mm	360x150)x265	360x15	0x265
Selectable mains power(Vac)	115 -230		115 -230	
Mains frequency (Hz)	50-60		50-60	
Fuses 230Vac (5x20) TIMED	2x 3.15A		2x 3.15A	
Fuses 115Vac (5x20) TIMED	2x 6.3A		2x 6.3A	
Power accuracy output warning system	•		•	
Split or not split patient plate allowed	•		•	
Timed delivery repetition	-		1-999n	ıs
Electrical Class (EN60601 - 1)	I CF		I CF	
MDD 93/42/EEC Class	II b		II b	
Patient circuit	F		F	
Duty cycle (action/pause) in seconds	10/30		10/30	

Diatermo MB 200 - MB 202 standard accessories

MB two-button handle (autoclavable code 30547) handle in beside picture is not correct MB operative foot-switch (usable in alternative to handle)

MB flat neutral metal plate with cable

Kit 9 short standard electrodes, diam. 2.4. mm.

Power cable 2 m Microsurgery handle - Microsurgery needle (10 pcs.) (only MB 202)

Manual: available in English, Italian, French (only MB 202)

Hospital HF Electrosurgical Units 240 and 380 Watt



CSO

MOD

CONTEMPORARY DUAL MODE MB 240 and 380 can be used in the same time in monopolar mode (by handle) and bipolar mode (by footswitch)

Code 30690 DIATERMO MB 240 C Code 30692 DIATERMO MB 380 C Code 30692 DIATERMO MB 380 C C Cost

These HF electrosurgical unit can be used to execute monopolar and bipolar surgery in the many fields of application where high precision and reliability are essential, as in the endoscopic surgery.

EASY TO USE

Graphic icons allow an easy selection of the operation mode. All operating conditions and selected output controls are represented by bright digital indications.

CUT

30690

The monopolar cut can be performed by pure sine current to obtain an incision with a minimum damage for the adjacent tissues and sure recovery for first intention.

Two different modalities of modulation allow to reduce bleeding during monopolar cut. In the bipolar modality the cut can be effected by pure sine current.

HEMOSTASIS

When the surgical action requires the obliteration of a blood vessel the availability of currents with different coagulative powers enables this type of work both with monopolar and bipolar surgery. **FULGURATION**

When it is necessary to cause a superficial necrosis of wide areas, protecting the deeper tissues, a special coagulant current that dehydrates the superficial layer of the tissue and reduces the possibility to damage those beneath is available for the operation. **OUTPUT CONTROL**

Output power levels are adjustable though incremental encoders that allow the exact pre-sets and repetition of the values. The output function is linearized and controlled by ultra-modern electronic micro-controllers which will interrupt power if any alarm condition happens. A special electronic circuit (Skin Plate Electronic Control) continuosly warns the plate to patient contact safety and unwanted short circuit in the connecting cable

SAFETY OF USE

Circuits dedicated to the safety of operator and patient are the priority. This ensure the leakage current is kept well under the values by the international requirements, under every output condition. Monopolar and bipolar output circuits are completely floating and the use of the defibrillator is allowed while the reference plate patient is connected.

RELIABILITY

DIATERMO MB uses all solid state electronic circuits and is made with interchangeable units for a fast and effective maintenance. Automatic control circuits protect the units from damage also in case of repeated improper use.



Monopolar power distribution

Load

resistance

300 Ohm

300 Ohm

300 Ohm

300 Ohm

300 Ohm

2000 Ohm

100 Ohm

100 Ohm

Peak to peak

voltage

1,4 kV

1,4 kV

1.4 kV

1,4 kV

 $14 \,\mathrm{kV}$

4,2 kV

0,5 kV

0,5 kV

Max power

240/MB 380

250W/375W

225W/340W

200W/300W

150W/225W

100W/150W

80W

90W

80W





20

CUT

COVE

Standard Accessories
1 - Power supply cord SIEM-CEE 5 m
1 - Two-button handle (autoclavable code 30547
5 - Two-button handle (cold sterilizable)
1 - Cable for disposable plate
5 - Disposable plate
1 - Water proof double foot switch
3 - Short, general surgery blade electrode
3 - Long, general surgery blade electrode
3 - Short, general surgery needle electrode
3 - Short, general surgery ball electrode
1 - User manual (Italian, English, Spanish)
1 - Service manual (Italian, English)

Activation davia

Technical specifications DIATERMO MB 240/DIATERMO MB 380

86



Hospital HF Electrosurgical Units 250 and 400 Watt



Code 30694 DIATERMO MB 250 Code 30696 DIATERMO MB 400

DIATERMO MB250 and MB400 are high frequency electrosurgical equipments suitable to deliver current for monopolar cut and coagulated cut (with different levels of coagulation), bipolar cut and coagulation. During bipolar coagulation there is an automatic "Autostart-Autostop" system activating when coagulation is reached.

A range of ten different modes and power levels can be easily stored and recalled. It is possible to use either single plate neutral electrodes or split conductive zone electrodes in order to

Technical specifications MB250/MB400 Work condition memorization Digital power visualization Continuous check control Automatic control of the plate-patient connection Automatic control of the impedance Automatic control of excessive time for distribution Automatic control of the supplied power level Bipolar coag with automatic activation/disact. Consistent with Argon unit Minimum preselectable power: 0 Unitary power step for powers from 0 W to 50 W Power step 10 for powers higher than 50 W Digital level display Selection of power through push-buttons Size LxHxP mm: 470x150x380 Weight (kg): 18 Selectable mains power (Vac): 115-230 Mains frequency (Hz): 50-60 Fuses 230Vac (5x20) TIMED: 2xT 4A/5A Fuses 115Vac (5x20) TIMED: 2xT 8A/10A Electrical input power (VA): 800/1000

Electrical input current (115Vac) (A): 7/9 Five steps adjustable sound level Self-check Power accuracy output warning Skin Plate Electronic Control (plate-patient control) Split or not split patient plate allowed Working condition storing: last 10 setup Electrical Class (EN60601-1): ICF MDD 93/42/EEC Class: II b EN55011 (CISPR 1 1) Class (Class/Group): 2/B Patient circuit: F Duty Cycle (action/pause) in seconds: 10-30 Output power control by foot-switch or finger-switch Defibrillation-proof Ten seconds delivery warning (OVT) Equipotential binding Metallic cabinet Polycarbonate covered panels Conform to EN60601-1 (1998) Conform to EN6060 1 - 1 -2 (2003) Conform to EN6060 1 -2-2 (2000)

Electrical input current (230Vac) (A): 3.5/4.5											
Monopolar and Bipolar application Diatermo MB 250 and MB 400											
	Max Power MB250/400	Imped.	Maximum output voltage	Modulation factor	Duty Cycle	Crest Factor					
Monopolar Applications	425 kHz										
Cut		250/400 W	300 Ω	1500 Vpp	-	-	1.6				
Cut/Coag 80%		220/300 W	300 Ω	1500 Vpp	10 kHz	80%	1.8				
Cut/Coag 60%		200/250 W	300 Ω	1500 Vpp	10 kHz	60%	2.1				
Cut/Coag 40%		150/200 W	300 Ω	1500 Vpp	10 kHz	40%	2.6				
Enhanced Cut		150/250 W	300 Ω	1500 Vpp	1.25 kHz	5%	1.6				
Blend		150/250 W	500 Ω	2500 Vpp	-	-	1.6				
Speedy Coag		100/120 W	500 Ω	2500 Vpp	8-12 kHz	20%	3.4				
Deep Coag		100/120 W	500 Ω	800 Vpp	-	-	1.6				
Spray Coag		60/100 W	2000Ω		1 kHz	20%	3.4				
Spray Coag Argon		60/100 W	2000Ω	4500 Vpp	1 kHz		3.4				
Bipolar Applications	525 kHz										
Bipolar Cut		120 W	150 Ω	800 Vpp	-	-	1.5				
Bipolar Cut/Coag 80%		100 W	150 Ω	800 Vpp	10 kHz	80%	1.7				
Bipolar Cut/Coag 60%		100 W	150 Ω	800 Vpp	10 kHz	60%	2.0				
Bipolar Cut/Coag 40%		60 W	150 Ω	800 Vpp	10 kHz	40%	2.4				
Bipolar Blend		100 W	300 Ω	1100 Vpp	-	-	1.7				
Bipolar Deep Coag		70 W	100 Ω	400 Vpp	-	-	1.5				

control impedance stability of plate to patient contact during the surgical operation.

Control of the units is made by front panel keys and display; mains inlet is located on the rear panel. The units have automatic control systems to monitor the internal parameters and alert on possible damages/errors. The operational parameters used are constantly stored so that the last selected parameters are recalled, every time the unit is switched on or the operative method is changed. The level of sound can be adjusted, every operator can choose his own level according to the environmental working conditions. The units can work through handles with pushbuttons or handles without pushbuttons but with double foot switch. It's possible to connect bipolar forceps to the unit for the bipolar functions.



Standard Accessories

- 1 Power supply cord SIEM-CEE 5 m 1 - Two-button handle (autoclavable code 30547)
- 5 Two-button handle (cold sterilizable)
- 1 Cable for disposable plate
- 5 Disposable plate
- 2 HP double Water proof foot switch
- 3 Short, general surgery blade electrode 7 cm
- 3 Long, general surgery blade electrode 10 cm
- 3 Short, general surgery needle electrode 5.5 cm
- 3 Short, general surgery ball electrode Ø 4 mm, 6 cm
- 1 Electrode brush
- 1 User manual (Italian, English) 1 - Service manual (Italian, English)



Loop Colposcopy Autoclavable Electrodes





Autoclavable Electrodes

GIMA	Reference	Autoclavable electrodes Ø 2.4 mm	Reference	GIMA	15 16	(17
code	number	Autociavable electroues @ 2.4 mm		code	15 10) 1/
lengt	h 5 cm	minimum order: 6 pcs.	length	10 cm	1 1 2 3 4 5 6 7 8 9 10 $\sqrt{7}$ cr	n
30501	1	Electrode wire - straight	21	30521		
30502	2	Electrode wire - angled 45°	22	30522	5 cm long electrodes - reference number	
30503	3	Electrode bend - \emptyset 4 - straight	23	30523	3	- 🚱 -
30504	4	Electrode bend - Ø 8 - straight	24	30524	4 4 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	
30505	5	Electrode hook - angled 45°	25	30525	5 / / / / /	
30506	6	Electrode wire 1 mm angled 45°	26	30526	6	-
30507	7	Electrode straight slip-knot - straight	27	30527	7	
30508	8	Electrode angled slip-knot - straight	28	30528	8 AUTOCLAVABLE	
30509	9	Electrode ball point - Ø ³ mm angled 45°	29	30529	9 AUTOCLAVABLE	1
30510	10	Electrode ball point - Ø 3 mm straight	30	30530	0 7 7 7 7 7 7 7 7 7 7 7 7	
30500	SET	Set of 10 electrodes	SET	30531	1	
lengt	n 7 cm	minimum order: 10 pcs. lengt		10 cm long electrodes - reference numb		cm 🛛
30511	15	Needle electrode	35	30532	2 2 21 22 23 24 25 26 27 28 29 30 35 36	
30512	16	Blade electrode	36	30533	$3 \begin{bmatrix} 21 & 22 & 23 & 24 & 23 & 20 & 27 & 28 & 29 & 30 \end{bmatrix} 53 \ 50 \ 50$, , , ,
30513	17	Ball electrode	37	30534	4	

Single use Sterile Electrodes

GIMA code	Reference number	Single use electrodes Ø 2.4 mm minimum order: 24 pcs.	Reference number	GIMA code	N. 13 Length N. 11
lengtl	n 7 cm	Sterile electrode	length	15 cm	7 cm
30670	13	Needle electrode - sterile electrode	33	30674	N. 12
30671	11	Blade electrode - sterile	31	30675	
30672	12	Ball ø 4 mm. electrode - sterile	32	30676	$\bigvee_{N=22}$ Length
		Sterile electrode			N. 55 15 cm
-	-	Loop electrode - 15mmx8mm	34	30678	• N. 32

Single Use, Metal and Rubber Plates





Code 30573 RUBBER PLATE 20x15 cm - without cable Code 30574 REM RUBBER PLATE 20x15 cm - without cable **Code 30575 CABLE FOR RUBBER PLATES** Code 30566 METAL PLATE - without cable Code 30563 CABLE FOR PLATES - 5 m Code 30559 CABLE FOR PLATES - 2.5 m



Monopolar Handles with or without switches

MB HANDLES with 2 "click" push-buttons GIMA autoclavable electrosurgery pencils with CUT-COAG switch have been studied and tested to offer maximum reliability and functionality to the operator. MB handles are provided with a 3 Pins socket Valley Lab type that fits all Gima mono-bipolar Diatermo MB (122, 132, 160, 200, 202, 240, 380) and majority of bipolar electrosurgical units: Aspen Lab, ES Generator, EMC Statome, Danieli, Braun, Berchtold, Ohmeda, Ritter, Conmed, Eschman, Bovie, Martin, Kontron, Bard, Birtcher 771, Cobi, Valley Lab, Led, Erbe...

Code 30554 MB AUTOCLAVABLE HANDLE - 100 times Autoclavable handle **with 2 large "click" push-button**, provided with a 3 meters long silicone cable and a blade electrode. It can be autoclaved up to 100 times (20 times electrode). **For electrodes Ø 2.4 mm Code 30548 STAR AUTOCLAVABLE HANDLE - 30 times**

Same as code 30554 but autoclavable up to 30 times (electrode is autoclavable up to 20 times). For electrodes Ø 2.4 mm Code 30549 STAR 5 AUTOCLAVABLE HANDLE - 30 times Same as STAR, but with a 5 meters long silicone cable

Code 30547 ORION AUTOCLAVABLE HANDLE - 100 times Same as 30554, but with a screw clamp locking system that not only guarantees a safe contact, but also adapts to the different electrode diameters.

Code 30551 KIRKY SINGLE-USE HANDLE-STERILE Single-use handle with "click" push-buttons for cut and coag. Includes blade electrode. minimum order: 10 pcs. Code 30553 GIMA SINGLE-USE HANDLE-STERILE Same as 30551. minimum order: 10 pcs.

106 HANDLES

These handles are provided with a 1 Pin socket (4 mm) that fits all Gima Diatermo and majority of electrosurgical units in the market. These handles **do not have push-buttons.**

Code 30519 AUTOCLAVABLE 106 HANDLE Autoclavable handle **without buttons**, provided with

a 3 meters long cable and a blade electrode.

It can be autoclaved up to 50 times.

Code 30518 KIRKY SINGLE-USE 106 HANDLE- STERILE Single-use handle **without button** with blade electrode with 4 mm PIN connection.

MICROSURGERY

Microsurgery accessories for all GIMA Diatermo and electro-depilators Code 30552 MICROSURGERY HANDLE Code 30560 MICROSURGERY NEEDLE

ELECTRODE BRUSH Code 30537 ELECTRODE BRUSH - 50x50 mm

Disposable sterile radiopaque abrasive tip cleaner pad. Box of 100



Monopolar Forceps, Scissors and Cables

30612 tip 2 mm FDA APPROVED C = 0120	30610	Monopolar forceps are provided with a 4 mm connection for standard monopolar cables. These can be used with all Gima, Led, Erbe and many other electrosurgical units in the market.
30613	GIMA code	Insulated Monopolar Instruments
	30610	Monopolar cable - 4 mm pin
30614	30611	Straight monopolar forceps 19 cm. (7 ^{1/2} ")
Metzenbaum	30612	Bayonet monopolar forceps - 19 cm. (7 ^{1/2} ")
30611	30613	Monopolar scissors - 18 cm. (7")
30011	30614	Metzenbaum monopolar scissors - straight - 18 cm (7")
tip 2 mm	30615	Metzenbaum monopolar scissors - curved - 18 cm (7")

Universal High Quality Insulated Bipolar Forceps



US Connector bipolar forceps

			-					
30621	SEMKIN		30	622	CUSHING	30623	JANSEN BAYONET	
GIMA	IMA Model		Application	Straight tip	(f 0120			
code	wiouei	Conne	cm	inches	Application	Size	FDA Approved	
30620	ADSON	US	12.1 cm	4 3/4"	GENERAL/PLASTIC	1 mm round points		30620
30621	SEMKIN	US	14 cm	5 1/2"	GENERAL/PLASTIC	0.5 mm points	ADSON	
30622	CUSHING	US	15.9 cm	6 1/4"	GENERAL/PLASTIC	1 mm round points	_UNIVER	SAL US
30623	JANSEN BAYONET	US	17.8 cm	7	GENERAL/PLASTIC	1 mm round points	CONN	ECTOR

Bipolar cables for major brands

F	0120
	0120

Quality highly flexible silicone bipolar cables. Autoclavable at 137°C 3 m long (10"). Suitable for most generators, see below compatibility, and with connector for European or US forceps		Connector ctrosurgical unit	Įį	ļ	ļĮ	Į
GIMA code	30640 3	30637	30	543	30639	30638
Connector to forceps	EU =	US		EU	EU	EU
Connector to electrosurgical	4 mm banana plug		GIMA			