

## R98eASME (V3237W-ASME)



### Type of Appliance

Rinnai model number

### Operation

Minimum/Maximum Gas Rate (Input)

### Electrical

### Electrical Consumption

### Ignition System

Hot Water Capacity

Temperature

Temperature (without controller)

Approved Gas Types

Installation

Thermal Efficiency

Service Connections

Water Flow Control

Minimum/Maximum Water Supply Pressure

This model has been built in accordance with the requirements of the ASME Boiler and Pressure Vessel Code and has received the Certificate of Authorization from the National Board. The heat exchanger has the NB and the HLW stamps.

Temperature controlled, continuous flow, gas hot water system

REU-V3237W-ASME

Forced combustion

19,000 - 237,000 BTU/h (Natural Gas or Propane)

Appliance: AC 120 Volts - 60 Hz  
Controller: DC 12 Volts

Normal 72 watts  
Standby 2 watts  
Anti-frost protection 116 watts

Direct electronic ignition

0.6 to 8.0 GPM (50° F rise) 0.9 to 9.8 GPM (35° F rise)

98° - 140° F

120° F (factory default)

Natural or Propane (ensure unit matches gas type)

Outdoor only

Natural Gas: 85% Propane: 83%


Gas supply: 3/4 inch MNPT  
Cold water inlet: 3/4 inch MNPT  
Hot water outlet: 3/4 inch MNPT

Water flow sensor, electronic water control and by-pass control

15 - 150 PSI (50 PSI or above is recommended for maximum flow)

### FLOW TABLE

#### Water Flow Capacity Curve



### Water Temperature Control

#### Controller

Simulation feed forward and feedback

MC-91-1US (included)

Deluxe controller: MC-100V-1US (optional)

Bathroom controller: BC-100V-1US (optional)

Wireless controller (with transceiver): MC-502RC-1US-MS (optional)

#### Controller Cable

Non-polarized two-core cable, minimum 22 gauge

#### Safety Devices

- Flame failure - Flame Rod
- Boiling protection
- Combustion fan rpm check
- Over current - glass fuse (3 amp)
- Remaining flame (OHS)
- Thermal fuse
- Automatic frost protection

#### Clearances from combustibles

- Top of heater - 12 inches
- Front (Panel) - 24 inches
- Front (Exhaust) - 24 inches
- Back of heater - 0 inches
- Bottom of heater - 12 inches
- Sides of heater - 6 inches

#### Clearances from non-combustibles

\* 24 inches required for serviceability

- Top of heater - 2 inches
- Front (Panel) - 0 inches \*
- Front (Exhaust) - 24 inches
- Back of heater - 0 inches
- Bottom of heater - 2 inches
- Sides of heater - 1/8 inch

#### Min. / Max. Gas Supply Pressure

Natural Gas: min 5" W.C. max 10.5" W.C.

Propane Gas: min 8" W.C. max 13.5" W.C.

#### Manifold Gas Pressure (inches W.C.)

Natural Gas: high fire 3.0" W.C. low fire 0.67" W.C.

Propane Gas: high fire 3.7" W.C. low fire 0.83" W.C.

#### NOx

Meets California and Texas NOx Emission Rules

#### Warranty

Residential only; heat exchanger 10 years\*; all other parts 5 years\*; labor 1 year; (\* 3 years if used as a circulating water heater within a circulation loop, where the water heater is in series with a circulation system and all circulating water flows through the water heater, and where on-demand recirculation is not incorporated )

*Rinnai is continually updating and improving products; therefore, specifications are subject to change without prior notice. Local, state, provincial and federal codes must be adhered to prior to installation.*

### DIMENSIONS

**WEIGHT: 55 LBS**

