



UNITED STATES STOVE COMPANY



"Keeping America Warm Since 1869"



WONDERCOAL CIRCULATOR - MODEL 2827


Wondercoal® Circulator

Model 2827

The Model 2827 WONDERCOAL® uses a plentiful, inexpensive fuel: coal. U.S. Stove's WONDERCOAL® combines energy efficiency with versatility making it the hottest model on the market. WONDERCOAL® provides the extra heat needed in the winter while keeping heating costs down. With the standard lift-top, it will not only heat, but also cook. WONDERCOAL® is the answer to today's energy demands, from America's oldest and most experienced stove maker, U.S. Stove.

FEATURES / BENEFITS

- Superior heating performance up to 48,000 BTU's per hour adequately heats large areas.
- Large capacity firebox provides heating for up to 10 hours at an "average" output on one fuel loading.
- Heavy-duty firebrick lining ensures high-combustion efficiency and safe performance.
- Heavy-gauge, aluminized steel construction assures longer firebox life and promotes rapid heat transfer.
- Heavy-duty, cast-iron, draw-style shaker grate provides years of trouble-free performance and eliminates dropping the "firebed".
- Cast-iron front and rear liners protect firebox ends and help distribute heat evenly.
- Fully air-tight construction aids in proper regulation of burn efficiency, as well as controlling proper combustion.
- Automatic bi-metallic thermostat provides trouble-free comfort control without electricity.
- Lift-top with positive safety latch provides access to auxiliary cooking surface and safely holds lift-top in open position.
- Positive, two-stage door latch prevents flashbacks upon opening of feed door.
- Heavy-duty, cast-iron feed and ash doors with ceramic door gaskets prevent warpage, enhance air-tight operation, provide greater efficiency, and promote longer burn times.
- Attractive earth-tone, high-temp textured enamel finish with raised, wood-grained escutcheon panel makes unit easy to clean and resistant to discoloration, while offering contemporary styling.
- Optional Blower - Model F36 Manual and/or Automatic.



SPECIFICATIONS

- Lining: Firebrick
- Grates: Cast Iron Shaker/Draw
- Dimensions: 33" H x 19" W x 32 1/2" L
- Flue Size: 6"
- Shipping Weight: 245 lbs.
- Floor Required: Non-combustible
- Clearance: 36" to any combustible rear wall; 24" to side wall
- Coal Capacity: 50 lbs.

Limited Warranty

Three (3) Years on Firebox
One (1) Year on All Other Components

IMPORTANT
Tested to U.L. Standard
1482 by Warnock Hersey.



HEARTH
PRODUCTS
ASSOCIATION



UNITED STATES STOVE COMPANY

P.O. BOX 151 • SOUTH PITTSBURG, TN 37380 • (423) 837-2100

Visit our website at www.usstove.com

Keeping America Warm Since 1869

Note: All photographs are for illustrative purposes only and are not meant to be a guide for actual installation. All safety regulations with respect to combustible materials and surfaces must be followed. See installation manual for specifics. Dimensions and specifications are subject to change without notice. Contact local building or fire official about restrictions and installation inspection requirements.