

Service Bulletin



Applies To: **2007 MDX** – ALL **October 16, 2008**

2008 MDX - From VIN 2HNYD28..8H500001 thru 2HNYD28..8H514713

A/C Whistles While in Recirculation Mode

(Supersedes 08-014, dated April 11, 2008, to update the information marked by the black bar)

SYMPTOM

A whistling noise occurs when recirculation mode is selected while the vehicle is driven above 50 mph.

PROBABLE CAUSE

The recirculation door is not completely closed, causing an air leak and creating a whistle.

CORRECTIVE ACTION

Replace the blower unit.

PARTS INFORMATION

Blower Sub-Assembly: P/N 79305-STX-A02

WARRANTY CLAIM INFORMATION

In warranty: The normal warranty applies.

Operation Number: 612100 Flat Rate Time: 0.7 hour

Failed Part: P/N 79305-STX-A02

© 2008 American Honda Motor Co., Inc. - All Rights Reserved

Defect Code: 03214 Symptom Code: 04201 Template ID: 08-014A

Out of warranty: Any repair performed after warranty expiration may be eligible for goodwill consideration by the District Parts and Service Manager or your Zone Office. You must request consideration, and get a decision, before starting work.

REPAIR PROCEDURE

- 1. Remove the glove box:
 - Refer to page 20-126 of the 07–08 MDX Service Manual, or
 - Online, enter keywords GLOVE BOX, and select Glove Box Removal/Installation from the list.
- 2. Remove the blower unit:
 - Refer to page 21-115 of the service manual, or
 - Online, enter keywords BLOWER REMOVAL and select Blower Unit Removal/Installation from the list.
- Remove the blower motor, the dust and pollen filter, and the recirculation control motor from the old blower unit.
- Install the blower motor, the dust and pollen filter, and the recirculation control motor on the new blower unit.

NOTE: Make sure the recirculation control motor is adjusted to the highest point possible by pushing the motor toward the top of the unit, and then tightening the screws.

RECIRCULATION MOTOR (Push on it while tightening the screws.)



NEW BLOWER UNIT

5. Install the blower unit in the reverse order of removal.

1 of 1