NEW

Uni-3L2 Bench Model

Uni-3L2 Pole Model

Specifications

Capacity (Dual Range):
0-15 x 0.005 lb/15-30 x 0.01 lb

Weighing Resolution:
3,000 display divisions maximum

Display Types:
L1: LCD, blue alphanumeric (23 digits 16 seg)
L2: LCD, backlight, alphanumeric (192 x 16 DM + 23 digits 7 seg)

Display Items:
Tare: Four-digits
Unit price: Five-digits
Total price: Six-digits

Preset Keys:
84 one-touch preset keys 168 presets (assign two items/key)

Memory Capacity:
2 MB

Communications:
TCP/IP 10/100 Base T Ethernet

Platter:
Countertop models: 14.5 x 10.5 in

Printing Speed:
3.9 in (100 mm) per second

Printing:
Direct thermal 2.2 in (56 mm) (448 dot, 8 dot/mm)

Label Size:
Width: 1.5-2.5 in (38-64 mm) {min}
Length: 1.2-6.9 in (30-175 mm) {max}

Label Roll:
Inside diameter: 1.6 in (40 mm)
Outside diameter: 3.9 in (100 mm)

Label Backing Paper:
Width: Up to 2.6 in (66 mm)

Power Supply:
AC100-240V, 50/60 Hz

Power Consumption:
Stand-by: 50 W
In operation: 100 W

Classification:
NTEP CC 07-005

Warranty:
One-year limited warranty

Ishida Uni-3
Price Computing Electronic System Scale Printer

With premium-class presets, fast print speed and more labeling functions, you are getting more flexibility and more features – all for less cost than comparable price computing scales with printers.

With three models and two display types, you can easily find a Uni-3 to fit your specific application needs.

Ethernet or optional wireless communication enables any Uni-3 to be added to your existing network – ensuring you have consistent control of all scales in your store.

Optional product management software ensures easy file maintenance as well as PLU and tare weight consistency throughout your operation.

The power of the Uni-3 is at your fingertips with flexible preset buttons to represent PLUs, container tare values, label formats, images and logos.

The Uni-3 L1 model features a vibrant blue alphanumeric display with a sharp white 16-segment capability. The Uni-3 L2 model features a clear alphanumeric LCD display with one line alphanumeric and one line numeric only. Each model offers a matching customer display.

Standard Features

- Dual-range weighing (0-15 x 0.005 lb/ 15-30 x 0.01 lb)
- Static TCP/IP Ethernet communication
- 2 MB standard memory
- Up to 168 function keys assist with intuitive operation
- Fast printing speed
- Meat nutrition labeling
- Multiple label formats

- Powerful batch printing feature
- Proportional tare
- Side-load label
- Compatible with third-party communication software, including ADC's InterScale and Invatron's PLUM

PART #	MODEL	CAPACITY
165200	Uni-3L1 Bench	0-15 x 0.005 lb/15-30 x 0.01 lb
165201	Uni-3L1 Pole	0-15 x 0.005 lb/15-30 x 0.01 lb
165202	Uni-3L2 Bench	0-15 x 0.005 lb/15-30 x 0.01 lb
165203	Uni-3L2 Pole	0-15 x 0.005 lb/15-30 x 0.01 lb

L1 Customer Display Bench Unit

Side-loading Label Feature

Uni-3 DISPLAYS

Uni-3L1

Uni-3L2

Ishida Uni-3
Price Computing Electronic System Scale Printer

PART #	MODEL/DESCRIPTION	CAPACITY	EST. SHIP WEIGHT	PRICE
165200	Uni-3L1 Bench	0-15 x 0.005 lb/15-30 x 0.01 lb	25 lb	Consult
165201	Uni-3L1 Pole	0-15 x 0.005 lb/15-30 x 0.01 lb	25 lb	Consult
165202	Uni-3L2 Bench	0-15 x 0.005 lb/15-30 x 0.01 lb	25 lb	Consult
165203	Uni-3L2 Pole	0-15 x 0.005 lb/15-30 x 0.01 lb	25 lb	Consult

Options/Accessories

170541	Lineless label modification kit	Consult
47976	Fish platter, (L x W x H) 9.5 x 13.5 x 0.7 in with drain	Consult
47997	Produce platter, (L x W x H) 9.5 x 13.5 x 0.7 in	Consult

Communication

|		
168750	ScaleLink Pro 5 Lite software CD, license file required and purchased separately (see page 66)	Consult
168751*	ScaleLink Pro 5 Lite license file, one license required per computer	Consult
168745	Internal wireless communication 802.11 b/g	Consult
78860	Cross cable Ethernet CAT5, 6 ft	Consult

Manuals and Service Tools

|		
166737	Additional owners manual	Consult
166736	Service manual	Consult
160906	USB flash memory device, 1 GB	Consult
168325	Uni-3 support CD	Consult
Consult	Additional operation mode manual	Consult

Label Stock

Please refer to labels section of this catalog for ordering information and case quantity pricing.

Software key is provided after online registration is completed

Manuals and software programs can be downloaded from the distributor section of www.ricelake.com/retail