Service Manual





PRODUCED & DISTRIBUTED BY:

WOLF STEEL

24 Napoleon Road Barrie, Ontario Canada L4M 4Y8

Tel: 705-721-1212 Fax: 705-722-6031

TECHNICAL HELP LINE

Tel: 1 - 888 - 721- TECH (8324)

Fax: 1 - 877 - FAX - TECH (329-8324)

Email: tech@napoleon.on.ca

Web: www.napoleonfireplaces.com

COPYRIGHT 2005 WOLF STEEL LTD.

ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Wolf Steel's Service Manual Index

Part 1: Troubleshooting: Direct Vents	
Pilot Not Lighting Flowchart	1
Pilot Not Holding Flowchart	
Pilot Failure Flowchart	3
Main Burner Not Lighting Flowchart	4
Main Burner Delayed Ignition Flowchart	5
Main Burner Low Flame Flowchart	
Main Burner Failure Flowchart	7
Complete Unit Shutdown	
Odour Flowchart	
Bout & Bushlashasting National Vanta	
Part 2: Troubleshooting: Natural Vents	40
Pilot Not Lighting Flowchart	
Pilot Not Holding Flowchart	
Pilot Failure Flowchart	
Main Burner Not Lighting Flowchart	15
Main Burner Delayed Ignition Flowchart	14
Main Burner Failure Flowchart	
Complete Unit Shutdown	
Odour Flowchart	10
Part 3: Troubleshooting: Vent Free	
Pilot Not Lighting Flowchart	19
Pilot Not Holding Flowchart	
Pilot Failure Flowchart	21
Main Burner Not Lighting Flowchart	22
Main Burner Delayed Ignition Flowchart	
Main Burner Low Flame Flowchart	
Complete Unit Shutdown	25
Odour Flowchart	26
Part 4: Troubleshooting: Other Issues	
Carboning Flowchart	27
Oil-Canning Flowchart	
Blower Flowchart	
Remote Control Guide	
Part 5: Testing & Adjustments	
Testing: Pressures	
Testing: Gasket	
Testing: Switches - Spill Switch	
Testing: Switches - T.stat/Toggle	
Testing: Millivolts - Thermocouple - Robertshaw Valve	
Testing: Millivolts - Thermocouple - SIT 820 Nova Valve	
Testing: Millivolts - Thermopile	35
Testing: Function - Magnet Coil - Robertshaw Valve	
Testing: Function - Operator Coil - Robertshaw Valve	
Testing: Function - Magnet Coil - SIT 820 Nova Valve	58
Testing: Function - Operator Coil - SIT 820 Nova Valve	
Testing: Pilot Flame	
Adjustments: Pilot Flame	
Adjustments: Spill Switch - Robertshaw Valve	
Adjustments: Spill Switch - SIT 820 Nova Valve	
Adjustments: Venturi/Air Shutter	
CUPYRIGHT 2003 WOLLD STEEL LID. ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE P PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA	RIOR WRITTE




PART 1: TROUBLESHOOTING: DIRECT VENTS

Pilot Not Lighting Flowchart	1
Pilot Not Holding Flowchart	2
Pilot Failure Flowchart	3
Main Burner Not Lighting Flowchart	4
Main Burner Delayed Ignition Flowchart	5
Main Burner Low Flame Flowchart	6
Main Burner Failure Flowchart	7
Complete Unit Shutdown	8
Odour Flowchart	9

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Pilot Not Lighting Flowchart






Troubleshooting: Direct Vents Pilot Not Holding Flowchart




COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA






COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA








Troubleshooting: Direct VentsMain Burner Delayed Ignition Flowchart



COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Troubleshooting: Direct Vents Main Burner Low Flame Flowchart




COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA






PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA





COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA








PART 2: TROUBLESHOOTING: NATURAL VENTS

Pilot Not Lighting Flowchart	10
Pilot Not Holding Flowchart	11
Pilot Failure Flowchart	12
Main Burner Not Lighting Flowchart	13
Main Burner Delayed Ignition Flowchart	14
Main Burner Low Flame Flowchart	15
Main Burner Failure Flowchart	16
Complete Unit Shutdown	17
Odour Flowchart.	18


COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Pilot Not Lighting Flowchart








COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Pilot Failure Flowchart



COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Troubleshooting: Natural Vents Main Burner Not Lighting Flowchart



COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Troubleshooting: Natural VentsMain Burner Delayed Ignition Flowchart

Main Barrier Belayed 1911	101011	. To World C	
Has the pilot flame position and size been examined?	NO	Check to make sure the pilot is large enough and in the proper position, to reach the ignition ports. (See	
KES KES		"Adjustments: Pilot Flame")	
Has the inline gas pressure been tested?	NO	Check to ensure the proper supply pressures are available for ignition.	
YES	,	(See "Testing: Pressures")	
Has the main burner & orifice been examined to see if it is the right size?	NO	Check the size of the orifice to ensure it meets manufacturers	
YES	,	specification.	
Has the main burner and orifice been checked for blockages?	NO	Check to make sure nothing is blocking the flow of gas through the	
KES		burner and orifice, contributing to the delay. Clean as necessary.	
Has the venturi (air shutter) been checked & adjusted?	NO	Check the venturi setting and adjust as necessary to improve the ignition	
	,	time. (See "Adjusting: Venturi")	
Has the positioning of the logs been checked?	NO	Out of place logs can alter the flow	
, KES	ν .	of air within the combustion chamber, causing an erratic pilot.	
Have the charcoal / glowing embers (where applicable) been checked?	NO	Check to make sure no ember	
]/	material is clogging the ports, and contributing to the delay.	

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Troubleshooting: Natural Vents Main Burner Low Flame Flowchart



COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA





COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Troubleshooting: Natural Vents Complete Unit Shutdown

Is the burner flame going blue and see-through NO (See: "Pilot Failure" Flowchart) before extinguishing? YES

NO


Is the venting within the specifications of the installation manual and local code requirements?

Check the venting requirements and return to specification.

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Troubleshooting: Natural Vents Odour Flowchart






PART 3: TROUBLE SHOOTING: VENT FREE

Pilot Not Lighting Flowchart	. 19
Pilot Not Holding Flowchart	. 20
Pilot Failure Flowchart	
Main Burner Not Lighting Flowchart	. 22
Main Burner Delayed Ignition Flowchart	
Main Burner Low Flame Flowchart	. 24
Complete Unit Shutdown	. 25
Odour Flowchart	

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Pilot Not Lighting Flowchart






Pilot Not Holding Flowchart




COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA





COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA





COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Troubleshooting: Vent Free Main Burner Delayed Ignition Flowchart

Has the pilot flame position and size been examined? NO Check to make sure the enough and in the position and in the positio	
Has the main burner & orifice been checked for blockages? Has the main burner orifice been examined to see if it is the right size? Has the venturi (air shutter) been checked & adjusted? Has the burner been checked to ensure it is level? Has the positioning of the logs been checked? NO Out of place logs can of air within the charcoal/glowing embers (where applicable) been Check to make sur blocking the flow of burner and orifice, of the delay. Clean as the clean of the logs been checked? NO Check the venturi set as necessary to improfit time. (See "Adjustice") Examine and level NO Out of place logs can of air within the charcoal/glowing embers (where applicable) been Check to make sur checked to make sur or checked to make sur or checked to make sur checked to ma	proper position tion ports. (See
Has the main burner orifice been examined to see if it is the right size? Has the venturi (air shutter) been checked & adjusted? Has the burner been checked to ensure it is level? Has the positioning of the logs been checked? NO Check the venturi set as necessary to improtime. (See "Adjustive.") Examine and level NO Out of place logs can of air within the chamber, causing an of air within the chamber, causing an other chamber.	lable for ignition
Has the venturi (air shutter) been checked & adjusted? Has the burner been checked to ensure it is level? Has the positioning of the logs been checked? NO Check the size of trensure it meets may specificate. NO Check the venturi set as necessary to improve time. (See "Adjustication of the logs been checked? NO Examine and level Out of place logs can of air within the chamber, causing and the chamber, causing and the chamber, causing and the chamber of the logs been checked? Have the charcoal/glowing embers (where applicable) been NO Check to make sure	of gas through the, contributing to
Has the burner been checked to ensure it is level? Has the positioning of the logs been checked? NO Out of place logs can of air within the chamber, causing an of air within the chamber, causing an of air within the chamber.	manufacturers
Has the positioning of the logs been checked? NO Out of place logs can of air within the chamber, causing an chamber, causing an chamber.	prove the ignition
of air within the chamber, causing and the chamber, causing and the chamber chamber is the chamber in the chamb	el as necessary.
	e combustion
checked? INO check to make sufficient is clogging contributing to	ng the ports, and

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Troubleshooting: Vent Free Main Burner Low Flame Flowchart



COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Complete Unit Shutdown Flowchart

Is the burner flame going ghostly and blue before extinguishing? YES NO Are the electrical Clean, tighten, or replace as connections Does the unit have a catalytic necessary. (thermopile, switch, door? remote, thermostat), clean/secure/unbroken? YES Ensure that the air NO Test the operator coil to ensure it is Has the intakes for the within specification. (See "Testing: operator coil catalytic door are Function - Operator Coil") been checked not plugged or for resistance? covered. YES Does the main Does the main burner flame shrink NO burner flame shortly after activation? remain a consistent size YES when activated? YES Check to make sure the pressure is not dropping off on activation. (See "Testing: Pressures") Have the combustion and ventilation air provision guidelines been Increase available room air or NO checked to see if relocate as necessary to meet the room is of requirements sufficient volume to sustain the unit?

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA





COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




PART 4: TROUBLESHOOTING: OTHER ISSUUES

Carboning Flowchart	27
Oil-Canning Flowchart	
Blower Flowchart	
Remote Control Guide	

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Troubleshooting: Other Issues



COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Troubleshooting: Other Issues




COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Troubleshooting: Other Issues

Blower Flowchart





Troubleshooting: Other Issues Remote Control Guide

Code Switch Setting:

- Set the code switch on the transmitter (hand-held) before the batteries are installed. The remote transmitter reads and remembers the code switch setting right after the batteries are installed.
- Place the receiver in the "remote" position.
- The remote receiver will remember the code switch setting in it's internal memory and will not lose the code switch setting even during a power outage or battery change.
- After the batteries are installed, the LCD (display screen) on the transmitter will blink. Pressing any button
 during when the screen is blinking will activate the code and transmit it to the receiver.
- Pressing any button during when the screen is blinking will activate the code and transmit it to the receiver. You should be five feet away from the unit when doing this.
- When the receiver learns the code transmitted by the hand-held, it will produce a single beep noise. If the
 receiver is installed inside a fireplace, the beep may be very faint.
- Repeat the previous steps, if you did not receive a beep from the receiver.

Installing Multiple Remote Controls:

- If more than one remote control is expected to operate within a 50 foot range, a different coding is required for proper operation. Radio frequency signals will travel through floors and walls in all directions.
- Follow the code switch setting procedure for the first unit being programmed, and verify that it's working properly
- Turn the first unit being installed to the off position, when you go to install and program the second unit. (Remembering to turn back to the "remote" position after setup of the other units are complete.)
- Change the transmitter code switch to a different combination for each unit installed.
- Move twenty feet away from all operating remote controls and follow the code switch setting procedure.
- Verify the correct operation of each remote.

Display Screen of the Transmitter is blank:

- Make sure fresh alkaline batteries are installed into the transmitter.
- Check that the batteries are properly installed into the battery compartment and the polarity is correct.
- After taking out the batteries from the transmitter, wait for at least 1 minute before replacing with fresh batteries.

Transmitter Cannot Switch off the Fireplace:

- Make sure the batteries at the transmitter are not empty. The low battery indicator will turn on automatically when the battery level is low. Change batteries if necessary.
- Check the temperature at the receiver. Make sure the temperature at the receiver is below 140F (when the fireplace is turned on).
- Reduce the distance between the transmitter and receiver if necessary.

Receiver Can Not Turn on the Fireplace:

- Make sure fresh alkaline batteries are installed into the receiver. (DC receiver only)
- Make sure the output cables are securely connected to the receiver, the gas valve and the millivolt generator.
- For DC receiver, switch the receiver to "on". For AC receiver, press the on/off button on the receiver. Use a multimeter to measure the resistance between the output cables. The multimeter should read zero, or very low resistance.

Receiver Turns off Automatically After Some Time:

- The receiver will turn itself off automatically if the temperature rises above 150F.
- Check the temperature at the receiver. Make sure the temperature is below 140F (when the fireplace is turned on).
- · Relocate receiver as necessary.

Receiver Turns on Unexpectedly:

- Check to ensure that the transmitter is off.
- Change code switch setting on the transmitter. (Nearby radio transmissions may interfere with proper operation).
- Place receiver slide switch in the off position when not in use. (On DC battery operated receiver only).

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



PART 5: TESTING & ADJUSTMENTS

Testing: Pressures	31
Testing: Gasket	32
Testing: Switches - Spill Switch	
Testing: Switches - T. stat/Toggle	
Testing: Millivolts - Thermocouple - Robertshaw Valve	33
Testing: Millivolts - Thermocouple - SIT 820 Nova Valve	34
Testing: Millivolts - Thermopile	35
Testing: Function - Magnet Coil - Robertshaw Valve	36
Testing: Function - Operator Coil - Robertshaw Valve	37
Testing: Function - Magnet Coil - SIT 820 Nova Valve	38
Testing: Function-Operator Coil-SIT 820 Nova Valve	39
Testing: Pilot Flame	40
Adjustments: Pilot Flame	41
Adjustments: Spill Switch - Robertshaw Valve	42
Adjustmetns: Spill Switch - SIT 820 Nova Valve	43
Adjustments: Venturi/Air Shutter	///

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Testing: Pressures

NATURAL GAS PROPANE

SUPPLY 7" 11"
WATER COLUMN WATER COLUMN

MANIFOLD 3.5" 10"
WATER COLUMN WATER COLUMN


To test inlet / outlet pressure by turning screw counter-clockwise 2 or 3 turns and then place gauge tubing over inlet / outlet hose fitting.


Test inlet pressure with the main burner on to determine if gas flow is sufficient.











After taking pressure readings, be sure to turn screws clockwise firmly to reseal. **DO NOT OVER TORQUE!** Use an appropriate screwdriver with .150" x .030" blade.

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Testing: Gasket

- 1. Take a 1" x 6" piece of paper, and place it in between the main body of the fireplace, and the door. Close the door and fasten it as per the method specified in the manual. Attempt to pull the paper out from between the door and body of the fireplace. If the paper will not be removed without tearing, the gasket is sealing well. If the paper pulls out easily, examine the door, gasket, and door latch assembly for any potential issues. Perform this test in varying positions around the doorframe.
- 2. Examine the opening of the firebox. Around its perimeter, you should see a distinct colour difference made by the pressure of the gasket around the opening. The colour difference should not penetrate past the perimeter of the gasket.

Testing & Adjustments

Testing: Switches - Spill Switch

Disconnect all wires. Set a digital multimeter to the Ohms setting (for measuring resistance). Touch the black lead of the multimeter to one of the spade connectors of the spill-switch, and the red lead to the other connector. The reading should be less than 1 Ohm, or 'Open Circuit'. If the reading is 1 Ohm or higher, replace the switch. If no multimeter is available, please refer to "Adjustments: Spill Switch - Robertshaw / SIT"

Testing & Adjustments

Testing: Switches - T.Stat/Toggle

When encountering difficulty with a switch, in order to isolate whether it is the switch itself, or the wiring to the switch, you must perform the following test.


Ensure the wire leads from the switch are connected to terminals 1+3 (top and bottom) of the valve. Disconnect the wire-leads from the switch itself and connect them to each other. Turn the gas valve to the 'on' position. If the burner activates, this proves the wiring is not the issue



<u>Testing & Adjustments</u>
Testing: Millivolts - Thermocouple

OPEN CIRCUIT = 20 - 30 mVCLOSED CIRCUIT = 10 - 15 mv






COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



<u>Testing & Adjustments</u>
Testing: Millivolts - Thermocouple

OPEN CIRCUIT = 20 - 30 mVCLOSED CIRCUIT = 10 - 15 mv





COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




<u>Testing & Adjustments</u> Testing: Millivolts - Thermopile

OPEN CIRCUIT TEST

- 1. Disconnect leads from terminals 1 & 2.
- 2. Set meter to millivolts.
- 3. Connect meter leads to thermopile leads.
- 4. Reading should be 500mv.

CLOSED CIRCUIT TEST

- 1. Connect leads from meter to terminals 1 & 2.
- 2. Set meter to millivolts.
- 3. Turn main burner on.
- 4. Reading should be a minimum of 150mv.



COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



<u>Testing & Adjustments</u>
Testing: Function - Magnet Coil - Robert Shaw Valve





VALVE CHECK

(Function of Millivolt Magnet Coil)

- 1. Remove all wires (with the exception of the magnet coil wire) from the valve operating head. (It may be necessary to remove spill switch wires from the wire connecting the wire coil to the operator terminal on some models)
- 2. Use an ohmmeter or multimeter set on OHMS setting.
- 3. Place black or ground lead from the meter to TP on the valve.
- 4. Place the red lead from the meter to TP/TH on the valve.








NOTE: Assure that the magnetic coil wire is re-attached to terminal 1 prior to testing.

Operating Head:



COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



<u>Testing & Adjustments</u>
Testing: Function - Operator Coil - Robert Shaw Valve





VALVE CHECK

(Function of Millivolt Magnet Coil)

- 1. Remove all wires from the valve operating head.
- 2. Use an ohmmeter or multimeter set on OHMS setting.
- 3. Place black or ground lead from the meter to TP on the valve.
- 4. Place the red lead from the meter to TP/TH on the valve.


Reading should be between 1.5 and 1.7 Ohms.





NOTE: Assure that the magnetic coil wire is re-attached to terminal 1 prior to testing.

Operating Head:



COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Testing: Function - Magnet Coil - SIT 820 Nova Valve



Since the resistance of the magnet coil is too low to be read by most meters (0.015 milliohms), a "hold-in" test is more practical. Connect one millivolt meter lead to the thermocouple capillary tube. The other lead should be connected to the solder button on the bottom of the valve. Light the pilot and hold in the on/pilot/off knob until your multimeter registers the proper amount of millivolts to keep the pilot burning (6 millivolts for regular product, 4.2 millivolts for vent-free product).

At this point, the knob is released and the pilot should continue to burn. If it does not continue to burn, the valve fails the test and should be replaced.






<u>Testing & Adjustments</u>
Testing: Function - Operator Coil - SIT 820 Nova Valve



- 1. Remove all wires from the valve operating head.
- 2. Use an ohmmeter or multimeter set on OHMS setting.
- 3. Place black or ground lead from the meter to TP on the valve.
- 4. Place the red lead from the meter to the TH on the valve.

Reading should be 2.25 Ohms.




COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Testing & Adjustments Testing: Pilot Flame

CORRECT FLAME




NOISY, LIFTING, BLOWING FLAME



CHECK FOR:

- · High gas pressure
- · Wrong orifice


LAZY YELLOW FLAME



CHECK FOR:

- Clogged primary air opening
- · Clogged orifice


WAVING BLUE FLAME



CHECK FOR:

• Drafts at pilot location


HARD, SHARP FLAME



CHECK FOR:

- · High gas pressure
- · Orifice too small

SMALL BLUE FLAME



CHECK FOR:


- · Wrong orifice
- · Low gas pressure
- · Clogged pilot tube
- Pilot tube gas leak

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Testing & Adjustments Adjustments: Pilot Flame





- 1. Remove the protective cap screw.
- 2. Turn the pilot adjustment screw:
 - a) Clockwise to reduce the pilot flame.
 - b) Counter clockwise to increase the pilot flame.





- 1. Turn the pilot adjustment screw:
 - a) Clockwise to reduce the pilot flame.
 - b) Counter clockwise to increase the pilot flame.

COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Adjustments: Spill Switch


Wall switch or thermostat




When troubleshooting natural draft appliances which make use of a spill switch, it is sometimes necessary to bypass it in order to test its function and that of the other ignition components.

It is illegal to keep the spill switch bypassed. The spill switch is a safety feature of the fireplace which is required for proper operation.

The following two diagrams illustrate how to bypass the spill switch on a commonly used Robertshaw system.



Switch Disconnected



COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



Adjustments: Spill Switch

Wall switch or thermostat




Switches Connected

When troubleshooting natural draft appliances which make use of a spill switch and vent safety switch, it is sometimes necessary to bypass them it in order to test their function and that of the other ignition components.


It is illegal to keep these switches bypassed. These switches are a safety feature of the fireplace which are required for proper operation.

The following two diagrams illustrate how to bypass the spill switch and vent safety switch on a commonly used SIT system.

Note: When B venting a stove use the high limit spill switch included in the GS-150KT. An addional connection to a terminal block must be made before connecting to the valve. Please review the respective installation manual of the stove for more information.



Switches Disconnected



ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA




Testing & Adjustments Adjustments: Venturi/Air Shutter

Adjustment may be required depending on fuel type, vent configuration and altitude.

Closing the air shutter will cause a more yellow flame, that can lead to carboning. Opening air shutter will cause a more blue flame, but can cause the flame to lift from the burner ports.

The flame may not appear yellow immediately; allow 15-30 minutes for the final flame colour to be established.

Loosen securing screw and rotate venturi (indicated) to open/close as desired.



COPYRIGHT 2005 WOLF STEEL LTD.
ALL RIGHTS RESERVED, NO PART OF THIS BOOK MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS - GRAPHIC, ELECTRONIC OR MECHANICAL WITHOUT THE PRIOR WRITTEN
PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



	Award Winning Products
	NOTES
_	

PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA



	Award Winning Products
	NOTES
_	

PERMISSION FROM WOLF STEEL LTD., BARRIE, ONTARIO, CANADA