


Q7751A Router

EXCEL5000 OPEN™
S Y S T E M

SPECIFICATION DATA



FEATURES

- Physical isolation between two channels.
- Supports installation of larger networks.
- Uses LONWORKS network protocol.
- Two-piece design allows pre-wiring and cable testing prior to installation.
- Color-coded screw terminals and polarity-insensitive power and network connections minimize chance of incorrect wiring.
- Operates from 16-30 Vac or Vdc, allowing router to be powered from same source as sensors and actuators.
- Power and network wiring are looped through each base plate, providing uninterrupted network continuity if replacing router.
- Two front panel jacks that access the twisted pair network without requiring disassembly.
- Front panel bar code including model, revision, and two removable Echelon® Neuron® chip ID stickers.

DESCRIPTION

The Q7751A Router doubles the bus length and the number of usable nodes on a LONWORKS® (previously called E-Bus) network. The Q7751A2010 has an FTT-10 transceiver. It is used on LONWORKS networks with the Excel 10 Series 2000 family of controllers. The Q7751A1012 has a TP-78 transceiver. It is used on LonWorks networks with the Excel 10 VAV1 Series 1000 controller.

SPECIFICATIONS

The Q7751A Router is a two-piece design allowing prewiring and cable testing prior to installing the electronic component. The front panel includes a printed circuit board (PCB) with active electronics. The front panel also has a service switch, a power/wink LED, an activity LED, and two network connectors. Network and power are connected to screw terminals located on a type 2 base plate where the router is plugged. Wiring is never directly connected to a router.

Power Supply

The Q7751A Router requires 2 VA at an operating voltage of 16 to 30 Vdc or Vac. There is a power ON LED located on the front panel.

Status Information

Two service LEDs (channel 1 and channel 2) light to provide service request information for each segment.

The Router Activity LED lights when transferring from one channel to another.

Front panel has the Service Request button for broadcasting the Neuron ID on the network.

Mounting Options

The type 2 base plate mounts to either a U.S. 4 in. square, 2 in. deep (10.16 cm x 5.08 cm) electrical box, U.S. double gang electrical box or an IP-65 (NEMA 4) enclosure.

Dimensions (HxWxD)

3-15/16 x 3-15/16 x 1-3/4 in. (100.0 x 100.0 x 44.5 mm).

Environmental Ratings:

Operating and shipping temperature

-40 to +185°F (-40 to +85°C).

Relative Humidity

-10 to 95% at 122°F (50°C).

Approval Bodies

U.L. LP Router 146747, Volume 2, Section 1.

LONWORKS® and Neuron® are registered trademarks of Echelon® Corporation.

Home and Building Control

Honeywell Inc.
Honeywell Plaza
P.O. Box 524
Minneapolis, MN 55408-0524

Home and Building Control

Honeywell Limited-Honeywell Limitee
155 Gordon Baker Road
North York, Ontario
M2H 3N7

Honeywell Asia Pacific Inc.

Room 3213-3225
Sun Hung Kai Centre
No. 30 Harbour Road
Wanchai
Hong Kong

Honeywell Latin American Region

480 Sawgrass Corporate Parkway
Suite 200
Sunrise, FL 33325

Honeywell Europe S.A.

3 Avenue du Bourget
1140 Brussels
Belgium

Honeywell

