



# 4532N Flat Top

Front-Breathing Flat Top Freezer Base

Project \_\_\_\_\_

Item \_\_\_\_\_

Quantity \_\_\_\_\_

CSI Section 11400

Approved \_\_\_\_\_

Date \_\_\_\_\_

4532N Flat Top  
Front-Breathing Flat Top Freezer Base

## Models

- 4532N Single section freezer with doors
- D4532N Single section freezer with drawers



4532N

## Standard Features

- 100% front breathing, which allows the unit to be pushed against a wall or built into a cabinet or an existing line up
- Durable, rugged stainless steel sides, top and front
- Features Delfield's exclusive ABS interior (on sides). ABS is extremely durable - it won't dent, chip or corrode and is backed by a limited lifetime warranty
- Heavy duty self-closing hinges
- "D" prefix models feature Delfield's exclusive new drawer system. Drawers are backed by a 10-year warranty on the track assembly
- Environmentally friendly R404A refrigerant
- High density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane keeps energy costs low
- Black recessed quick grip handle
- Standard on 2" casters for easy cleaning and installation
- 60-cycle single phase electrical system
- 7' cord and plug supplied
- Cord spring relief - prevents cord rollover
- One epoxy coated wire shelf standard, installed per door section
- ACT solid state electronic control
- One year parts and 90 day labor standard warranty.

## Options & Accessories

- Flat lift off cover
  - 18" wide single tier overshef
  - Stainless steel finish on back
  - Plastic laminate on front
  - Additional wire shelves
  - Door lock
  - Exterior thermometer
  - Interior lights
  - Glass door(s)
  - \*220V/50Hertz electrical system
- \*Inclusion of this option will alter electrical specifications of the unit.

## Specifications

**Exterior top** is one-piece, 22-gauge stainless steel with integral square nosing on the front.

**Exterior back and bottom** are two-piece 24-gauge galvanized steel.

**Exterior ends** are stainless steel.

**Interior sides** are thermoformed ABS plastic with shelves supported on plugs. Interior back is one-piece 22-gauge stainless steel. Interior bottoms are thermofoamed ABS plastic. Base is fully insulated with high-density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane.

**Refrigeration** system uses HFC-404A refrigerant. Compressor is 1/5 H.P., with condenser coil and hot gas condensate evaporator mounted on rear of the cabinet. Evaporator coils are located on the interior rear wall of the cabinet. Refrigerant

flow is controlled by a capillary tube. Cabinet maintains an interior cabinet temperature of 0°F to 10°F (-18°C to -12°C).

**Electrical** connection is 115 volt, 60 Hertz, single phase. Unit has a 7' (2.1m) long electrical cord and NEMA 5-15P plug.

**Casters** Equipment is mounted on 2" (5.08cm) (2.5" ride height), diameter plate casters with front two locking.

**Door** has a 24-gauge stainless steel exterior, with thermoformed ABS plastic interior liner.

**Drawers** have 24-gauge stainless steel exterior with thermoformed ABS plastic interior liner. Drawer frames are 12-gauge stainless steel. Drawer slides are 11-gauge stainless steel with Delrin bearings. Top drawer holds two full size 12" x 20", 4"-6" (30.5cm x 50.8cm x 10.2cm) deep pans. Bottom drawer holds one full size 12 x 20" and three 1/6 size 4" deep pans. Pans are supplied by others.





# 4532N Flat Top

Front-Breathing Flat Top Freezer Base

**4532N Elevation View**  
 32.13" (81.61)  
 36.00" (91.40)  
 33.59" (85.31)

**4532N Right Side View**  
 31.50" (80.00)  
 23.79" (60.43)  
 12.98" (33.00)  
 17.35" (44.08)  
 7.53" (19.10)  
 6.11" (15.52)  
 26.86" (68.22)  
 20.75" (52.70)  
 21.94" (55.73)  
 2.50" (6.30)  
 ALT SHELF  
 SHELF

**4532N ISO VIEW**  
 30.67" (77.90) NOSE OF UNIT TO EDGE OF DOOR  
 28.75" (73.03) INTERIOR DIMENSION

**4532N & D4532N ISO View**  
 1.95" (4.96)  
 1.21" (3.08) CORD DIMENSIONS

**D4532N ISO View**  
 19.69" (49.77) NOSE OF UNIT TO EDGE OF DRAWER

**D4532N Elevation View**  
 32.13" (81.61)  
 36.00" (91.40)  
 33.59" (85.31)

**D4532N Right Side View**  
 31.50" (80.01)  
 4.00" OR 6.80" DEEP PANS ON TOP  
 4.00" DEEP PANS ONLY ON BOTTOM  
 2.50" (6.30)

**INSTALLATION NOTE:**  
 Refrigeration system is designed so that air will flow under the unit, through the compressor area and out the front of the unit. Any restriction to this air flow path will void the warranties.

**PLEASE NOTE:**  
 Air flow through the louver on the back of the unit is not necessary for operation, however, any air which passes through the louver is beneficial.

**Specifications**

Model	Number of Shelves	Shelf Area	Storage Capacity	H.P.	V/Hz/Ph	Amps	NEMA Plug	Ship Weight
4532N	1	3.97ft <sup>2</sup>	6.9ft <sup>3</sup>	1/3	115/60/1	9.50	5-15P	280lbs/127kg
D4532N	NA	NA	2.7ft <sup>3</sup>	1/3+	115/60/1	12.00	5-15P	315lbs/143kg

Delfield reserves the right to make changes to the design or specifications without prior notice.

980 S. Isabella Rd.  
 Mt. Pleasant, Michigan 48858

Phone: 800-733-8948 or 989-773-7981  
 Fax: 800-669-0619  
 www.delfield.com

Printed in the U.S.A.  
 DS4532N  
 01/08

Enodis®