


CHANNEL VISION
Limited Warranty

Channel Vision Technology will repair or replace any defect in material or workmanship which occurs during normal use of this product with new or rebuilt parts, free of charge in the USA, for two years from the date of original purchase. This is a no hassle warranty with no mail in warranty card needed. This warranty does not cover damages in shipment, failures caused by other products not supplied by Channel Vision Technology, or failures due to accident, misuse, abuse, or alteration of the equipment. This warranty is extended only to the original purchaser, and a purchase receipt, invoice, or other proof of original purchase date will be required before warranty repairs are provided.

Mail in service can be obtained during the warranty period by calling (800) 840-0288 toll free. A Return Authorization number must be obtained in advance and can be marked on the outside of the shipping carton.

This warranty gives you specific legal rights and you may have other rights (which vary from state to state). If a problem with this product develops during or after the warranty period, please contact Channel Vision Technology, your dealer or any factory-authorized service center.



CHANNEL VISION™

VDA-12

Audio/Video Distribution Amplifier

CHANNEL VISION™

234 Fischer Avenue · Costa Mesa, CA 92626
(714) 424-6500 · (800) 840-0288 · (714) 424-6510 fax
www.channelvision.com · email: sales @ channelvision.com

© 2004, Channel Vision™

Description:

Channel Vision's VDA-12 is an audio and base-band video distribution amplifier. It can expand the RCA output socket of your AV equipment by incorporating an audio input and a video input, which are distributed to twelve audio/video outputs. A built-in clamp circuit was designed to eliminate up & down roll pictures. The VDA-12 offers optimal picture quality with the audio/video cascade outputs that feature automatic video impedance. Overall, the VDA-12 is especially useful for connecting audio/video components to RF modulators or multiple zones.

Specifications:

| | <u>Audio:</u> | <u>Video:</u> |
|--------------------|------------------------------|----------------------|
| Input Impedance | 20K ohm | 1K ohms |
| Output Impedance | 600ohms | 75 ohms |
| Gain | 11dB | 6dB |
| Clamp Capability | | 60dB |
| Frequency Response | 20Hz to 20XHz | 20Hz to 8MHz |
| Max. Input | 5Vp-p | 4Vp-p |
| Max. Output | 4.5Vp-p(4/7x Load) | 1.8Vp-p(75ohms load) |
| Power Requirement | AC 110V/60Hz or AC 220V/50Hz | |
| Power Consumption | 5W (Max.) | |

Features:

- ◆ Gold plated RCA connectors
- ◆ 17" component, space saving – inline power adapter
- ◆ Black brushed aluminum
- ◆ Low distortion
- ◆ 1 – Set AV input, 12 – Set AV output
- ◆ Dimensions: 3-1/8" x 17-1/8" x 9-1/2" (H) x (W) x (D)

