

Electrolux

Refrigeration SMART 1 Door Freezer (23 FT³)

ITEM # _____

MODEL # _____

PROJECT NAME # _____

SIS # _____

AIA # _____



Smart 1 Door Freezer (23 FT³)

726597 (RH06FE1FEU)	23 ft ³ Full Size Freezer 1 door 115 V/1p/60Hz
727012 (RH06FE1FEU)	23 ft ³ Full Size Freezer 1 door 115 V/1p/60Hz remote version

Short Form Specification

Item No. _____

The Electrolux range of refrigerated cabinets are built with external and internal AISI 304 stainless steel. High-density expanded polyurethane insulating foam, 3" (75 mm) in thickness. Full door with lock and microswitch to switch off the fan when the door is opened. Built-in refrigeration unit; ventilated operating mode; SMART Electronic Control equipped with: history (HACCP) for critical high temperature, alarm service, full diagnostic, remote control via modem; electronic defrost only when required; defrost outlet pipe; external digital temperature display. Humidity level adjustment. Internal lighting. Cavity drain. For ambient temperatures up to 110 °F (43 °C). CFC and HCFC free. R134a gas in refrigeration circuit. Gas in foam: cyclopentane. Energy Star certification for energy savings. Supplied with n. 4 x 2/1GN Rilsan coated grids and n. 4 sets of 2 Stainless steel grid runners.

Covered by Electrolux Platinum Star[®] Service Program two-year parts and one-year labor warranty, installation start-up and performance check-up after one year from installation.



5-15P

Approval: _____

Main features

EASY TO INSTALL

- Mounted on adjustable stainless steel feet, with castors as an option.
- Choice of doors to suit varying kitchen requirements.
- Freezer models have operating temperatures that can be adjusted from 5 °F to -11 °F (-15 to -24 °C) to suit both meat and dairy storage requirements.
- Performance guaranteed at ambient temperatures of 110 °F (43 °C).

EASY TO CLEAN

- Forced air circulation for rapid cool down and even temperature uniformity.
- Constructed from the highest quality AISI 304 stainless steel.
- Interior base with corners, pressed from a single sheet.
- Sides and back of the 1-door models are formed from a single sheet of Stainless steel to avoid dirt traps.
- Evaporator unit is placed outside the cell to provide the maximum storage capacity.
- Refrigerators are fitted with outlet pipe.

EASY TO USE

- Accommodates GN 2/1 containers or shelves on anti-tilt runners.
- External digital temperature display.
- Interior light and lockable door.
- SMART electronic control gives the following benefits:
 - HACCP: when temperature exceeds critical limits, an acoustic and visual alarm are activated. All events are recorded displaying date and time of all events.
 - SMART defrost: the defrost cycle is activated only when necessary thanks to the four-probe control and a patented algorithm for ice detection.
 - Intelligence when failure: when a probe breaks it remembers its performance of last 24 hours and continue to work. In this way food is safe and service can be called.
 - Diagnostic: four probes constantly control working condition of the appliances.
 - Food categories: depending by food stored it can be selected appropriate temperature and humidity just pushing a button.

EASY TO MAINTAIN

- Heavy-duty construction that avoids use of any plastic parts.
- The cooling unit (compressor, condenser and evaporator) can be removed with a single operation from either the top or back.
- Evaporator cover is easily removable for service.
- Fault indication from the smart control.

EASY ON THE ENVIRONMENT

- SMART electronics defrost only when required to save energy.
- Cabinet fitted with up to 3" (75 mm) thickness of cyclopentane insulation for best insulating performance. CFC and HCFC-free insulation.
- Refrigerant type: R134a or R404a.

Accessories

- Pair of stainless steel runners for 23 and 50 ft³ SMART refrigerators 4
- Rilsan[®] coated full-size sheet grid 4

Optional Accessories

- Basic HACCP Printer (PNC 880048)
- 4 wheels (2 with brake) (PNC 880121)
- Pair of stainless steel runners for 23 and 50 ft³ SMART refrigerators (PNC 880175)
- Rilsan[®] coated full-size sheet grid (PNC 880176)
- Pedal opening for 23 ft³ SMART refrigerators (PNC 881458)



Electrolux

SMART 1 Door Freezer (23 FT³) Refrigeration

Electrolux Professional, Inc.

www.electroluxusa.com/professional

3225 SW 42nd Street, Fort Lauderdale, Florida, 33312 • Telephone Number: 866-449-4200 • Fax Number: 954-327-6789

