Manual de instalação do ProJuris 5 - Estação

1. Instale o Projuris na estação.

Importante: as configurações de compartilhamento no servidor devem já estar prontas e configuradas corretamente para que todos os usuários possam alterar/modificar os arquivos.

- 2. Abra o Painel de Controle em: Iniciar -> Configurações -> Painel de controle.
- 3. Abra o programa BDE Administrador



4. Selecione PROJRUIS5. No lado direito na opção <u>PATH</u> deve-se colocar o caminho do banco de dados no servidor. Em nosso exemplo, a máquina servidora nomeia-se SRV01, e o compartilhamento criado nomeia-se DADOS

🕰 BDE Administrator e:\Arquivos de Programas\Borland\Common Files\BDE\IDAPI32.CFG				
Object Edit View Options Help	/			
β X κγ α				
All Database Aliases	Definition of Projuris5			
Databases Configuration	Definition			
□ Image: Constraint of the sector of th	Type DEFAULT DRIVER ENABLE CD PATH	STANDARD PARADOX FALSE \\SRV01\Dados		
Driver tried first.	,			

5. Na aba CONFIGURATION: vá em DRIVER -> NATIVE -> e escolha <u>PARADOX</u>.

Verifique no contexto à direita a primeira linha chamada NET DIR. Coloque aqui o caminho compartilhado no servidor. Novamente, nosso exemplo usar o servidor SRV01 e o compartilhamento NETDIR.

🚨 BDE Administrator e:\Arquivos de Programas\Borland\Common Files\BDE\.coAPI32.CFG				
Object Edit View Options Help				
$\mathfrak{B} \times \mathfrak{O} \mathfrak{O}$				
Drivers and System	Definition of PARADOX			
Databases Configuration	Definition			
Configuration	NET DIR VERSION TYPE LANGDRIVER BLOCK SIZE FILL FACTOR LEVEL STRICTINTEGRTY	\\SRV01\Netdir 4.0 FILE Pdox ANSI Int/850 2048 95 4 TRUE		
Location of the application's network control file (PD	OXUSRS.NET).			

6. Clique agora no ícone azul APPLY para salvar.

🚨 BDE Administrator e:\Arquivos de Programas\Borland\Common Files\BDE\IDAPI32.CFG					
Object Edit View Options Help					
$e \times o \alpha$					
Drivers and System	Definition of INIT				
Databases Configuration	Definition				
🖃 🕨 🔁 Configuration	AUTO ODBC	FALSE			
📄 🕨 🏷 Drivers	DATA REPOSITORY				
🚍 – 🕨 😏 Native	DEFAULT DRIVER	PARADOX			
PARADOX	LANGDRIVER	Pdox ANSI Intl850			
🚽 💮 DBASE	LOCAL SHARE	TRUE	<u> </u>		
FOXPRO	LOW MEMORY USAGE LIMIT	32			
INTRBASE	MAXBUFSIZE	2048			
MSACCESS	MAXFILEHANDLES	48			
- 😚 MSSQL	MEMSIZE	16			
🚽 💮 ORACLE	MINBUFSIZE	128			
⊡ 🕀 🔁 ODBC	MTS POOLING	FALSE			
🖻 🕨 🖳 System	SHAREDMEMLOCATION				
	SHAREDMEMSIZE	2048			
🗄 🖳 Formats	SQLQRYMODE				
	SYSFLAGS	0			
	VERSION	4.0			
Specifies whether or not to lock files that may be shared with local non-BDE applications.					