

# Orion<sup>®</sup> StarMax 102mm EQ<sup>™</sup>

#9824 Equatorial Maksutov-Cassegrain Telescope



**ORION**  
**TELESCOPES & BINOCULARS**  
*Providing Exceptional Consumer Optical Products Since 1975*

Customer Support (800) 676-1343  
E-mail: [support@telescope.com](mailto:support@telescope.com)  
Corporate Offices (831) 763-7000  
P.O. Box 1815, Santa Cruz, CA 95061




Figure 1. StarMax 102mm EQ Parts Diagram

Welcome to a new world of adventure. Your new StarMax 102mm EQ is designed for high-resolution observing of astronomical objects, and can also be used for terrestrial exploration. With its precision optics and equatorial mount, you'll be able to locate and enjoy hundreds of fascinating celestial objects, including the planets, Moon, and a variety of deep-sky galaxies, nebulae, and star clusters.

If you have never owned a telescope before, we would like to welcome you to amateur astronomy. Take some time to familiarize yourself with the night sky. Learn to recognize the patterns of stars in the major constellations. With a little practice, a little patience, and a reasonably dark sky away from city lights, you'll find your telescope to be a never-ending source of wonder, exploration, and relaxation.

These instructions will help you set up, properly use and care for your telescope. Please read them over thoroughly before getting started.

## Table of Contents

1. Unpacking .....	3
2. Parts List.....	3
3. Assembly .....	4
4. Getting Started .....	5
5. Setting Up and Using the Equatorial Mount .....	7
6. Using Your Telescope—Astronomical Observing.....	10
7. Terrestrial Viewing.....	13
8. Photography.....	13
9. Care and Maintenance .....	13
10. Specifications.....	14

## 1. Unpacking

The entire telescope system will arrive in one box. Be careful unpacking the box. We recommend keeping the original shipping containers. In the event that the telescope needs to be shipped to another location, or returned to Orion for warranty repair, having the proper shipping containers will help ensure that your telescope will survive the journey intact.

Make sure all the parts in the Parts List are present. Be sure to check boxes carefully, as some parts are small. If anything appears to be missing or broken, immediately call Orion Customer Support (800)676-1343 or email support@telescope.com for assistance.

**WARNING: *Never look directly at the Sun through your telescope or its finder scope—even for an instant—without a professionally made solar filter that completely covers the front of the instrument, or permanent eye damage could result. Young children should use this telescope only with adult supervision.***

## 2. Parts List

Qty.	Description
1	Optical tube assembly
1	Optical tube dust cover
1	25mm (52x) Sirius Plössl eyepiece (1.25")
1	Mirror star diagonal
1	6x26 correct-image finder scope
1	Dovetail finder scope bracket with O-ring
1	Equatorial mount
3	Tripod legs
1	Counterweight shaft
1	Counterweight
1	Tripod accessory tray
1	Accessory tray bracket
2	Slow-motion control cables
1	1/4"-20 adapter
1	Soft carry case
3	Assembly tools (wrench, Phillips screwdriver, flathead screwdriver key)

### 3. Assembly

Assembling the telescope for the first time should take about 30 minutes. No tools are needed other than the ones provided. All bolts should be tightened securely to eliminate flexing and wobbling, but be careful not to over-tighten or the threads may strip. Refer to Figure 1 during the assembly process.

During assembly (and anytime, for that matter), DO NOT touch the surface of the telescope's meniscus lens or the lenses of the finder scopes or eyepieces with your fingers. The optical surfaces have delicate coatings on them that can easily be damaged if touched inappropriately. NEVER remove any lens assembly from its housing for any reason, or the product warranty and return policy will be voided.

1. Lay the equatorial mount on its side. Attach the tripod legs one at a time to the mount by sliding the bolts installed in the tops of the tripod legs into the slots at the base of the mount and tightening the wing nuts finger-tight. The accessory tray bracket attachment point on each leg should face inward.
2. Tighten the leg lock knobs on the bottom braces of the tripod legs. For now, keep the legs at their shortest (fully retracted) length; you can extend them to a more desirable length later, after the telescope is completely assembled.
3. With the tripod legs now attached to the equatorial mount, stand the tripod upright (be careful!) and spread the legs

wide enough to connect each end of the accessory tray bracket to the attachment point on each leg. Use the screw that comes installed in each attachment point to do this. First remove the screw using the supplied screwdriver, then line up one of the ends of the bracket with the attachment point and reinstall the screw. Make sure that the accessory tray bracket is oriented so that the ribs in its plastic molding face downward.

4. With the accessory tray bracket attached, spread the tripod legs apart as far as they will go, until the bracket is taut. Attach the accessory tray to the accessory tray bracket with the three wing screws already installed in the tray. Do this by pushing the wing screws up through the holes in the accessory tray bracket, and threading them into the holes in the accessory tray.
5. Tighten the bolts at the tops of the tripod legs, so the legs are securely fastened to the equatorial mount. Use the larger wrench and your fingers to do this.
6. Orient the equatorial mount as it appears in Figure 2, at a latitude of about 40°, so the pointer next to the latitude scale (located directly above the latitude lock t-bolt) is pointing to the mark at "40." To do this, loosen the latitude lock t-bolt, and turn the latitude adjustment t-bolt until the pointer and the "40" line up. Then retighten the latitude lock t-bolt. The declination (Dec.) and right ascension (R.A.) axes may need re-positioning (rotation) as well. Be

Figure 2a. **The equatorial mount.**  
("Front" view.)




Figure 2b. "Rear" view.

sure to loosen the R.A. and Dec. lock knobs before doing this. Retighten the R.A. and Dec. lock knobs once the equatorial mount is properly oriented.

7. Slide the counterweight onto the counterweight shaft. Make sure the counterweight lock knob is adequately loosened to allow the counterweight shaft to pass through the hole in the counterweight.
8. With the counterweight lock knob still loose, grip the counterweight with one hand and thread the shaft into the equatorial mount (at the base of the declination axis) with the other hand. When it is threaded as far in as it will go, position the counterweight about halfway up the shaft and tighten the counterweight lock knob. The retaining screw and washer on the bottom of the shaft prevent the counterweight from falling off (and onto your foot!) if the counterweight lock knob becomes loose.
9. Attach the 1/4"-20 adapter to the top of the equatorial mount using the bolts and washers that come with the adapter. Push the bolts, with washers attached, up through the holes in top of the mount and thread them into the bottom of the adapter. Tighten the bolts securely with the supplied wrench.
10. Connect the optical tube assembly to the 1/4"-20 adapter on the mount by threading the adapter's shaft into the hole in the optical tube's mounting block. Orient the optical tube so that is parallel to the length of the adapter, as it is in Figure 1. Tighten this connection firmly by rotating the knurled thumb wheel on the adapter counter-clockwise.
11. Attach the two slow-motion cables to the R.A. and Dec. worm gear shafts of the equatorial mount by positioning the thumb screw on the end of the cable over the indented slot on the worm gear shaft and then tightening the thumb screw. We recommend that the shorter cable be used on the R.A. worm gear shaft and the longer cable on the Dec. worm gear shaft. The Dec. worm gear shaft and cable should extend toward the rear of the optical tube, as is shown in Figure 1. If it does not, you will need to rotate the optical tube 180° on the 1/4"-20 adapter. Do this by first loosening the adapter's knurled thumb wheel.
12. To place the finder scope in the finder scope bracket, first unthread the two black nylon screws until the screw ends are flush with the inside diameter of the bracket. Place the O-ring that comes on the base of the bracket over the body of the finder scope until it seats into the groove on the middle of the finder scope. Slide the eyepiece end (narrow end) of the finder scope into the end of the bracket's cylinder that does not have the alignment screws while pulling the chrome, spring-loaded tensioner on the bracket with your fingers (see Figure 3). Push the finder scope through the bracket until the O-ring seats just inside the front opening of the bracket's cylinder. Now, release the tensioner and tighten the two black nylon screws a couple of turns each to secure the finder scope in place. The tips of the tensioner and nylon screws should seat into the wide groove on the rear of the finder scope's body.




Figure 3. **To install the finder scope in the finder scope bracket, pull the spring-loaded tensioner while inserting the eyepiece end of the finder scope into the bracket.**

13. Insert the base of the finder scope bracket into the dovetail holder on the optical tube. Lock the bracket into position by tightening the knurled thumb screw on the dovetail holder.
14. Remove the cap from the eyepiece adapter on the rear of the optical tube and insert the chrome barrel of the mirror star diagonal. Secure the diagonal with the thumb screws on the eyepiece adapter.
15. Insert the chrome barrel of the eyepiece into the star diagonal. Secure the eyepiece with the thumb screws on the star diagonal.

The telescope system is now fully assembled. Keep the dust cover over the front end of the telescope when it is not in use. It is also a good idea to cover the eyepiece; use the cover cap that came with it.

## 4. Getting Started

### Balancing the Telescope

To insure smooth movement of the telescope on both axes of motion (R.A. and Dec.) of the equatorial mount, it is imperative that the optical tube be properly balanced.

1. Keeping one hand on the telescope optical tube, loosen the R.A. lock knob. Make sure the Dec. lock knob is locked. The telescope should now be able to rotate freely about the R.A. axis. Rotate it until the counterweight shaft is parallel to the ground (i.e., horizontal).
2. Loosen the counterweight lock knob and slide the counterweight along the shaft until it exactly counterbalances the telescope (Figure 4a). That's the point at which the shaft remains horizontal even when you let go of the telescope with both hands (Figure 4b).
3. Retighten the counterweight lock knob.



The telescope is now balanced on the R.A. axis. It is not necessary to balance the telescope on the Dec. axis, since the optical tube's mounting block is positioned so that the telescope will automatically be balanced on that axis. Now when you loosen the lock knob on one or both axes of motion and manually point the telescope, it should move without resistance and should not drift from where you point it.



Figure 4a, b. **Proper operation of the equatorial mount requires balancing the telescope tube on the R.A. axis. (a) With the R.A. lock knob released, slide the counterweight along the counterweight shaft until it just counterbalances the tube. (b) When you let go with both hands, the tube should not drift up or down.**

### Focusing the Telescope

Point the telescope so the front end is aimed in the general direction of an object at least 1/4-mile away. Now, with your fingers, slowly rotate the focusing knob until the object comes into sharp focus. Go a little bit beyond sharp focus until the image starts to blur again, then reverse the rotation of the knob, just to make sure you've hit the exact focus point. You will have to readjust the focus when aiming at subjects of varying distance, or after changing eyepieces.

If you have trouble focusing, rotate the focus knob counter-clockwise as far as it will go. Now look through the eyepiece

while slowly rotating the focus knob clockwise. You should soon see the point at which focus is reached.

### Do You Wear Eyeglasses?

If you wear eyeglasses, you may be able to keep them on while you observe. In order to do this, your eyepiece must have enough "eye relief" to allow you to see the entire field of view with glasses on. You can try this by looking through the eyepiece first with your glasses on and then with them off, to see if the glasses restrict the view to only a portion of the full field. If the glasses do restrict the field of view, you may be able to observe with your glasses off by refocusing the telescope the needed amount.

If your eyes are astigmatic, images will probably appear best with glasses on. This is because a telescope's focuser can accommodate for nearsightedness or farsightedness, but not astigmatism. If you have to wear your glasses while observing and cannot see the entire field of view, you may want to purchase additional eyepieces that have longer eye relief.

### Aligning the Finder Scope

The finder scope must be aligned accurately with the telescope for proper use. To align it, aim the main telescope in the general direction of an object at least 1/4-mile away, such as the top of a telephone pole, a chimney, etc. Do this by first loosening the R.A. and Dec. lock knobs. Position the telescope so the object appears in the eyepiece's field of view and then retighten the R.A. and Dec. lock knobs. Use the slow-motion control cables to center the object in the eyepiece.

Now, look in the finder scope. Is the object visible? Ideally, it will be somewhere in the finder's field of view. If it is not, some coarse adjustments of the two black nylon finder scope alignment thumb screws will be needed to get the finder scope roughly parallel to the main tube.

**Note: The image in the telescope's eyepiece will appear inverted from left-to-right (mirror reversed), which is normal for telescopes that utilize a star diagonal. The image in the finder scope is oriented the same as the naked eye.**

By loosening or tightening the alignment thumb screws, you change the line of sight of the finder scope. Continue making adjustments to the alignment thumb screws until the image in both the finder scope and the telescope's eyepiece is exactly centered. Check the alignment by moving the telescope to another object and fixing the finder scope's crosshairs on the exact point you want to look at. Then look through the telescope's eyepiece to see if that point is centered in the field of view. If it is, the job is done. If not, make the necessary adjustments until the two images match up.

The finder scope alignment needs to be checked before every observing session. This can easily be done at night, before viewing through the telescope. Choose any bright star or planet, center the object in the telescope eyepiece, and then adjust the finder scope's alignment screws until the star or planet is also centered on the finder's crosshairs. The finder scope is an invaluable tool for locating objects in the night sky; its usage for this purpose will be discussed later, in detail.

## Focusing the Finder Scope

If, when looking through the finder scope, the images appear somewhat out of focus, you will need to refocus the finder scope for your eyes. Loosen the lock ring located behind the objective lens cell on the body of the finder scope (see Figure 5). Back the lock ring off by a few turns, for now. Refocus the finder scope on a distant object by threading the objective lens cell in or out on the finder scope body. Precise focusing will be achieved by focusing the finder scope on a bright star. Once the image appears sharp, retighten the lock ring behind the objective lens cell. The finder scope's focus should not need to be adjusted again.




Figure 5. The 6x26 correct-image finder scope and bracket.

## 5. Setting Up and Using the Equatorial Mount

When you look at the night sky, you no doubt have noticed that the stars appear to move slowly from east to west over time. That apparent motion is caused by the Earth's rotation (from west to east). An equatorial mount (Figure 2) is designed to compensate for that motion, allowing you to easily "track" the movement of astronomical objects, thereby keeping them from drifting out of the telescope's field of view while you're observing.

This is accomplished by slowly rotating the telescope on its right ascension (R.A.) axis, using only the R.A. slow-motion cable. But first the R.A. axis of the mount must be aligned with the Earth's rotational (polar) axis—a process called polar alignment.

### Polar Alignment

For Northern Hemisphere observers, approximate polar alignment is achieved by pointing the mount's R.A. axis at the North Star, or Polaris. It lies within  $1^\circ$  of the north celestial pole (NCP), which is an extension of the Earth's rotational axis out into space. Stars in the Northern Hemisphere appear to revolve around the NCP.


To find Polaris in the sky, look north and locate the pattern of the Big Dipper (Figure 6). The two stars at the end of the "bowl" of the Big Dipper point right to Polaris.

Observers in the Southern Hemisphere aren't so fortunate to have a bright star so near the south celestial pole (SCP). The star Sigma Octantis lies about  $1^\circ$  from the SCP, but it is barely visible with the naked eye (magnitude 5.5).

For general visual observation, an approximate polar alignment is sufficient.

1. Level the equatorial mount by adjusting the length of the three tripod legs.
2. Loosen the latitude lock t-bolt. Turn the latitude adjustment t-bolt and tilt the mount until the pointer on the latitude scale is set at the latitude of your observing site. If you don't know your latitude, consult a geographical atlas to find it. For example, if your latitude is  $35^\circ$  North, set the pointer to 35. Then retighten the latitude lock t-bolt. The latitude setting should not have to be adjusted again unless you move to a different viewing location some distance away.
3. Loosen the Dec. lock knob and rotate the telescope optical tube until it is parallel with the R.A. axis, as it is in Figure 1. The pointer on the Dec. setting circle should read  $90^\circ$ . Retighten the Dec. lock lever.
4. Loosen the azimuth lock knob at the base of the equatorial mount and rotate the mount so the telescope tube (and R.A. axis) points roughly at Polaris. If you cannot see Polaris directly from your observing site, consult a compass and rotate the mount so the telescope points North. Retighten the azimuth lock knob.

Figure 6. To find Polaris in the night sky, look north and find the Big Dipper. Extend an imaginary line from the two "Pointer Stars" in the bowl of the Big Dipper. Go about five times the distance between those stars and you'll reach Polaris, which lies within  $1^\circ$  of the north celestial pole (NCP).



---

The equatorial mount is now polar aligned for casual observing. More precise polar alignment is recommended for astrophotography.

From this point on in your observing session, you should not make any further adjustments in the azimuth or the latitude of the mount, nor should you move the tripod. Doing so will undo the polar alignment. The telescope should be moved only about its R.A. and Dec. axes.

#### Use of the R.A. and Dec. Slow-Motion Control Cables

The R.A. and Dec. slow-motion control cables allow fine adjustment of the telescope's position to center objects within the field of view. Before you can use the cables, you must manually "slew" the mount to point the telescope in the vicinity of the desired target. Do this by loosening the R.A. and Dec. lock knobs and moving the telescope about the mount's R.A. and Dec. axes. Once the telescope is pointed somewhere close to the object to be viewed, retighten the mount's R.A. and Dec. lock knobs.

The object should now be visible somewhere in the telescope's finder scope. If it isn't, use the slow-motion controls to scan the surrounding area of sky. When the object is visible in the finder scope, use the slow-motion controls to center it. Now, look in the telescope's eyepiece. If the finder scope is properly aligned, the object should be visible somewhere in the field of view. Once the object is visible in the eyepiece, use the slow-motion controls to center it in the field of view.

The Dec. slow-motion control cable can move the telescope a maximum of 25°. This is because the Dec. slow-motion mechanism has a limited range of mechanical travel. (The R.A. slow-motion mechanism has no limit to its amount of travel.) If you can no longer rotate the Dec. control cable in a desired direction, you have reached the end of travel, and the slow-motion mechanism must be reset. This is done by first rotating the control cable several turns in the opposite direction from which it was originally being turned. Then, manually slew the telescope closer to the object you wish to observe (remember to first loosen the Dec. lock knob). You should now be able to use the Dec. slow-motion control cable again to fine adjust the telescope's position.

#### Tracking Celestial Objects

When you observe a celestial object through the telescope, you'll see it drift slowly across the field of view. To keep it in the field, if your equatorial mount is polar aligned, just turn the R.A. slow-motion control cable clockwise. The Dec. slow-motion control cable is not needed for tracking. Objects will appear to move faster at higher magnifications, because the field of view is narrower.

#### Optional Motor Drives for Automatic Tracking

An optional DC motor drive can be mounted on the R.A. axis of the equatorial mount to provide hands-free tracking. Objects will then remain stationary in the field of view without any manual adjustment of the R.A. slow-motion control cable.

#### Understanding the Setting Circles

The setting circles on an equatorial mount enable you to locate celestial objects by their "celestial coordinates". Every object resides in a specific location on the "celestial sphere". That location is denoted by two numbers: its right ascension (R.A.) and declination (Dec.). In the same way, every location on Earth can be described by its longitude and latitude. R.A. is similar to longitude on Earth, and Dec. is similar to latitude. The R.A. and Dec. values for celestial objects can be found in any star atlas or star catalog.

The R.A. setting circle is scaled in hours, from 1 through 24, with small marks in between representing 10-minute increments (there are 60 minutes in 1 hour of R.A.). The lower set of numbers (closest to the plastic R.A. gear cover) apply to viewing in the Northern Hemisphere, while the numbers above them apply to viewing in the Southern Hemisphere. The R.A. coordinate indicator arrow is between the "R" and the "A" on the plastic R.A. gear cover (see Figure 7); ignore the metal pointer on the R.A. axis of the mount.

The Dec. setting circle is scaled in degrees, with each mark representing 1° increments. Values of Dec. coordinates range from +90° to -90°. The 0° mark indicates the celestial equator (see Figure 7). When the telescope is pointed north of the celestial equator, values of the Dec. setting circle are positive, and when the telescope is pointed south of the celestial equator, values of the Dec. setting circle are negative.

So, the coordinates for the Orion Nebula listed in a star atlas will look like this:

**R.A. 5h 35.4m Dec. -5° 27'**

That's 5 hours and 35.4 minutes in right ascension, and -5 degrees and 27 arc-minutes in declination (there are 60 arc-minutes in 1 degree of declination).


Before you can use the setting circles to locate objects, the mount must be well polar aligned, and the R.A. setting circle must be calibrated. The Dec. setting circle has been permanently calibrated at the factory, and should read 90° whenever the telescope optical tube is parallel with the R.A. axis.

#### Calibrating the Right Ascension Setting Circle

1. Identify a bright star in the sky near the celestial equator (Dec. = 0°) and look up its coordinates in a star atlas.
2. Loosen the R.A. and Dec. lock knobs on the equatorial mount, so the telescope optical tube can move freely.
3. Point the telescope at the bright star whose coordinates you know. Lock the R.A. and Dec. lock knobs. Center the star in the telescope's field of view with the slow-motion control cables.
4. Loosen the R.A. setting circle lock thumb screw (see Figure 2); this will allow the setting circle to rotate freely. Rotate the setting circle until the arrow between the "R" and the "A" on the plastic gear cover indicates the R.A. coordinate listed in the star atlas for the object. Retighten the thumb screw.



Dec. coordinate indicator arrow  
Celestial equator (Dec. = 0°)



Use these numbers on  
the R.A. setting circle  
(Northern Hemisphere)

Plastic R.A. gear cover

R.A. coordinate indicator arrow

**Figure 7. For Northern Hemisphere observers, use the lower set of numbers on the R.A. setting circle. The R.A. coordinate indicator arrow is between the “R” and the “A” on the plastic gear cover. The telescope (not shown) is pointing north of the celestial equator, so the approximate coordinates of the mount in the image are R.A. 8h 30m Dec. 60°.**

### Finding Objects With the Setting Circles

Now that both setting circles are calibrated, look up in a star atlas the coordinates of an object you wish to view.

1. Loosen the Dec. lock knob and rotate the telescope until the Dec. value from the star atlas matches the reading on the Dec. setting circle. Remember that values of the Dec. setting circle are positive when the telescope is pointing north of the celestial equator (Dec. = 0°), and negative when the telescope is pointing south of the celestial equator. Retighten the lock knob.
2. Loosen the R.A. lock knob and rotate the telescope until the R.A. value from the star atlas matches the reading on the R.A. setting circle. Remember to use the lower set of numbers on the R.A. setting circle. Retighten the lock knob.

Most setting circles are not accurate enough to put an object dead-center in the telescope's eyepiece, but they should place the object somewhere within the field of view of the finder scope, assuming the equatorial mount is accurately polar aligned. Use the slow-motion controls to center the

object in the finder scope, and it should appear in the telescope's field of view.

The R.A. setting circle must be re-calibrated every time you wish to locate a new object. Do so by calibrating the setting circle for the centered object before moving on to the next one.

### Confused About Pointing the Telescope?

Beginners occasionally experience some confusion about how to point the telescope overhead or in other directions. In Figure 1 the telescope is pointed north, as it would be during polar alignment. The counterweight shaft is oriented downward. But it will not look like that when the telescope is pointed in other directions. Let's say you want to view an object that is directly overhead, at the zenith. How do you do it?

DO NOT make any adjustment to the latitude adjustment t-bolt. That will nullify the mount's polar alignment. Remember, once the mount is polar aligned, the telescope should be moved only on the R.A. and Dec. axes. To point the scope overhead, first loosen the R.A. lock knob and rotate the telescope on the R.A. axis until the counterweight shaft is horizontal (parallel to the ground). Then loosen the Dec. lock knob and rotate the telescope until it is pointing straight overhead. The counterweight shaft is still horizontal. Then retighten both lock knobs.

Similarly, to point the telescope directly south, the counterweight shaft should again be horizontal. Then you simply rotate the scope on the Dec. axis until it points in the south direction.

What if you need to aim the telescope directly north, but at an object that is nearer to the horizon than Polaris? You can't do it with the counterweight down as pictured in Figure 1. Again, you have to rotate the scope in R.A. so the counterweight shaft is positioned horizontally. Then rotate the scope in Dec. so it points to where you want it near the horizon.

To point the telescope to the east or west, or in other directions, rotate the telescope on its R.A. and Dec. axes. Depending on the altitude of the object you want to observe, the counterweight shaft will be oriented somewhere between vertical and horizontal.

Figure 8 illustrates how the telescope will look pointed at the four cardinal directions—north, south, east, and west

The key things to remember when pointing the telescope is that a) you only move it in R.A. and Dec., not in azimuth or latitude (altitude), and b) in actual use the counterweight and shaft will rarely appear as it does in Figure 1.




Figure 8a, 8b, 8c, 8d. **This illustration shows the telescope pointed in the four cardinal directions: (a) north, (b) south, (c) east, (d) west. Note that the tripod and mount have not been moved; only the telescope tube has been moved on the R.A. and Dec. axes.**

## 6. Using Your Telescope—Astronomical Observing

### Choosing an Observing Site

When selecting a location for observing, get as far away as possible from direct artificial light such as street lights, porch lights, and automobile headlights. The glare from these lights will greatly impair your dark-adapted night vision. Set up on a grass or dirt surface, not asphalt, because asphalt radiates more heat. Heat disturbs the surrounding air and degrades the images seen through the telescope. Avoid viewing over rooftops and chimneys, as they often have warm air currents rising from them. Similarly, avoid observing from indoors through an open (or closed) window, because the tempera-

ture difference between the indoor and outdoor air will cause image blurring and distortion.

If at all possible, escape the light-polluted city sky and head for darker country skies. You'll be amazed at how many more stars and deep-sky objects are visible in a dark sky!

### "Seeing" and Transparency

Atmospheric conditions vary significantly from night to night. "Seeing" refers to the steadiness of the Earth's atmosphere at a given time. In conditions of poor seeing, atmospheric turbulence causes objects viewed through the telescope to "boil". If, when you look up at the sky with just your eyes, the stars are twinkling noticeably, the seeing is bad and you will be limited to viewing with low powers (bad seeing affects images at high powers more severely). Planetary observing may also be poor.

In conditions of good seeing, star twinkling is minimal and images appear steady in the eyepiece. Seeing is best overhead, worst at the horizon. Also, seeing generally gets better after midnight, when much of the heat absorbed by the Earth during the day has radiated off into space.

Especially important for observing faint objects is good "transparency"—air free of moisture, smoke, and dust. All tend to scatter light, which reduces an object's brightness. Transparency is judged by the magnitude of the faintest stars you can see with the unaided eye (6th magnitude or fainter is desirable).

### Cooling the Telescope

All optical instruments need time to reach "thermal equilibrium". The bigger the instrument and the larger the temperature change, the more time is needed. Allow at least 30 minutes for your telescope to cool to the temperature outdoors. In very cold climates (below freezing), it is essential to store the telescope as cold as possible. If it has to adjust to more than a 40° temperature change, allow at least one hour.

### Let Your Eyes Dark-Adapt

Don't expect to go from a lighted house into the darkness of the outdoors at night and immediately see faint nebulas, galaxies, and star clusters—or even very many stars, for that matter. Your eyes take about 30 minutes to reach perhaps 80% of their full dark-adapted sensitivity. As your eyes become dark-adapted, more stars will glimmer into view and you'll be able to see fainter details in objects you view in your telescope.

To see what you're doing in the darkness, use a red-filtered flashlight rather than a white light. Red light does not spoil your eyes' dark adaptation like white light does. A flashlight with a red LED light is ideal, or you can cover the front of a regular incandescent flashlight with red cellophane or paper. Beware, too, that nearby porch and streetlights and car headlights will ruin your night vision.

### Eyepiece Selection

By using eyepieces of varying focal lengths, it is possible to attain many magnifications with the StarMax 102mm EQ. The telescope comes with one high-quality 25mm Sirius Plossl, which gives a magnification of 52x. Other eyepieces can be used to achieve higher or lower powers. It is quite common for

---

an observer to own five or more eyepieces to access a wide range of magnifications. This allows the observer to choose the best eyepiece to use depending on the object being viewed.

To calculate the magnification, or power, of a telescope and eyepiece combination, simply divide the focal length of the telescope by the focal length of the eyepiece:

$$\text{Magnification} = \frac{\text{focal length of telescope}}{\text{focal length of eyepiece}}$$

For example, the StarMax 102mm EQ, which has a focal length of 1300mm, used in combination with the 25mm eyepiece, yields a power of

$$1300\text{mm} \div 25\text{mm} = 52\text{x}$$

Every telescope has a useful limit of power of about 2x per mm of aperture (about 204x for the StarMax 102mm EQ). Claims of higher power by some telescope manufacturers are a misleading advertising gimmick and should be dismissed. Keep in mind that at higher powers, an image will always be dimmer and less sharp (this is a fundamental law of optics). The steadiness of the air (the “seeing”) will also limit how much magnification an image can tolerate.

Whatever you choose to view, always start by inserting your lowest-power (longest focal length) eyepiece to locate and center the object. Low magnification yields a wide field of view, which shows a larger area of sky in the eyepiece. This makes acquiring and centering an object much easier. If you try to find and center objects with high power (narrow field of view), it's like trying to find a needle in a haystack!

Once you've centered the object in the eyepiece, you can switch to higher magnification (shorter focal length eyepiece), if you wish. This is especially recommended for small and bright objects, like planets and double stars. The Moon also takes higher magnifications well.

Deep-sky objects, however, typically look better at medium or low magnifications. This is because many of them are quite faint, yet have some extent (apparent width). Deep-sky objects will often disappear at higher magnifications, since greater magnification inherently yields dimmer images. This is not the case for all deep-sky objects, however. Many galaxies are quite small, yet are somewhat bright, so higher power may show more detail.

The best rule of thumb with eyepiece selection is to start with a low power, wide field, and then work your way up in magnification. If the object looks better, try an even higher magnification. If the object looks worse, then back off the magnification a little by using a lower-power eyepiece.

### Rotating the Diagonal

When looking at objects in different areas of the night sky, the eyepiece may become positioned so that is uncomfortable or impossible to look through. If the eyepiece is in an undesirable position, the diagonal can be rotated in order to provide a more comfortable viewing angle. First, loosen the thumb screws on the eyepiece adapter, but make sure to hold the diagonal in place so that it won't fall to the ground. Also, secure the eyepiece in the diagonal so that it won't fall out

when rotating the diagonal. Retighten the thumb screws on the eyepiece adapter once the diagonal has been rotated to an appropriate position.

### Objects to Observe

Now that you are all set up and ready to go, one critical decision must be made: what to look at?

#### A. The Moon

With its rocky surface, the Moon is one of the easiest and most interesting targets to view with your telescope. Lunar craters, maria, and even mountain ranges can all be clearly seen from a distance of 238,000 miles away! With its ever-changing phases, you'll get a new view of the Moon every night. The best time to observe our one and only natural satellite is during a partial phase, that is, when the Moon is NOT full. During partial phases, shadows are cast on the surface, which reveal more detail, especially right along the border between the dark and light portions of the disk (called the “terminator”). A full Moon is too bright and devoid of surface shadows to yield a pleasing view. Make sure to observe the Moon when it is well above the horizon to get the sharpest images.

Use an optional Moon filter to dim the Moon when it is very bright. It simply threads onto the bottom of the eyepieces (you must first remove the eyepiece from the focuser to attach a filter). You'll find that the Moon filter improves viewing comfort, and also helps to bring out subtle features on the lunar surface.

#### B. The Sun

You can change your nighttime telescope into a daytime Sun viewer by installing an optional full-aperture solar filter over the front opening of the StarMax 102mm EQ. The primary attraction is sunspots, which change shape, appearance, and location daily. Sunspots are directly related to magnetic activity in the Sun. Many observers like to make drawings of sunspots to monitor how the Sun is changing from day to day.

**Important Note: Do not look at the Sun with any optical instrument without a professionally made solar filter, or permanent eye damage could result.**

#### C. The Planets

The planets don't stay put like the stars, so to find them you should refer to Sky Calendar at our website ([www.telescope.com](http://www.telescope.com)), or to charts published monthly in *Astronomy*, *Sky & Telescope*, or other astronomy magazines. Venus, Mars, Jupiter, and Saturn are the brightest objects in the sky after the Sun and the Moon. Your StarMax 102mm EQ is capable of showing you these planets in some detail. Other planets may be visible but will likely appear star-like. Because planets are quite small in apparent size, optional higher-power eyepieces are recommended and often needed for detailed observations. Not all the planets are generally visible at any one time.

**JUPITER** The largest planet, Jupiter, is a great subject for observation. You can see the disk of the giant planet and watch the ever-changing positions of its four largest moons—Io, Callisto, Europa, and Ganymede. Higher-power eyepieces should bring out the cloud bands on the planet's disk.

**SATURN** The ringed planet is a breathtaking sight when it is well positioned. The tilt angle of the rings varies over a period of many years; sometimes they are seen edge-on, while at other times they are broadside and look like giant “ears” on each side of Saturn’s disk. A steady atmosphere (good seeing) is necessary for a good view. You will probably see a bright “star” close by, which is Saturn’s brightest moon, Titan.

**VENUS** At its brightest, Venus is the most luminous object in the sky, excluding the Sun and the Moon. It is so bright that sometimes it is visible to the naked eye during full daylight! Ironically, Venus appears as a thin crescent, not a full disk, when at its peak brightness. Because it is so close to the Sun, it never wanders too far from the morning or evening horizon. No surface markings can be seen on Venus, which is always shrouded in dense clouds.

**MARS** The Red Planet makes its closest approach to Earth every two years. During close approaches you’ll see a red disk, and may be able to see the polar ice cap. To see surface detail on Mars, you will need a high-power eyepiece and very steady air!

#### D. The Stars

Stars will appear like twinkling points of light. Even powerful telescopes cannot magnify stars to appear as more than a point of light. You can, however, enjoy the different colors of the stars and locate many pretty double and multiple stars. The famous “Double-Double” in the constellation Lyra and the gorgeous two-color double star Albireo in Cygnus are favorites. Defocusing a star slightly can help bring out its color.

#### E. Deep-Sky Objects

Under dark skies, you can observe a wealth of fascinating deep-sky objects, including gaseous nebulas, open and globular star clusters, and a variety of different types of galaxies. Most deep-sky objects are very faint, so it is important that you find an observing site well away from light pollution. Take plenty of time to let your eyes adjust to the darkness. Do not expect these subjects to appear like the photographs you see in books and magazines; most will look like dim gray smudges. Our eyes are not sensitive enough to see color in deep-sky objects except in a few of the brightest ones. But as you become more experienced and your observing skills get sharper, you will be able to ferret out more and more subtle details and structure.

#### How to Find Deep-Sky Objects: Star Hopping

Star hopping, as it is called by astronomers, is perhaps the simplest way to hunt down deep-sky objects to view in the night sky. It entails first pointing the telescope at a bright star close to the object you wish to observe, and then progressing to other stars closer and closer to the object until it is in the field of view of the eyepiece. It is a very intuitive technique that has been employed for hundreds of years by professional and amateur astronomers alike. Keep in mind, as with any new task, that star hopping may seem challenging at first, but will become easier over time and with practice.

To star hop, only a minimal amount of additional equipment is necessary. A star chart or atlas that shows stars to at least mag-

nitude 5 is required. Select one that shows the positions of many deep-sky objects, so you will have a lot of options to choose from. If you do not know the positions of the constellations in the night sky, you will need a planisphere to identify them.




Figure 9: **Star hopping is a good way to locate hard-to-find objects. Refer to a star chart to map a route to the object that uses bright stars as guideposts. Center the first star you’ve chosen in the finder scope and telescope eyepiece (1). Now move the scope carefully in the direction of the next bright star (2), until it is centered. Repeat (3 and 4). The last hop (5) should place the desired object in the eyepiece.**

Start by choosing bright objects to view. The brightness of an object is measured by its visual magnitude; the brighter an object, the lower its magnitude. Choose an object with a visual magnitude of 9 or lower. Many beginners start with the Messier objects, first catalogued about 200 years ago by the French astronomer Charles Messier, which represent some of the best and brightest deep-sky objects.

Determine in which constellation the object lies. Now, find the constellation in the sky. If you do not recognize the constellations on sight, consult a planisphere. The planisphere gives an all-sky view and shows which constellations are visible on a given night at a given time.

Now, look at your star chart and find the brightest star in the constellation that is near the object you are trying to find. Using the finder scope, point the telescope at this star and center it on the crosshairs. Next, look again at the star chart and find another suitably bright star near the bright star currently centered in the finder. Keep in mind that the field of view of the finder scope is about 6°, so you should choose another star that is no more than 6° from the first star, if possible. Move the telescope slightly, until the telescope is centered on the new star.



---

Continue using stars as guideposts in this way until you are at the approximate position of the object you are trying to find (Figure 9). Look in the telescope's eyepiece, and the object should be somewhere within the field of view. If it's not, sweep the telescope carefully around the immediate vicinity until the object is found.

If you have trouble finding the object, start the star hop again from the brightest star near the object you wish to view. This time, be sure the stars indicated on the star chart are in fact the stars you are centering in the eyepiece.

## 7. Terrestrial Viewing

The StarMax 102mm not only excels at astronomical observing, it's great for terrestrial (land) viewing too. The equatorial mount, however, is not well suited for land viewing due to its motion about R.A. and Dec. axes instead of altitude (vertical) and azimuth (horizontal) axes. Because of this, we recommend removing the optical tube from the EQ-2 Mount and placing it on an appropriate photo-style tripod. This is easily done by rotating the thumb wheel clockwise on the mount's 1/4"-20 adapter. Make sure to have a firm grip on the tube as it releases from the mount. Now, connect the optical tube to a photo tripod by threading the tripod's 1/4"-20 shaft into the hole in the tube's mounting block.

The included mirror star diagonal, while preferred for astronomical observing because of its viewing angle and better resolution, is not optimal for land viewing because it inverts images from left-to-right. We recommend purchasing an optional 45° correct-image diagonal for terrestrial observing; it provides a more comfortable viewing angle for land viewing and an image that is oriented the same as the naked eye.

For terrestrial viewing, it's best to stick with low power eyepieces that yield a magnification under 100x. At higher powers, images rapidly lose sharpness and clarity due to "heat waves" caused by Sun-heated air.

Remember to aim well clear of the Sun, unless the front of the telescope is fitted with a professionally made solar filter and the finder scope is covered with foil or some other completely opaque material.

## 8. Photography

With an optional camera adapter, the StarMax 102mm becomes a 1300mm f/12.7 telephoto lens for a single-lens reflex camera. For long-distance terrestrial or astronomical photography, you need only a T-ring for your specific camera model. The T-ring attaches to your camera and threads onto the StarMax's eyepiece adapter (first remove eyepiece and diagonal), coupling the camera body to the telescope.

Use the camera's viewfinder to frame the picture. Use the telescope's focuser to focus the image.

You may want to consider using a remote shutter release instead of the shutter release on the camera. Touching the camera can vibrate the system and blur the resulting photographic image. Also, be sure to use a solid tripod.

## 9. Care and Maintenance

### Transporting

The included soft carry case provides an excellent way to transport the optical tube and its accessories. Remove the tube from the mount by rotating the knurled thumb wheel on the mount's 1/4"-20 adapter. Make sure to have a firm grip on the tube as it releases from the mount. To place the optical tube in the case, the eyepiece, diagonal, finder scope and bracket must be removed from the tube. When removing the eyepiece and diagonal, remember to first loosen the securing thumb screws. The finder scope and bracket can be removed together by loosening the thumb screw on the tube's dovetail mount. Cover the front of the optical tube with the dust cover and the rear opening of the eyepiece adapter with its cap. Now place the tube in the case's main compartment underneath the padded divider. The finder scope and bracket can be placed on top of the divider as one unit. The eyepiece and diagonal should be covered with their caps and placed in the external compartments of the case.

It is not necessary to completely disassemble the mount to transport it. It will be convenient to remove the accessory tray (by unthreading the three wing screws) in order to fold the tripod legs together. It may also be convenient to remove the slow-motion control cables and counterweight shaft. Orion offers an optional Padded Scope Case that will fit the entire EQ-2 Mount.

### Storing

If you give your telescope reasonable care, it will last a lifetime. Store it in a clean, dry, dust-free place, safe from rapid changes in temperature and humidity. Do not store the telescope outdoors, although storage in a garage or shed is OK. Small components like eyepieces, diagonals, and other accessories can be kept in the included carry case or in an optional eyepiece case. Keep the dust cover on the front of the telescope and cap the rear opening of the eyepiece adapter. Also keep the finder scope caps on if you leave it attached to the optical tube.

### Cleaning the Tube

Your StarMax 102mm EQ telescope requires very little mechanical maintenance. The optical tube is aluminum and has a smooth painted finish that is fairly scratch-resistant. If a scratch does appear on the tube, it will not harm the telescope. If you wish, you may apply some auto touch-up paint to the scratch. Smudges on the tube can be wiped off with a soft cloth and a household cleaner such as Windex or Formula 409.

### Cleaning Lenses

Any quality optical lens cleaning tissue and optical lens cleaning fluid specifically designed for multi-coated optics can be used to clean the StarMax's front meniscus lens or exposed lenses of your eyepieces or finder scope. Never use regular glass cleaner or cleaning fluid designed for eyeglasses. Before cleaning with fluid and tissue, however, blow any loose particles off the lens with a blower bulb or compressed air.



---

Then apply some cleaning fluid to a tissue, never directly on the optics. Wipe the lens gently in a circular motion, then remove any excess fluid with a fresh lens tissue. Oily fingerprints and smudges may be removed using this method. Use caution; rubbing too hard may scratch the lens. For the large surface of the meniscus lens, clean only a small area at a time, using a fresh lens tissue on each area. Never reuse tissues.

## 10. Specifications

Optical design: Maksutov-Cassegrain

Aperture: 102mm

Effective focal length: 1300mm

Focal ratio: f/12.7

Central obstruction diameter: 31mm

Primary mirror coating: Aluminum with overcoat

Meniscus lens coating: Anti-reflection multi-coatings on both sides of lens

Eyepiece adapter: Accepts 1.25" accessories, camera t-threads

Eyepiece: 25mm Sirius Plossl, fully coated with multi-coatings, 1.25" format

Magnification with supplied eyepiece: 52x

Actual field of view with supplied eyepiece: 0.92°

Diagonal: 90° mirror star diagonal, 1.25" format

Near focus (with supplied eyepiece & diagonal): Approximately 11 feet

Finder scope: 6x magnification, 26mm aperture, correct-image, achromatic, 6.3° field

Finder scope bracket: Dovetail base, spring-loaded X-Y alignment

Optical tube mounting block: Fits standard photo-style tripods

Mount: EQ-2, German-type equatorial

Slow-motion controls: R.A. and Dec. axes

Setting Circles: R.A. scaled in 10 minute increments, Dec. scaled in 1° increments

Counterweight: 4.8 lbs

Latitude range: 5° to 75°

Tripod: Adjustable-height aluminum legs, accessory tray included

Case: Deluxe carry case for optical tube included, padded case for EQ-2 mount optional

Motor drives: Optional

Weight: 21.9 lbs (tube 5.0 lbs, mount 16.9 lbs)



---

## One-Year Limited Warranty

This Orion StarMax 102mm EQ™ is warranted against defects in materials or workmanship for a period of one year from the date of purchase. This warranty is for the benefit of the original retail purchaser only. During this warranty period Orion Telescopes & Binoculars will repair or replace, at Orion's option, any warranted instrument that proves to be defective, provided it is returned postage paid to: Orion Warranty Repair, 89 Hangar Way, Watsonville, CA 95076. If the product is not registered, proof of purchase (such as a copy of the original invoice) is required.

This warranty does not apply if, in Orion's judgment, the instrument has been abused, mishandled, or modified, nor does it apply to normal wear and tear. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state. For further warranty service information, contact: Customer Service Department, Orion Telescopes & Binoculars, P. O. Box 1815, Santa Cruz, CA 95061; (800) 676-1343.

Orion Telescopes & Binoculars

Post Office Box 1815, Santa Cruz, CA 95061

Customer Support Help Line (800) 676-1343 • Day or Evening

---

# Collimating Orion StarMax™ and Apex™ Maksutov-Cassegrain Telescopes

**(StarMax 90,102, and 127, Apex 90, 102, and 127)  
(9821,9824,9826,9820,9823,9825)**

Collimating is the process of aligning a telescope's optics. Your StarMax or Apex's primary mirror was aligned at the factory and should not need adjustment unless the telescope is handled roughly. This manual contains information on how to test the collimation of your telescope and instructions for proper alignment should that be needed.

## Star-Testing the Telescope

Before you start adjusting the primary mirror of your telescope, make certain that it is actually out of collimation by performing a star test.

Take your telescope out at dusk and let it acclimate to the outside temperature; this usually takes 30-60 minutes. When it is dark, point the telescope upwards at a bright star and accurately center it in the eyepiece's field of view. Slowly de-

focus the image with the focusing knob. If the telescope is correctly collimated, the expanding disk should be a circle (Figure 1). If the image is unsymmetrical, the scope is out of collimation. Also, the dark shadow cast by the secondary mirror should appear in the very center of the out-of-focus circle, like the hole in a donut. If the "hole" appears off-center, the telescope is out of collimation.

If you try the star test but the bright star you have selected is not accurately centered in the eyepiece, the optics will always appear out of collimation, even though they may be perfectly aligned. It is critical to keep the star centered, so over time you will need to make slight corrections to the telescope's position in order to account for the sky's apparent motion.

## Collimating the StarMax/Apex

To collimate your telescope, remove the diagonal and eyepiece and look into rear opening of the tube (also remove the dust cover from the front of the tube). This should be done indoors, with the telescope pointed at a white wall in a well-lit room. Try to keep your eye centered with respect to the rear opening of the tube as best as possible. Using an Orion Collimating Eyepiece will aid greatly in keeping your eye centered and is strongly recommend.

Alternatively, you can make a crude collimating tool out of an empty, black plastic 35mm film canister. It will not have crosshairs, so it won't be as precise, but it will be better than nothing. Cut 1/2" from the top lip of the canister and put a 1/16" to 1/8" diameter hole in the center of its bottom. Insert the film canister collimating tool into the focuser like an eyepiece with the bottom end out.




Figure 1: A star test will determine if a telescope's optics are properly collimated. An unfocused view of a bright star through the eyepiece should appear as illustrated on right if optics are perfectly collimated. If circle is unsymmetrical, as in illustration on left, scope needs collimation.




Figure 2a: If the telescope's optics are out of alignment the view through the rear opening of the telescope will resemble Figure 2a.

Once you are ready to collimate, look into rear opening of the tube. If your telescope is out of collimation, it will resemble Figure 2a, a properly collimated scope will resemble Figure 2b. The direction of the misalignment in your telescope may differ from Figure 2a, but the diagram will give you the general idea of how things will look.

Note there are six alignment screws on the back of the optical tube, three large and three small. You will need 3mm and 2mm Allen wrenches to turn these screws. These alignment screws push and pull the mirror cell in order to tilt it. When you loosen or tighten one of these screws, the other five screws must be adjusted as well to keep the proper amount of pressure on the back of the mirror cell. By making slight adjustments to how much the screws are tightened and loosened, you will change the alignment of the primary mirror.

Look into the rear opening of the tube and locate the black crescent that shows the telescope is out of alignment. (Figure 2a). Note which way the front of the telescope would need to move in order to "fill" that black crescent and resemble Figure 2b. Then look at the back end of the telescope and locate the alignment screw that is in the direction that the




Figure 2b: With the optics properly aligned the view through the rear opening of the telescope will resemble Figure 2b.

front of the telescope needs to move. For example, if the view in your telescope resembled Figure 2a, then you would want to move the front opening of the telescope scope to the right. Then the alignment screw you would start with would be the screw on the right as shown in Figure 3.

Your actions now depend on whether this alignment screw is a small or large screw. Please note that you will be working to adjust the mirror cell by keeping all the screws not too loose and not too tight. Follow the steps listed below carefully and refer to the figures that accompany them.




Figure 3: If the view through the rear opening of the telescope resembled Figure 2a, then the alignment screw you would start with would be this one. The actual first alignment screw you would pick will vary depending on which way the front opening would need to move in order to "fill" the black crescent.






Figure 4a

Figure 4a: Using the 3mm Allen wrench, turn the large screw *clockwise* a small amount, no more than 1/4 of a turn. (Note, actual selected alignment screw will vary.)




Figure 4b

Figure 4b: Now, with the 2mm Allen wrench, turn the two adjacent small screws *counterclockwise* no more than 1/4 turn.




Figure 4c

Figure 4c: Turn the small screw that is 180° opposite the first screw *clockwise* no more than 1/4 turn.




Figure 4d

Figure 4d: Turn the two large screws adjacent to the small screw *counterclockwise* no more than 1/4 turn.

**If the alignment screw is a large screw**

First, using the 3mm Allen wrench, turn the large screw *clockwise* a small amount, no more than a 1/4 turn. (Figure 4a)

Now, with the 2mm Allen wrench turn the two adjacent small screws (Figure 4b) *counterclockwise* no more than 1/4 turn.

Locate the small screw that is 180° opposite the first screw (Figure 4c) and turn it *clockwise* no more than 1/4 turn.

Turn the two large screws adjacent to the small screw (Figure 4d) *counterclockwise* no more than 1/4 turn.

Repeat the above steps until the front opening is centered in the direction you wanted it to go. You may need to repeat this (or the small screw adjustment process) with other screws in order to align it in other directions.




Figure 5a

Figure 5a: Using the 2mm Allen wrench, turn the large screw *counterclockwise* a small amount, no more than 1/4 of a turn. (Note: Actual selected alignment screw will vary.)




Figure 5b

Figure 5b: Now, with the 3mm Allen wrench turn the two adjacent large screws *clockwise* no more than 1/4 turn.




Figure 5c

Figure 5c: Turn the large screw that is 180° opposite the first screw *counterclockwise* no more than 1/4 turn.




Figure 5d

Figure 5d: Turn the two large screws adjacent to the small screw *clockwise* no more than 1/4 turn.

**If the alignment screw is a small screw**

First, using the 2mm Allen wrench, turn the small screw *counterclockwise* a small amount, no more than a 1/4 turn. (Figure 5a)

Now, with the 3mm Allen wrench, turn the two adjacent large screws (Figure 5b) *clockwise* no more than 1/4 turn.

Locate the large screw that is 180° opposite the first screw (Figure 5c) and turn it *counterclockwise* no more than 1/4 turn.

Turn the two small screws adjacent to the large screw (Figure 5d) *clockwise* no more than 1/4 turn.

Repeat the above steps until the front opening is centered in the direction you wanted it to go. You may need to repeat this (or the large screw adjustment process) with other screws in order to align it in other directions.

Repeat these two procedures as needed until the view through the scope resembles Figure 2b.

**Finishing Collimation**

Once you have finished adjusting your telescope, you will need to perform another star test (described earlier) to check the collimation. If your telescope appears collimated after star testing, it should not need adjustment again unless it is roughly handled.

If you have gone through this process and your telescope is still out of collimation, please contact Orion customer support. You may need to return the telescope for repair (covered on warranty for 1 year after purchase).