

GP SERIES

COMMERCIAL / RESIDENTIAL PORTABLE GENERATORS

FEATURES:

- Generac OHVI® Overhead Valve Industrial Engine With Full Pressure Lubrication and Spin-on Oil Filter
- High performance alternator
- Steel fuel tank with incorporated fuel gauge
- Mobility kit with locking fold-down handles and never-flat wheels
- 1-1/4" diameter hardened steel tube cradle
- Hour meter with maintenance resets
- Electric Start (Includes Starting Battery)
- Circuit breaker protected outlets
- Low-tone muffler

GP7000E

Model 05626

Running Watts: 7000

Starting Watts: 8750



Ratings	
AC Rated Output	7.0kW / 7000 Watts
AC Maximum Output	8.75 kW / 8750 Watts
AC Voltage	120V/240V
AC Frequency	60 Hz
120 V C Amperage	Rated 58.3/Max 72.9
240 VAC Amperage	Rated 29.1/Max 36.4
Engine	
Engine Type and Displacement	OHVI Single Cylinder 410cc
Oil Capacity w/ Filter Change	1.5 Qt. (1.4 liter)
Oil Capacity w/o Filter Change	1.2 Qt. (1.14 liter)
Low Oil Pressure Shutdown	Standard

Fuel	
Fuel Capacity	8.0 Gallons (30.28 liters)
Run Time @ ½ Load	11 Hours
Assembled Dimensions and Weight	
Dimensions L x W x H (inches)	33.5 x 26.5 x 27.5
Dimensions L x W x H (mm)	850.9 x 673.1 x 698.5
Unit Weight	195 lbs. (88.4 kg.)
Warranty	
Residential	2 Year Limited
Commercial	1 Year Limited

Outlets

4 x 5-20R



1 x L14-30R



Maximum wattage and current are subject to, and limited by, such factors as fuel Btu content, ambient temperatures, altitude, engine condition, etc. Maximum power decreases about 3.5% for each 1,000 feet above sea level; and will also decrease about 1% for each 6° C (10° F) above 16° C (60° F) ambient temperature.