MOUNTING

Grinder must be bolted to a bench or B&D pedestal #53536 for optimum use —

EXHAUST PORTS

Unit equipped with ports to facilitate connection to a dust removal system.

EXTRA EQUIPMENT

- 1. Buffing wheels
- 2. Wire brushes
- 3. Eye shields (requires drilling out hol on top of guard for mounting).
- 4. Wheel dressers



Black & Decker. POWER TOOLS



IMPORTANT!

To assure product SAFETY and RELIABILITY, repairs, maintenance and adjustments should be performed by BLACK & DECKER Service Centers or other qualified service organizations, always using BLACK & DECKER replacement parts.

	Area Code	Telephone No.
LABAMA: Birmingham 35233, 1717 Third Ave., South	205	324-6691
DIZONA Dhooniy 95004 537 F McDowell Rd	602	AL 8-1332
RKANSAS: Little Rock 72201, 519 West Seventh St CALIFORNIA: Anaheim 92802, 1235 So. Euclid Ave	501	FR 2-3040
ALIFORNIA: Anaheim 92802, 1235 So. Euclid Ave	714	772-4050
Los Angeles 90007, 2432 S. Broadway	.213	RI 9-0371
Oakland 94606, 1107 E. 14th St	.415	TE 4-5944
Sacramento 95814, 1915 Seventeenth St.	.916	444-3188
San Diego 92105, 3811 El Cajon Blvd	.714	280-3331
Santa Clara 95050, 2291 The Alameda	.408	241-9162
South San Francisco 94080, 1139 Airport Blvd	.415	871-7278
Van Nuys 91401, 14920 Victory Blvd	.213	787-5531
COLORADO: Denver 80204, 675 Kalamath St	303	222-0621
CONNECTICUT: Hartford 06114, 131 Meadow St	203	249-6241
FLORIDA: Jacksonville 32208, 5224 Pearl St	.904	356-2951
Miami 33168, 13345 N.W. Seventh Ave	305	681-6658
Orlando 32806, 940 So. Orange Ave	305	423-1651
Tampa 33609 3401 W Kennedy Blyd	813	872-8317
GEORGIA: Atlanta 30313, 316 Techwood Drive, N.W	404	JA 4-0431
HAWAII - Honolulu 96813, 675 Aughi St	808	536-9374
ILLINOIS: Chicago 60607, 1100 W. Jackson Blvd	312	TA 9-3500
Chicago 60646, Lincolnwood, 6710 N. Crawford Ave	312	OR 3-0923
Chicago 60643, 10708 S. Western Ave. (Beverly Hills)	312	BE 3-6832
Rock Island 61201, 725 30th St	309	788-1744
INDIANA: Evansville 47708, 931 Bond St	812	425-4269
Indianapolis 46202, 1125 W. 16th St	317	632-5569
IOWA: Des Moines 50312, 2811 Ingersoll Ave	515	CH 4-7257
KANSAS: Wichita 67214, 203 N. Mathewson St	316	263-6571
KENTUCKY: Louisville 40209, 4407 Park Blvd	502	366-1495
LOUISIANA: New Orleans 70002,		007.0550
3310 N. Causeway Blvd. (Metairie)	504	837-2550
MARYLAND: Baltimore 21211, 203 West 28th St	301	HO 7-7411
Baltimore 21205, 4712 Erdman Ave	301	485-5550
Bladensburg 20710, 4501 Baltimore Ave	301	779-3808
Towson 21204, 701 E. Joppa Rd	301	828-2910
MASSACHUSETTS: Boston 02135, 12 Market St. (Brighton)		07.0.0004
12 Market St. (Brighton)	617	ST 2-6264
MICHIGAN: Detroit 48219, 18133 W. McNichols Rd	313	534-8880
Detroit 48234, 11360 East Seven Mile Rd. (Mt. Elliott)313	527-5010
Grand Rapids 49509, 3662 Clyde Park Ave., S.W	616	534-7708
MINNESOTA: Minneapolis 55408, 2815 Nicollet Ave.	612	823-5283 HA 1-1493
MISSOURI: Kansas City 64108, 2705 McGee Trafficway	816	JE 3-2210
St. Louis 63110, 615 S. Vandeventer Ave.	314	
NEBRASKA: Omaha 68102, 2218 Leavenworth St	402	HU 3-1076

	Area Code	Telephone
	Code	Ño.
NEW MEXICO: Albuquerque 87110,		
4700 Lomas Blvd. N.E	505	265-6401
NEW YORK: Buffalo 14209, 881 W. Delavan Ave	716	TT 4-6220
New York 10462, 1894 E. Tremont Avenue (Bronx)		SY 2-2700
New York 10014, 227 Varick St. (Manhattan)	212	WA 9-6450
New York 11377, 56-15 Queens Blvd. (Woodside)	212	DE 5-1042
Rochester 14620, 476 Clinton Ave. S	716	454-3814
Syracuse 13224, 2140 Erie Blvd. E	315	446-3086
NORTH CAROLINA: Charlotte 28206, 1710 N. Graham St.	704	FR 5-3721
Fayetteville 28306, P.O. Box 4305, Highway 301, S.	919	425-1181
Greensboro 27403, 1008 W. Lee St		275-0906
OHIO: Cincinnati 45203, 1225 Western Ave		421-2275
Cleveland 44113, 3901 Detroit Ave	216	OL 1-4243
Columbus 43202, 3975 East Livingston Ave	614	237-0461
Dayton 45420, 617 Watervliet St	513	252-1821
Solon 44139, 6225 Cochran Rd	216	CH 8-5330
Toledo 43606, 2629 W. Central Ave	419	475-6771
OKLAHOMA: Oklahoma City 73106, 1318 Linwood Blvd.	405	CE 2-7515
Tulsa 74145, 3120 South Sheridan Rd	918	622-5666
OREGON: Portland 97209, 1640 N. W. Johnson St	503	CA 8-8631
PENNSYLVANIA: Harrisburg 17112,		
6070 Allentown Blvd.	717	545-0651
Lancaster 17604, 715 Fountain Ave	717	393-5831
Philadelphia 19103, 333 No. 20th St	215	LO 4-5520
Pittsburgh 15232, 5437 Baum Blvd	412	362-2700
RHODE ISLAND: E. Providence 02914, 2777 Pawtucket Ave		
2777 Pawtucket Ave	401	434-1655
SOUTH CAROLINA: Greenville 29601, 407 Pendleton St.	803	232-3038
TENNESSEE: Knoxville 37917, 1123 North Central St.	615	546-2481
Memphis 38116, 986 East Brooks Rd		332-3444
Nashville 37203, 601 Eighth Ave., South		254-1061
TEXAS: Amarillo 79106, 3008 West 6th Ave	806	DR 3-1531
Dallas 75207, 1808 N. Industrial Blvd		RI 1-6401
Fort Worth 76103, 1801 Bomar St	817	336-0175
Houston 77003, 105 Sampson St	713	228-7521
San Antonio 78210, 1111 S. Prensa St	512	LE 4-4611
UTAH: Salt Lake City 84115, 1541 S. Second West	801	HU 6-7056
VIRGINIA: Falls Church 22046, 129 Annandale Rd	703	533-1147
Norfolk 23517, 337 W. 21st St	703	627-4521
Richmond 23222, 1424 Chamberlayne Ave	703	649-9245
WASHINGTON: Seattle 98109, 701 Third Ave., N	206	AT 2-6432
Spokane 99207, 3550 N. Market St	509	HU 9-9164
WEST VIRGINIA: Charleston 25312, 1638 Sixth Ave.	304	343-0289
WISCONSIN: Milwaukee 53213. 6301 Blue Mound Rd.	414	476-7800

NACK & DECKER MEG. CO., Limited, Canada

	BLACK & DECKER WITG.	CO., Cillicon, Gallega	
BROCKVILLE, ONTARIO		MONTREAL 10, P. Q	
CALGARY, ALBERTA	1003 11th Avenue, S. W.	OTTAWA, ONTARIO	
DON MILLS (Toronto)	2 Valleybrook Drive	OUEBEC CITY, P. O.	330 St. Roch Street
EDMONTON, ALBERTA		REGINA, SASKATCHEWAN	1076 Albert Street
HALIFAX, NOVA SCOTIA	903 Mclean Street	SASKATOON SASK. Diamon	nd Ind. Center, Quebec & 33rd St.
HALIFAX, NOVA SCOTTA	100 Desirate Aug. N	VANCOUVER 10, B. C.	24 West 2nd Ave
HAMILTON, ONTARIO	180 Parkdale Ave., N.	VANCOUVER TO, B. C.	024 04 1 04
LONDON ONTARIO	631 Commissioners Rd., East	WINNIPEG 10, MANITOBA	934 St. James St.

ALABAMA, Montgomer ALASKA, Anchorage Fairbanks ARIZONA, Tucson CONNECTICUT, New Haven DELAWARE, Wilmington FLORIDA, Pensacola IDAHO, Boise, Lewiston

, New Haven MAINE, Westbrook MISSISSIPPI, Jackson NEVADA, Reno, Las V. Lewiston NEW YORK, Schenect


OHIO, Youngstown
PENNSYLVANIA, Allentown
Erie
SOUTH CAROLINA, Charlestor

TEXAS, Corpus Christi
El Paso
VIRGINIA, Roanoke
WASHINGTON, Yakima
WEST VIRGINIA Wheeling

Guarantee Black & Decker guarantees, for one year from date of purchase, to correct by repair or parts replacement without charge any defect due to faulty material or workmanship. Simply return the complete unit, transportation prepaid, to any Black & Decker Service Center or Authorized Service Station. Naturally, we assume no responsibility for damage caused by misuse, careless handling or where repairs have been made or attempted by others. No other guarantee, written or verbal, is authorized by us.

THE BLACK & DECKER MFG. CO. — TOWSON, MARYLAND 21204, U.S.A.

(C3-FB) Printed in U.S.A.



OWNER'S MANUAL

This booklet is provided for your convenience in the Use & Care of your new Black & Decker Bench Grinder. These instructions include Safety Precautions, Operation, Preventive Maintenance, Maintenance and other pertinent data to assist you in assuring long life and dependable service from your Bench Grinder.

CAT. NOS. 4330, 4330-01, 4335 — TYPE 1

10"
HEAVY-DUTY
BENCH
GRINDER

Bulletin 2928-1



P.T.I. SAFETY RULES FOR STATIONARY **POWER TOOLS**

- 1. KNOW YOUR POWER TOOL. Read the owner's manual carefully. Learn its application and limitation, as well as the specific potential hazards peculiar to this tool.
- 2. KEEP GUARDS IN PLACE and in working order.
- 3. GROUND ALL TOOLS. If tool is equipped with threeprong plug, it should be plugged into a three-hole electrical receptacle. If an adapter is used to accommodate a two-prong receptacle, the adapter wire must be attached to a known ground. Never remove the third prong.
- 4. REMOVE ADJUSTING KEYS AND WRENCHES. Form habit of checking to see that keys and adjusting wrenches are removed before turning on tool.
- 5. KEEP WORK AREA CLEAN. Cluttered areas and benches invite accidents.
- 6. AVOID DANGEROUS ENVIRONMENT. Don't use power tools in damp or wet locations. Keep your work area well illuminated.
- 7. KEEP CHILDREN AWAY. All visitors should be kept a safe distance from work area.
- 8. MAKE WORKSHOP KIDPROOF-with padlocks, master switches, or by removing starter keys.
- 9. DON'T FORCE TOOL. It will do the job better and be safer at the rate for which it was designed.
- 10. USE RIGHT TOOL. Don't force tool or attachment to do a job it was not designed for.
- 11. WEAR PROPER APPAREL. No loose clothing or jewelry to get caught in moving parts.
- 12. USE SAFETY GLASSES. Also use face or dust mask if cutting operation is dusty.
- 13. SECURE WORK. Use clamps or a vise to hold work, when practical. It's safer than using your hand, frees both hands to operate tool.
- 14. DON'T OVERREACH. Keep your proper footing and balance at all times.
- 15. MAINTAIN TOOLS IN TOP CONDITION. Keep tools sharp and clean for best and safest performance. Follow instructions for lubricating and changing accessories.
- 16. DISCONNECT TOOLS before servicing and when changing accessories such as blades, bits, cutters.
- 17. USE RECOMMENDED ACCESSORIES. Consult owner's manual. Use of improper accessories may be hazardous.
- 18. AVOID ACCIDENTAL STARTING. Make sure switch is off before plugging in cord.

GROUNDING

These units are equipped with an outlet box mounted on the back of the unit for permanent wiring, as required by Underwriters Laboratories. Wiring diagrams are pasted to the underside of the base. To insure proper wiring & "grounding" of tool, have connection made by a qualified electrician.

LUBRICATION

This tool is equipped with lubricant sealed ball bearings which require no further lubrication for the life of the bearing.

MOTOR

Four pole capacitor start induction motor. Squirrel cage rotor.

Cat.				Rated	RPM	
No.	Phase	HP	Cycles	@ 115 V.	No Load	Voltage, A.C.
4330	1	1	50/60	14.6/13	1500/1800	115 Volts
4330-03	1 1	1	50/60	14.6/13	1500/1800	220 Volts
4335	3	1	50/60	14.6/13	1500/1800	220/440
						Reconnectable

CHANGING WHEELS

Remove 4 screws holding wheel guard cover. Loosen and remove hexagon nut. (Nut on left wheel has left hand threads, nut on right wheel has right hand threads) and clamp washer. Remove wheel. To reassemble, reverse above steps. Do not overtighten nut. Wheel size 10" O.D., 3/4" I.D., 1" Width.

ACCESSORIES

No. 34575 One Shatter-Proof Eve Shield . . . Fastens permanently to Bench Grinder. Adjusts quickly to various positions to suit operator. Not illuminated. (Replacement glass,

No. 19115 Cutter Wheel Dresser . . . Has spare set of cutter wheels. Dresses wheels quickly for fast grinding.

No. 21961 Diamond Dresser . . . Produces an accurate, smooth face for finish grinding.

No. 53536 Pedestal . . . Holds grinder at convenient height. Has detachable water pot. Height: 31%"; Base: 16 square. Grinding Wheels (10" Diam. x 1" Face x ¾" Hole):
No. 10274 Specification A24Q6V, Type 1
No. 10275 Specification A46N6V, Type 1

Wire Wheel Brushes (10" Diam. x 1%" Face x ¾" Hole: No. 21407 .014 Wire Diam. (30 Gage)

No. 27012 .0118 Wire Diam. (33 Gage)

Cotton Buffing Wheels (10" Diameter x 3/4" Hole):
No. 26873 5/8" Wide
No. 26876 1/4" Wide

CAUTION: Recommended accessories for your Bench Grinder are listed above. The use of any other accessory might be more hazardous.

ADDITIONAL GRINDER SAFETY RULES

- 1. Always wear safety glasses or other eye protection when operating this tool, and eye shields, mounted on the wheel guards, are strongly recommended.
- 2. Replace a cracked wheel immediately. Handle grinding wheels carefully to avoid bumping or dropping. DO NOT use a grinding wheel that has been dropped. Before using, inspect each grinding wheel for cracks or flaws and if these are evident, discard the wheel.
- 3. Before mounting a new wheel, be sure that it is marked with an R.P.M. that is the same as, or higher than, the no-load speed of the grinder as marked on the nameplate. Do not overtighten wheel nut. Use only flanges furnished with this arinder.
- 4. Never start a grinder with anyone, including the operator, standing in line with the wheel. After installing a replacement wheel, stand to one side and allow it to revolve freely for about one minute.
- Do not grind on the sides of grinding wheels unless they are the special wheels designed specifically for this
- Use of any other accessory or attachment other than those specified might create a hazard for the operator.

10" BENCH GRINDER

