



DIMENSIONS



FLAT (Compact Fluorescent & Incandescent Units)



SHALLOW CASTING
(Units with CSTG, F1 Option, EM & SC Option and SCB18 Accessory)

DESCRIPTION

The Fail-Safe Terrapin Series provides exceptional aesthetics with remarkable strength. The wide variety of products allow an interior and exterior architectural theme throughout an entire facility. Cast, extra-heavy aluminum walls of the housings offer rugged durability and afford efficient heat dissipation. AccUView UV-Guard coating protects the inside and outside of all UV stabilized polycarbonate lenses. The combination of narrow prismatic blondels on the interior and a prescription texture on the exterior of the lens provides exceptional lamp obscuration. **Lifetime Warranty** against breakage.



ROUND SERIES 18" Harmony™ VR

26W - 70W

Compact Fluorescent

75W - 200W

Incandescent

HARMONY™
Vandal Resistant



- Lens is one piece injection molded polycarbonate, .125" thick. In clear prismatic or opal, the lens is scientifically designed to obscure lamp image while maintaining efficiency. All lenses are provided with AccUView UV guard on interior and exterior surfaces.
- Precision die-cast aluminum housing. Extra-heavy thickness, minimum .125" thick, promotes durability and efficient heat dissipation. Marine-grade low-copper alloy aluminum resists corrosion.
- Eyelid face consists of high-impact, injection molded, .125" minimum thickness, polycarbonate overlay attached to lens with two recessed stainless steel TORX fasteners. Provides true 360° backlit halo effect
- Incandescent sockets are Porcelain medium base sockets with nickel-plated brass screw shell. Compact Fluorescent sockets are polycarbonate.
- Compact Fluorescent ballasts are electronic, universal voltage 120-277V, with minimum starting temperatures of -17°C (0°F) for 57, 70W.

ORDERING INFORMATION

SAMPLE NUMBER: TRE18-C-342CT-DT-BK

Product T=Terrapin	Lamp Qty/Type Compact Fluorescent 1, 2, or 3/26CT ¹ 1, 2, or 3/32CT ¹ 1, 2, or 3/42CT ³ 1, 2, or 3/57CT ^{3,4} 1, 2, or 3/70CT ^{3,4} Incandescent 1 or 2/75IN 1 or 2/100IN ² 1/150IN 1/200IN ²	Voltage Compact Fluorescent: DT=Universal 120-277V Ballast 347V=347V Ballast Incandescent: 120V=120V	Options EM ⁵ =Emergency Battery Pack (Fluorescent Only) F1 ⁵ =Single Fuse 120, 277, or 347V (with HID specify single voltage only) L=With lamp SC ³ =Surface conduit taps w/plugs (standard with HID units) CSTG=Shallow Casting	Accessories (Order Separately) VRSD=TORX® screwdriver VRSB=TORX screwdriver bit SCB18=Surface conduit box, 18"
Shape R=Round		Color BK=Black WH=White		
Style B=Border Paint E=Eyelid O=Open Face				
Size 18=18"				
Lens C=Clear prismatic O=Opal				

To View Style Options, please go to page #1413.



Notes: For additional options, consult your Cooper Lighting Representative. Specifications and dimensions subject to change without notice. Products also available in non-US voltages and 50Hz for international markets.

¹ Ceiling mount three (3) 26CT & three (3) 32CT require CSTG, Shallow Casting; TRB18-C-332CT-DT-BK-CSTG. ² Ceiling mount 200W Incandescent version to be mounted on non-combustible material only. ³ Three (3) 42CT, three (3) 57CT, & three (3) 70CT, EM & SC come standard with Shallow Casting, (CSTG). ⁴ Wall Mount Only. ⁵ Supplied with Shallow Casting (CSTG).

TORX® is a registered trademark of Camcar Division of Textron Inc.