

DESCRIPTION

R4C


Matches P4C Series emergency lighting units. Impact resistant thermoplastic housing is UL924 rated. Black thermoplastic body with white plastic collar and reflector. For semi-recessed installation, order USF1 accessory. For fully recessed installation, order FRK1 accessory.

ORDERING INFORMATION

R4C Series

Catalog No.	Lamp Type	Volts	Watts	Lamp No.
R4C140	Halogen Bi-Pin T2 1/4	6	10	029-40
R4C145	Halogen Bi-Pin T2 1/4	12	12	029-45

Alternate Lamps⁽¹⁾
Other Finishes⁽¹⁾



R4C SERIES

Emergency Remotes

DESCRIPTION

RFR

20 gauge die-stamped steel housing with white baked enamel finish. 5 1/2" housing accommodates 2x6 joist construction. Available with 6 volt or 12 volt incandescent double contact bayonet base lamps. UL Damp Location Listed.

ORDERING INFORMATION

RFR Series

Catalog No.	Finish	Lamp Type	Volts	Watts	Lamp No.
RFR130	White Trim	Incandescent DC Bayonet Base	6	6.6	029-30
RFR153	White Trim	Incandescent DC Bayonet Base	12	7.5	029-53

Alternate Lamps⁽¹⁾
Other Finishes⁽¹⁾



RFR SERIES

Emergency Remotes

DESCRIPTION

ULTIMATE REMOTE HEAD

The Sure-Lites Ultimate Series explosion-proof, emergency lighting fixtures are designed for remote mounting in Class I, Division II Group A, B, C, and D locations such as oil refineries, oil and gasoline loading docks, chemical and petrochemical plants, paint manufacturing sites, pumping stations and other process industry facilities where similar hazards threaten. UL 844 listed. UL 924 wet location listed.

ORDERING INFORMATION - CLASS I, DIVISION II, GROUPS A, B, C, D (UL844 HAZARDOUS LISTED)

Catalog Number	Lamp Type	Volts	Watts	Lamp No.	T-Code	Lamp Data
MRT6T5HAZ	MR16	6	5	029-139	T3A	ADX031520
MRT6T9HAZ	MR16	6	9	029-143	T2C	ADX031520
MRT6T12HAZ	MR16	6	12	029-140	T2A	ADX031520
MRT12T12HAZ	MR16	12	12	029-141	T2A	ADX031520
MRT12T20HAZ	MR16	12	20	029-142	T1	ADX031520

ORDERING INFORMATION - WET LOCATION (UL924 WET LOCATION LISTED)

Catalog Number	Lamp Type	Volts	Watts	Lamp No.	Lamp Data
MRT6T5W	MR16	6	5	029-139	ADX031520
MRT6T9W	MR16	6	9	029-143	ADX031520
MRT6T12W	MR16	6	12	029-140	ADX031520
MRT12T12W	MR16	12	12	029-141	ADX031520
MRT12T20W	MR16	12	20	029-142	ADX031520
MRT12T50W	MR16	12	50	029-144	ADX031520



ULTIMATE REMOTE SERIES

Emergency Remotes

DESCRIPTION

HZB/HZP

The Sure-Lites HZP Series and HZB Series explosion-proof, emergency lighting fixtures are designed for remote mounting in Class I, Division 1, Group C, D and Class II, Division 1, Group E, F, G locations such as oil refineries, oil and gasoline loading docks, chemical and petrochemical plants, paint manufacturing sites, pumping stations and other process industry facilities where similar hazards exist. Body and globe guard are copper-free, corrosion resistant light weight aluminum, with a heat and impact resistant glass globe. UL 924 Listed, Life Safety NFPA 101, NEC Class I, division 1, Groups C, D and Class II, Division 1, Groups E, F, G, NEC/OSHA, most state and local codes. UL Damp Location Listed.

ORDERING INFORMATION

HZ Series

Catalog No.	Mounting	Lamp Type	Volts	Watts	Lamp No.
12X25HZP	Pendant	Incandescent	12	25	ZZ-13
12X25HZB	Bracket	Incandescent	12	25	ZZ-13



HZB/HZP SERIES

Emergency Remotes

⁽¹⁾ Consult your Cooper Lighting Representative.