


Note: Tub only model does not include access panels unless ordered as an option.

Rough-In Plumbing Measurements



SPECIFICATIONS:

GENERAL SPECIFICATIONS:

Tub Size	60" x 32" x 20 1/4"
	152 cm x 81 cm x 51 cm
Bathing Well	41" long
	18" wide
	16 3/4" interior depth
Maximum Water Depth	13 1/2"
Shipping Weight	161 lbs. / 73 kg
Tub Weight Filled	561 lbs. / 254 kg
Tub Only Weight	120 lbs. / 120 kg
Gallons to Overflow	53 gal. / 201 L
Gallons to Operate	42 gal. / 159 L

ELECTRICAL SPECIFICATIONS:

Pump	.80 HP; 5.5 AMP; 110V
Requirement	15 AMP; 110V, separate circuit required protected w/ Class A GFCI

STANDARD EQUIPMENT:

6 Hydrotherapy Jets including:

- 2 Spinning Back Jets
- 4 Directional Jets

Aquatic Quality Features:

- .80 HP Run-Dry Pump
- Bath-Side On/Off Air Button
- Comfort Designed Back Rest
- "Quiet Pad" Anti-Vibration Pump Mount for Quiet Pump Operation
- Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
- 2 Arm Rests
- Integrally Molded Tile Flange
- Color Matched Integral Skirt with Removable Access Panels
- Color Matched Trim and Jets (Select Colors)
- Right or Left Hand Drain
- Durable, Easy to Clean, Lucite® Cast Acrylic Surface
- Available in 8 Standard No-Charge Colors

UL and IAPMO Listed, Factory Tested

Limited 10 Year Warranty

OPTIONAL EQUIPMENT:

- Comfort Pillow--Oval or Rectangle
- Lift & Turn Waste and Overflow
 - Chrome, Polished Brass, Gold, Satin Nickel, Polished Nickel, or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
 - Chrome, Polished Brass, Gold, Satin Nickel, Polished Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- Removable Access Panels (Tub Only)

All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.

**Fax-On-Demand
Document # 1278**

