# cortina® whirlpool bath

mountainous, pristine cortina—Italy's winter playground—serves as fitting inspiration for our cortina®, a whirlpool bath of extraordinary luxury.



Like its namesake, the Cortina® whirlpool bath is a welcome escape a holiday for the senses.

#### features:

- 4 PowerPro® jets
- 4 directionally adjustable AccuPro<sup>™</sup> body and side jets
- Integral seat
- Contoured backrest
- Multi-speed motor
- RapidHeat<sup>™</sup> inline heater
- Chromatherapy™ lighting system capable of 256 colors
- Wave Pulse™ system
- All-in-one electronic control panel
- Water level system
- PrO<sup>™</sup><sub>3</sub> Cleansing System

### cortina® whirlpool bath

model number: EE35

exterior dimensions:

72" long x 72" wide x  $22\frac{1}{4}$ " high

interior dimensions: 51" long x 42" wide

# of Jets/type of Jets:

4 PowerPro® Jets,

4 Body and Side Jets

operating gallons:

100 gallons









# Cortina® Whirlpool Bath

Model: EE35

# **Ordering Information**

Product Code:

EE35 Cortina® Whirlpool Bath Right Hand

- Center Drain Location
- · Accessories / Hardware:

Trim Kit: AccuPro<sup>TM</sup> Jet Rings #P556 Trim Kit: 1 X PowerPro<sup>TM</sup> Jet Rings #M952 Trip-Lever Drain Kit #X559 Rotary Drain Kit, 26" Cable #8730

• Trim Kit Finishes Available:

(827) - Chrome

(898) - Brushed Chrome

(815) - Satin Nickel

(829) - Bright Brass

(805) - Platinum

(826) - Brushed Nickel

(849) - Oil Rubbed Bronze

# 14"x5"\* 14"x5"\* 72" Heater 12" Hx 18" L Service Access 9"-72"

Product Shown: Cortina® Whirlpool Bath Right Hand Shown Model: EE35

#### **Installation Notes**

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

## **Technical Specifications**

#### **Dimensions**

72" L x 72" W x 22-1/4" H (1829 mm) L x (1829 mm) W x (565 mm) H

#### Drain/Overflow

A: 16-3/4" (426 mm) B: 19-1/4" (489 mm)

#### Cutout

70" Dia. Hole

#### **Total Weight**

1293 lb (587 kg) / 36 lb/sq. ft. (176 kg/m<sup>2</sup>)

#### **Operating Gallonage**

100 U.S. Gal. (379 Liters)

#### **Product Weight**

210 lb (95 kg)

#### **Skirt Mounting**

Not Available

#### **Electrical Specifications**


Requires a dedicated GFCI protected separate circuit.


Motor/Pump: 120 VAC, 20 AMP, 60 Hz. RapidHeat $^{TM}$ : 120 VAC, 15 AMP, 60 Hz.


#### **Heater (Standard)**

Requires a dedicated GFCI protected separate circuit.

RapidHeat™: P/N U395000







<sup>\*</sup> Measurements inside unit represent cutout in floor to allow for drain/overflow.