



Ordering Information

Catalog No.	Finish	Volts	Ballast	Lamping
4733	Satin Aluminum, Opal Glass	120V	NA	(1) 60W A19
4734	Satin Aluminum, Opal Glass	120V	NA	(2) 60W A19
4735	Satin Aluminum, Opal Glass	120V	NA	(3) 60W A19

Features

- Housing:** Corrosion resistant .40" aluminum backplate. Wire way holes hemmed (.08" thick)
- Diffuser Assembly:** White hand blown opal glass provides ample and even illumination.
- Lamp:** A-19 60W max. (Frosted lamps recommended).
- Mounting:** Center knock-out pattern for direct mounting to 3" or 4" octagonal outlet boxes.

Mounting

For horizontal or vertical wall mount only.

Electrical

Rated for connection to 60°C building wire.
Lamp Holder: Medium base, porcelain, nickel-plate screw shell.

Labels

UL (Suitable for Damp Locations)

Romex® is a registered trademark of General Cable Industries Inc.

US Patent No.: 5,045,985; 4,327,403

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte company www.lightolier.com
631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
© 2007 Genlyte Group LLC • A0707