

QuestVapco

SURRENDER

Ultra High-Temp
Anti-Seize

SURRENDER

Ultra High-Temp
Anti-Seize

Ultra Antigripante de
Alta-Temperatura

Stops Corrosion

Withstands Extreme Pressure

Temperature Range of -30° to 2200°F

**Decreases Seizure, Pitting,
Galling & Thread Distortion**

CAUTION/PRECAUCIÓN:

KEEP OUT OF REACH OF CHILDREN

SEE ADDITIONAL CAUTIONS ON BACK PANEL

NO SE DEJE AL ALCANCE DE LOS NIÑOS

VEA PRECAUCIONES ADICIONALES EN EL PANEL TRASERO

NET CONTENTS: 14.5 OZ. (411 g)

QuestVapco Corporation
Brenham, TX • St. Louis, MO

Contains no lead or copper.
Non-melting base.

SURRENDER ANTI-SEIZE is three
useful maintenance compounds
in one:

1. A high temperature anti-seize compound from -30°F to +2200°F.
2. A high temperature anti-friction bearing and slide lubricant with high dropping point, extreme pressure high speed capabilities to 350°F and low-speed high temperature dry film lubrication to 1500°F (low RPM bearing applications only).
3. A protective coating for highly corrosive service in high temperature applications from -30°F to +1000°F.

It is well suited for service where water is a problem, is insoluble in polar solvents but miscible at room temperature with all hydrocarbon solvents.

USES:

INDUSTRIAL: For nuts, valves, flanges, studs, threaded fittings, bushings, manifold surfaces, plugs, valve shafts, valve assemblies, gaskets, bolts, conveyors, gear reducers, transmission shafts, fans, blowers, compressor pumps, turbines, etc.
STATIONARY AND MARINE ENGINES: Valve gauges and gaskets, fuel injectors, air starting valves, compressor gauges and piping, cylinder head gaskets and stud assemblies.

TRUCK FLEETS: Cylinder head assemblies, exhaust manifold

and turbo charger fittings, torque rod tubes and pins, brake anchor pins, air cylinder assemblies.

DIRECTIONS FOR USE: Pump in new product until old comes out. Remove old product if possible.

MODO DE EMPLEO: Inyecte producto nueva hasta que la vieja salga. Remueva la producto vieja si es posible.

CAUTION: Keep out of reach of children. Avoid contact with eyes and clothing.

PRECAUCIÓN: No se deje al alcance de los niños. Evite el contacto con ojos y ropa.

CONTAINS (CAS#): Hydrotreated Naphthenic Petroleum Distillate (64742-52-5), Aluminum (7429-90-5), Lithium Stearate (4485-12-5).

NLGI GRADE: 2

HMIS Ratings: Health - 1, Flammability - 1, Reactivity - 0, Personal - A.

Made in USA

600005056



ITEM L63900001-CART