

# INSTALLATION INSTRUCTIONS (USA only)

MODELS DSKS433 AND DSKS333 MUST BE INSTALLED WITH CONTROL PANEL AT BOTTOM IN ORDER TO OPERATE ADEQUATELY.

## BEFORE YOU BEGIN

Read these instructions completely and carefully.

- **IMPORTANT** - Save these instructions for local inspector's use.
- **IMPORTANT** - Observe all governing codes and ordinances.
- **Note to Installer** - Be sure to leave these instructions with the customer.
- **Note to Customer** - Keep these instructions with your Use and Care Book for future reference.
- Before the old dryer is removed from service or discarded, remove the dryer door.
- Service information and the wiring diagram are located in the control console.
- Do not allow children on or in the appliance. Close supervision of children is necessary when the appliance is used near children.
- Install the dryer where the temperature is above 50°F for satisfactory operation of the dryer control system.

## ⚠️ WARNING RISK OF FIRE

- To reduce the risk of severe injury or death, follow all installation instructions.
- Clothes dryer installation must be performed by a qualified installer.
- Install the clothes dryer according to these instructions and in accordance with local codes.
- This dryer must be exhausted to the outdoors.
- Use only 4" rigid metal ducting for exhausting the clothes dryer to the outdoors.
- **DO NOT** install a clothes dryer with flexible plastic ducting materials. If flexible metal (semi-rigid or foil-type) duct is installed, it must be UL listed and installed in accordance with the instructions found in "Connecting The Dryer To House Vent" on page 4 of this manual. Flexible venting materials are known to collapse, be easily crushed, and trap lint. These conditions will obstruct dryer airflow and increase the risk of fire.
- Do not install or store this appliance in any location where it could be exposed to water and or weather.
- Save these instructions. (Installers: Be sure to leave these instructions with the customer).

## DETERMINE ELECTRICAL REQUIREMENTS FOR YOUR DRYER MODEL


- This dryer must be connected to an individual branch circuit of proper voltage and frequency as specified on Rating Plate (located inside dryer door) with no other appliances or fixtures attached.

EXCEPTION:

- A 120V receptacle is located on the back on the dryer and is available only for use with a washer that is affixed to the dryer with a WDF-85 kit. It may not be used for any other appliance or any conditions other than slated above (208 & 240V models only).
- Branch circuit must be protected by the required time-delay fuses or circuit breakers 208V or 240V installation - 30 amps 120V installation 15 or 20 amps.
- The electrical installation must conform to the national and local codes.

**208V AND 240V MODELS ARE NOT APPROVED FOR 120 V INSTALLATION.**

### TOOLS YOU WILL NEED



### STACKING KITS FOR DRYERS

(comes with individual installation instructions)


- Over washer
  - Use Wall Mount Kit WMK-35 or
  - Stack Rack DSDR24 or
  - Stack Rack DSR-24
- For alcove and closet depth and width requirements see specific kit instructions
- All stacking kits are available from your local sales outlet.

### MATERIALS YOU WILL NEED



### UNPACKING AND PREPARING FOR INSTALLATION

- Prepare the area and exhaust for installation of new dryer.
- Check and ensure the existing external exhaust is clean and meets attached installation specifications.
- Remove the literature and accessories bag from the dryer drum. Place the literature in a convenient place.
- Using foam pads from dryer carton, turn dryer upside down as shown.
- Install knobs. For location, refer to "Use and Care" Book.
- Dryer is now ready to be mounted above washer using accessory kit.
- Remove the foam shipping pads from under dryer.
- Move the dryer to the desired location.
- Follow the steps in the following pages to connect the dryer to the external exhaust and power supply.



# ELECTRICAL CONNECTION DETAILS

## OBSERVE ALL GOVERNING CODES AND ORDINANCES

### GROUNDING INSTRUCTIONS

- The operating voltage (Volts), Amperage (Amps) and Frequency (Hz) of this dryer are indicated on the Rating Plate located to the right of the loading port.
- Connect this dryer to a circuit corresponding to that indicated on rating plate and protected by fuses or a circuit breaker in accordance with local codes.
- Use a power supply cord marked for use with clothes dryer.
- For 208V and 240V models, use a power supply cord kit marked for use with clothes dryers.

#### DO NOT USE EXTENSION CORD WITH THIS APPLIANCE

For alternate 208V or 240V power supply hook-up, proceed as follows:

- Remove rear access panel.
- Connect supply wire leads to terminal block as shown on sketch below, depending on type of installation.

**WARNING:** Appliance grounded to neutral conductor through a link. If used in a mobile home or if local codes do not permit grounding through neutral, a 4-conductor cord or cable assembly for use with clothes dryers must be used with the following specifications: Type St. Cable, 125/250 Min Volt, 30 Amp with closed-loop terminals and secured with a UL recognized strain relief. See manufacturer's instructions

- Make sure screws on terminal block are tight.

This appliance must be grounded. In the event of malfunction or breakdown, grounding will reduce the risk of electric shock by providing a path of least resistance for electrical current.


**WARNING:** Improper connection of the equipment grounding conductor can result in a risk of electric shock. Check with a qualified electrician or serviceman if you are in doubt as to whether the appliance is properly grounded.

Do not modify the plug provided with the appliance - if it will not fit the outlet, have a proper outlet installed by a qualified electrician.

### FOR THREE-WIRE SUPPLY (208V & 240V MODELS)

- Connect two (2) HOT lines to outer screws (L1 and L2) of terminal block.
- Connect Neutral line to center screw (N) of terminal block.

POWER SUPPLY CORD 3#10  
AWG MINIMUM COPPER  
CONDUCTORS  
30 AMP, 240V, WITH  
TYPE UL RECOGNIZED  
MINIMUM RATED 90°C




INSIDE TOP VIEW OF DRYER

208 OR 240  
VOLT OPERATION  
120/208 OR 120/240  
VOLT SUPPLY  
(USE ONLY  
30 AMP FUSES)

### FOR FOUR-WIRE SUPPLY (208V & 240V MODELS)

- Remove ground strap and discard. Rescrew green grounding screw in place.
- Connect two (2) HOT lines to outer screws (L1 and L2) of terminal block.
- Connect NEUTRAL line to center screw (N) of terminal block.
- Attach ground wire of power supply to green grounding screw beside terminal block.

POWER SUPPLY CORD 4 #10  
AWG MINIMUM COPPER  
CONDUCTORS, 30 AMP, 240V,  
WITH CLOSED-LOOP TERMINALS  
TYPE UL RECOGNIZED  
MINIMUM RATED 90°C.



REMOVE GROUND  
STRAP AND DISCARD  
208 OR 240  
VOLT OPERATION  
120/208 OR 120/240  
VOLT SUPPLY  
(USE ONLY  
30 AMP FUSES)

#### FOR PERSONAL SAFETY, THIS APPLIANCE MUST BE PROPERLY GROUNDED.

- Properly strain relief the cord set or cable to the cable entry hole with UL recognized strain relief.
- Make sure cordset or the cable is away from the rotating drum.
- Replace access panel.


#### FOR PERSONAL SAFETY, THIS APPLIANCE MUST BE PROPERLY GROUNDED.

- Properly strain relief the cord set or cable to the cable entry hole with UL recognized strain relief.
- Make sure cordset or the cable is away from the rotating drum.
- Replace access panel.

### 3 WIRE RECEPTACLE (10-30R)




Typical 30 amp receptacle for use where local codes permit use of flexible type power supply cord (pigtail).



### 4-WIRE RECEPTACLE (14-30R)

Typical 30 amp receptacle for use where local codes permit use of flexible type power supply cord (pigtail).



### 4-CONDUCTOR CORD ASSEMBLY ( Type ST Cable)

Typical 30 amp cord assembly for use where local codes do not permit grounding through neutral.

## EXHAUST INFORMATION

**⚠ WARNING - IN CANADA AND IN THE UNITED STATES, THE REQUIRED EXHAUST DUCT DIAMETER IS 4 IN (102mm). DO NOT USE DUCT LONGER THAN SPECIFIED IN THE EXHAUST LENGTH TABLE.**

Using exhaust longer than specified length will:

- Increase the drying times and the energy cost.
- Reduce the dryer life.
- Accumulate lint, creating a potential fire hazard.

The correct exhaust installation is **YOUR RESPONSIBILITY**. Problems due to incorrect installation are not covered by the warranty.

Remove and discard existing plastic or metal foil transition duct and replace with UL listed transition duct.

The MAXIMUM ALLOWABLE duct length and number of bends of the exhaust system depends upon the type of duct, number of turns, the type of exhaust hood (wall cap), and all conditions noted below. The maximum duct length for rigid metal duct is shown in the table on the next page.

## EXHAUST SYSTEM CHECK LIST

### HOOD OR WALL CAP

- Terminate in a manner to prevent back drafts or entry of birds or other wildlife.
- Termination should present minimal resistance to the exhaust air flow and should require little or no maintenance to prevent clogging.
- **Never** install a screen in or over the exhaust duct. This could cause lint build up.
- Wall caps must be installed at least 12 in. above ground level or any other obstruction with the opening pointed down.

### SEPARATION OF TURNS

For best performance, separate all turns by at least 4 ft. of straight duct, including distance between last turn and exhaust hood.

### TURNS OTHER THAN 90°

- One turn of 45° or less may be ignored.
- Two 45° turns should be treated as one 90° turn.
- Each turn over 45° should be treated as one 90° turn.

### SEALING OF JOINTS

- All joints should be tight to avoid leaks. The male end of each section of duct must point away from the dryer.
- Do not assemble the ductwork with fasteners that extend into the duct. They will serve as a collection point for lint.
- Duct joints can be made air and moisture-tight by wrapping the overlapped joints with duct tape.
- Horizontal runs should slope down toward the outdoors ½ inch per foot

### INSULATION

Duct work that runs through an unheated area or is near air conditioning should be insulated to reduce condensation and lint build-up.

## EXHAUST CONNECTION

**⚠ WARNING - TO REDUCE THE RISK OF FIRE OR PERSONAL INJURY:**

- This clothes dryer must be exhausted to the outdoors.
- Use only 4" rigid metal ducting for the home exhaust duct.
- Use only 4" rigid metal or UL-listed flexible metal (semi-rigid or foil-type) duct to connect the dryer to the home exhaust duct. It must be installed in accordance with the instructions found in "Connecting The Dryer To House Vent" on page 4 of this manual.
- Do not terminate exhaust in a chimney, a wall, a ceiling, gas vent, crawl space, attic, under an enclosed floor, or in any other concealed space of a building. The accumulated lint could create a fire hazard.
- Never terminate the exhaust into a common duct with a kitchen exhaust system. A combination of grease and lint creates a potential fire hazard.
- Do not use duct longer than specified in the exhaust length table. Longer ducts can accumulate lint, creating a potential fire hazard.
- Never install a screen in or over the exhaust duct. This will cause lint to accumulate, creating a potential fire hazard.
- Do not assemble ductwork with any fasteners that extend into the duct. These fasteners can accumulate lint, creating a potential fire hazard.
- Do not obstruct incoming or exhausted air.
- Provide an access for inspection and cleaning of the exhaust system, especially at turns and joints. Exhaust system shall be inspected and cleaned at least once a year.

## ALTERNATE EXHAUST DIRECTIONS

### IF YOUR DRYER COMES WITH REAR EXHAUST, TO CHANGE TO SIDE OR DOWN EXHAUST:


Remove access panel at back of dryer to gain access to internal ducts.  
Disconnect duct exhaust from blower housing (remove tape securing duct).

### FOR SIDE EXHAUST:

Remove desired knockout plate (either right or left side).  
Cut a 115 mm (4 ½") length of 100 mm (4") dia rigid duct as shown (remove burrs from cut edge).  
Attach this extension duct to blower housing duct.  
Attach a 90° elbow facing desired opening.  
Attach a section of 100 mm (4") dia, rigid duct to elbow to protrude through side of cabinet.  
Seal all joints with duct tape.  
Reinstall rear access panel.

### FOR BOTTOM EXHAUST:

Remove cover plate at bottom of dryer.  
Install a 90° elbow.  
Seal all joints with duct tape.  
Reinstall rear access panel.  
Place cover plate (removed from bottom of dryer) over rear exhaust opening.



It is important to replace the ground clip after cutting the exhaust duct, (on rear exhaust model).

### IF YOUR DRYER COMES WITH TOP EXHAUSTING, TO CHANGE TO SIDE OR REAR EXHAUST:

Remove rear access panel.  
Disconnect retaining plate & 90° elbow by removing mounting screw from the chassis & remove tape securing elbow to blower housing.  
Remove cover plate from rear access panel and place over top exhaust opening.

### FOR SIDE EXHAUST:

Remove desired knockout plate (either right or left side).  
Cut a 115 mm (4 ½") length of 100 mm (4") dia, rigid duct as shown (remove burrs from cut edge).  
Attach this extension duct to blower housing duct.  
Attach the 90° elbow facing desired opening.  
Attach a section of 100 mm (4") dia, rigid duct to elbow to protrude thru side of cabinet.  
Seal all joints with duct tape.  
Reinstall rear access panel.

### FOR REAR EXHAUST:

Cut a 295 mm (11 ½") length of 100 mm (4") dia, rigid duct as shown (remove burrs from cutting edge).  
Attach this extension duct to blower housing.  
Seal all joints with duct tape.  
Reinstall rear access panel.

# EXHAUST LENGTH CALCULATION

## RIGID (Preferred)


Parts are available from your local service organization:

WX8X63 4"X1' Duct    WX8X51 Elbow  
 WX8X64 4"X2' Duct    WX8X59 Aluminum hood


### RECOMMENDED MAXIMUM LENGTH

#### Exhaust Hood Types

#### Recommended



#### Use only for short run installations



No. of 90° Elbows	Rigid Metal	Rigid Metal
0	14 m (46 ft)	11 m (37 ft)
1	11 m (38 ft)	9 m (30 ft)
2	9 m (31 ft)	6.5 m (22 ft)
3	7 m (24 ft)	4.5 m (15 ft)

### FLEXIBLE

Total length of flexible metal duct shall not exceed 8 ft (2.4 m). The following kit is available from you local service organization:  
 Kit WX08X10077 - 4" dia. flexible metal (semi-rigid) UL-listed transition duct (includes 2 elbows).

# ALCOVE OR CLOSET INSTALLATION

If your dryer is approved for installation in an alcove or closet, it will be stated on a label on the dryer back. The installation must conform to the following specifications;

- **WARNING: TO PREVENT LARGE AMOUNTS OF LINT AND MOISTURE FROM ACCUMULATING AND TO MAINTAIN DRYER EFFICIENCY, THIS MACHINE MUST BE EXHAUSTED OUTDOORS.**
- Minimum clearances between dryer cabinet and adjacent walls or other surfaces are:

	Alcove	Closet
Sides	0"	1"
Top	1"	1"
Front	-	3"
Rear	3"	3"

- Closet doors must be louvered or otherwise ventilated and must contain at least 60 square inches of area equally distributed. If this closet contains both a washer and a dryer, doors must contain at least 120 square inches of open area equally distributed.

**NOTE: The clearances stated above are minimums. Consideration must be given to the type accessory kit used with dryer. Refer to the specific kit instruction for details.**

# CONNECTING THE DRYER TO HOUSE VENT

## RIGID METAL TRANSITION DUCT

- For best drying performance, a rigid metal transition duct is recommended.
- Rigid metal transitions ducts reduce the risk of crushing and kinking.

## UL-LISTED FLEXIBLE METAL (SEMI-RIGID) TRANSITION DUCT

- If rigid metal duct cannot be used, then UL-listed flexible metal (semi-rigid) ducting can be used (Kit WX08X10077).
- Never install flexible metal duct in walls, ceilings, floors or other enclosed spaces.
- Total length of flexible metal duct should not exceed 8 feet (2.4m).
- For many applications, installing elbows at both the dryer and the wall is highly recommended (see illustrations below). Elbows allow the dryer to sit close to the wall without kinking and or crushing the transition duct, maximizing drying performance.
- Avoid resting the duct on sharp objects.

## UL-LISTED FLEXIBLE METAL (FOIL-TYPE) TRANSITION DUCT

- In special installations, it may be necessary to connect the dryer to the house vent using a flexible metal (foil-type) duct. A UL-listed flexible metal (foil-type) duct may be used **ONLY** in installations where rigid metal or flexible metal (semi-rigid) ducting cannot be used **AND** where a 4" diameter can be maintained throughout the entire length of the transition duct.
- In Canada and the United States, only the flexible metal (foil-type) ducts that comply with the "Outline for Clothes Dryer Transition Duct Subject 2158A" shall be used.
- Never install flexible metal duct in walls, ceilings, floors or other enclosed spaces.
- Total length of flexible metal duct should not exceed 8 feet (2.4m).
- Avoid resting the duct on sharp objects.
- For best drying performance:
  1. Slide one end of the duct over the clothes dryer outlet pipe.
  2. Secure the duct with a clamp.
  3. With the dryer in its permanent position, extend the duct to its full length. Allow 2" of duct to overlap the exhaust pipe. Cut off and remove excess duct. Keep the duct as straight as possible for maximum airflow.
  4. Secure the duct to the exhaust pipe with the other clamp.

### NOTE TO INSTALLER - ...AFTER INSTALLATION CHECK THE FOLLOWING

- EXHAUST DUCT - must meet specs on Page 3. No excessive turns. No kinks or obstructions to air flow.
- EXHAUST HOOD - should work freely and open downward.
- GROUNDING - Dryer must be properly grounded to conform to local codes and ordinance requirements.
- OPERATION - turn dryer on and check for heat.
- HAND CUSTOMER THE USE AND CARE BOOK - Give instructions on operating the dryer - answer any questions.
- GIVE THESE INSTALLATION INSTRUCTIONS to the customer.

### WHEN INSTALLED IN MANUFACTURED (MOBILE) HOMES -

Dryer must be exhausted to the outside. Exhaust **MUST NOT** be terminated beneath mobile home. Exhaust material **MUST NOT** support combustion. Installation **MUST** conform to Manufactured Home Construction & Safety Standard, Title 24 CFR, Part 32-80 or when such standard is not applicable, the American National Standard of Mobile Homes, ANSI/NFRA No. 501B-1977.

For electrical connection, see "Connecting dryer using 4 wire connection".

#### USE OF CASTERS (120V PORTABLE MODELS ONLY)

• For a portable installation screw casters into the holes on the bottom of the dryer. Refer to the "Installation Instructions for caster assembly" sheet to install casters.