

# IPSO®

simply

On-Premises Laundry

*On-premises laundries face enough daily challenges, wrestling with complicated, inefficient equipment shouldn't be one of them. IPSO's HF model washer-extractors combine proven designs with user-friendly controls to streamline the laundry process. Our goal is building equipment that's simple to own and even more simple to operate.*

## Simplifying Ownership

**VERSATILE.** The PS40 microprocessor offers managers the highest level of control to set spin speeds and water levels, while a simple design ensures employees are quickly trained on its operation. It comes with 10 preprogrammed cycles and room to customize 30 additional cycles. Programming easily is accomplished by uploading from a PC through an infrared connection.

**EFFICIENT.** With a maximum extract of 475 G-Force, the HF significantly reduces drying time — in some cases, by up to 80%. As a result, operations benefit from lower utility consumption.

**RUGGED RELIABILITY.** A heavy-duty steel frame, with a minimum of welds, provides one of the most stable bases in the market. That translates into years of worry-free operation. In addition, three layers of paint protect the frame from corrosion, while heavy-duty bearings and a rugged housing ensure longevity.

**PEACE OF MIND.** Our commitment to you comes with a 3/5-year limited parts warranty.

**WASHABILITY.** While the HF is designed to increase productivity and efficiency, managers don't have to sacrifice quality. IPSO washer-extractors deliver superior consistent finished results.



**TIME SAVINGS.** The HF's automatic supply injection system — which supports up to 12 pumps — eliminates the need for staff to manually add chemicals. This saves time and allows them to concentrate on other laundry tasks. In addition, for laundries utilizing finishing equipment, the high extract speed of the HF allows pieces to go directly from the washer to ironers with no drying necessary.

**THE BOTTOM LINE.** We believe the efficiency in design and operation of our washer-extractors combined with the features of our intuitive controls will have the ultimate impact on your laundry's productivity and bottom line. Put simply, IPSO gets results.

HF035 - 35 lb Washer-Extractor  
HF045 - 45 lb Washer-Extractor  
HF055 - 55 lb Washer-Extractor  
HF075 - 75 lb Washer-Extractor  
HF100 - 100 lb Washer-Extractor  
HF135 - 135 lb Washer-Extractor  
HF165 - 165 lb Washer-Extractor



# HF Series Washer-Extractor

# HF Series Washer-Extractor Specifications

	HF035	HF045	HF055	HF075	HF100	HF135	HF165
Capacity - lb (kg)	35 (15)	45 (18.5)	55 (23.4)	75 (30.4)	100 (45.5)	135 (57.5)	165 (73)
Height - in (mm)	51 5/8" (1310)	51 5/8" (1310)	59 1/4" (1276)	60 1/4" (1530)	75 9/16" (1919)	75 9/16" (1919)	85 1/16" (2178)
Width - in (mm)	33 1/2" (850)	33 1/2" (850)	35 7/16" (902)	41 3/4" (1060)	47 1/4" (1200)	47 1/4" (1200)	51 1/16" (1553)
Depth - in (mm)	35 13/16" (910)	40 5/8" (1030)	39 1/2" (1003)	48 1/4" (1226)	52 9/16" (1335)	59 1/16" (1500)	63 3/4" (1619)
Door Opening - in (mm)	16" (400)	16" (400)	16" (400)	16" (400)	16" (400)	16" (400)	24 1/2" (622)
Net Weight - lb (kg)	764 (347)	847 (385)	1257 (571)	1907 (866)	3344 (1518)	3619 (1643)	4630 (2102)
Crated Weight - lb (kg)	831 (377)	915 (415)	1389 (630)	2194 (996)	3741 (1698)	4017 (1824)	5181 (2352)
Cylinder Dimensions							
Diameter - in (mm)	27" (680)	27" (680)	29 1/2" (750)	33 7/16" (850)	38 5/8" (904)	38 9/16" (903)	43 1/8" (1092)
Depth - in (mm)	16" (400)	19 3/4" (500)	20 7/8" (530)	21 1/8" (537)	23 3/16" (590)	30 1/2" (775)	30 1/2" (775)
Volume - cu.ft. (liters)	5.3 (150)	6.54 (185)	8.27 (234)	10.76 (304)	15.9 (450)	20.31 (575)	25.78 (730)
Cylinder Speed							
Wash - RPM	10-50	10-50	10-50	10-50	10-50	10-50	10-50
Extract - RPM	250-1000	1000	1000	1000	800	800	750
G-Force - RPM	380	380	419	475	350	350	350
Drain Size - in (mm)	3" (76)	3" (76)	3" (76)	3" (76)	3" (76)	3" (76)	3" (76)
Water Inlet - (std/opt)	2/3	2/3	2/3	2/3	2/3	2/3	2/3
Voltage/Hz/Phase							
Circuit Breaker - FLA							
(N)	440-480/50-60/3ph 20	440-480/50-60/3ph 20	440-480/50-60/3ph 20	440-480/50-60/3ph 20	440-480/50-60/3ph 30	440-480/50-60/3ph 30	440-480/50-60/3ph 40
(P)	380-415/50-60/3ph 20	380-415/50-60/3ph 20	380-415/50-60/3ph 20	380-415/50-60/3ph 20	380-415/50-60/3ph 30	380-415/50-60/3ph 30	380-415/50-60/3ph 40
(Q)	200-240/50-60/3ph 20	200-240/50-60/3ph 20	200-240/50-60/3ph 20	200-240/50-60/3ph 20	200-240/50-60/3ph 30	200-240/50-60/3ph 50	200-240/50-60/3ph 80
(X)	200-240/50-60/1-3 20	200-240/50-60/1-3 20	200-240/50-60/1-3 20	200-240/50-60/1-3 20	200-240/50-60/1-3 N/A	200-240/50-60/1-3 N/A	200-240/50-60/1-3 N/A
Agency Approvals	ETL	ETL	ETL	ETL	ETL	ETL	ETL

Due to continuous improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant. Features and certifications may vary by model.

©Copyright 2007 Alliance Laundry Systems LLC

Printed in the U.S.A.

 Printed on paper manufactured with virgin pulp from certified sources and a minimum of 10% post-consumer recovered fiber.

## Control Options



**PS40** Microprocessor

Questions? Contact us at:  
 1 800 USA IPSO or [www.ipsousa.com](http://www.ipsousa.com)  
 1 800 (872-4776)

