

**On-Premises
Washers & Dryers**

UniMac

**Commercial Topload Washer
Commercial Frontload Washer
Commercial Stack Washer/Dryer
Commercial Dryer
Commercial Stack Dryer**



Expert Solutions from the Laundry Experts

UniMac

Dryers

At UniMac, washers and dryers are considered more than just laundry equipment. They are key players in the success of on-premise laundry facilities and as such, must continuously achieve high levels of efficiency, quality and durability. UniMac has always maintained a standard of excellence in laundry equipment manufacturing that is recognized around the world. With over 50 years of engineering expertise you can be assured that you are getting the best washers and dryers on the market that will meet your needs now and in the future.



Extra Large 7.0 cu. ft. Capacity

UniMac's extra large capacity drying cylinder needs very little space yet easily handles sizeable wash loads. Smooth baffles tumble loads freely for maximum dry air movement.



Stack Washer/Dryers



Floor Space

By stacking the dryer on top of the washer, you gain a large amount of floor space. Dream of the possibilities for how you could use the extra space. These units are the **ultimate space saver**. You can place laundry equipment in places that were never before possible.

The utility connections are identical to those used with residential style equipment. There is no extra work or floor space required.

Large Door Opening

For ease in loading and unloading, UniMac designed its dryer with a 2.06 sq. ft. door opening, one of the **largest in the industry**.



Front Serviceability

UniMac's two piece front panel increases ease of service which can **save time** and expense. Motor, blower, heating element, gas valve and thermostats can be serviced through lower panel without disconnecting door switch.

Frontload Washers



Utility Cost Savings

Utility costs are a big part of your laundry dollar. UniMac can help you reduce your costs with our energy efficient frontload washers.

The frontload washer is **ENERGY STAR® qualified** and excels in energy efficiency. The listing was earned by our washer's low usage of hot water,

low motor energy consumption and high moisture removal. The washer's **super high spin speed** reduces drying time and energy costs.

You could **save hundreds of dollars** per year on electricity, gas, water and sewer fees. These savings are due to **less hot water**, less overall water consumption and shorter drying times.

Saves Time

If you believe **time is money**, then you will be excited to experience how UniMac's frontload washers cut time from every wash and dry cycle. The super high **spin speed of 1000 rpm** removes much more water than topload washers. This greatly **reduces the drying time**. In fact, our tests show as much as 30%!

Front Controls and Supply Dispenser

The unique front control design allows for **convenient storage** on top or it can easily fit under a counter.

Add your detergent, bleach or softener with the automatic front mount supply dispenser, **walk away** and the washer will take care of the rest.



Liquid Supply Injector

Some installations may require a connection to an automated liquid supply system. There are two supply signals and two injection ports included within the washer.

Heavy Duty See-through Door

UniMac has constructed a heavy duty door with 10" stainless steel hinges that are capable of **swinging 180°**, allowing for easy loading and unloading. The see-through door allows users to view the reversing wash action that gets linens their cleanest.



Topload Washers



Rugged Suspension System

UniMac incorporates a liquid-filled balance ring at the top of the tub along with a 7 point suspension system to handle **bulky loads with ease**.

Front Serviceability

UniMac engineered its washer to easily handle large loads while occupying minimal floor space. Our **100% front serviceable** design eliminates the need for extra floor space around the unit making it ideal for small or large laundry rooms. Simple removal of front panel or control hood provides easy access to all major components from installed position which can save you time and money.



Durable Stainless Steel Tub

To keep linens looking their best longer – UniMac's washer features a stainless steel tub that will actually become smoother with each use, so it won't pill, fray or snag fabric. In fact, stainless steel won't corrode, chip, crack or pit under normal use and it is extremely rust resistant and that's why we provide a **lifetime warranty**.



Agitator

For superior washability, UniMac's wavy vane agitator offers a 210° agitation stroke that delivers maximum side-to-side, top-to-bottom washing action to **get linens their cleanest**.



Specifications

Washer	Topload UWT021	Frontload FTU91
Width (in/mm)	25.63" (650 mm)	26.87" (683 mm)
Depth (in/mm)	28" (711 mm)	28" (711 mm)
Height (in/mm)	43" (1092 mm)	42.75" (1086 mm)
Height to Work Surface (in/mm)	36" (914 mm)	41.2" (1046 mm)
Operation	Manual control	Pull-Start
Basket Volume	2.52 cu. ft. (71 liters)	2.84 cu. ft. (80 liters)
Spin Speed	High Speed 710 rpm Low Speed 474 rpm	500 rpm, 650 rpm, 1000 rpm
Water Temperatures	Hot, Warm and Cold	Hot/Cold, Warm/Warm Warm/Cold, Cold/Cold
Cycles	Normal, Permanent Press or Delicate	Normal, Permanent Press or Delicate
Cycle Time	28.75 minutes plus fill time	N/A
Water Pressure	Pressure fill 20 to 120 p.s.i. (1.4/8.3 Bar)	Pressure full 20 to 120 p.s.i. (1.4/8.3 Bar)
Out-of Balance Switch	Not required	N/A
Cycle Cue Lights	Yes	N/A
Top and Lid Finish	Porcelain	Porcelain
Colors	White	White
Motor	2-speed, 1/2 HP reversing for 1725 or 1140 rpm	Multi-speed 3/4 HP
Electrical Specifications	120/60/1-15 amp	120/60/1-15 amp
Net Weight (Approx.)	180 lb (82 kg)	225 lb (102 kg)
Dom. Shipping Weight (Approx.)	200 lb (91 kg)	235 lb (106 kg)
Agency Approvals	UL	UL, cULus

Dryers	Single Rear Control UDE007 (Electric) UDG009 (Gas)	Single Front Control FEU17 (Electric) FGU17 (Gas)	Stack USE007 (Electric) USG009 (Gas)
Width (in/mm)	26.88" (683 mm)	26.88" (683 mm)	26.88" (683 mm)
Depth (in/mm)	28" (711 mm)	28" (711 mm)	28" (711 mm)
Height (in/mm)	43" (1092 mm)	43" (1092 mm)	76.5" (1950 mm)
Height to Work Surface (in/mm)	36" (914 mm)	43" (1092 mm)	N/A
Cylinder Volume	7.0 cu. ft. (201 liters)	7.0 cu. ft. (201 liters)	7.0 cu. ft. (201 liters)
Colors	White	White	White
Motor HP	60 Hz: 1/3 HP, 5.5 amp	60 Hz: 1/3 HP, 5.5 amp	60 Hz: 1/3 HP, 5.5 amp
Motor rpm	60 Hz: 1725 rpm	60 Hz: 1725 rpm	60 Hz: 1725 rpm
Btu Per Hour	25,000 (6,300 kcal)	25,000 (6,300 kcal)	25,000 (6,300 kcal)
Electrical Requirements	Gas: 120/60/1 - 15 amp Electric: 120/240/60/1 - 30 amp 120/208/60/1 - 30 amp	Gas: 120/60/1 - 15 amp Electric: 120/240/60/1 - 30 amp 120/208/60/1 - 30 amp	Gas: 120/60/1 - 15 amp Electric: 120/240/60/1 - 30 amp 120/208/60/1 - 30 amp
Heating Element (Electric)	60 Hz: 5350W, 240V Also 4750W, 208V	60 Hz: 5350W, 240V Also 4750W, 208V	60 Hz: 5350W, 240V Also 4750W, 208V
Type of Gas (Gas models only)	Factory-equipped for natural/mixed gas Convertible to LP gas**	Factory-equipped for natural/mixed gas Convertible to LP gas**	Factory-equipped for natural/mixed gas Convertible to LP gas**
Utility Connections	3/8" NPT (9.5 mm)	3/8" NPT (9.5 mm)	3/8" NPT (9.5 mm)
Air Outlet Diameter	4" (102 mm)	4" (102 mm)	4" (102 mm)
Exhaust Airflow*	220 (105 liters/sec.)	220 (105 liters/sec.)	220 (105 liters/sec.)
Net Weight (Approx.)	Gas: 135 lb (61 kg) Electric: 130 lb (59 kg)	Gas: 155 lb (70 kg) Electric: 150 lb (68 kg)	Gas: 275 lb (125 kg) Electric: 265 lb (120 kg)
Dom. Shipping Weight (Approx.)	Gas: 145 lb (65 kg) Electric: 140 lb (63 kg)	Gas: 165 lb (75 kg) Electric: 160 lb (73 kg)	Gas: 290 lb (132 kg) Electric: 280 lb (127 kg)
Agency Approvals	UL, CSA	UL, CSA	UL, CSA

Strong Limited Parts Warranty

UniMac proudly offers the following limited warranties on its topload washer:
Through Three Years* – any part on the entire machine.
Through Five Years* – the transmission assembly.
Through Lifetime* – the stainless steel wash tub.

UniMac proudly offers the following limited warranties on its frontload washer:
Through One Year* – any part on the entire machine.
Through One Year* – the transmission assembly.
Through Lifetime* – the stainless steel wash tub.

UniMac proudly offers the following limited warranty on its commercial dryer:
Through Three Years* – any part on the entire machine.

*Parts only, labor not included. See UniMac Warranty Bond for specifics.



Stack Washer/Dryer Unit Specifications

LTU97 (Electric) LTU99 (Gas)	
Width (in/mm)	26.87" (683mm)
Depth (in/mm)	28" (711 mm)
Height (in/mm)	74.5" (1890 mm)
Net Weight (Approx.)	Gas: 375 lb (170 kg) Electric: 370 lb (168 kg)
Dom. Shipping Weight (Approx.)	Gas: 390 lb (177 kg) Electric: 385 lb (174 kg)
Agency Approvals	UL, CSA

** Measured at point of exit from dryer. Maximum exhaust static back pressure: 60 Hz: 0.6" W.C. Gas models are certified by CSA International; electric models are Underwriters Laboratories certified.

Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems at all Alliance Laundry Systems facilities have been awarded ISO 9001 certification. Features and certifications may vary by model.

IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel. Any approvals may vary depending on configuration. Consult factory for details.

©Copyright 2003 Alliance Laundry Systems LLC



AU03-210

www.uniwash.com

Alliance Laundry Systems
Shepard Street, Ripon, WI 54971 Telephone: 1-800-587-5458

