

# Ice-O-Matic®

## MFI2406 - Remote Low Side Flake Ice Maker



MFI2406 on B100

### Features

- High capacity 42" (1067 mm) wide design.
- Remote low side unit
- Produces up to 2365 lbs (1072kg) of ice per day.
- *Load Monitoring System* constantly checks workload on gearbox — shutting down system before a problem develops and preventing costly repairs.
- Water sensor eliminates low or no water failures and cannot be affected by adverse water conditions.
- Rugged stainless steel evaporator and auger ensures reliability.
- Industrial-grade roller bearings and heavy duty gearbox provide years of trouble free service.

### Options & Accessories

Water Filters			
Ice Machine Model	Manifold		Inline
	System	Replacement	System
MFI2406	IFQ2	IOMQ (2)	N/A

### Ice Maker Warranty

Every Ice-O-Matic ice maker is backed by a warranty that provides both parts and labor coverage.

#### Parts & Labor

- Three years **Parts and Labor**.
- Five years **Parts on compressor**.

### Ice Form



### Bin Chart

Kits for Combining Wider Bins with Smaller Models

Ice Storage Bins									
Model No.	B25	B40	B42	B55	B100	B120	B150	B170	
Capacity	255 lbs (116 kg)	365 lbs (165 kg)	374 lbs (170 kg)	556 lbs (252 kg)	927 lbs (420 kg)	1193 lbs (541 kg)	1499 lbs (679 kg)	1866 lbs (846 kg)	
Width	30 in (762 mm)	30 in (762 mm)	22 in (559 mm)	30 in (762 mm)	48 in (1219 mm)	48 in (1219 mm)	60 in (1524 mm)	60 in (1524 mm)	
Kits	MFI12406LS	N/A	N/A	N/A	N/A	KBT26	KBT26	N/A	N/A

\*MFI Flakers are available internationally only.  
\*See Ice-O-Matic Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.





MFI2406 Remote Low Side Flake Ice Maker

# Ice-O-Matic®

MF12406 Remote Low Side Flake Ice Maker

## Low Side Remote

- A. Ice maker potable water in, 3/8" Male Flare.
- B. Drain, 3/4" FPT.
- C. Hole for electrical connection.
- D. Remote liquid inlet, 1/2" (12.7 mm) O.D.
- E. Remote suction connection 7/8" (22.23 mm) O.D.



Rear View

## Operating Requirements

	Minimum	Maximum
Ambient Temp. Range Air	50°F (10°C)	100°F (38°C)
Water Temp.	40°F (4.4°C)	100°F (38°C)
Water Pressure	20 PSIG (1.4 BAR)	120 psig (8.3 BAR)

Note: Requires a R404 refrigeration system of 12,000 Btu/h

## Dimensions

All Models	
W x D x H (inches)	42 x 24 x 27
W x D x H (mm)	1067 x 610 x 686

## Specifications

Model Number	Cond. Unit	Ice Production per 24hrs		Water Usage gallons per 100 lbs of Ice 90°F air/70°F water		kWH Used per 100 lbs of ice @ 90°F air/70°F water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Approx. BTUs per hour
		70°F air/50°F water lbs (kg)	90°F air/70°F water lbs (kg)	Potable	Condenser					
MF12406LS	Remote Low Side	2,365 (1,072)	2,000 (907)	12.0		3.26	208-230/60/1	2.7	15	12,000

### NOTES:

Number of Wires: 3 (including ground)  
 Approx. Shipping Weight lbs (kg): MF12406LS 255 (115)  
 Refrigerant Type: R404A