

# WH95TP

# FEATURES

PERFORMANCE	<ul> <li>High output daily ice rate of up to 23 lbs and storage of up to 12 lbs of crescent ice (1/2" W × 3/4" H × 2-1/2" L)</li> <li>Conserves energy by using less electricity than a 75-watt light bulb</li> <li>Uses under 3 gallons of water to produce 25 lbs of ice</li> <li>No drain required makes it easy and inexpensive to install and requires only a 1/4" outside diameter water line</li> <li>Manual defrost maximizes ice making potential</li> <li>220 volt model available with a 4 – 6 week order lead time</li> </ul>
INTERIOR / EXTERIOR	<ul> <li>Vinyl coated cabinet helps withstand tough marine environments</li> <li>Corrosion and UV resistant marine grade hardware provide better product longevity in harsh environments</li> <li>Aluminum framed door with durable aluminum handle weathers outdoor elements</li> <li>Travel pin included for optimized, hygienic and safe at-sea travel and storage</li> </ul>
INTEGRATION	<ul> <li>Field reversible door with zero clearance door swing simplifies installation</li> <li>1/2" flange flush to cabinet</li> <li>No additional clearance around sides, top or rear of unit is needed for ventilation</li> <li>Sleek and contemporary look provides a very clean, high-end aesthetic</li> <li>Do not obstruct front grille air flow</li> <li>For proper installation and cut-out dimensions, see backside for details</li> </ul>
8900 NORTH 55TH STREET MILWAUKEE, WISCONSIN 53223 414,354,0300 FAX	



White



## WH95TP White Model

\* Add I-I/2" for water line clearance

### DIMENSIONS AND SPECIFICATIONS

#### OVERALL DIMENSIONS

Height Width Depth

Shipping weight: Black and white models 25-1/8" (63.8) 14" (37.8) 17" (43.2) WH95TPWhite 110VULN-WH95TP-03White 220VULN-WH95TP-20

k and white models

66 lbs (30 kg)

Up to 23 lbs

Up to 12 lbs

110/115 volt, 60 Hz

2.5

18.0

Running amps Maximum start-up amps Amps pertain to voltage rating Approximate daily ice production Ice storage

Optional in 220/230 voltage, 50/60 Hz On the 220/230 volt models, amps are decreased by approximately 50 percent.

Please visit www.u-line.com for installation guide. All specifications are subject to change without notice.

