

Specifications

Model			SCC-C4233(P)	SCC-C4333(P)	SCC-C4235(P)	SCC-C4335(P)	
Camera Type			Color				
Image	Device		1/4" Super-HAD IT CCD		1/4" Ex-View-HAD PS CCD		
	Effective Pixels	NTSC	768(H) x 494(V)				
PAL		752(H) x 582(V)					
Minimum Scene Illumination	Color		0.6 Lux(15IRE,Sens-up Off)		0.3 Lux(15IRE,Sens-up Off)		
			0.002 Lux(15IRE, Sens-up x256)		0.001 Lux(15IRE, Sens-up x256)		
	B/W		0.06 Lux(15IRE,Sens-up Off)		0.03 Lux(15IRE,Sens-up Off)		
			0.0002 Lux(15IRE, Sens-up x256)		0.0001 Lux(15IRE, Sens-up x256)		
Functions	Number of Privacy Zone		16				
	Day & Night		Color/BW/Auto (Moving Filter)				
	Line Lock		N/A	INT/Line Lock	N/A	INT/Line Lock	
	White Balance		ATW1/ATW2/AWC/MANUAL				
	D-Zoom		Yes (~16x)				
	High Speed Shutter		Yes (OFF ~ 1/10K)				
	Motion Detection		Yes				
	Sens Up		Yes (2x ~ 256x)				
	Camera ID		Max 20 Character				
	Remote Control		RS485, Power Zoom/Focus				
	Alarm	Input		N/A			
		Output		1			
Wide Dynamic Range		N/A		Yes			
Horizontal Resolution			540(Color)/570(BW) TV Lines				
Video Output			VBS 1.0Vp-p				
S/N Ratio			About 50 dB				
Lens	Focal Length		3.55 ~ 113mm				
	Zoom Ratio		32x Optical				
	Aperture Ratio		F1.69(W)/F4.17(T)				
	Viewing Angle	Tele		1.78°(H) x 1.34°(V)			
		Wide		56.41°(H) x 43.01°(V)			
Operating Temperature			-10°C ~ + 50°C				
Operating Humidity			Less than 90%				
Power	Power Requirement	NTSC	DC 12V	AC24V/DC12V,60Hz	DC12 V	AC24V/DC12V,60Hz	
		PAL		AC24V/DC12V,50Hz		AC24V/DC12V,50Hz	
	Power Consumption		4W	5W		5.5W	
	LED Indicator		Yes				
Dimensions	Net(mm)		60.5 X 59.5 X 125.2	60.5 X 59.5 X 159.2	60.5 X 59.5 X 125.2	60.5 X 59.5 X 159.2	
Weight	Net		444g	595g	444g	595g	
Color	Body		Silver				